



## AMERICAN NATIONAL STANDARD

*Accredited Standards  
Committee B3*

# Load Ratings And Fatigue Life For Ball Bearings ANSI/ABMA 9:2015 (Revision of ANSI/ABMA 9:1990)

**Secretariat**

**American Bearing  
Manufacturers Association**

**ANSI/ABMA 9:2015**



ABMA  
2025 M Street, NW  
Suite 800  
Washington, DC 20036  
Ph: 202-367-1155  
Fax: 202-367-2155  
E-mail: [info@americanbearings.org](mailto:info@americanbearings.org)  
[www.americanbearings.org](http://www.americanbearings.org)

## AMERICAN NATIONAL STANDARD

### **(This is not an approved part of the standard)**

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus, and other criteria for approval have been met by the standards developer.

Consensus means substantial agreement has been reached by directly and materially affected interests. This signifies the concurrence of more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that an effort be made toward their resolution.

The use of an American National Standard is completely voluntary; their existence does not in any respect preclude anyone, whether they approved the standard or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standard.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretations should be addressed to the secretariat of the sponsor whose name appears on the title page of this standard.

**CAUTION NOTICE:** This American National Standard may be revised or withdrawn at any time.

**This standard is maintained under stabilized maintenance and will be reviewed by Accredited Standards Committee B3 on a 10-year cycle. Any materially affected and interested party that feels this standard should be revised or withdrawn should submit their rationale for revision or withdrawal to the B3 Secretariat at the address below.**

Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute or online at [www.ANSI.org](http://www.ANSI.org).

Published by

American Bearing Manufacturers Association

2025 M Street, N.W., Suite 800

Washington, DC 20036

Copyright © 2015 by American Bearing Manufacturers Association

All rights reserved.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without prior written permission of the publisher.

Printed in the United States of America

**Load Ratings and Fatigue Life  
For Ball Bearings**

CONTENTS

SECTION	PAGE
1. Introduction .....	1
1.1 Purpose of Standard .....	1
1.2 Life Criterion .....	1
1.3 Static Load Criterion .....	1
2. Symbols .....	2
3. Definitions .....	3
3.1 Life .....	3
3.2 Reliability .....	3
3.3 Static Load .....	4
3.4 Pitch Diameter of a Ball Set, $D_{pw}$ .....	4
3.5 Rating Life .....	4
3.6 Basic Rating Life, $L_{10}$ .....	4
3.7 Adjusted Rating life, $L_{na}$ .....	4
3.8 Basic Dynamic Radial Load Rating, $C_r$ .....	4
3.9 Basic Static Radial Load Rating, $C_{0r}$ .....	4
3.10 Basic Dynamic Axial Load Rating, $C_a$ .....	4
3.11 Basic Static Axial Load Rating, $C_{0a}$ .....	4
3.12 Dynamic Equivalent Radial Load, $P_r$ .....	4
3.13 Static Equivalent Radial Load, $P_{0r}$ .....	5
3.14 Dynamic Equivalent Axial Load, $P_a$ .....	5
3.15 Static Equivalent Axial Load, $P_{0a}$ .....	5
3.16 Static Safety Factor, $S_0$ .....	5
3.17 Nominal Contact Angle, $\alpha$ .....	5
3.18 Conventional Operating Conditions .....	5
3.19 Viscosity ratio, $\kappa$ .....	5
3.20 Film Parameter, $\Lambda$ .....	5
3.21 Pressure-viscosity Coefficient .....	5
3.22 Bearing Arrangements: Paired Mounting .....	5
3.23 Bearing Arrangements: Back-to-back .....	5
3.24 Bearing Arrangements: Face-to-face .....	5
3.25 Bearing Arrangements: Tandem .....	6
4. Scope .....	6
4.1 Bearing Types .....	6
4.1.1 General .....	6
4.1.2 Radial, Deep Groove and Angular Contact .....	6
4.1.3 Filling Slot, Deep Groove .....	6
4.1.4 Radial, Self-Aligning .....	6
4.1.5 Thrust .....	6
4.1.6 Double Row, Radial and Angular Contact .....	6
4.2 Limitations .....	6
4.2.1 Truncated Contact Area .....	6
4.2.2 Materials .....	6
4.2.3 Bearing Types .....	7
4.2.4 Lubrication .....	7
4.2.5 Ring Support and Alignment .....	7
4.2.6 Internal Clearance .....	7
4.2.7 High Speed Effects .....	7
4.2.8 Interference Fits .....	7
4.2.9 Residual Stress .....	7
4.2.10 Groove Radii .....	7
4.2.11 Tolerances .....	8
4.2.12 Plastic Deformation in the Contact Area .....	8

4.3	Operating Parameters .....	8
5	Radial and Angular Contact Ball Bearings .....	9
5.1	Basic Dynamic Radial Load Rating .....	9
5.1.1	Basic Dynamic Radial Load Rating for Single Bearings .....	9
5.1.2	Basic Dynamic Radial Load Rating for Bearing Combinations .....	9
5.2	Dynamic Equivalent Radial Load .....	12
5.2.1	Dynamic Equivalent Radial Load for Single Bearings .....	12
5.2.2	Dynamic Equivalent Radial Load for Bearing Combinations .....	12
5.3	Basic Rating Life .....	12
5.3.1	Life Equation .....	12
5.3.2	Loading Restriction on the Life Equation .....	15
5.4	Basic Static Radial Load Rating .....	15
5.4.1	Basic Static Radial Load Rating for Single Bearings .....	15
5.4.2	Basic Static Radial Load Rating for Bearing Combinations .....	15
5.5	Static Equivalent Radial Load .....	17
5.5.1	Static Equivalent Radial Load for Single Bearings .....	17
5.5.2	Static Equivalent Radial Load for Bearing Combinations .....	17
6	Thrust Ball Bearings .....	18
6.1	Basic Dynamic Axial Load Rating .....	18
6.1.1	Basic Dynamic Axial Load Rating for Single-row Bearings .....	18
6.1.2	Basic Dynamic Axial Load Rating for Bearings with Two or More Rows of Balls .....	18
6.2	Dynamic Equivalent Axial Load .....	20
6.3	Basic Rating Life .....	21
6.3.1	Life Equation .....	21
6.3.2	Loading Restriction on the Life Equation .....	21
6.4	Basic Static Axial Load Rating .....	21
6.5	Static Equivalent Axial Load .....	21
7	Static Safety Factor .....	22
7.1	General .....	22
8	Adjusted rating Life .....	22
8.1	General .....	22
8.2	Limitations .....	23
8.3	Life Adjustment Factor for Reliability, $a_1$ .....	23
8.4	Life Adjustment Factor for Special Bearing Properties, $a_2$ .....	23
8.5	Life Adjustment Factor for Operating Conditions, $a_3$ .....	24
8.5.1	General .....	24
8.5.2	Viscosity Ratio .....	24
8.5.3	Calculation of Life Under Low Load Conditions .....	25

LIST OF TABLES

TABLE NO.	TITLE	PAGE
RADIAL AND ANGULAR CONTACT BALL BEARINGS		
1	Values for $f_{cm}$ for Radial and Angular Contact Ball Bearings .....	10
2	Values for X and Y for Radial and Angular Contact Ball Bearings .....	13
3	Values for $f_0$ for Ball Bearings .....	16
4	Values for $X_0$ and $Y_0$ for Radial Ball Bearings .....	17
THRUST ROLLER BEARINGS		
5	Values for $f_{cm}$ for Thrust Ball Bearings .....	19
6	Values for X and Y for Thrust Ball Bearings .....	20
7	Guideline Values for the Static Safety Factor $S_0$ for Ball Bearings .....	22
8	Life Adjustment Factor for Reliability, $a_1$ .....	23

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
1	Reference Kinematic Viscosity, $\nu_1$ .....	25

# Load Ratings and Fatigue Life for Ball Bearings

## 1. INTRODUCTION

### 1.1 Purpose of Standard

Ball bearing performance is a function of many variables. These include the bearing design, the characteristics of the material from which the bearings are made, the way in which they are manufactured, as well as many variables associated with their application. The only sure way to establish the satisfactory operation of a bearing selected for a specific application is by actual performance in the application. As this is often impractical, another basis is required to estimate the suitability of a particular bearing for a given application. This is the purpose of this standard.

This standard specifies the method of calculating the basic dynamic load rating of rolling bearings within the size ranges shown in the relevant ANSI/ABMA standards, manufactured from contemporary, commonly used, good quality hardened bearing steel in accordance with good manufacturing practice and basically of conventional design as regards the shape of rolling contact surfaces.

This standard also specifies the method of calculating the basic rating life, which is the life associated with 90% reliability, with commonly used high quality material, good manufacturing quality and with conventional operating conditions. In addition, it specifies the method of calculating adjusted rating life, in which various reliabilities, special bearing properties and specific operating conditions are taken into account by means of life adjustment factors.

Furthermore, this standard specifies the method of calculating the basic static load rating and the static equivalent load for ball bearings within the size ranges shown in the relevant ANSI/ABMA Standards, manufactured from good quality hardened bearing steel, in accordance with good manufacturing practice and basically of conventional design as regards the shape of rolling contact surfaces.

### 1.2 Life Criterion

Even if ball bearings are properly mounted, adequately lubricated, protected from foreign matter, and are not subjected to extreme operating conditions, they can ultimately fatigue. Under ideal conditions, the repeated stresses developed in the contact areas between the ball and the raceways eventually can result in fatigue of the material which manifests itself as spalling of the load carrying surfaces. In most applications the fatigue life is the maximum useful life of a bearing. This fatigue is the criterion of life used as the basis for the first part of this standard.

Fatigue life calculated in accordance with this standard does not represent the maximum that can be attained by applying all known technology to ball bearing design and application. Neither does it represent the minimum that should be expected of a bearing made by a producer lacking skill and experience in the design and manufacture of ball bearings, even though the bearing meets the geometric parameters given below. The calculated fatigue life represents the performance normally expected from high quality bearings made by reputable manufacturers. Manufacturers can supply longer lived bearings by the application of advanced materials and manufacturing processes. The present standard has evolved as a means for bearing users to specify a reasonable standard of performance for the bearing they wish to purchase.

### 1.3 Static Load Criterion

A static load is a load acting on a non-rotating bearing. Permanent deformations appear in balls and raceways under a static load of moderate magnitude and increase gradually with increasing load.

It is often impractical to establish whether the deformations appearing in a bearing in a specific application are permissible by testing the bearing in that application. Other methods are therefore required to establish the suitability of the bearing selected.