



American
Gear Manufacturers
Association

Technical Resources

AGMA 918-A93
Reaffirmed March 10, 2015

AGMA Information Sheet

A Summary of Numerical
Examples Demonstrating
the Procedures for
Calculating Geometry
Factors for Spur and
Helical Gears

**American
Gear
Manufacturers
Association**

***A Summary of Numerical Examples Demonstrating the Procedures for
Calculating Geometry Factors for Spur and Helical Gears***

AGMA 918-A93

CAUTION NOTICE: AGMA technical publications are subject to constant improvement, revision or withdrawal as dictated by experience. Any person who refers to any AGMA Technical Publication should be sure that the publication is the latest available from the Association on the subject matter.

[Tables or other self-supporting sections may be referenced. Citations should read: See AGMA 918-A93, *A Summary of Numerical Examples Demonstrating the Procedures for Calculating Geometry Factors for Spur and Helical Gears*, published by the American Gear Manufacturers Association, 1001 N. Fairfax Street, Suite 500, Alexandria, Virginia 22314, <http://www.agma.org>.]

Approved January 1993

ABSTRACT

This information sheet provides numerical examples for calculating the pitting resistance geometry factor, I , and bending strength geometry factor, J , for typical gearsets that are generated by rack-type tools (hobs, rack cutters or generating grinding wheels) or pinion-type tools (disk-type shaper cutters). The numerical examples are shown in tabular form and provide the values for all variables as calculated using the procedures and equations in AGMA 908-B89. A flow chart, intended to assist in the development of a computer program for these variables, is also included.

Published by

**American Gear Manufacturers Association
1001 N. Fairfax Street, Suite 500, Alexandria, Virginia 22314**

Copyright © 1993 by American Gear Manufacturers Association
Reaffirmed 1998
All rights reserved.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without prior written permission of the publisher.

Printed in the United States of America

ISBN: 1-55589-617-0

Contents

Foreword	v
1 Scope	1
1.1 Numerical examples	1
1.2 Flow chart	1
1.3 Exceptions	1
2 Definitions and symbols	1
2.1 Definitions	1
2.2 Symbols	2
3 Numerical examples	4
3.1 Examples	4
3.1.1 Accurate spur gears	4
3.1.2 Inaccurate spur gears	4
3.1.3 Conventional helical gears	4
3.1.4 Low axial contact ratio (LACR) helical gears	4
3.1.5 Conventional helical gears, different tools	4
3.1.6 Spur sun and planet gear	4
3.1.7 Spur planet and ring gear	4
3.1.8 Helical sun and planet gear	4
3.1.9 Helical planet and ring gear	4
3.1.10 Conventional double helical gears	5
3.1.11 Herringbone gears	5
3.2 Tabulation of examples	5
4 Flow chart	5
5 Cutting tool geometry	5
5.1 Rack type cutting tools	5
5.2 Pinion type cutting tools	5
5.3 Cutting tool drawings	5

Tables

Table 1 - Symbols used in equations	2
Table 2A – Accurate spur gears, example 3.1.1	6
Table 3A – Inaccurate spur gears, example 3.1.2	8
Table 4A – Conventional helical gears, example 3.1.3	10
Table 5A – Low axial contact ratio (LACR) helical gears, example 3.1.4	12
Table 6A – Conventional helical gears, different tools, example 3.1.5	14
Table 7A – Spur, sun and planet gear, example 3.1.6	16
Table 8A – Spur, planet and ring gear, example 3.1.7	18
Table 9A – Helical, sun and planet gear, example 3.1.8	20
Table 10A – Helical, planet and ring gear, example 3.1.9	22
Table 11A – Conventional double helical gears, example 3.1.10	24
Table 12A – Herringbone gears, example 3.1.11	26

Figures

Figure 1 - Flow chart for <i>I</i> and <i>J</i> subroutines for AGMA 908-B8	28
Figure 2 - Hob for example 3.1.1 and 3.1.2	36
Figure 3 - Hob for example 3.1.3 and 3.1.4	37
Figure 4 - Hob for example 3.1.5	37
Figure 5 - Helical pinion type shaper cutter for example 3.1.5	38
Figure 6 - Hob for examples 3.1.6 and 3.1.7	38
Figure 7 - Spur pinion type shaper cutter for example 3.1.7	39
Figure 8 - Hob for example 3.1.8	39
Figure 9 - Helical pinion type shaper cutter for examples 3.1.8 and 3.1.9	40
Figure 10 - Helical pinion type shaper cutter for example 3.1.9	40
Figure 11 - Hob for example 3.1.10	41
Figure 12 - Helical pinion type shaper cutter for example 3.1.11	41

Foreword

[The foreword, footnotes and annexes, if any, in this document are provided for informational purposes only and are not to be construed as a part of AGMA 918-A93, *A Summary of Numerical Examples Demonstrating the Procedures for Calculating Geometry Factors for Spur and Helical Gears.*]

This AGMA information sheet and related publications are based on typical or average data, conditions, or application.

This information sheet, AGMA 918-A93, was prepared to assist designers in the proper use and interpretation of AGMA 908-B89 and to assist in the development of computer programs when calculating geometry factors for pitting resistance, I , and bending strength, J . A flow chart provides a step by step procedure for the calculation of these factors, either manually or by computer program. Several examples are provided to demonstrate the calculation procedure for the various characteristics of geometry as described in AGMA 908-B89.

These include accurate and inaccurate spur gears, conventional and LACR helical gears, internal and external gears, double helical and herringbone (Sykes) gears, and addendum modifications. The calculation of J -factor for internal gears is not defined in AGMA 908-B89 and, therefore, is not covered in this information sheet. A tabulation of all calculated variables is provided for each example based on its design criteria. This provides the designer with known results to check against when calculating or programming these factors.

Suggestions for improvement of this standard will be welcome. They should be sent to the American Gear Manufacturers Association, 1001 N. Fairfax Street, Suite 500, Alexandria, Virginia 22314.

PERSONNEL of the AGMA Helical Gear Rating Committee

Chairman: D. McCarthy.....Dorris Company
Vice Chairman: N. Hulse.....General Electric

ACTIVE MEMBERS

K.E. Acheson The Gear Works-Seattle
M. Antosiewicz Falk
J. Bentley..... Peerless-Winsmith
E.S. Berndt..... C&M of Indiana
J.D. Black GM/Allison Div.
E.J. Bodensieck Bodensieck Engineering
N.K. Burrell..... Metal Improvement Co.
M.F. Dalton..... General Electric
G. DeLange Emerson Power Trans.
J.R. DeMarais Bison Gear
R J. Drago Boeing
R L. Errichello..... Academic Member
H. Hagan Cincinnati Gear
H.R. Johnson Lufkin Industries
O. LaBath Cincinnati Gear
G. Lian..... Amarillo Gear Co.
L. Lloyd..... Lufkin Industries
D.R. McVittie Gear Engineers, Inc.
A. Milburn Milburn Engineering
C. Moyer..... The Timken Co.
R. Nay Pratt & Whitney
M.W. Neesley..... WesTech Gear
W.P. Pizzichil Philadelphia Gear
J.W. Polder..... Academic Member
E R. Sewall..... Sewall Gear
J. Tellman..... Reliance Electric/Reeves
T. Turnbull Mobile Pulley & Machine
W. Wagner Sewall Gear
C.C. Wang..... 3E Software & Engrg.
R. Wasilewski..... Arrow Gear

American Gear Manufacturers Association -

A Summary of Numerical Examples Demonstrating the Procedures for Calculating Geometry Factors for Spur and Helical Gears

1 Scope

This information sheet provides a set of numerical examples which calculate the geometry factor for pitting resistance, I , and bending strength, J , for a variety of gearsets selected to demonstrate the various gear geometries analyzed in AGMA 908-B89, *Geometry Factors for Determining the Pitting Resistance and Bending Strength of Spur, Helical and Herringbone Gear Teeth*. A flow chart is also included to formalize the calculation procedures for the numerical examples and to assist in the practical application of AGMA 908-B89.

1.1 Numerical examples

Numerical examples were selected to demonstrate the following conditions: accurate and inaccurate spur gears, conventional and LACR (low axial contact ratio) helical gears, internal and external gears, double helical and herringbone (Sykes) gears and addendum modification. For simplification purposes and for demonstrating the effect on resulting geometry factors, similar examples were selected with different load locations (example 3.1.1 vs 3.1.2) and face widths (example 3.1.3 vs 3.1.4)

The results are presented in tabular form by providing the numerical results for each equation as presented in AGMA 908-B89 and appropriate to that gear geometry. Gear cutter data is presented for each component in each numerical example. All gearsets are functional and do not violate any of the exceptions stated in the scope of AGMA 908-B89. The examples used are for demonstration purposes only and are not intended to be recommendations for gearset design.

1.2 Flow chart

The flow chart provides a step by step procedure for calculating geometry factors, I and J , using the equations and instructions from AGMA 908-B89. The numerical value tables are formatted to coincide with the flow chart procedures.

1.3 Exceptions

A procedure for the calculation of bending strength geometry factor, J , for internal gears has not been established by AGMA. For this reason, numerical examples and flow chart procedures for such a calculation are not included.

2 Definitions and symbols

2.1 Definitions

The terms used, wherever applicable, conform to the following standards:

ANSI Y10.3-1968, *Letter Symbols for Quantities Used in Mechanics of Solids*;

AGMA 904-B89, *Metric Usage*;

AGMA 1012-F90, *Gear Nomenclature, Definitions of Terms with, Symbols*.