

AGMA 918-A93



Reproduced By GLOBAL
ENGINEERING DOCUMENTS
With The Permission Of AGMA
Under Royalty Agreement

AMERICAN GEAR MANUFACTURERS ASSOCIATION

***A Summary of Numerical Examples
Demonstrating the Procedures for
Calculating Geometry Factors for
Spur and Helical Gears***

AGMA 918-A93



AGMA INFORMATION SHEET

(This Information Sheet is NOT an AGMA Standard)

918–A93, A Summary of Numerical Examples Demonstrating the Procedures for Calculating Geometry Factors for Spur and Helical Gears

CAUTION NOTICE: AGMA standards are subject to constant improvement, revision, or withdrawal as dictated by experience. Any person who refers to any AGMA Technical Publication should be sure that the publication is the latest available from the Association on the subject matter.

[Tables or other self-supporting sections may be quoted or extracted in their entirety. Credit line should read: Extracted from AGMA 918–A93, *A Summary of Numerical Examples Demonstrating the Procedures for Calculating Geometry Factors for Spur and Helical Gears*, with the permission of the publisher, the American Gear Manufacturers Association, 1500 King Street, Suite 201, Alexandria, Virginia 22314.]

ABSTRACT

This information sheet provides numerical examples for calculating the pitting resistance geometry factor, I , and bending strength geometry factor, J , for typical gearsets that are generated by rack-type tools (hobs, rack cutters or generating grinding wheels) or pinion-type tools (disk-type shaper cutters). The numerical examples are shown in tabular form and provide the values for all variables as calculated using the procedures and equations in AGMA 908–B89. A flow chart, intended to assist in the development of a computer program for these variables, is also included.

Copyright ©, 1993 by American Gear Manufacturers Association

Published by

**American Gear Manufacturers Association
1500 King Street, Suite 201, Alexandria, Virginia 22314**

January, 1993

ISBN: 1–55589–617–0

Table of Contents

	Page
Foreword	v
1 Scope	1
1.1 Numerical examples	1
1.2 Flow chart	1
1.3 Exceptions	1
2 Definitions and symbols	1
2.1 Definitions	1
2.2 Symbols	1
3 Numerical examples	4
3.1 Examples	4
3.2 Tabulation of examples	5
4 Flow chart	28
5 Cutting tool geometry	37
5.1 Rack type cutting tools	37
5.2 Pinion type cutting tools	37
5.3 Cutting tool drawings	37
Tables	
1 Symbols used in equations	2
2A Accurate spur gears, example 3.1.1	6
2B Accurate spur gears, example 3.1.1	7
3A Inaccurate spur gears, example 3.1.2	8
3B Inaccurate spur gears, example 3.1.2	9
4A Conventional helical gears, example 3.1.3	10
4B Conventional helical gears, example 3.1.3	11
5A Low axial contact ratio (LACR) helical gears, example 3.1.4	12
5B Low axial contact ratio (LACR) helical gears, example 3.1.4	13
6A Conventional helical gears, different tools, example 3.1.5	14
6B Conventional helical gears, different tools, example 3.1.5	15
7A Spur sun and planet gear, example 3.1.6	16
7B Spur sun and planet gear, example 3.1.6	17
8A Spur planet and ring gear, example 3.1.7	18
8B Spur planet and ring gear, example 3.1.7	19
9A Helical sun and planet gear, example 3.1.8	20
9B Helical sun and planet gear, example 3.1.8	21
10A Helical planet and ring gear, example 3.1.9	22
10B Helical planet and ring gear, example 3.1.9	23
11A Conventional double helical gears, example 3.1.10	24
11B Conventional double helical gears, example 3.1.10	25
12A Herringbone gears, example 3.1.11	26
12B Herringbone gears, example 3.1.11	27
Figures	
1 Flow chart for <i>I</i> and <i>J</i> subroutines for AGMA 908–B89	28
2 Hob for examples 3.1.1 and 3.1.2	37
3 Hob for examples 3.1.3 and 3.1.4	38

Table of Contents (cont)

	Page
4 Hob for example 3.1.5	38
5 Helical pinion type shaper cutter for example 3.1.5	39
6 Hob for examples 3.1.6 and 3.1.7	39
7 Spur pinion type shaper cutter for example 3.1.7	40
8 Hob for example 3.1.8	40
9 Helical pinion type shaper cutter for examples 3.1.8 and 3.1.9	41
10 Helical pinion type shaper cutter for example 3.1.9	41
11 Hob for example 3.1.10	42
12 Helical pinion type shaper cutter for example 3.1.11	42

FOREWORD

[The foreword, footnotes, and annexes, if any, in this document are provided for informational purposes only and are not to be construed to be part of AGMA 918–A93, *A Summary of Numerical Examples Demonstrating the Procedures for Calculating Geometry Factors for Spur and Helical Gears.*]

This AGMA information sheet and related publications are based on typical or average data, conditions, or application.

This information sheet, AGMA 918–A93, was prepared to assist designers in the proper use and interpretation of AGMA 908–B89 and to assist in the development of computer programs when calculating geometry factors for pitting resistance, I , and bending strength, J . A flow chart provides a step by step procedure for the calculation of these factors, either manually or by computer program. Several examples are provided to demonstrate the calculation procedure for the various characteristics of geometry as described in AGMA 908–B89.

These include accurate and inaccurate spur gears, conventional and LACR helical gears, internal and external gears, double helical and herringbone (Sykes) gears, and addendum modifications. The calculation of J -factor for internal gears is not defined in AGMA 908–B89 and, therefore, is not covered in this information sheet. A tabulation of all calculated variables is provided for each example based on its design criteria. This provides the designer with known results to check against when calculating or programming these factors.

Suggestions for the improvement of this information sheet will be welcome. They should be sent to the American Gear Manufacturers Association, 1500 King Street, Suite 201, Alexandria, Virginia, 22314.

PERSONNEL of the AGMA Committee for Helical Gear Rating

Chairman: D. McCarthy (Dorris Company)

Vice Chairman: N. Hulse (General Electric)

ACTIVE MEMBERS

K. E. Acheson The Gear Works—Seattle
 M. Antosiewicz Falk
 J. Bentley Peerless—Winsmith
 E. S. Berndt C&M of Indiana
 J. D. Black GM/Allison Div.
 E. J. Bodensieck Bodensieck Engineering
 N. K. Burrell Metal Improvement Co.
 M. F. Dalton General Electric
 G. DeLange Emerson Power Trans.
 J. R. DeMarais Bison Gear
 R. J. Drago Boeing
 R. L. Errichello Academic Member
 H. Hagan Cincinnati Gear
 H. R. Johnson Lufkin Industries
 O. LaBath Cincinnati Gear

G. Lian Amarillo Gear Co.
 L. Lloyd Lufkin Industries
 D. R. McVittie Gear Engineers, Inc.
 A. Milburn Milburn Engineering
 C. Moyer The Timken Co.
 R. Nay Pratt & Whitney
 M. W. Neesley WesTech Gear
 W. P. Pizzichil Philadelphia Gear
 J. W. Polder Academic Member
 E. R. Sewall Sewall Gear
 J. Tellman Reliance Electric/Reeves
 T. Turnbull Mobile Pulley & Machine
 W. Wagner Sewall Gear
 C. C. Wang 3E Software & Engrg.
 R. Wasilewski Arrow Gear

ASSOCIATE MEMBERS

J. Adamson TIW Systems
 R. G. Allenby Hamilton Gear
 J. Amendola MAAG/Artec
 K. Beckman Lufkin Industries
 D. L. Borden Gear Research Institute
 E. R. Braun Eaton
 G. Buziuk Brad—Foote
 A. Cardou Universite Laval
 M. R. Chaplin Contour Hardening Inc.
 J. Cianci General Electric
 A. S. Cohen Engranos y Maquinaria
 J. T. Cook Power—Tech
 R. DiRusso Kaman
 D. W. Dudley Honorary Member
 K. A. Evans GM—Saginaw Div.
 R. Geary Terrell Gear Drives
 R. Giuffra ABS
 L. L. Haas SPECO Corporation
 F. M. Hager Cummins Engine
 A. C. Hayes DACA
 W. H. Heller Peerless—Winsmith
 G. Henriot Engrenages et Reducteurs
 M. Hirt Renk Tacke GmbH
 D. R. Houser Academic Member
 F. Irey New Angle Gear
 T. W. Jessup Lucas Western Inc./ATD
 T. Kameyama Seiki—Kogyosho
 M. Lawrenz Metal Improvement
 J. Liesicki Falk Corporation
 J. Maddock Consultant
 D. Mairet Falk Corporation

T. J. Maiuri Gleason Works
 P. C. McAvoy Cummins Engine
 B. W. McCoy Marathon Letourneau
 F. Myers Horsburgh & Scott
 D. Moser Nuttall Gear
 B. L. Mumford Alten—Foundry
 W. Nageli MAAG
 B. C. Newcomb Chicago Gear—D.O.James
 H. C. A. Nielsen F. L. Smith
 J. Nyerup F. L. Smith
 T. Okamoto Nippon Gear
 G. E. Olson Cleveland Gear
 J. A. Pennell Academic Member
 A. E. Phillips Reliance Electric
 B. D. Pyeatt Amarillo Gear
 V. Z. Rychlinski Brad Foote
 E. Sandberg Det Norske Veritas
 W. F. Schierrenbeck Xtek Incorporated
 A. Seireg Academic Member
 E. E. Shipley Mechanical Technology
 D. A. Sylvester Flender Corporation
 D. Senkfor Precision Gear
 L. J. Smith Invincible Gear
 F. A. Thoma Honorary Member
 W. J. Toner IMO Delaval, Inc.
 H. J. Trapp Klingelberg
 F. C. Uherek Flender Corporation
 T. Urabe Tsubakimoto Chain
 D. A. Wagner General Motors/AGT
 H. Winter Academic Member

A Summary of Numerical Examples Demonstrating the Procedures for Calculating Geometry Factors for Spur and Helical Gears

1 Scope

This information sheet provides a set of numerical examples which calculate the geometry factor for pitting resistance, I , and bending strength, J , for a variety of gearsets selected to demonstrate the various gear geometries analyzed in AGMA 908–B89, *Geometry Factors for Determining the Pitting Resistance and Bending Strength of Spur, Helical and Herringbone Gear Teeth*. A flow chart is also included to formalize the calculation procedures for the numerical examples and to assist in the practical application of AGMA 908–B89.

1.1 Numerical examples

Numerical examples were selected to demonstrate the following conditions: accurate and inaccurate spur gears, conventional and LACR (low axial contact ratio) helical gears, internal and external gears, double helical and herringbone (Sykes) gears and addendum modification. For simplification purposes and for demonstrating the effect on resulting geometry factors, similar examples were selected with different load locations (example 3.1.1 vs 3.1.2) and face widths (example 3.1.3 vs 3.1.4)

The results are presented in tabular form by providing the numerical results for each equation as presented in AGMA 908–B89 and appropriate to that gear geometry. Gear cutter data is presented for each component in each numerical example. All gearsets are functional and do not violate any of the exceptions stated in the scope of AGMA 908–B89. The examples used are for demonstration purposes

only and are not intended to be recommendations for gearset design.

1.2 Flow chart

The flow chart provides a step by step procedure for calculating geometry factors, I and J , using the equations and instructions from AGMA 908–B89. The numerical value tables are formatted to coincide with the flow chart procedures.

1.3 Exceptions

A procedure for the calculation of bending strength geometry factor, J , for internal gears has not been established by AGMA. For this reason, numerical examples and flow chart procedures for such a calculation are not included.

2 Definitions and symbols

2.1 Definitions

The terms used, wherever applicable, conform to the following standards:

ANSI Y10.3–1968, *Letter Symbols for Quantities Used in Mechanics of Solids*;

AGMA 904–B89, *Metric Usage*;

AGMA 1012–F90, *Gear Nomenclature, Definitions of Terms with, Symbols*.

2.2 Symbols

The symbols used in the geometry factor formulas are shown in table 1.

NOTE – The symbols, definitions and terminology used in this information sheet may differ from other AGMA documents. The user should not assume that familiar symbols can be used without a careful study of these definitions.

Units of measure are not shown in table 1 because the equations are in terms of unity normal module or unity normal diametral pitch.