

AMERICAN GEAR MANUFACTURERS ASSOCIATION

*Load Distribution Factors - Analytical
Methods for Cylindrical Gears*

AGMA 927-A01



AGMA INFORMATION SHEET

(This Information Sheet is NOT an AGMA Standard)

American
Gear
Manufacturers
Association

Load Distribution Factors - Analytical Methods for Cylindrical Gears
AGMA 927-A01

CAUTION NOTICE: AGMA technical publications are subject to constant improvement, revision or withdrawal as dictated by experience. Any person who refers to any AGMA technical publication should be sure that the publication is the latest available from the Association on the subject matter.

[Tables or other self-supporting sections may be quoted or extracted. Credit lines should read: Extracted from AGMA 927-A01, *Load Distribution Factors - Analytical Methods for Cylindrical Gears*, with the permission of the publisher, the American Gear Manufacturers Association, 1500 King Street, Suite 201, Alexandria, Virginia 22314.]

Approved October 22, 2000

ABSTRACT

This information sheet describes an analytical procedure for the calculation of the face load distribution. The iterative solution that is described is compatible with the definitions of the term face load distribution (K_H) of AGMA standards and longitudinal load distribution ($K_{H\beta}$ and $K_{F\beta}$) of the ISO standards. The procedure is easily programmable and flow charts of the calculation scheme as well as examples from typical software are presented.

Published by

American Gear Manufacturers Association
1500 King Street, Suite 201, Alexandria, Virginia 22314

Copyright © 2000 by American Gear Manufacturers Association
All rights reserved.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without prior written permission of the publisher.

Printed in the United States of America

ISBN: 1-55589-779-7

Contents

	Page
Foreword	iv
1 Scope	1
2 References	1
3 Definitions and symbols	2
4 Iterative analytical method	3
5 Coordinate system, sign convention, gearing forces and moments	4
6 Shaft bending deflections	9
7 Shaft torsional deflection	14
8 Gap analysis	15
9 Load distribution	19
10 Future considerations	21

Annexes

A Flowcharts for load distribution factor	22
B Load distribution examples	26

Figures

1 Base tangent coordinate system for CW driven rotation from reference end .	5
2 Base tangent coordinate system for CCW driven rotation from reference end	6
3 Hand of cut for gears and explanation of apex for bevel gears	7
4 Gearing force sense of direction for positive value from equations	8
5 Example general case gear arrangement (base tangent coordinate system) .	8
6 View A-A from figure 5	9
7 Example shaft	11
8 Calculated shaft diagrams	13
9 Torsional increments	15
10 Shaft number 3 gap	17
11 Shaft number 4 gap	17
12 Total mesh gap	18
13 Relative mesh gap	18
14 Tooth section with spring constant $C_{\gamma m}$, load L , and deflection C_d	19
15 Deflection sections	19
16 Mesh gap section grid	20

Tables

1 Symbols and definitions	2
2 Values for factors hand, apex, rotation, and drive	7
3 Calculation data and results	10
4 Evaluation of mesh gap for mesh #3, μm	16

Foreword

[The foreword, footnotes and annexes, if any, in this document are provided for informational purposes only and are not to be construed as a part of AGMA Information Sheet 927-A01, *Load Distribution Factors - Analytical Methods for Cylindrical Gears*.]

This information sheet provides an analytical method to calculate a numeric value for the face load distribution factor for cylindrical gearing.

This is a new document, which provides a description of the analytical procedures that are used in several software programs that have been developed by various gear manufacturing companies. The method provides a significant improvement from the procedures used to define numeric values of face load distribution factor in current AGMA standards. Current AGMA standards utilize either an empirical procedure or a simplified closed form analytical calculation. The empirical procedure which is used in ANSI/AGMA 2101-C95 only allows for a nominal assessment of the influence of many parameters which effect the numeric value of the face load distribution factor. The closed form analytic formulations which have been found in AGMA standards suffer from the limitation that the shape of the load distribution across the face width is limited to a linear form.

The limitations of the previous AGMA procedures are overcome by the method defined in this information sheet. This method allows for including a sufficiently accurate representation of many of the parameters that influence the distribution of load along the face width of cylindrical gears. These parameters include the elastic effects due to deformations under load, and the inelastic effects of geometric errors as well as the tooth modifications which are typically utilized to offset the deleterious effects of the deformations and errors.

The analytical method described in this information sheet is based on a "thin slice" model of a gear mesh. This model treats the distribution of load across the face width of the gear mesh as being independent of the any transverse effects. The method also represents all of the elastic effects of a set of meshing teeth (tooth bending, tooth shear, tooth rotation, Hertzian deflections, etc.) by one constant, i.e., mesh stiffness ($C_{\gamma m}$). Despite these simplifying assumptions, this method provides numeric values of the face load distribution factor that are sufficiently accurate for industrial applications of gearing which fall within the limitations specified.

The first draft of this information sheet was made in February, 1996. This version was approved by the AGMA membership on October 22, 2000.

Special mention must be made of the devotion of Louis Lloyd of Lufkin for his untiring efforts from the submittal of the original software code through the prodding for progress during the long process of writing this information sheet. Without his foresight and contributions this information sheet may not have been possible.

Suggestions for improvement of this document will be welcome. They should be sent to the American Gear Manufacturers Association, 1500 King Street, Suite 201, Alexandria, Virginia 22314.

PERSONNEL of the AGMA Helical Rating Committee and Load Distribution Subcommittee

Chairman: D. McCarthy Dorris Company
Vice Chairman: M. Antosiewicz The Falk Corporation
SubCommittee Chairman: J. Lisiecki The Falk Corporation

SUBCOMMITTEE ACTIVE MEMBERS

K.E. Acheson ...	The Gear Works - Seattle	J.J. Luz	General Electric Company
W.A. Bradley	Consultant	D.R. McVittie	Gear Engineers, Inc.
M.F. Dalton	General Electric Company	M.W. Neesley ...	WesTech Gear Corporation
G.A. DeLange ...	Prager, Inc.	W.P. Pizzichil ...	Philadelphia Gear Corp.
O. LaBath	The Cincinnati Gear Co.	F.C. Uherek	Flender Corporation
L. Lloyd	Lufkin Industries, Inc.		

COMMITTEE ACTIVE MEMBERS

K.E. Acheson ...	The Gear Works-Seattle, Inc.	G. Lian	Amarillo Gear Company
J.B. Amendola ..	MAAG Gear AG	J.V. Lisiecki	The Falk Corporation
T.A. Beveridge ..	Caterpillar, Inc.	L. Lloyd	Lufkin Industries, Inc.
W.A. Bradley	Consultant	J.J. Luz	General Electric Company
M.J. Broglie	Dudley Technical Group, Inc.	D.R. McVittie	Gear Engineers, Inc.
A.B. Cardis	Mobil Technology Center	A.G. Milburn	Milburn Engineering, Inc.
M.F. Dalton	General Electric Company	G.W. Nagorny ...	Nagorny & Associates
G.A. DeLange ...	Prager, Incorporated	M.W. Neesley ...	Philadelphia Gear Corp.
D.W. Dudley	Consultant	B. O'Connor	The Lubrizol Corporation
R.L. Errichello ...	GEARTECH	W.P. Pizzichil ...	Philadelphia Gear Corp.
D.R. Gonnella ...	Equilon Lubricants	D.F. Smith	Solar Turbines, Inc.
M.R. Hoeprich ..	The Timken Company	K. Taliaferro	Rockwell Automation/Dodge
O.A. LaBath	The Cincinnati Gear Co.		

COMMITTEE ASSOCIATE MEMBERS

M. Bartolomeo ..	New Venture Gear, Inc.	M. Hirt	Renk AG
A.C. Becker	Nuttall Gear LLC	R.W. Holzman ..	Milwaukee Gear Company, Inc.
E. Berndt	Besco	R.S. Hyde	The Timken Company
E.J. Bodensieck .	Bodensieck Engineering Co.	V. Ivers	Xtek, Incorporated
D.L. Borden	D.L. Borden, Inc.	A. Jackson	Mobil Technology Company
M.R. Chaplin	Contour Hardening, Inc.	H.R. Johnson ...	The Horsburgh & Scott Co.
R.J. Ciszak	Euclid-Hitachi Heavy Equip. Inc.	J.G. Kish	Sikorsky Aircraft Division
A.S. Cohen	Engranes y Maquinaria Arco SA	R.H. Klundt	The Timken Company
S. Copeland	Gear Products, Inc.	J.S. Korossy	The Horsburgh & Scott Co.
R.L. Cragg	Consultant	I. Laskin	Consultant
T.J. Dansdill	General Electric Company	J. Maddock	The Gear Works - Seattle, Inc.
F. Eberle	Rockwell Automation/Dodge	J. Escanaverino .	ISPJAE
L. Faure	C.M.D.	G.P. Mowers	Consultant
C. Gay	Charles E. Gay & Company, Ltd.	R.A. Nay	UTC Pratt & Whitney Aircraft
J. Gimper	Danieli United, Inc.	M. Ocrtrue	CETIM
T.C. Glasener ...	Xtek, Incorporated	T. Okamoto	Nippon Gear Company, Ltd.
G. Gonzalez Rey	ISPJAE	J.R. Partridge ...	Lufkin Industries, Inc.
M.A. Hartman ...	ITW	M. Pasquier	CETIM
J.M. Hawkins ...	Rolls-Royce Corporation	J.A. Pennell	Univ. of Newcastle-Upon-Tyne
G. Henriot	Consultant	A.E. Phillips	Rockwell Automation/Dodge
G. Hinton	Xtek, Incorporated	J.W. Polder	Delft University of Technology

E. Sandberg	Det Nordske Veritas	F.A. Thoma	F.A. Thoma, Inc.
C.D. Schultz	Pittsburgh Gear Company	D. Townsend	NASA/Lewis Research Center
E.S. Scott	The Alliance Machine Company	L. Tzioumis	Dodge
A. Seireg	University of Wisconsin	F.C. Uherek	Flender Corporation
Y. Sharma	Philadelphia Gear Corporation	A. Von Graefe	MAAG Gear AG
B.W. Shirley	Emerson Power Transmission	C.C. Wang	3E Software & Eng. Consulting
L.J. Smith	Invincible Gear Company	B. Ward	Recovery Systems, LLC
L. Spiers	Emerson Power Trans. Corp.	R.F. Wasilewski . . .	Arrow Gear Company
A.A. Swiglo	IIT Research Institute/INFAC	H. Winter	Technische Univ. Muenchen
J.W. Tellman	Dodge		

American Gear Manufacturers Association - Load Distribution Factors - Analytical Methods for Cylindrical Gears

1 Scope

This information sheet covers a method for the evaluation of load distribution across the teeth of parallel axis gears. A general discussion of the design and manufacturing factors which influence load distribution is included.

The load distribution factors for use in AGMA parallel axis gear rating standards are defined, to improve communication between users of those standards.

Historically, analytical methods for evaluating load distribution in both AGMA and ISO standards have been limited by the assumption that load is linearly distributed across the face width of the meshing gear set. The result of this assumption is often overly conservative (high) values of load distribution factors. The method given here is considered more correct.

1.1 Method

A simplified iterative method for calculation of the face load distribution factor, based on combined twisting and bending displacements of a mating gear and pinion, is presented. The transverse load distribution (in the plane of rotation) is not evaluated in this information sheet. This method assumes that the mesh stiffness is a constant through the entire contact roll and across the face. General guidance for design modifications to improve load distribution is also included.

1.2 Limitations of method

This method is intended to be used for general gear design and rating purposes. It is intended to provide a value of load distribution factor and a means by which different gear designs can be analytically compared. It is not intended for rigorous detailed analysis to calculate the actual distribution of load across the face width of gear sets.

The knowledge and judgment required to evaluate the results of this method come from experience in designing, manufacturing and operating gear units. This method is intended for use by the experienced gear designer, capable of understanding its limitations and purposes. It is not intended for use by the engineering public at large.

2 References

The following documents were used in the development of this information sheet. At the time of publication, the editions were valid. All publications are subject to revision, and the users of this manual are encouraged to investigate the possibility of applying the most recent editions of the publications listed:

AGMA Technical Paper P109.16, *Profile and Longitudinal Corrections on Involute Gears*, 1965

ANSI/AGMA 1012-F90, *Gear Nomenclature, Definitions Of Terms With Symbols*

ANSI/AGMA 2101-C95, *Fundamental Rating Factors And Calculation Methods For Involute Spur And Helical Gear Teeth*

ANSI/AGMA ISO 1328-1, *Cylindrical Gears - ISO System of Accuracy - Part 1: Definitions and Allowable Values of Deviations Relevant to Corresponding Flanks of Gear Teeth*

ISO 6336-1:1996, *Calculation of load capacity of spur and helical gears - Part 1: Basic principles, introduction and general influence factors*

Dudley, D.W., *Handbook of Practical Gear Design*, McGraw-Hill, New York, 1984

Timken Engineering Design Manual, Volume 1