

 Under Royalty Agreement

ANSI/AGMA 1003-G93

(Revision of AGMA 207.06-1974)

AMERICAN NATIONAL STANDARD

Tooth Proportions for Fine-Pitch Spur and Helical Gearing

ANSI/AGMA 1003-G93



AGMA STANDARD

Tooth Proportions for Fine-Pitch Spur and Helical Gearing
AGMA 1003-G93
Revision of AGMA 207.06-1974

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus, and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretation of this standard should be addressed to the American Gear Manufacturers Association.

CAUTION NOTICE: AGMA Standards are subject to constant improvement, revision, or withdrawal as dictated by experience. Any person who refers to any AGMA Technical Publication should be sure that the publication is the latest available from the Association on the subject matter.

[Tables or other self-supporting sections may be quoted or extracted in their entirety. Credit line should read: Extracted from AGMA 1003-G93, *Tooth Proportions for Fine-Pitch Spur and Helical Gearing*, with the permission of the publisher, the American Gear Manufacturers Association, 1500 King Street, Suite 201, Alexandria, Virginia 22314.]

Approved January 22, 1993

American National Standards Institute, Inc.

ABSTRACT:

Tooth proportions for fine pitch gearing are similar to those of coarse pitch gearing except in the matter of clearance. For 20 degree profile angle fine pitch gearing, this standard provides a system of enlarged pinions which use the involute form above 5 degrees of roll. Data on 14-1/2 and 25 degree profile angle systems are included in the annexes.

Copyright © 1992 by American Gear Manufacturers Association

Published by

American Gear Manufacturers Association
1500 King Street, Suite 201, Alexandria, Virginia 22314

ISBN: 1-55589-580-8

Contents

	Page
Foreword	v
1 Scope	
1.1 Tooth proportions	1
1.2 Number of teeth	1
1.3 References	1
2 Terms and symbols	
2.1 Terms	1
2.2 Symbols	1
3 General features	
3.1 Basic rack	3
3.2 Pressure angle and profile angle	3
3.3 Working depth	4
3.4 Addendum	4
3.5 Clearance	4
3.6 Tooth thickness and backlash	5
3.7 Whole depth	5
3.8 Generating tools	5
3.9 Tool tip radius	5
4 Basis for enlarged (long addendum) pinions	
4.1 Enlargement	5
4.2 Form diameter	7
4.3 Limit diameter	9
4.4 Top land	9
4.5 Undercut	9
4.6 Root diameter	10
4.7 Mating gear (standard)	10
4.8 Mating gear (reduced—short addendum)	10
4.9 Formula for enlargement of spur pinions	19
4.10 Standard center distance (for standard gears)	11
4.11 Standard center distance (for enlarged spur pinions and reduced gears)	11
4.12 Enlarged center distance (for enlarged spur pinion mating with a standard gear)	12
4.13 Center distance caution (enlarged pinion meshing with enlarged pinion)	13
4.14 Contact ratio	14
4.15 Enlargement criteria	14
4.16 Example (spur pinion center distance)	14

Tables

1	Terms and symbols	2
2	Standard diametral pitch tooth proportions and formulas (inch system)	6
2M	Standard module tooth proportions and formulas (metric system)	7
3	Standard diametral pitch tooth dimensions (in)	8
3M	Standard module tooth dimensions (mm)	8
4	20° Profile angle – enlarged spur pinions	12
5	20° Profile angle – reduced spur gears	13

Figures

1	Basic rack (normal plane)	4
2	Form diameter on undercut teeth	9
3	Form diameter on fillet blend teeth	9
4	Center distance and line of action	14

Annexes

A	Tooth proportions for 14–1/2 degree fine–pitch gearing	16
B	Tooth proportions for 25 degree fine–pitch gearing	18
C	Helical pinion enlargement	20
D	Calculations to obtain standard clearance for enlarged pinions and standard gears	22
E	References and bibliography	24

FOREWORD

[The foreword, footnotes, and annexes are provided for informational purposes only, and should not be construed as a part of ANSI/AGMA 1003-G93, *Tooth Proportions for Fine-Pitch Spur and Helical Gearing.*]

As originally developed by the American Gear Manufacturers Association, this standard was in two parts: the first part, *Clearance for 20-Degree Pressure Angle Fine-Pitch Gears* (AGMA 470.01); and the second, *20-Degree Involute Fine-Pitch System for Spur Gears* (AGMA 207.02).

In May, 1949, the two standards were combined and completely re-edited.

The next revision of this standard was begun in 1955.

As a result of the increasing use of gears by sintering and injection molding process, and for greater tooth strength, tooth forms for 25 degree pressure angle were included. Control gearing containing large numbers of teeth was recognized by data on the 14-1/2 degree pressure angle system in the information sheets.

AGMA 207.05, was approved by Sectional Committee B6 and by the sponsors, and designated USA Standard B6.7-1967 as of September 18, 1967.

Due to difficulties encountered in fabricating gears with involute profiles to the base circle, the Fine-Pitch committee developed a new set of tooth proportions for enlarged pinions that would not require active tooth profiles below the five degrees of roll.

AGMA 207.06 was approved by the Fine-Pitch Gearing Committee in June, 1971 and approved by the membership as of May, 1974.

AGMA 1003-G93 is a revision of AGMA 207.06.

The term "profile angle" was introduced in place of the basic rack "pressure angle."

Metric data were added, including ISO symbols. Tables for 20 degree profile angle were revised, and supported with simpler equations and procedures. The lower range of tooth numbers was redone with less enlargement and improved contact ratio and less specific sliding. Data for 7 and 8 tooth pinions were omitted, as they require special design consideration beyond the scope of this standard.

A revised procedure was employed to verify undercut limits, superseding the approximate and more conservative prior method.

Formulas were supplied for all tabulated data.

The data on helical gearing was revised using a simple procedure to allow helical configuration.

Information was added to clarify the distinction between form diameter as generated and the limit diameter established by operational contact which determines the contact ratio.

Clarification was made regarding categories of center distance which often was a source of confusion in the prior standard.

Cautionary notes were added to indicate meshes employing very small numbers of teeth, while geometrically correct, still require analyses for strength, durability, and clearances.

The 5 degree form diameter enlargement method was extended to include the 14-1/2 degree system, and revisions were made to the 25 degree system.

ANSI/AGMA 1003-G93 was approved by the Fine-Pitch Gearing Committee in February, 1992 and approved by the AGMA Board of Directors as of May, 1992.

Suggestions for the improvement of this standard are welcome. They should be sent to the American Gear Manufacturers Association, 1500 King Street, Suite 201, Alexandria, Virginia 22314.

PERSONNEL of the AGMA Committee for Fine Pitch Gearing

Chairman: Daniel E. Bailey Rochester Gear, Inc.

Editor: Leonard J. Smith Invincible Gear

ACTIVE MEMBERS

David A. Castor Eastman Kodak
Paul M. Dean, Jr. Honorary Member
F. Reed Estabrook, Jr. Consultant
Irving Laskin Consultant
John M. Mann Bison Gear
David McCarroll Gleason
Joseph R. Mihelick Reliance Electric Company
Robert C. Mills Eastman Kodak
David H. Senkfor Precision Gear
Robert E. Smith Consultant
George Thomas Bison Gear

ASSOCIATE MEMBERS

Charles R. Firestone Reliance Electric
Theodore J. Krenzer Gleason
George E. Olson Cleveland Gear
Joseph M. Olchawa Litton
Glenn R. Schwartz Power-Tech
Eugene E. Shipley Mechanical Technology
Joe L. Smallwood Smallwood & Son Machine Co.
Dominic A. Sylvester Power-Tech
Tomoichi Urabe Tsubakimoto Chain
Gary L. Vesey ITW/Spiroid

American National Standard – Tooth Proportions for Fine-Pitch Spur and Helical Gearing

1 Scope

This standard is applicable to external spur and helical gears with diametral pitch of 20 through 120 (1.25 through 0.2 module) and a profile angle of 20 degrees.

It only applies to standard gears with 24 teeth or more; enlarged pinions with 9 through 23 teeth; and reduced gears.

Much of this same information is applicable to internal gears.

1.1 Tooth proportions

The tooth proportions shown herein may be used for many gear designs of finer than 120 diametral pitch (0.2 module); however, such designs should be checked for suitability, particularly in the areas of contact ratio, undercutting, and clearance.

The spur gear portions of this standard closely follow AGMA 201.02, *Tooth Proportions for Coarse-Pitch Involute Spur Gears*.

The main difference between the proportions of fine-pitch gears and those of the coarse-pitch is in the clearance. In fine-pitch gearing, wear on the points of the cutting tools is proportionally greater than in coarse-pitch tools. The fillet radius produced by such tooling will therefore be proportionally greater. The increased clearance in gearing of 20 diametral pitch (1.25 module) and finer provides both for the relatively larger fillet and also for foreign material that tends to accumulate at the bottoms of the teeth.

1.2 Number of teeth

Gear designs with low numbers of teeth should be checked for suitability, particularly in the areas of contact ratio, undercutting, and clearance, as well as for strength and durability for load and life considerations.

1.3 References

The following standards contain provisions which, through reference in this text, constitute provisions of this American National Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this American National Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below.

AGMA 201.02, *Tooth Proportions for Coarse-Pitch Involute Spur Gears*

AGMA 370.01, *Design Manual for Fine-Pitch Gearing*

ANSI/AGMA 1012-F90, *Gear Nomenclature, Definitions of Terms with Symbols*

ANSI/AGMA 2002-B88, *Tooth Thickness Specification and Measurement*

ANSI B94.7 *Hobs*

ANSI B94.21 *Shaper Cutters*

2 Terms and symbols

2.1 Terms

The terms used, wherever applicable, conform to the following standards:

ANSI/AGMA 1012-F90, *Gear Nomenclature, Definitions of Terms with Symbols*

AGMA 904-B89, *Metric Usage*

2.2 Symbols

The symbols used in this standard are shown in table 1.