

AMERICAN NATIONAL STANDARD

***Cylindrical Wormgearing Tolerance and
Inspection Methods***

ANSI/AGMA 2011-A98



AGMA STANDARD

American National Standard

Cylindrical Wormgearing Tolerance and Inspection Methods

ANSI/AGMA 2011–A98

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing or using products, processes or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretation of this standard should be addressed to the American Gear Manufacturers Association.

CAUTION NOTICE: AGMA technical publications are subject to constant improvement, revision or withdrawal as dictated by experience. Any person who refers to any AGMA Technical Publication should be sure that the publication is the latest available from the Association on the subject matter.

[Tables or other self-supporting sections may be quoted or extracted. Credit lines should read: Extracted from ANSI/AGMA 2011–A98, *Cylindrical Wormgearing Tolerance and Inspection Methods*, with the permission of the publisher, the American Gear Manufacturers Association, 1500 King Street, Suite 201, Alexandria, Virginia 22314.]

Approved October 1, 1998

ABSTRACT

This standard describes and defines variations that may occur in unassembled wormgearing. It displays measuring methods and practices, giving suitable warnings if a preferred probe cannot be used. The applicability of single or double flank composite testing is discussed, using a reference gear. Tooth thickness measurement is shown using direct measurement as well as the use of measurements over wires or pins. Equations for the maximum variations are given for the stated ranges, as a function of size, pitch and tolerance grade.

Published by

**American Gear Manufacturers Association
1500 King Street, Suite 201, Alexandria, Virginia 22314**

Copyright © 1998 by American Gear Manufacturers Association
All rights reserved.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without prior written permission of the publisher.

Printed in the United States of America

ISBN: 1–55589–716–9

Contents

	Page
Foreword	iv
1 Scope	1
2 Symbols, terms and definitions	1
3 Manufacturing and purchasing considerations	5
4 Measuring methods and practices	7
5 Equations for worm and wormgear tolerances	20

Tables

1 Symbols used	2
----------------------	---

Figures

1 Functional part of the profile – cutoff points, drop-off region	4
2 Lead and lead form variation	4
3 Worm thread runout inspection, V_{rW}	7
4 Worm pitch variation inspection, V_{pW} – method A	8
5 Worm pitch variation inspection, V_{pW} – method B	9
6 Worm thread profile inspection, $V_{\phi W}$	10
7 Worm thread profile tolerance band, $V_{\phi TW}$	10
8 Worm thread lead inspection, V_{lW}	11
9 Wormgear tooth runout, V_{rG}	12
10 Location of probe – wormgear pitch variation, V_{pG}	13
11 Two probe device	13
12 Schematic of single probe device	14
13 Relationships of pitch variation, V_{pG} , and accumulated pitch variation, V_{apG} ..	15
14 Pitch variation, V_{pG} , graphical data from two probe device	15
15 Pitch variation V_{pG} , and accumulated pitch variation, V_{apG} : graphical data from single probe device	15
16 Schematic of a double flank wormgear tester	17
17 Schematic of a single flank wormgear tester	17
18 Thread thickness measurement by means of a gear tooth caliper	18
19 Thread thickness measurement over pins	18

Annexes

A Inspection tolerance tables	21
-------------------------------------	----

Bibliography	43
---------------------------	-----------

Foreword

[The foreword, footnotes and annexes, if any, in this document are provided for informational purposes only and are not to be construed as a part of ANSI/AGMA Standard 2011–A98, *Cylindrical Wormgearing Tolerance and Inspection Methods*.]

The purpose of this standard is to establish geometrical accuracy communication between a manufacturer and purchaser of unassembled cylindrical wormgearing with axes at right angles.

AGMA 390.02 September 1964 was a replacement for AGMA 234.01 for fine pitch wormgearing. ANSI/AGMA 2000–A88 is a partial revision of AGMA 390.03, but does not cover wormgearing. AGMA 390.03a of 1988 still only covered fine pitch wormgearing. ANSI/AGMA 2011–A98 then is a replacement for AGMA 390.03a for fine pitch wormgearing. In addition, it also covers coarse pitch wormgearing.

The Cylindrical Wormgearing Committee began working on this standard in August, 1993. At that time, it was determined the International Standards Organization's (ISO) method for tolerance grades would be used in this standard.

ANSI/AGMA 2011–A98 was approved by the AGMA membership in June, 1998 and approved as an American National standard on October 1, 1998.

Suggestions for improvement of this standard will be welcome. They should be sent to the American Gear Manufacturers Association, 1500 King Street, Suite 201, Alexandria, Virginia 22314.

PERSONNEL of the AGMA Cylindrical Wormgearing Committee

Chairman: J.R. DeMarais Bison Gear & Engineering Corporation
Vice Chairman: R.J. Dickhaus Boston Delroyd Operations

ACTIVE MEMBERS

J. Bentley Peerless–Winsmith, Inc.
G. Estell Accurate Specialties
J. Forberg Baldor Motors & Drives
V. Kin David Brown Metrology Systems
S. Moulis Emerson Power Transmission
G.E. Olson Olson Engineering Service
G.M. Sawchak Rexnord Corporation
E. Tzioumis Rockwell Automation/Dodge
F.C. Uherek Flender Corporation
R.J. Will Boston Delroyd Operations (Retired)

ASSOCIATE MEMBERS

R.E. Bergmann Gear Research Institute
M. Brown Skidmore Gear Company
J. Cadisch Reishauer, Ltd.
A.S. Cohen Engranes y Maquinaria Arco
M. Engesser Reishauer Corporation
R.J. Ericson Otis Elevator Company
R.K. Glatt Flender Corporation
G. Henriot Ingenieur Conseil
W.A. Johnson Cone Drive Operations
T. Keenan Emerson Power Transmission
D. Laing Cleveland Gear Company
J.R. Mihelick Rockwell Automation/Dodge
W.P. Pizzichil Philadelphia Gear Corporation
J.T. Rawlinson Renold, Inc.
P.N. Salvucci Boston Gear Division
H.O. Schlenker Hub City, Inc.
J. Simonelli Emerson Power Transmission
R.E. Smith R.E. Smith & Company, Inc.
L.J. Smith Invincible Gear Company
L. Spiers Emerson Power Transmission
R. Stephens Regal–Beloit Corporation
D. Stieren NIST
J.W. Tellman Retired
D. Von Eschen Hub City, Inc.
G.I. Wyss Reishauer Corporation

(This page is intentionally left blank.)

American National Standard – Cylindrical Wormgearing Tolerance and Inspection Methods

1 Scope

This standard establishes a classification system which may be used to communicate geometrical accuracy specifications of unassembled cylindrical wormgearing with axes at right angles. It also provides information on measuring methods and practices. This standard provides the gear manufacturer and the gear purchaser with a mutually advantageous reference for uniform tolerances and inspection procedures. Tolerance grades 3 through 12 are defined in this standard and are based on the relative effect of geometrical errors on conjugate action for wormgear sets acting as speed reducers.

1.1 Tolerance equations and tables

Tolerance equations are provided in clause 5 for calculating the maximum values allowed by the specific tolerance grade. Tables are provided in annex A for reference.

1.2 Measuring methods and practices

Measuring methods and practices are included in order to promote uniform inspection procedures (see clause 4). These methods permit the manufacturer and purchaser to conduct measuring procedures which are accurate and repeatable to a degree compatible with the specified tolerance grade.

1.3 Exceptions

This standard applies to individual worm and gear components. It does not establish a tolerance grade for enclosed drive assemblies. Establishing ratings based on tolerance grade is beyond the scope of this standard. Gear design and backlash are also beyond the scope of this standard. Refer to the latest

AGMA Publications Catalog for applicable standards. This standard does not apply to worms with mean diameters larger than 16 inches, nor does it apply to wormgears with mean diameters larger than 100 inches. This standard does not apply to geometry finer than 0.063 axial pitch. This standard does not apply to spiral gears or any type other than cylindrical single enveloping wormgearing.

1.4 Limitations

The American Gear Manufacturers Association makes no representation, warranty or guarantee in connection with the publication of any AGMA Standard and hereby expressly disclaims any liability or responsibility for loss or damage resulting from their use. Similarly, violation of any federal, state or municipal regulation with which an AGMA Standard may conflict, or for the infringement of any patent resulting from the use of an AGMA Standard is the responsibility of the user.

2 Symbols, terms and definitions

The symbols, terms and definitions used in this standard are, wherever possible, consistent with ANSI/AGMA 1012–F90 and other approved AGMA documents.

2.1 Symbols

Table 1 is a list of the symbols used in this standard, along with the associated terms. The “Where first used” column gives the clause or equation number where the particular symbol is first used.

2.2 Definition of terms

axial plane: The axial plane is the plane containing the line of axis of the worm. Diameters may be measured in this plane but thread surfaces would require a theoretical knife edge measurement. These measurements may be obtained by indirect means using normal plane measurements. The probe measurement in Method “A” will give a direct axial measurement, however, since the normal to probe center is repeated at each point.

datum thread: The designated thread used as the starting point for measuring other threads.