



American
Gear Manufacturers
Association

Technical Resources

Replaces ANSI/AGMA 2000-A88
Reaffirmed March 2014

American National Standard

Accuracy Classification System - Tangential Measurements for Cylindrical Gears

American National Standard

Accuracy Classification System - Tangential Measurements for Cylindrical Gears

ANSI/AGMA 2015-1-A01

[Revision of ANSI/AGMA 2000-A88]

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus, and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretation of this standard should be addressed to the American Gear Manufacturers Association.

CAUTION NOTICE: AGMA technical publications are subject to constant improvement, revision, or withdrawal as dictated by experience. Any person who refers to any AGMA technical publication should be sure that the publication is the latest available from the Association on the subject matter.

[Tables or other self-supporting sections may be quoted or extracted. Credit lines should read: Extracted from ANSI/AGMA 2015-1-A01, *Accuracy Classification System - Tangential Measurements for Cylindrical Gears*, with the permission of the publisher, the American Gear Manufacturers Association, 1500 King Street, Suite 201, Alexandria, Virginia 22314.]

Approved August 1, 2002

ABSTRACT

This standard, for spur and helical gearing, correlates gear accuracy grades with gear tooth tolerances. It provides information on minimum requirements for accuracy groups as well as gear measuring practices. Annex material provides guidance on filtering and information on comparison of gear inspection methods.

Published by

**American Gear Manufacturers Association
1500 King Street, Suite 201, Alexandria, Virginia 22314**

Copyright © 2002 by American Gear Manufacturers Association
All rights reserved.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without prior written permission of the publisher.

Printed in the United States of America

ISBN: 1-55589-797-5

Contents

	Page
Foreword	iv
1 Scope	1
2 Normative references	1
3 Symbols, terminology and definitions	2
4 Manufacturing and purchasing considerations	8
5 Application of the AGMA classification system	14
6 Measuring methods and practices	14
7 Tolerance values	14
8 Master gears	16

Annexes

A Tolerance tables	17
B Tolerance system development and comparison	21
C Example of statistical process control (SPC) application	31
D Involute and helix data filtering	33
E Sector pitch deviation	35
Bibliography	37

Figures

1 Helix deviations	4
2 Profile deviations	5
3 Functional profile	6
4 Pitch deviations	7
5 Illustration of AGMA classification number	14

Tables

1 Alphabetical table of terms with symbols, by terms	2
2 Alphabetical table of symbols with terms, by symbols	3
3 Reference for methods and tolerances	9
4 Gear types and measurement methods	10
5 Minimum number of measurements	10

Foreword

[The foreword, footnotes and annexes, if any, in this document are provided for informational purposes only and are not to be construed as a part of ANSI/AGMA Standard 2015-1-A01, *Accuracy Classification System - Tangential Measurements for Cylindrical Gears*.]

This standard provides tolerances for different gear accuracy grades from A2 to A11 for unassembled spur and helical gears. Applicable definitions are provided.

The purpose is to provide a common basis for specifying accuracy, and for the procurement of unassembled gears. It is not a design manual for determining the specific quality levels for a given application.

AGMA 390.03 of 1973 was a consolidation of several AGMA publications, including:

AGMA 235.02 (Feb. 1966), *Information Sheet for Master Gears*

AGMA 239.01 (Oct. 1965), *Measuring Methods and Practices Manual for Control of Spur, Helical and Herringbone Gears*

AGMA 239.01A (Sept. 1966), *Measuring Methods and Practices Manual for Control of Bevel and Hypoid Gears*, and parts of

AGMA 236.05 (ASA B6.11, June 1956), *Inspection of Fine-Pitch Gears*

AGMA 390.02 (Sept. 1964), *Gear Classification Manual* originally published as AGMA 390.01 (1961)

Data was added for Gear Rack and Fine-Pitch Worms and Wormgears. The former AGMA 390.02 for Coarse-Pitch and Fine-Pitch Spur, Helical and Herringbone Gearing was enhanced to offer a single, compatible classification system. The tolerance identifier "Q" was added to indicate that the tolerances in 390.03 apply. If Q is not used as a prefix in the quality number, tolerances in AGMA 390.01 and 390.02 applied.

ANSI/AGMA 2000-A88 was an update of those sections from AGMA 390.03 for parallel axis gears only. Additionally, the formulas stated the tolerances in metric terms. The content was revised, but basic tolerance levels were unchanged from AGMA 390.03. The other material in AGMA 390.03 on Bevels and Worms was replaced by ANSI/AGMA 2009-A99 and ANSI/AGMA 2011-A98, respectively. ANSI/AGMA 2000 was approved by AGMA membership in January 1988, and as a American National Standard Institute (ANSI) standard on March 31, 1988.

The user of this American National Standard is alerted that differences exist between it and ANSI/AGMA 2000-A88. Differences include, but are not limited to:

- Accuracy grade numbering system is reversed, such that the smallest number represents the smallest tolerance;
- Relative magnitudes of elemental tolerances for a single grade are in a different proportion;
- The "helix evaluation range", where the tolerances are applied, are defined for less flank area than in ANSI/AGMA 2000-A88;
- The "K Chart" is not used for the permissible tolerance values;
- Runout is not included as one of the elements with a tolerance;
- Concepts of "mean measurement trace", "design profile", "slope deviation" and "form deviation" are added, similar to ISO 1328-1.

Therefore, the user of ANSI/AGMA 2015-1-A01 must be very careful when comparing tolerance values formerly specified using ANSI/AGMA 2000-A88.

ANSI/AGMA 2015-1-A01 is a replacement for ANSI/AGMA 2000-A88 and ANSI/AGMA ISO 1328-1. It is a complete revision, including accuracy grades, in order to be more compatible with ISO. It combines the grading system of ISO 1328-1 with the methods of ANSI/AGMA 2000-A88, and adds concepts of accuracy grade grouping for minimum measurement requirements, filtering, data density, and roughness limits to form deviations.

This revision was started by the AGMA Inspection and Handbook Committee in 1997. It was approved by the AGMA membership in June, 2001. It was approved as an American National Standard on August 1, 2002.

Suggestions for improvement of this standard will be welcome. They should be sent to the American Gear Manufacturers Association, 1500 King Street, Suite 201, Alexandria, Virginia 22314.

PERSONNEL of the AGMA Inspection and Handbook Committee

Chairman: Edward Lawson M&M Precision Systems Corp.

ACTIVE MEMBERS

D.R. Choiniere . . Profile Engineering, Inc.
J. Clatworthy Gear Metrology, Inc.
B.L. Cox BWXT Y-12, LLC
T.C. Glasener . . . Xtek, Incorporated
G.G. Grana The Gleason Works
B. Hofrichter Arrow Gear Company
I. Laskin Consultant

S. Lindley The Falk Corporation
M. May The Gleason Works
D.A. McCarroll . . . ZF Industries
D.R. McVittie Gear Engineers, Inc.
S. Moore Martin Sprocket & Gear, Inc.
L.J. Smith Consultant
R.E. Smith R.E. Smith & Company, Inc.

ASSOCIATE MEMBERS

M. Antosiewicz . . The Falk Corporation
M.J. Barron Gear Motions, Inc.
D. Behling Hamilton Sundstrand Aero.
M.K. Considine . . Considine Associates
R. Considine Considine Associates
J.S. Cowan Eaton Corporation
M.E. Cowan Process Equipment Co.
B. Cowley Mahr Corporation
C. Dick The Horsburgh & Scott Co.
H.D. Dodd Caterpillar, Inc.
R. Green R-7 Group, Gear Consultants
D. Gregory Gear Products, Inc.
B. Gudates Fairfield Manufacturing Co., Inc.
J.S. Hamilton Regal-Beloit Corporation
H. Harary NIST
D. Heinrich Xtek, Incorporated
G. Henriot Consultant
J. Horwell Brown & Sharpe
S. Johnson The Gear Works - Seattle, Inc.
T. Klemm Liebherr
D.E. Kosal National Broach & Machine Co.
J. Koshiol Columbia Gear Corporation

W.E. Lake Mitsubishi Gear Tech.Center (AG)
A.J. Lemanski Penn State University
G.A. Luetkemeier . . Rockwell Automation/Dodge
D. Matzo Northwest Gears, Inc.
P.A. McNamara Caterpillar, Inc.
W.J. Michaels Sundstrand Corporation
M. Milam Amarillo Gear Company
T. Miller The Cincinnati Gear Company
M. Nanlawala IIT Research Institute/INFAC
M. Octrue Centre Technique Des Ind. Mec.
T. Okamoto Nippon Gear Company, Ltd.
J.A. Pennell Univ. of Newcastle-Upon-Tyne
K.R. Price Eastman Kodak Company
R.S. Ramberg The Gear Works - Seattle, Inc.
V.Z. Rychlinski Brad Foote Gear Works, Inc.
D.H. Senkfor Precision Gear Company
S. Shariff PMI Food Equipment Group
E. Storm Consultant
T. Waldie Philadelphia Gear Corporation
R.F. Wasilewski . . . Arrow Gear Company
F.M. Young Forest City Gear Company
P. Zwart Caterpillar, Inc.

American National Standard – Accuracy Classification System – Tangential Measurements for Cylindrical Gears

1 Scope

This part of ANSI/AGMA 2015 establishes an accuracy grade system relevant to tangential measurements on flanks of individual cylindrical involute gears.

It specifies definitions for gear tooth accuracy terms, the structure of the gear accuracy grade system, and allowable values.

It is strongly recommended that any user of this part of ANSI/AGMA 2015 be very familiar with the methods and procedures outlined in AGMA 915-1-A02. Use of techniques other than those of AGMA 915-1-A02 combined with the limits described in this part of ANSI/AGMA 2015 may not be suitable.

This standard provides the gear manufacturer and the gear buyer with a mutually advantageous reference for uniform tolerances. Ten accuracy grades are defined in this standard, numbered A2 through A11, in order of decreasing precision.

1.1 Equations for tolerances

Equations for tolerances and their ranges of validity are provided in 7.2 for the defined accuracy of gearing. In general, these tolerances cover the following ranges:

$$\begin{aligned} 5 &\leq z \leq 1000 \text{ or } 10\,000/m_n \text{ whichever is less} \\ 5 \text{ mm} &\leq D \leq 10\,000 \text{ mm} \\ 0.5 &\leq m_n \leq 50 \\ 4 \text{ mm} &\leq b \leq 1000 \text{ mm} \\ \beta &\leq 45^\circ \end{aligned}$$

where

- D is pitch diameter;
- m_n is normal module;
- b is facewidth (axial);
- z is number of teeth;
- β is helix angle.

See clause 4 for required and optional measuring methods.

1.2 Exceptions

This standard does not apply to enclosed gear unit assemblies, including speed reducers or increasers, gear motors, shaft mounted reducers, high speed units, or other enclosed gear units which are manufactured for a given power, speed, ratio or application.

Gear design is beyond the scope of this standard. The use of the accuracy grades for the determination of gear performance requires extensive experience with specific applications. Therefore, the users of this standard are cautioned against the direct application of tolerance values to a projected performance of unassembled (loose) gears when they are assembled. Refer to the latest AGMA Publications Index for applicable standards.

NOTE: Tolerance values for gears outside the limits stated in this standard should be established by determining the specific application requirements. This may require setting a tolerance smaller than calculated by the formulas in this standard.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this American National Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this American National Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below.

AGMA 915-1-A02, *Inspection Practices – Part 1: Cylindrical Gears – Tangential Measurements*

AGMA 915-3-A99, *Inspection Practices – Gear Blanks, Shaft Center Distance and Parallelism*