



American
Gear Manufacturers
Association

Technical Resources

Revision of AGMA 170.01
Reaffirmed May 2008

American National Standard

Design Guide for Vehicle Spur and Helical Gears

Design Guide for Vehicle Spur and Helical Gears ANSI/AGMA 6002–B93

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus, and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretation of this standard should be addressed to the American Gear Manufacturers Association.

CAUTION NOTICE: AGMA Standards are subject to constant improvement, revision, or withdrawal as dictated by experience. Any person who refers to any AGMA Technical Publication should be sure that the publication is the latest available from the Association on the subject matter.

[Tables or other self-supporting sections may be quoted or extracted in their entirety. Credit lines should read: Extracted from ANSI/AGMA 6002–B93, *Design Guide for Vehicle Spur and Helical Gears*, with the permission of the publisher, the American Gear Manufacturers Association, 1500 King Street, Suite 201, Alexandria, Virginia 22314].

Approved February 5, 1993

American National Standards Institute, Inc.

ABSTRACT

This standard provides the engineer, who is familiar with gear designing, a guide to sound design approaches for vehicle gear applications. It is the updated and expansion of AGMA 170.01–1976 *Design Guide for Vehicle Spur and Helical Gears*.

Through this standard, the engineer is guided to selecting design considerations paramount to the parallel axis gear sets required in vehicle drive lines. These include tooth and blank proportions, lubrication, profile and lead modification requirements, and gear tooth tolerances. Properties of the commonly used steels and processes for their heat treatment are outlined, as well as details for calculating design limits for bending and contact stresses.

An annex is provided detailing sample problems showing design procedures and calculations.

For full effectiveness, this guide should be used in conjunction with other applicable AGMA Standards.

Copyright ©, 1993 by American Gear Manufacturers Association

Published by

**American Gear Manufacturers Association
1500 King Street, Suite 201, Alexandria, Virginia, 22314**

ISBN: 1–555898–616–2

Contents

	Page
Foreword	v
1 Scope	
1.1 Use	1
1.2 Applications	1
1.3 References	1
1.4 Definitions and symbols	1
2 Design considerations	
2.1 Size and weight limitations	3
2.2 Tooth proportions	3
2.3 Typical design values	3
2.4 Long and short addendums	4
2.5 Non-standard center distances	4
2.6 Sliding velocities	4
2.7 Rim proportion	5
2.8 Heat treat variation	5
2.9 Involute profile modifications	5
2.10 Lead crowning (tooth alignment)	5
2.11 Axial lead (tooth alignment) modifications	6
2.12 Lubrication	6
2.13 Gear tolerances	7
2.14 Noise considerations	7
3 Materials and heat treatment	
3.1 Material selection	7
3.2 Case carburized steels	8
3.3 Induction and flame hardening	11
3.4 Guide for minimum case depth	16
3.5 Other hardening methods	16
3.6 Shot peening	18
4 Determination of load capacity	
4.1 Capacity to resist bending fatigue	20
4.2 Capacity to resist pitting	21
4.3 Capacity to resist scuffing	24
5 Variable loading	
5.1 Introduction	33
5.2 Miner's rule	33
5.3 Procedure	34
5.4 Overload factors	35
5.5 Failure mode	35
Tables	
1 Symbols and terms	2
2 Total profile modification in vehicle gearing to compensate for bending under load	5
3 Carburizing steels commonly used for vehicle spur and helical gears	8
4 Major metallurgical factors affecting carburized and hardened gears	9
5 Flame and induction hardening materials commonly used for spur and helical gears	14
6 Major metallurgical factors affecting flame or induction hardened gears	15
7 Major metallurgical factors affecting through hardened gears	18

Contents (cont)

	Page
8	Major metallurgical factors affecting nitrided gears 19
9	Typical standard addendum spur gear Hertz factor, C_K , and Bending stress factor, C_t , normal pressure angle 20 degrees 25
10	Typical 1.25 pinion addendum spur gear Hertz factor, C_K , and bending stress factor, C_t , normal pressure angle 20 degrees 25
11	Typical 1.25 pinion addendum spur gear Hertz factor, C_K , and bending stress factor, C_t , normal pressure angle 20 degrees 26
12	Typical standard addendum spur gear Hertz factor, C_K , and bending stress factor, C_t , normal pressure angle 25 degrees 26
13	Typical 1.25 pinion addendum spur gear Hertz factor, C_K , and bending stress factor, C_t , normal pressure angle 25 degrees 27
14	Typical standard addendum helical gear Hertz factor, C_K , and bending stress factor, C_t , normal pressure angle 20 degrees 27
15	Typical standard addendum helical gear Hertz factor, C_K , and bending stress factor, C_t , normal pressure angle 20 degrees 28
16	Typical standard addendum helical gear Hertz factor, C_K , and bending stress factor, C_t , normal pressure angle 25 degrees 28
17	Typical standard addendum helical gear Hertz factor, C_K , and bending stress factor, C_t , normal pressure angle 25 degrees 29
18	Typical 1.25 pinion addendum helical gear Hertz factor, C_K , and bending stress factor, C_t , normal pressure angle 20 degrees 29
19	Typical 1.25 pinion addendum helical gear Hertz factor, C_K , and bending stress factor, C_t , normal pressure angle 20 degrees 30
20	Typical 1.25 pinion addendum helical gear Hertz factor, C_K , and bending stress factor, C_t , normal pressure angle 25 degrees 30
21	Typical 1.25 pinion addendum helical gear Hertz factor, C_K , and bending stress factor, C_t , normal pressure angle 25 degrees 31
22	Typical derating factor for vehicle spur and helical gears 31
23	Allowable bending stress number, s_{at} , for steel gears 32
24	Allowable contact stress number, s_{ac} , for steel gears 33

Figures

1	Minimum addendum to eliminate undercut on 1 $P_d(25.4 m_n)$ vehicle full depth spur gears . . . 4
2	Lead tolerances (tooth alignment) for crowned tooth 6
3	Typical tooth profile tolerance chart 7
4	Case hardened tooth cross section 12
5	Depth of effective case at mid-tooth height for spur and helical gears, for carburized and Type A induction 12
6	Variations in hardening patterns obtainable on gear teeth with flame or induction hardening 13
7	Core hardness coefficient for nitrided gears, U_C 17
8	Minimum total case depth for nitrided gears, h_C 17
9	Bending stress design limits, carburize and harden, induction Type A (contour) hardened 22
10	Bending stress design limits, induction and flame hardened 23
11	Contact stress design limits for steel gears 24
12	Duty cycle curve 34

Annex

A	Sample problems 36
---	------------------------------

FOREWORD

[The foreword, footnotes, and annexes, if any, are provided for informational purposes only, and should not be construed as part of American Gear Manufacturers Association Standard 6002–B93, *Design Guide for Vehicle Spur and Helical Gears*.]

This standard was prepared by the AGMA Vehicle Gearing Committee. It is provided as a guide to sound approaches for designing gears used in vehicle drive lines. This guide is intended for use by design engineers capable of selecting reasonable values for rating factors, material grades, heat treatment, and gear manufacturing capabilities. It updates, expands, and replaces AGMA 170.01–1976, *Design Guide for Vehicle Spur and Helical Gears*. The committee intends to continue updating this standard to incorporate the latest data and technologies as they are developed.

This guide establishes a gear set design by following a sequential approach using:

- a) Design considerations;
- b) Material and heat treatment;
- c) Load capacity determination;
- d) Variable loading.

The decision to produce a vehicle gearing design guide was made by the Vehicle Gearing Committee on May 4, 1971. The first draft of AGMA 170.01 was dated May 1972. Standard AGMA 170.01 was approved by the Committee in July 1974, by the Board of Directors and Technical Division Executive Committee in July 1975 and by the AGMA membership as of February 1976.

The Vehicle Gearing Committee was reactivated in October 1987 to develop an updated vehicle gearing design guide.

ANSI/AGMA 6002–B93 was approved by the Committee in February 1990, by the Board of Directors and Technical Division Executive Committee in September 1992, and by the AGMA membership in November 1992.

Suggestions for the improvement of this standard will be welcome. They should be sent to the American Gear Manufacturers Association, 1500 King Street, Suite 201, Alexandria, Virginia, 22314.

PERSONNEL of the AGMA Committee for Vehicle Gearing

Chairman: M. R. Chaplin Contour Hardening
Vice Chairman: T. McGinty McGinty Gear

ACTIVE MEMBERS

E. R. Braun	Eaton Corporation	A. Mankowski	Columbia Gear
D. Brownlie	Dana Corporation	R. Miller	Fairfield
D. Crouch	Metal Improvement	J. A. Nelson	General Electric
C. Dieterle	C-Dot Engineering	O. Olson	Eaton Corporation
K. Ho	G.M. Gear Center	L. J. Smith	Invincible Gear
F. T. Huscher	Rockwell Intl.	D. Thurman	Caterpillar
W. Karrasch	Outboard Marine Corp (retired)	J. Vaughn	Cloyes Gear Company
J. M. Lange	American Pfauter	L. Wang	Getrag Gears of North America
W. McVea	Clark-Hurth	E. Wudi	Dana Corporation

ASSOCIATE MEMBERS

J. Bentley	Peerless/Winsmith	O. A. LaBath	Cincinnati Gear
G. L. Bowers	General Motors/ATD	B. W. McCoy	Marathon LeTourneau
M. Browne	Reishauer Limited	R. H. Moderow ...	ITW/Illitron
C. Buscema	Sier-Bath	J. L. O'Berry	ITW/Illinois Tools
J. Cadisch	Reishauer	G. E. Olson	Cleveland Gear
J. Clatworthy	Gleason	P. B. Patel	Cummins Engine
J. F. Craig	Cummins Engine	R. L. Platt	General Motors/ATD
F. W. Cumbow ...	M&M Precision	P. C. Renzo	Sier-Bath
D. E. DeRocker ..	Sier-Bath	N. Revenaugh ...	Dana Corporation
D. W. Dudley	Honorary Member	T. Riley	NWL Control System
J. Eaton	Liebherr Machine Tool	L. Schnipke	SPECO Corporation
J. Eckersley	Metal Improvement	E. R. Sewall	Sewall Gear
P. A. Eicher	Reishauer	I. Shearing	Liebherr Machine Tool
J. A. Ferrett	National Broach	E. E. Shipley	Mechanical Technology
P. Fox	Clark Components Intl.	R. E. Smith	Consultant
F. M. Hager	Cummins Engine	E. L. Storm	Eaton Corporation
J. S. Hamilton	Ohio Richmond	M. Sullivan	Dana Corporation
J. Hamilton	Cloyes Gear	D. A. Sylvester ...	Foote-Jones
E. Hawkinson	Metal Finishing	P. Vogel	Reishauer
B. Hicks	Eaton Corporation	D. Vukovich	Eaton Corporation
D. L. Hillman	Komatsu Dresser	T. P. Wagner	General Motors/ATD
D. E. Imwalle	Cincinnati Gear	D. Webb	Fairfield
I. Kalns	Eaton Corporation	R. A. Weinreber ..	Gleason
A. Karvelis	Borg-Warner Research Ctr	G. I. Wyss	Reishauer
F. Krist	Mercury Marine		

American National Standard – Design Guide for Vehicle Spur and Helical gears

1 Scope

1.1 Use

This standard provides information on the design of spur and helical vehicle power transmission gears. Included are considerations for design, material and heat treatment, determination of load capacity, mounting features, and typical design problems.

In determining load capacity, the knowledge and judgment required to evaluate the various rating factors come from years of accumulated experience in designing, manufacturing, and operating gear units. This standard is intended for use by the experienced gear designer, capable of selecting reasonable values for the rating factors. It is not intended for use by the engineering public at large.

1.2 Applications

Vehicle Gearing is defined as: "Drive line components of self-propelled, wheeled or non-wheeled vehicles; for transportation, recreational or industrial use. Propulsion of these vehicles should be a primary function of its power source, and its mobility not confined to the constraints of a closely defined area."

1.3 References

The following standards contain provisions which, through reference in this text, constitute provisions of this American National Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this American National Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below.

AGMA 246.02A, *Recommended Procedure for Carburized Aerospace Gearing*.

AGMA 908-B89, *Geometry Factors for Determining the Pitting Resistance and Bending Strength of Spur, Helical, and Herringbone Gear Teeth*.

ANSI/AGMA 2000-A88, *Gear Classification and Inspection Handbook*.

ANSI/AGMA 2001-B88, *Fundamental Rating Factors and Calculation Methods for Involute Spur and Helical Gear Teeth*.

ANSI/AGMA 2007-B92, *Surface Temper Etch Inspection After Grinding*.

ANSI/AGMA 6033-A88, *Standard for Marine Propulsion Gear Units, Part 1, Materials*.

ANSI/SAE AMS 2301G, *Magnetic Particle Inspection, Aircraft-Quality Steel Cleanliness*.

ASTM A388-80, *Recommended Practice for Ultrasonic Examination of Heavy Steel Forgings*.

ASTM A534-87, *Standard Specification for Carburizing Steels for Anti-Friction Bearings*.

ASTM A609-83, *Specification for Steel Castings, Carbon and Low Alloy, Ultrasonic Examination Thereof*.

ASTM E428-71, *Recommended Practice for Fabrication and Control of Steel Reference Blocks Used in Ultrasonic Inspection*.

ASTM E709-80, *Magnetic Particle Examination*.

1.4 Definitions and symbols

1.4.1 Definitions

The terms used, wherever applicable, conform to the following standards:

ANSI/AGMA 1012-F90, *Gear Nomenclature, Definitions of Terms with Symbols*

AGMA 904-B89, *Metric Usage*

ANSI Y10.3-1968, *Letter Symbols for Quantities Used in Mechanics of Solids*

1.4.2 Symbols

The symbols used in the pitting resistance and bending strength formulas are shown in table 1.

NOTE – The symbols and definitions used in this standard may differ from other AGMA Standards. The user should not assume that familiar symbols can be used without a careful study of these definitions.