

ANSI/AGMA 6014-A06

Reaffirmed September 2012

AMERICAN NATIONAL STANDARD

***Gear Power Rating for Cylindrical Shell
and Trunnion Supported Equipment***

ANSI/AGMA 6014-A06



AGMA STANDARD

American National Standard

Gear Power Rating for Cylindrical Shell and Trunnion Supported Equipment ANSI/AGMA 6014-A06

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus, and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretation of this standard should be addressed to the American Gear Manufacturers Association.

CAUTION NOTICE: AGMA technical publications are subject to constant improvement, revision, or withdrawal as dictated by experience. Any person who refers to any AGMA technical publication should be sure that the publication is the latest available from the Association on the subject matter.

[Tables or other self-supporting sections may be referenced. Citations should read: See ANSI/AGMA 6014-A06, *Gear Power Rating for Cylindrical Shell and Trunnion Supported Equipment*, published by the American Gear Manufacturers Association, 500 Montgomery Street, Suite 350, Alexandria, Virginia 22314, <http://www.agma.org>.]

Approved October 18, 2006

ABSTRACT

This standard specifies a method for rating the pitting resistance and bending strength of open or semi-enclosed spur, single helical, double helical, and herringbone gears made from steel and spheroidal graphitic iron for use on cylindrical shell and trunnion supported equipment such as cylindrical grinding mills, kilns, coolers and dryers. Annexes cover installation, alignment, maintenance, lubrication, and a rating method for gears made from ausferritic ductile iron.

Published by

American Gear Manufacturers Association
500 Montgomery Street, Suite 350, Alexandria, Virginia 22314

Copyright © 2006 by American Gear Manufacturers Association
All rights reserved.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without prior written permission of the publisher.

Printed in the United States of America

ISBN: 1-55589-876-9

Contents

	Page
Foreword	v
1 Scope	1
2 Normative references	2
3 Definitions and symbols	3
4 Application	5
5 Criteria for tooth capacity	7
6 Rating formulas	9
7 Geometry factors, I and J	10
8 Dynamic factor, K_{vm}	10
9 Elastic coefficient, C_p	12
10 Service factor	12
11 Hardness ratio factor, C_H	13
12 Load distribution factor, K_m	14
13 Allowable stress numbers, s_{ac} and s_{at}	16
14 Momentary overloads	30
15 Stress cycle factors, Z_N and Y_N	31
 Bibliography	 71
 Annexes	
A New equipment installation and alignment	33
B Drive characteristics – Multiple pinion drives	35
C Rim thickness/deflection	38
D Open gearing lubrication	40
E Sample problems	44
F Material mechanical properties	58
G Operation and maintenance	59
H Ausferritic ductile iron (ADI)	61
I Service factors	67
J Method for determination of dynamic factor with AGMA 2000–A88	69
 Figures	
1 Rim thickness factor, K_{Bm}	10
2 Dynamic factor, K_{vm}	11
3 Hardness ratio factor, C_H	13
4 Pinion proportion factor, C_{pf}	15
5 Mesh alignment factor, C_{ma}	16
6 Allowable contact stress number for through hardened steel gears, s_{ac}	18
7 Allowable bending stress number for through hardened steel gears, s_{at}	18
8 Allowable contact stress number for spheroidal graphitic iron gears, s_{ac}	19
9 Allowable bending stress number for spheroidal graphitic iron gears, s_{at}	19
10 Hardening pattern obtainable on pinion teeth with induction hardening	30
11 Minimum effective case depth for carburized and induction hardened pinions, $h_{e\ min}$	30
12 Steel and spheroidal graphitic iron pitting resistance stress cycle factor, Z_N	32
13 Steel and spheroidal graphitic iron bending strength stress cycle factor, Y_N	32

Tables

1	Symbols and definitions	4
2	Empirical constants: A , B , and C	16
3	Allowable contact stress number, s_{ac} , for steel and spheroidal graphitic iron gears	16
4	Allowable bending stress number, s_{at} , for steel and spheroidal graphitic iron gears	17
5	Metallurgical characteristics for steel pinions and gears	20
6	Metallurgical characteristics for spheroidal graphitic iron gears	23
7	Metallurgical characteristics for wrought carburized and hardened pinions .	24
8	Metallurgical characteristics for wrought induction hardened pinions	27

Foreword

[The foreword, footnotes and annexes, if any, in this document are provided for informational purposes only and are not to be construed as a part of AGMA Standard 6014-A06, *Gear Power Rating for Cylindrical Shell and Trunnion Supported Equipment.*]

AGMA 321.01 was originally developed to cover gears used primarily for ball and rod mills, and for kilns and dryers. It was approved in October 1943, and later modified in June 1946. In June 1951, AGMA 321.03 was approved as a standard. Further changes and additions were approved in June 1959, and AGMA 321.04 was issued in March 1960. AGMA 321.05 was approved in March 1968 and issued in March 1970.

In February 1979, the mill gearing committee was reorganized to review AGMA 321.05 and revise it in accordance with AGMA 218.01, *Rating the Pitting Resistance and Bending Strength of Spur and Helical Involute Gear Teeth*. With AGMA 218.01 as a guide, the committee submitted the first draft of ANSI/AGMA 6004-F88 in March 1984.

ANSI/AGMA 6004-F88 superseded AGMA 321.05, *Design Practice for Helical and Herringbone Gears for Cylindrical Grinding Mills, Kilns, Coolers, and Dryers*. It was approved by the AGMA membership in January 1988 and approved as an American National Standard on May 31, 1988.

ANSI/AGMA 6004 was not widely accepted by the industry and many continued to use AGMA 321.05. As such, the AGMA Mill Gearing began work on ANSI/AGMA 6014-A06 in November 2001. Changes to the standard include a new dynamic factor analysis as a function of transmission accuracy number, revised allowable stress numbers, the use of the stress cycle factor in the rating practice, and ratings for gears made from spheroidal graphitic iron. Extensive discussions on new equipment installation and alignment, lubrication, and use of ausferritic ductile iron were added to the annex.

Values for factors assigned in previous standards are not applicable to this Standard, nor are the values assigned in this Standard applicable to previous standards. The ability to design gears, and the knowledge and judgment required to properly evaluate the various rating factors comes primarily from years of accumulated experience in gearing. The detailed treatment of the general rating formulas for specific applications is best accomplished by those experienced in the field.

ANSI/AGMA 6014-A06 supersedes ANSI/AGMA 6004-F88, *Gear Power Rating for Cylindrical Grinding Mills, Kilns, Coolers and Dryers*. The first draft of ANSI/AGMA 6014-A06 was made in November 2001. It was approved by the AGMA membership in July 2006 and approved as an American National Standard on October 18, 2006.

Suggestions for improvement of this standard will be welcome. They should be sent to the American Gear Manufacturers Association, 500 Montgomery Street, Suite 350, Alexandria, Virginia 22314.

PERSONNEL of the AGMA Mill Gearing Committee

Chairman: Craig Danecki Rexnord Industries, LLC
Vice Chairman: Gary A. Bish Horsburgh & Scott Company

ACTIVE MEMBERS

J.C. Berney-Ficklin Bechtel Corporation
J. Carr FLSmidth & Company
J.L. Daubert FLSmidth & Company
M. Dreher Ferry-Capitain
T.C. Glasener Xtek, Incorporated
R.W. Hanks A-C Equipment Services Corporation
E.O. Hurtado FFE Minerals
M.J. Raab Anderol, Inc.
V. Svalbonas Metso Minerals, Ltd.
Y. Theberge Metso Minerals, Ltd.
F.C. Uherek Rexnord Industries, LLC

American National Standard – Gear Power Rating for Cylindrical Shell and Trunnion Supported Equipment

1 Scope

1.1 Applicability

This standard provides a method to determine the power rating of gear sets for cylindrical grinding mills, kilns, coolers, and dryers. The formulas are applicable to steel and spheroidal graphitic iron gears with machined spur, single helical, double helical, or herringbone gear teeth commonly used for this purpose. Calculations determine the allowable rating for pitting resistance and bending strength of external spur and helical involute gear teeth.

1.2 Rating formulas

This standard provides a method by which different gear designs can be rated and compared. It is not intended to assure the performance of assembled gear drive systems.

These rating formulas are applicable for rating the pitting resistance and bending strength of external spur and helical involute gear teeth operating on parallel axes with adjustable center distances. The formulas evaluate gear tooth capacity as influenced by the major factors which affect gear tooth pitting and gear tooth fracture at the fillet radius.

This standard is intended for use by experienced gear designers, capable of selecting reasonable values for the rating factors. It is not intended for use by the engineering public at large.

Values for factors assigned in other standards are not applicable to this standard nor are the values

assigned in this standard applicable to other standards. Mixing values from other standards with those from this standard could lead to erroneous ratings.

The gear designer or manufacturer is not responsible for the total system unless such a requirement is clearly identified in the contractual agreement.

It is imperative that the system designer be satisfied that the system of connected rotating parts is compatible, free from critical speeds and from torsional or other vibrations within the specified speed range, no matter how induced.

Where empirical values for rating factors are given by curves, curve-fitting equations are provided to facilitate computer programming. The constants and coefficients used in curve fitting often have significant digits in excess of those inferred by the reliability of the empirical data. Experimental data from actual gear unit measurements are seldom repeatable within a plus or minus 10 percent band. Calculated gear ratings are intended to be conservative, but the scatter in actual results may exceed 20 percent.

CAUTION: Compliance with this standard does not constitute a warranty of the rating of the gear set under installed field service conditions.

1.3 Limitations

- 1) Rating procedures are limited to open or semi-enclosed gearing where the gear reaction forces are transmitted through a structure which provides independent bearing support for the gear and pinion. Open gears operate without any enclosure. Semi-enclosed gears operate with a guard that provides some degree of protection against contamination from dust or dirt and retains lubricant.
- 2) Enclosed gear drives or speed reducers are expressly excluded from this standard.
- 3) When multiple pinions are used, the number of contacts per revolution, q , shall be the same as the number of pinions.
- 4) Unless otherwise specified by contractual agreement, the connected motor nameplate power including motor service factor shall be used to determine service factors as defined later within this standard. When not provided by the