



American
Gear Manufacturers
Association

Technical Resources

Reaffirmed August 2013

American National Standard

Design, Rating and Application of Industrial Globoidal Wormgearing

ANSI/AGMA 6035-A02

American National Standard

Design, Rating and Application of Industrial Globoidal Wormgearing ANSI/AGMA 6035-A02

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus, and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretation of this standard should be addressed to the American Gear Manufacturers Association.

CAUTION NOTICE: AGMA technical publications are subject to constant improvement, revision, or withdrawal as dictated by experience. Any person who refers to any AGMA technical publication should be sure that the publication is the latest available from the Association on the subject matter.

[Tables or other self-supporting sections may be quoted or extracted. Credit lines should read: Extracted from ANSI/AGMA 6035-A02, *Design, Rating and Application of Industrial Globoidal Wormgearing*, with the permission of the publisher, the American Gear Manufacturers Association, 500 Montgomery Street, Suite 350, Alexandria, Virginia 22314.]

Approved March 20, 2003

ABSTRACT

This standard provides guidelines for the design, rating and application of globoidal wormgearing mounted with axes at a 90 degree angle. Specific definitions for globoidal wormgearing terms are presented, along with formulas for determining the geometric sizes of the major features for the worm and gear. Design considerations, design procedures, gear blanks and self-locking conditions are also discussed. Procedures for rating the load capacity of globoidal wormgearing are included.

Published by

American Gear Manufacturers Association
500 Montgomery Street, Suite 350, Alexandria, Virginia 22314

Copyright © 2002 by American Gear Manufacturers Association
All rights reserved.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without prior written permission of the publisher.

Printed in the United States of America

ISBN: 1-55589-792-4

Contents

	Page
Foreword	iv
1 Scope	1
2 Symbols, terms and definitions	2
3 General design considerations	9
4 Gearset design	13
5 Self-locking	16
6 Adjustments and contact patterns of globoidal wormgearing	16
7 Run-in procedures	16
8 Rating and efficiency	17
9 Gear blank design	27

Annexes

A Basic assembly procedure	29
B Analysis of gearing forces, worm bending stress and deflection of globoidal wormgearing	32
C Backlash measurement	37
D Service factors	39
E Overhung load factors	41
F Reducer efficiency	43
G Formulas for rating factors	45

Figures

1 Worm and gear mesh in central plane	3
2 Gearset central plane	4
3 Relationship of central plane and transverse plane	5
4 Gearset transverse plane	6
5 Pitch circles	7
6 Lead angle, normal and axial pressure angles	7
7 Contact lines - Hindley design	10
8 Contact lines - Full contact design	10
9 Hindley design, 4" C.D., 10:1 ratio, 3 threads, 30 teeth	17
10 Hindley design, 4" C.D., 30:1 ratio, 1 thread, 30 teeth	18
11 Full contact design, 4" C.D., 30:1 ratio, 1 thread, 30 teeth	19
12 Gear blank types	27
13 Typical gear blank configuration minimum rim thickness	28

Tables

1 Symbols used in design of industrial globoidal wormgears	2
2 Recommended number of gear teeth	13
3 Basic pressure factor, C_s	20
4 Ratio correction factor, C_m	21
5 Face width and materials factor, C_a	21
6 Velocity factor, C_v	22

Foreword

[The foreword, footnotes and annexes, if any, in this document are provided for informational purposes only and are not to be construed as a part of ANSI/AGMA Standard 6035-A02, *Design, Rating and Application of Industrial Globoidal Wormgearing*.]

This standard revises, combines and supersedes two previous independent standards: ANSI/AGMA 6030-C87, *Design of Industrial Double-Enveloping Wormgears*, and ANSI/AGMA 6017-E86, *Rating and Application of Single and Multiple Reduction Double-Enveloping Worm and Helical-Worm Speed Reducers*. It presents guidelines and practices for the design, rating and application for industrial globoidal wormgearing.

The first draft of ANSI/AGMA 6035-A02 was made in December 2000. It was approved by the AGMA membership in October, 2001. It was approved as an American National Standard on March 20, 2003.

Suggestions for improvement of this standard will be welcome. They should be sent to the American Gear Manufacturers Association, 500 Montgomery Street, Suite 350, Alexandria, Virginia 22314.

PERSONNEL of the AGMA Wormgearing Committee

Chairman: R. Gregory Estell Accurate Specialties, Inc.
Vice Chairman: James A. Bentley Peerless-Winsmith, Inc.

ACTIVE MEMBERS

H.M. Ball Gear Products, Inc.
N. Chen Peerless-Winsmith, Inc.
R.J. Dickhaus Colfax PT Group/Delroyd Worm Gear Operation
J.H. Forberg Baldor Motors and Drives
J.E. Hardy Textron Power Transmission
J.B. Hagaman Textron Power Transmission
S. Moulis EPT Gearing
G.E. Olson Olson Engineering Service
P.C. Patel Rockwell Automation/Dodge
G.M. Sawchak Rexnord Corporation

ASSOCIATE MEMBERS

K.E. Acheson The Gear Works - Seattle, Inc.
D. Brick Leeson Electric Corporation
A.S. Cohen Engranos y Maquinaria Arco, S.A.
W.P. Crosher Flender Corporation
P. DeRegt PDR Enterprises, Inc.
F. Eberle Rockwell Automation/Dodge
R.J. Ericson Otis Elevator Company
L. Faure Compagnie Engrenages et Reducteurs
R.K. Glatt Flender Corporation
G.G. Rey Instituto Superior Politcnico
G. Henriot Ingenieur Conseil
T. Keenan EPT Gearing
C.R. Mason Franke Gear Works, Inc.
M. Octrue Centre Technique des Industries Mecanique
M. Peculis Cleveland Gear Company
W.P. Pizzichil, Jr. Rockwell Automation/Dodge
J.T. Rawlinson Renold, Inc.
P.N. Salvucci Boston Gear
H.O. Schlenker Hub City, Inc.
L.J. Smith Consultant
R.E. Smith R.E. Smith & Co., Inc.
L. Spiers Emerson Power Transmission Corporation
R.K. Stephens Regal-Beloit Corporation
F.C. Uherek Flender Corporation
P. Vogel Reishauer, Ltd.
D. Von Eschen Hub City, Inc.
C. Weyand M&M Precision Systems Corporation
G.I. Wyss Reishauer Corporation

American National Standard – Design, Rating and Application of Industrial Globoidal Wormgearing

1 Scope

This standard provides guidelines for the design, rating and application of globoidal wormgearing mounted with axes at a 90 degree angle. This type of gearing is called double enveloping wormgearing in the United States, but the term globoidal is more commonly used worldwide.

This standard discusses the two main categories of globoidal wormgearing manufactured in industry today: the traditional Hindley designs, and the more recently developed full contact designs. The standard presents the formulas for calculating general gearset proportions for the globoidal designs and a rating procedure for Hindley designs. It does not provide a detailed or complete procedure for the design of gearsets and the cutting tools required.

Globoidal wormgearing of the Hindley design has been used in industrial applications for over 200 years. The manufacturers of Hindley wormgearing have each designed and built their own tooling to manufacture the gearing. The Hindley design uses a common base circle to form all of the tooth profiles. The worm thread is generated by a cutting edge (line) rotating in a single plane.

The more recently developed full contact designs do not use a constant base circle to form the tooth profiles. The worm thread is generated in multiple planes by a generating surface. The manufacturers of full contact gearing have each conducted their own research, and the details of their designs are proprietary to each company. This design may provide increased load carrying capability over the

Hindley design, but a standard rating method for full contact designs has not been established.

1.1 Types of reducers

This standard provides information pertaining to globoidal wormgear speed reducers of the following specific types:

- single reduction reducers incorporating globoidal wormgearing;
- multiple reduction reducers incorporating globoidal wormgearing in each stage of reduction;
- the wormgear portion of multiple reduction reducers incorporating globoidal wormgearing with other types of gearing.

1.2 Speed limitation

The velocity factor table in this standard provides data for sliding velocities up to 6000 feet per minute. For velocities in excess of 6000 feet per minute, the manufacturer should be consulted.

Where the sliding velocity of the worm thread exceeds 2000 feet per minute, additional consideration must be given to the lubrication of gears and bearings. Special lubricants and a pressurized lubrication system may be required.

1.3 Included ratios

The input power formulas for globoidal wormgearing apply for ratios of 3:1 and greater. Engineering practice dictates that ratios in excess of 74:1 should be discussed with the manufacturer.

1.4 Exceptions

Wildhaber plane enveloping globoidal gearing is not covered in this standard.

This standard does not pertain to globoidal wormgearing used as speed increasers. For such applications, the manufacturer should be consulted.

1.5 Intended use

The equations and values presented provide a general approach to design and rating. Deviations from the methods and values stated in this manual may be made when justified by experience, testing or more specific analysis. It is intended for use by experienced gear designers capable of selecting reasonable values based on their knowledge of the