



American
Gear Manufacturers
Association

ANSI/AGMA 6101-F19
Revision of ANSI/AGMA 6101-E08

American National Standard

Design and Selection of Components for Enclosed Gear Drives (Metric Edition)

**American
National
Standard**

Design and Selection of Components for Enclosed Gear Drives (Metric Edition)

ANSI/AGMA 6101-F19

[Metric Edition of ANSI/AGMA 6001-F19]

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus, and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretation of this standard should be addressed to the American Gear Manufacturers Association.

CAUTION NOTICE: AGMA technical publications are subject to constant improvement, revision, or withdrawal as dictated by experience. Any person who refers to any AGMA technical publication should be sure that the publication is the latest available from the Association on the subject matter.

[Tables or other self-supporting sections may be referenced. Citations should read: See ANSI/AGMA 6101-F19, *Design and Selection of Components for Enclosed Gear Drives (Metric Edition)*, published by the American Gear Manufacturers Association, 1001 N. Fairfax Street, Suite 500, Alexandria, Virginia 22314, <http://www.agma.org>.]

Approved February 1, 2019

ABSTRACT

This standard outlines the basic practices for the design and selection of components, other than gearing, for use in commercial and industrial enclosed gear drives.

Published by

**American Gear Manufacturers Association
1001 N. Fairfax Street, Suite 500, Alexandria, Virginia 22314**

Copyright © 2019 by American Gear Manufacturers Association
All rights reserved.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without prior written permission of the publisher.

Printed in the United States of America

ISBN: 978-1-64353-034-5

Contents

Foreword	v
1 Scope.....	1
1.1 Exceptions.....	1
1.2 Intended use.....	1
2 Normative references	1
3 Symbols and definitions.....	2
3.1 Definitions.....	2
3.2 Symbols.....	2
4 Design conditions	5
4.1 Load spectrum analysis	6
4.2 Momentary peak loads	6
4.3 System analysis	6
5 Shafts.....	6
5.1 Design criteria	6
5.2 Fatigue safety factor.....	7
5.3 Peak load safety factor.....	8
5.3.1 Allowable stress to yield strength factor, F_{ya}	8
5.3.2 Peak load factor, F_p	8
5.4 Calculated stresses	8
5.4.1 The general case	10
5.4.2 The simplified case	12
5.5 Material requirements	14
5.5.1 Estimated properties of steel	14
5.6 Modified fatigue strength.....	15
5.6.1 Surface finish factor, k_a	15
5.6.2 Size factor, k_b	16
5.6.3 Reliability factor, k_c	16
5.6.4 Temperature factor, k_d	17
5.6.5 Life factor, k_e	17
5.6.6 Modifying factor for stress concentration, k_f	18
5.6.7 Miscellaneous effects factor, k_g	20
5.6.8 Permissible number of peak load cycles	21
5.7 Deflection	21
5.7.1 Permissible deflection.....	22
6 Keys and interference fits	23
6.1 Size and tolerances.....	23
6.2 Limitations	23
6.3 Keyed interference fit	24
6.4 Allowable compressive stress	24
6.5 Allowable shear stress	25
6.6 Allowable torque based on compressive stress calculation.....	25
6.7 Allowable torque based on shear stress calculation	25
6.8 Allowable torque.....	25

6.9	Keyless interference fit.....	25
6.10	Reversing loads	26
7	Bearings.....	27
7.1	Roller and ball bearing selection criteria	27
7.1.1	Reliability	27
7.1.2	Life adjustment factors	27
7.2	Sleeve bearing selection criteria	27
7.2.1	Boundary and mixed film regimes	28
7.2.2	Hydrodynamic regime.....	28
8	Housings.....	28
8.1	Housing construction and styles	29
8.2	Housing materials	30
8.3	Housing rigidity and strength.....	30
8.4	Housing accessory provisions.....	31
8.4.1	Inspection covers.....	31
8.4.2	Fill, vent, and drain provisions	31
8.4.3	Lifting provisions.....	31
9	Threaded fasteners	31
9.1	Fastener preload tensile stress, σ_M	32
9.2	Fastener torque, T_f	33
9.3	Allowable fastener tensile stress, σ_{fa}	33
9.3.1	Allowable tensile load, F_A	34
9.4	Engagement length	34
9.5	Locking devices for fasteners.....	34
10	Miscellaneous components	34
10.1	Shims	34
10.2	Gaskets	35
10.3	Oil seals.....	35
10.4	Breathers.....	35
10.5	Expansion chambers.....	35
10.6	Oil level indicators	35
10.7	Bearing retainers.....	36
10.8	Grease retainers	36
10.9	Dowels and pins	36
10.9.1	Dowels and pins used for positive location	36
10.9.2	Dowels and pins used to prevent movement	36
10.10	Spacers	36
10.11	Seal retainers	36
10.12	Special tools	37
10.13	Monitoring.....	37
10.13.1	Temperatures; sump, inlet, bearing race(s)	37
10.13.2	Pressures; inlet.....	37
10.13.3	Oil level.....	37
10.13.4	Chip or ferrous debris monitor.....	37
10.13.5	Flow	37

10.13.6 Vibration.....	37
------------------------	----

Annexes

Annex A (informative) Allowable stresses for typical key materials.....	38
Annex B (informative) Material properties for typical threaded fasteners.....	40
Annex C (informative) Previous method – shaft design.....	42
Annex D (informative) Sample problems – transmission shaft design	45
Annex E (informative) Shaft deflection.....	52
Annex F (informative) Sample problems – keys	59
Annex G Bibliography	62

Figures

Figure 1 – Design criteria	7
Figure 2 – Cyclic loading.....	10
Figure 3 – Stress convention showing orbiting element	11
Figure 4 – Surface finish factor, k_a [2]	15
Figure 5 – Size factor, k_b [2].....	16
Figure 6 – Reliability factor, k_c [1] [2].....	17
Figure 7 – Notch sensitivity – through-hardened steel, q [2].....	18
Figure 8 – Theoretical stress concentration factor in bending for a circular shaft with a square shoulder, K_t (nominal stress is calculated at diameter d_{she}) [7].....	19
Figure 9 – Theoretical stress concentration factor in bending for a circular shaft with a u-notch, K_t (nominal stress is calculated at diameter d_{she}) [7].....	20
Figure 10 – Theoretical stress concentration factor in bending for a circular shaft with a radial hole, K_t (based on full section without considering hole) [7]	20
Figure 11 – Key nomenclature	24
Figure 12 – Variation of coefficient of friction versus the bearing parameter	28
Figure 13 – Cast housings	29
Figure 14 – Fabricated housings	30
Figure 15 – Fastener grip requirement	32

Tables

Table 1 – Symbols used in equations	2
Table 2 – Modifying factor for stress concentration, k_f – typical values for keyways in solid round steel shafts ¹⁾ [8].....	20
Table 3 – Typical allowable misalignment per bearing type	22
Table 4 – Joint stiffness factor, K_j	33

Foreword

[The foreword, footnotes and annexes, if any, in this document are provided for informational purposes only and are not to be construed as a part of ANSI/AGMA Standard 6101-F19, *Design and Selection of Components for Enclosed Gear Drives (Metric Edition)*.]

AGMA 260.02 was approved by the AGMA membership on February 1, 1973 and issued in January of 1974. It consolidated with minor revision, information contained in the following superseded AGMA Standards:

AGMA 255.02 (November 1964), *Bolting (Allowable Tensile Stress) for Gear Drives*;

AGMA 260.01 (March 1953), *Shafting – Allowable Torsional and Bending Stresses*;

AGMA 260.02 also incorporated allowable stresses for keys;

AGMA 265.01 Bearings – *Allowable Loads and Speeds*.

The purpose of ANSI/AGMA 6001-C88, as a replacement for AGMA 260.02, was to establish a common base for the design and selection of components for the different types of commercial and industrial gear drives.

ANSI/AGMA 6001-C88 was expanded to include a generalized shaft stress equation which included hollow shafting, miscellaneous components, housings, and keyway stress calculations. All design considerations were revised to allow for 200 percent peak load for helical, spiral bevel, spur and herringbone gearing, and 300 percent peak load for wormgearing. The bearing section was updated to include consideration of life adjustment factors, bearing lives other than 5000 hours and reliability levels other than L_{10} .

During the preparation of ANSI/AGMA 6001-C88, a considerable amount of time was spent on the shaft design section in an effort to include the most recent theories on shaft stresses and material characteristics. The standard included the existing practice for shaft design, and for reference purposes, appendix C included a description of, and excerpts from, ANSI/ASME B106.1M, *Design of Transmission Shafting*, published in 1985 [1].

ANSI/AGMA 6001-C88 was approved by the membership in May 1988 and approved as an American National Standard on June 24, 1988.

ANSI/AGMA 6001-D97 was expanded to include more recent theories on shaft design and analysis. Also, equations for shaft deformation were added. ANSI/AGMA 6001-D97 was approved by the membership in October 1996 and approved as an American National Standard on August 7, 1997.

ANSI/AGMA 6101-E08 was updated to become a metric standard as required by ANSI practices. In the process several improvements and simplifications were included. Minimum material requirements were added for shaft material and the shaft deflection clause was moved to an annex. Also, the clauses on keys and fasteners were revised to reflect current practices with higher allowable stresses in some cases.

ANSI/AGMA 6101-F19 was reviewed and updated in accordance with ANSI practices, with general updates and corrections that had accumulated since publication of E08. In particular, Clause 8, Housings, was expanded to include graphics and discussion of stress analysis. Also, Clause 10, Miscellaneous components, was significantly upgraded in content.

The first draft of ANSI/AGMA 6101-F19 was made in April 2018. It was approved by the AGMA membership in December 2018. It was approved as an American National Standard on February 1, 2019.

Suggestions for improvement of this standard will be welcome. They should be sent to tech@agma.org.

PERSONNEL of the AGMA Enclosed Drives for Industrial Applications Committee

Chairman: Todd Praneis Cotta Transmission Company

ACTIVE MEMBERS

M. Allen Amarillo Gear Company
H. Almoghrabi Nord Gear Corporation
J. Bond Integrated Machinery Solutions
M. Groff Xtek
R. Holly Rexnord Gear Group
H. Johnson BHGE, Lufkin Industries
A. Miles SEW-Eurodrive
W. Weber Flender

American National Standard –

Design and Selection of Components for Enclosed Gear Drives (Metric Edition)

1 Scope

This standard provides an acceptable practice for the design and selection of components for enclosed gear drives. Fundamental equations provide for the proper sizing of shafts, keys, and fasteners based on stated allowable stresses. Other components are discussed in a manner to provide an awareness of their function or specific requirements. This standard applies to the following types of commercial and industrial enclosed gear drives, individually or in combination: spur, helical, herringbone, double helical, or bevel gearing in single or multiple stages. Bevel gear drives may include shaft angles other than 90 degrees.

1.1 Exceptions

The equations in this standard are not applicable when gear drives are subjected to conditions that introduce vibrations of a sufficient level to affect the performance of the gear drive and may result in unpredictable fatigue failure.

The procedure for design or selection of the specific gear components is varied and complex and is beyond the scope of this standard. Designers must refer to the specific rating or enclosed drive standards for this aspect of drive design.

1.2 Intended use

The equations and values presented provide a general approach to design. Deviations from the methods and values stated in this standard may be made when justified by experience, testing, or more specific analysis. This standard is intended for use by experienced gear designers capable of selecting reasonable values based on their knowledge of the performance of similar designs and the effect of such items as lubrication, deflection, manufacturing tolerances, metallurgy, residual stresses, and system dynamics. It is not intended for use by the engineering public at large.

2 Normative references

The following documents contain provisions which, through reference in this text, constitute provisions of this American National Standard. At the time of publication, the editions were valid. All standards are subject to revision, and parties to agreements based on this standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below.

AGMA 904-C96, *Metric Usage*

AGMA 927-A01, *Load Distribution Factors – Analytical Methods for Cylindrical Gears*

AGMA 938-A05, *Shot Peening of Gears*

ANSI B17.1, *Keys and Keyseats*

ANSI B17.2, *Woodruff Keys and Keyseats*

ANSI/AGMA 1012-G05, *Gear Nomenclature, Definitions of Terms with Symbols*

ANSI/AGMA 2101-D04, *Fundamental Rating Factors and Calculation Methods for Involute Spur and Helical Gear Teeth (Metric Edition)*