



American
Gear Manufacturers
Association

ANSI/AGMA 6113-B16
(Revision of ANSI/AGMA 6113-A06)

American National Standard

Standard for Industrial Enclosed Gear Drives (Metric Edition)

**American
National
Standard**

Standard for Industrial Enclosed Gear Drives (Metric Edition)

ANSI/AGMA 6113-B16

[Revision of ANSI/AGMA 6113-A06]

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing or using products, processes or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretation of this standard should be addressed to the American Gear Manufacturers Association.

CAUTION NOTICE: AGMA technical publications are subject to constant improvement, revision or withdrawal as dictated by experience. Any person who refers to any AGMA Technical Publication should be sure that the publication is the latest available from the Association on the subject matter.

[Tables or other self-supporting sections may be referenced. Citations should read: See ANSI/AGMA 6013-B16, *Standard for Industrial Enclosed Gear Drives*, published by the American Gear Manufacturers Association, 1001 N. Fairfax Street, Suite 500, Alexandria, Virginia 22314, <http://www.agma.org>.]

Approved April 5, 2016

ABSTRACT

This standard includes design, rating, lubrication, testing, and selection information for enclosed gear drives, including foot mounted, shaft mounted, screw conveyor drives, and gearmotors. These drives may include spur, helical, herringbone, double helical, or bevel gearing in single or multistage arrangements and wormgearing in multistage drives, as either parallel, concentric, or right angle configurations.

Published by

**American Gear Manufacturers Association
1001 N. Fairfax Street, Suite 500, Alexandria, Virginia 22314**

Copyright © 2016 by American Gear Manufacturers Association
All rights reserved.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without prior written permission of the publisher.

Printed in the United States of America

ISBN: 978-1-55589-051-3

Contents

Foreword	vi
1 Scope.....	1
1.1 Limitations.....	1
1.2 Exceptions	1
2 Normative references	1
3 Symbols and terms	2
3.1 Symbols	2
3.2 Terms.....	3
3.2.1 Gearmotors	3
3.2.2 Shaft mounted drives.....	3
3.2.3 Foot mounted drives	3
3.2.4 Flange or face mounted drives	3
3.2.5 PAO synthetic lubricant	3
3.2.6 PAG synthetic lubricant	3
4 Application and design considerations	3
4.1 Momentary load	3
4.2 Rating factors.....	4
4.3 System analysis	4
4.4 Considerations for cold temperature operation	4
4.5 Inertia effects	4
4.5.1 Large motor inertia – small driven inertia	4
4.5.2 Small motor inertia – large driven inertia	4
4.5.3 Other inertia considerations.....	4
4.6 Additional application and design considerations	5
5 Unit rating	5
5.1 External loading	5
5.2 Efficiency.....	5
5.2.1 Electric motor	6
5.3 Application power.....	6
5.4 Momentary overloads	6
6 Gear rating criteria.....	6
6.1 Pitting resistance power rating, P_{az}	7
6.1.1 Pitting resistance for spur and helical gearing	7
6.1.2 Pitting resistance for bevel gears.....	8
6.2 Bending strength power rating, P_{ay}	8
6.2.1 Bending strength for spur and helical gearing	8
6.2.2 Bending strength for bevel gears.....	9
6.3 Allowable stress numbers for pitting resistance and bending strength	9
6.4 Load spectrum analysis	9
7 Thermal power rating.....	9
8 Component design	10
8.1 Housing.....	10
8.2 Threaded fasteners.....	10
8.3 Bearings.....	10
8.4 Shafting.....	10
8.5 Balancing.....	10

8.6	Keys	10
8.6.1	External keyways	10
8.6.2	Interference fit of hubs and shafts	10
8.7	Torque arms	11
8.8	Backstops	12
8.8.1	Backstop types	12
8.8.2	Selection and application	12
8.8.3	Installation	12
8.8.4	Lubrication	13
8.9	Couplings	13
8.10	Shrink discs	13
8.11	Shaft bushings	13
8.11.1	Bushing types	13
8.11.2	Design considerations	14
8.11.3	Installation criteria	15
8.12	Electric motors	15
8.12.1	Motor types	15
8.12.2	Selection criteria	16
8.13	Other components	16
9	Service factors and application classification	17
9.1	Selection of recommended factors	17
9.2	Service factors	17
9.3	Application classification numbers	17
9.4	Determining service factor or application class number	18
9.4.1	Operational characteristics	18
9.4.2	System conditions	18
9.4.3	Special considerations	19
10	Overhung load	19
11	Lubrication and lubricants	20
11.1	Lubrication	20
11.1.1	Ambient temperature	20
11.1.2	Other considerations	20
11.1.3	Oil sump temperature	20
11.1.4	Food and drug	21
11.1.5	Mounting position	21
11.1.6	Corrosion	21
11.2	Lubricant viscosity	21
11.3	Lubricant recommendation	21
11.3.2	Lubricant viscosity considerations	22
11.4	Cold temperature conditions	22
11.4.1	Cold temperature gear lubricants	22
11.4.2	Sump heaters	23
11.5	Lubricant types	23
11.5.1	Rust and oxidation inhibited gear lubricants	23
11.5.2	Antiscuff lubricants	23
11.5.3	Synthetic gear lubricants	23
11.5.4	Synthetic lubricant selection	23
11.6	Lubricant maintenance	24
11.6.1	Initial lubricant maintenance	24
11.6.2	Subsequent lubricant maintenance	24
11.6.3	Abnormal operating conditions	24
11.6.4	Cleaning and flushing	24

11.6.5	Cleaning with solvents	25
11.6.6	Inspection.....	25
11.6.7	Lubricant disposal.....	25
12	Sound and vibration.....	25
13	Assembly and shaft rotation	25
14	Ratios and output speeds.....	28
15	Sizes, designations and ratios for AGMA standard size shaft mounted gear drives	29
15.1	AGMA standard sizes	29
15.2	Ratios.....	29
16	Screw conveyor drive dimensions	29
17	Marking and identification.....	29
18	Storage	30
18.1	Normal storage	30
18.2	Adverse conditions or long term storage	30
18.3	Removal from storage	30
19	Installation.....	30

Annexes

Annex A (informative)	Service factors and application classification numbers.....	31
Annex B (informative)	Keys and keyways for shaft extensions	45
Annex C (informative)	Test and inspection procedures	52
Annex D (informative)	Owner responsibilities	54
Annex E (informative)	Screw conveyor drive dimensions.....	56
Annex F (informative)	Illustrative examples	58
Annex G (informative)	Recommended bore sizes for AGMA standard size shaft mounted drives	67
Annex H (informative)	Installation	68
Annex I (informative)	Wormgearing	72
Annex J	Bibliography	76

Figures

Figure 1	– Threaded rod torque arm.....	11
Figure 2	– Torque link	11
Figure 3	– Single point torque arm.....	12
Figure 4	– Shaft rotation.....	25
Figure 5	– Parallel shaft spur, helical and herringbone gear drives, single or multiple stages.....	26
Figure 6	– Horizontal bevel gear drives, single stage; horizontal bevel - helical drives, multiple stage	27
Figure 7	– Vertical bevel gear drives, single stage; vertical bevel - helical drives, multiple stage	27
Figure B.1	– Diagrams for metric keys.....	45
Figure B.2	– Diagrams for metric keyways	47
Figure B.3	– Diagrams for inch keys with fillet radius and key chamfer	49
Figure B.4	– Diagrams for inch keyways	50
Figure E.1	– Drive shaft dimensions	56
Figure E.2	– Screw conveyor drive mounting dimensions.....	57

Tables

Table 1	– Symbols	2
Table 2	– Shaft diameter tolerances for supporting shafts	15
Table 3	– Service factor, K_{SF}	18
Table 4	– Overhung load factor, K_{oh}	20
Table 5	– Viscosity grade requirements.....	21
Table 6	– Viscosity grade guidelines	22
Table 7	– Output speeds for preferred ratios	28
Table 8	– Standard sizes and maximum bores.....	29
Table 9	– Nominal ratios	29

Table A.1 – Conversion table for single or multi-cylinder engines.....	32
Table A.2 – Service factors for enclosed gear drives	32
Table A.3 – Application classification.....	38
Table A.4 – Industrial duty overhead electric crane service factors	43
Table A.5 – Service factors for industrial duty overhead electric cranes	43
Table A.6 – Mill duty overhead electric crane service factors.....	43
Table B.1 – Metric dimensions and tolerances of keys, millimeters	46
Table B.2 – Metric dimensions and tolerances of keyways, millimeters.....	48
Table B.3 – Inch dimensions and tolerances of keys, inches	49
Table B.4 – Inch dimensions and tolerances of keyways, inches.....	51
Table E.1 – Screw conveyor drive shaft dimensions, inches.....	56
Table E.2 – Screw conveyor drive mounting dimensions, inches.....	57
Table G.1 – Recommended output bore diameters for metric shafts.....	67

Foreword

[The foreword, footnotes and annexes, if any, in this document are provided for informational purposes only and are not to be construed as a part of ANSI/AGMA 6113-B16, *Standard for Industrial Enclosed Gear Drives (Metric Edition)*.]

This standard revises, combines and supersedes two previous independent standards, ANSI/AGMA 6009-A00, *Standard for Gearmotors, Shaft Mounted and Screw Conveyor Drives*, and ANSI/AGMA 6010-F97, *Standard for Spur, Helical, Herringbone and Bevel Enclosed Drives*. The history of these standards have their roots in:

- AGMA 420.04, *Practice for Enclosed Speed Reducers or Increasesers Using Spur, Helical, Herringbone and Spiral Bevel Gears*
- AGMA 460.05, *Practice for Gearmotors Using Spur, Helical, Herringbone and Spiral Bevel Gears*
- AGMA 480.06, *Practice for Spur, Helical and Herringbone Gear Shaft-Mounted Speed Reducers*

ANSI/AGMA 6113-A06 presents general guidelines and practices for design, rating and lubrication of parallel, concentric, and right angle shaft drives. It includes foot mounted, shaft mounted, screw conveyor drives, and gearmotors. It includes the available data, gear technology, and operational experience.

The comprehensive thermal rating procedure has been removed but is included by reference to AGMA ISO 14179-1.

This standard reflects the consolidation of "Enclosed Drives," to include gearmotors, shaft mounted and screw conveyor drives, into a single document.

The allowable stress numbers used in this standard are derived from ANSI/AGMA 2101-D04, *Fundamental Rating Factors and Calculation Methods for Involute Spur and Helical Gear Teeth*, and ANSI/AGMA 2003-C10, *Rating the Pitting Resistance & Bending Strength of Generated Straight Bevel, Zerol Bevel, and Spiral Bevel Gear Teeth*, and, along with other rating factors, provide a rating basis for enclosed gear reducers and increasers. The rating formulas are based on many years of experience in the design and application of enclosed gear drives for industrial use. Provisions are included in this standard for using stress cycle factors other than 1.0 to adjust the rating for extended or reduced life. Using a stress cycle adjustment factor does not guarantee a certain number of life hours or stress cycles, but is a method of approximating gear life under different load and speed conditions.

In addition to a general update to match current industry practices, substantial changes in the new 6113-B16 include:

- moved wormgearing related text to Annex I;
- expanded crane service factor recommendations;
- revised and updated lubrication clause.

The competence to design enclosed gear drives, especially the knowledge and judgment required to properly evaluate the various rating factors, comes primarily from years of experience in designing, testing, manufacturing and operating similar gear drives. The proper application of the general rating formulas for enclosed gear drives is best accomplished by those experienced in the field.

The first draft of ANSI/AGMA 6113-A06 was created in November 2000. It was approved by the AGMA membership in March 2006. It was approved as an American National Standard on April 25, 2006.

The first draft of ANSI/AGMA 6113-B16 was created in November 2013. It was approved by the AGMA membership in October 2015. It was approved as an American National Standard on April 5, 2016.

Suggestions for improvement of this standard will be welcome. They may be submitted to tech@agma.org.

PERSONNEL of the AGMA Enclosed Drives for Industrial Applications Committee

Chairman: Todd Praneis Cotta Transmission Company, LLC
Vice Chairman: Walt Vann ExxonMobil Research and Engineering

ACTIVE MEMBERS

H. Almoghrabi Nord Gear Corporation
B. Arno Xtek, Inc.
J. Campbell Amarillo Gear Company LLC
B. Ford Integrated Machinery Solutions, LLC
R. Holly Rexnord Gear Group
H. Johnson Lufkin Industries, Inc.
W. McFarland SEW-Eurodrive, Inc.
J. Posada Lufkin Industries, Inc.
C. Smith Chalmers & Kubeck, Inc.
W. Weber Siemens Industry, Inc.
K. Wheelock Santasalo Gears Inc.

American National Standard—

Standard for Industrial Enclosed Gear Drives (Metric Edition)

1 Scope

This standard is applicable to enclosed gear drives including configurations of parallel, concentric, and right angle shafts. It includes foot mounted, shaft mounted, screw conveyor drives, and gearmotors. These enclosed drives utilize spur, helical, herringbone, double helical, or bevel gearing in single or multiple stages. Bevel gear drives may include shaft angles other than 90 degrees.

1.1 Limitations

This standard is applicable to gear drives having single or multiple stage gearing with pitch line velocities not exceeding 35 m/s for spur, helical, and spiral bevel gearing and 30 m/s for straight bevel, and shaft speeds not exceeding 4500 rpm for helical, spur, straight bevel, and spiral bevel gearing.

1.2 Exceptions

This standard does not cover epicyclic or crossed-helical gear drives. This standard does not cover the rating of spur, helical, or bevel gears due to wear or scuffing. The design and rating of the electric motor is beyond the scope of this standard. This standard does not apply to gear drives that are covered by other specific AGMA application standards.

For gear drives using wormgears, the design parameters shall be in accordance with the methods and procedures of ANSI/AGMA 6135-A02 for double enveloping wormgears and ANSI/AGMA 6034-B92 for cylindrical wormgears. Refer to Annex I for more details.

2 Normative references

The following documents contain provisions which, through reference in this text, constitute provisions of this American National Standard. At the time of publication, the editions shown were valid. All standards are subject to revision, and the users of this standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below.

AGMA 908-B89, *Geometry Factors for Determining the Pitting Resistance and Bending Strength of Spur, Helical and Herringbone Gear Teeth*

AGMA ISO 14179-1, *Gear Reducers – Thermal Capacity*, Based on ISO/TR 14179-1

ANSI/AGMA 1010-F14, *Appearance of Gear Teeth – Terminology of Wear and Failure*

ANSI/AGMA 1012-G05, *Gear Nomenclature, Definitions of Terms with Symbols*

ANSI/AGMA 2101-D04, *Fundamental Rating Factors and Calculation Methods for Involute Spur and Helical Gear Teeth*

ANSI/AGMA 2003-C10, *Rating the Pitting Resistance and Bending Strength of Generated Straight Bevel, Zerol Bevel, and Spiral Bevel Gear Teeth*

ANSI/AGMA 6000-B96, *Specification for Measurement of Linear Vibration on Gear Units*

ANSI/AGMA 6101-E08, *Design and Selection of Components for Enclosed Gear Drives*

ANSI/AGMA 6025-D98, *Sound for Enclosed Helical, Herringbone, and Spiral Bevel Gear Drives*

ANSI/AGMA 6034-B92, *Practice for Enclosed Cylindrical Wormgear Speed Reducers and Gearmotors*