



American
Gear Manufacturers
Association

Technical Resources

Revision of AGMA 510.03
Reaffirmed January 2008

American National Standard

Flexible Couplings - Nomenclature for Flexible Couplings

American National Standard

Flexible Couplings - Nomenclature for Flexible Couplings

ANSI/AGMA 9009-D02
(Revision of AGMA 510.03)

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing or using products, processes or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretation of this standard should be addressed to the American Gear Manufacturers Association.

CAUTION NOTICE: AGMA technical publications are subject to constant improvement, revision or withdrawal as dictated by experience. Any person who refers to any AGMA Technical Publication should be sure that the publication is the latest available from the Association on the subject matter.

[Tables or other self-supporting sections may be quoted or extracted. Credit lines should read: Extracted from ANSI/AGMA 9009-D02, *Flexible Couplings - Nomenclature for Flexible Couplings*, with the permission of the publisher, the American Gear Manufacturers Association, 1500 King Street, Suite 201, Alexandria, Virginia 22314.]

Approved June 27, 2002

ABSTRACT

This standard presents the nomenclature common to flexible couplings as used in mechanical power transmission drives. It does not address nomenclature for flexible shafts, quill shafts, universal joints or devices which exhibit slip such as clutches, fluid couplings, magnetic couplings or torque converters. The standard was prepared to reduce the language barriers that arise between designers, manufacturers and users when attempting to designate or describe various types of flexible couplings and their elements.

Published by

**American Gear Manufacturers Association
1500 King Street, Suite 201, Alexandria, Virginia 22314**

Copyright © 2002 by American Gear Manufacturers Association
All rights reserved.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without prior written permission of the publisher.

Printed in the United States of America

ISBN: 1-55589-796-7

Contents

	Page
Foreword	iv
1 Scope	1
2 Normative references	1
3 Symbols	1
4 Coupling definitions	2
5 Bores in hubs	5
6 Keys, keyways and keyseats	6
7 Shaft relationships	6
8 Coupling physical properties and other characteristics	6
9 Terms used in coupling selection	8
10 System terms	12
11 General terms	13

Index	15
-------------	----

Figures

1 Shaft relationships	7
2 Torsional stiffness	7
3 Damping coefficient	8
4 Example of pulsating torque	9
5 Example of reversing torque	10
6 Static unbalance	11
7 Couple unbalance	11
8 Dynamic unbalance	12

Tables

1 Symbols	1
-----------------	---

Foreword

[The foreword, footnotes and annexes, if any, in this document are provided for informational purposes only and are not to be construed as a part of ANSI/AGMA Standard 9009–D02, *Flexible Couplings – Nomenclature for Flexible Couplings*.]

This Standard was prepared to reduce the language barriers that arise between designers, manufacturers, and users when attempting to designate or describe various types of flexible couplings and their elements.

The first draft copy of AGMA 510.01 was prepared by the Flexible Coupling Nomenclature Committee in October, 1963. It was accepted as an AGMA Standard on July 9, 1965. AGMA 510.01 was editorially changed and approved as AGMA 510.02 in August 1969.

AGMA 510.03 was approved in October, 1983. The revised standard contained an improved clarity in definitions, simplification of nomenclature, addition of coupling physical property terms and units including SI Units, and introduction of an axial travel term for couplings.

ANSI/AGMA 9009–D02 is a revision of AGMA 510.03, and was approved by the AGMA membership in May 2001. It was approved as an American National Standard on June 27, 2002. This revision includes additional nomenclature from standards developed since the previous revision.

Suggestions for improvement of this standard will be welcome. They should be sent to the American Gear Manufacturers Association, 1500 King Street, Suite 201, Alexandria, Virginia 22314.

PERSONNEL of the AGMA Flexible Couplings Committee

Chairman: Glenn Pokrandt The Falk Corporation
Vice Chairman: James Paluh Boston Gear/Ameridrives Gear Coupling Ops.

ACTIVE MEMBERS

D.A. Boccio Boston Gear/Ameridrives Gear Coupling Ops.
T. Cain Lucas Aerospace
D.E. Crysler T.B. Wood's, Inc.
D.B. Cutler Rexnord Coupling Division
P.J. Dixon Metal Improvement Company
A. Hasebrock Flender Corporation
T. Hewitt Rexnord Coupling Division
D. Hindman Rexnord Elastomer Products Division
J.W. Mahan Lovejoy, Inc.
J.R. Mancuso Kop-Flex, Inc./Emerson Power Transmission Corp.
S.L. Pearson Mobil Oil Corporation
R.S. Post Rexnord Coupling Division
J. Sherred Renold, Inc.
R.G. Thompson T.B. Wood's, Inc.
R. Whitney Riverhawk Company

ASSOCIATE MEMBERS

D. Drechsler Huffman Corporation
K.H. Hoelmer Xtek, Incorporated
V. Ivers Xtek, Incorporated
D. Lindsay Emerson Gearing/Morse, Browning, USEM
L. Lloyd Lufkin Industries, Inc.
R.E. Munyon Kop-Flex, Inc./Emerson Power Transmission Corp.
M.A. O'Neill Riverhawk Company
D. Reynolds Rockwell Automation/Dodge
E.I. Rivin Wayne State University
T. Van Cleave Xtek, Incorporated
W. Welsch Metal Improvement Company

(This page is intentionally left blank.)

American National Standard –

Flexible Couplings – Nomenclature for Flexible Couplings

1 Scope

1.1 Applicability

This standard provides nomenclature common to flexible couplings and their application as used in mechanical power transmission drives.

1.2 Exceptions

The following coupling types are not included in this standard:

- flexible shaft;
- quill shaft;
- universal joint;
- devices which exhibit slip such as clutches, fluid couplings, magnetic couplings and torque converters.

2 Normative references

The following documents contain provisions which, through reference in this text, constitute provisions of the standard. At the time of publication, the editions were valid. All publications are subject to revision, and the users of this manual are encouraged to investigate the possibility of applying the most recent editions of the publications listed.

ANSI/AGMA 9000-C90, *Flexible Couplings – Potential Unbalance Classification*

ANSI/AGMA 9002-A86, *Bores and Keyways for Flexible Couplings (Inch Series)*

ANSI/AGMA 9004-A99, *Flexible Couplings – Mass Elastic Properties and Other Characteristics*

3 Symbols

The symbols used in this standard are shown in table 1.

NOTE: The symbols and terms contained in this document may vary from those used in other AGMA standards. Users of this standard should assure themselves that they are using these symbols and terms in the manner indicated herein.

Table 1 - Symbols

Symbol	Definition	Units		Where first used
		SI (inch)		
A_D	Damping energy during one cycle	N-m	lb-in	Eq 2
A_E	Elastic deformation energy	N-m	lb-in	Eq 2
dT	Rate of change in torque	Nm	lb-in	Eq 1
$d\theta$	Rate of change in torsional deflection	radians	radians	Eq 1
F	Force	N	lb	Eq 3
J	Polar mass moment of inertia	N-m-s ²	lb-in-s ²	8.4
k	Torsional stiffness	Nm/radian	lb-in/radian	8.5
M	Mass	kg	slug	8.1
R_a	Arithmetic average of surface finish	μm	μin	11.5.1
R_q	Root-mean-square of surface finish	μm	μm	11.5.2
r	Distance	m	in	Eq 3
T	Torque	Nm	lb-in	Eq 3

(continued)