



American
Gear Manufacturers
Association

ANSI/AGMA 9103-C17
(Revision of ANSI/AGMA 9103-B08)

American National Standard

Flexible Couplings – Keyless Fits (Metric Edition)

**American
National
Standard**

Flexible Couplings – Keyless Fits (Metric Edition)

ANSI/AGMA 9103-C17

[Revision of ANSI/AGMA 9103-B08]

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing or using products, processes or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretation of this standard should be addressed to the American Gear Manufacturers Association.

CAUTION NOTICE: AGMA technical publications are subject to constant improvement, revision or withdrawal as dictated by experience. Any person who refers to any AGMA Technical Publication should be sure that the publication is the latest available from the Association on the subject matter.

[Tables or other self-supporting sections may be referenced. Citations should read: See ANSI/AGMA 9103-C17, *Flexible Couplings – Keyless Fits (Metric Edition)*, published by the American Gear Manufacturers Association, 1001 N. Fairfax Street, Suite 500, Alexandria, Virginia 22314, <http://www.agma.org>.]

Approved December 6, 2017

ABSTRACT

This standard presents information on design, dimensions, tolerances, inspection, mounting, removal, and equipment that is in common use with keyless tapered and keyless straight (cylindrical) bore hubs for flexible couplings.

Published by

**American Gear Manufacturers Association
1001 N. Fairfax Street, Suite 500, Alexandria, Virginia 22314**

Copyright © 2017 by American Gear Manufacturers Association
All rights reserved.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without prior written permission of the publisher.

Printed in the United States of America

ISBN: 978-1-64353-001-7

Contents

Foreword	iv
1 Scope.....	1
1.1 Applicability	1
1.2 Exclusions.....	1
2 Normative references	1
3 Terms and symbols	1
3.1 Terms.....	1
3.2 Symbols	1
4 Responsibility.....	2
5 Design considerations	3
5.1 Determination of interference fit required to transmit the specified torque.....	5
5.2 Pressure required to mount or dismount hub	6
5.3 Hub stresses.....	6
5.4 Hub bore surface finish.....	7
6 Configurations for hydraulic installation or removal of hubs.....	7
6.1 Oil ports.....	7
6.2 Oil pressure retention and O-ring design.....	8
7 Tapers, interference rate, and advance	9
7.1 Tapers.....	9
7.2 Interference rate, i	9
7.3 Advance, S	9
8 Hydraulic mounting and removal equipment.....	10
9 Hub inspection, mounting and removal procedures for taper bores	11
9.1 Hub-to-gage contact check.....	11
9.2 Hub-to-shaft fit	11
9.3 Hub mounting.....	11
9.4 Hub retention	15
9.5 Hub removal procedures	15
9.6 Shaft stress relief groove in hub	15
10 Hub inspection, mounting and removal procedures for straight cylindrical bores.....	15
10.1 Hub bore checking.....	15
10.2 Shaft checking	16
10.3 Preparation for mounting	16
10.4 Hub mounting.....	16
10.5 Hub removal procedure	17
10.6 Shaft stress relief groove in hub	17

Annexes

Annex A (informative) Derivation of constants.....	18
Annex B (informative) Typical designs and dimensions for grooving and hydraulic fitting holes	21
Annex C (informative) Mounting and dismounting equipment	24
Annex D (informative) Example calculations	27
Annex E Bibliography.....	29

Tables

Table 1 – Symbols and definitions	2
Table 2 – Hub advance per millimeter of shaft diameter, S_d , vs. interference rate, i , for specified diametral tapers	10
Table B.1 – Typical hydraulic fitting hole dimensions, millimeters.....	21
Table B.2 – Typical oil groove dimensions, millimeters	22
Table B.3 – Typical shaft stress relief groove dimensions in hubs, millimeters.....	23

Figures

Figure 1 – Hub with multiple sections	3
Figure 2 – Flexible hub, gear tooth section influencing torque capacity and pressure.....	3
Figure 3 – Rigid hub, flange not influencing torque capacity and pressure.....	4
Figure 4 – Rigid hub, flange influencing torque capacity and pressure	4
Figure 5 – Bore configurations	4
Figure 6 – Oil port in shaft.....	7
Figure 7 – Oil ports in hub.....	8
Figure 8 – O-ring groove locations.....	8
Figure 9 – O-rings with back-up rings	9
Figure 10 – Typical mechanism for hydraulic mounting and removal	10
Figure 11 – Initial position measurement.....	12
Figure 12 – Measurement of hub advance	12
Figure 13 – Retaining mechanisms	14
Figure 14 – Relief groove.....	15
Figure 15 – Hub retainer plate and stress relief groove.....	16
Figure B.1 – Hydraulic fitting holes	21
Figure B.2 – Oil injection grooves	22
Figure B.3 – Oil groove positions	23
Figure B.4 – Shaft stress relief groove in hub.....	23
Figure C.1 – Taper bored hub mounting and dismounting equipment (mounting shown)	24
Figure C.2 – Straight bored hub dismounting equipment	26

Foreword

[The foreword, footnotes and annexes, if any, in this document are provided for informational purposes only and are not to be construed as a part of AGMA 9103-C17, *Flexible Couplings – Keyless Fits (Metric Edition)*.]

This standard was developed after intensive study of existing practices, standards and literature. The intent of this document is to offer to rotating equipment designers and users a standard for design practice and dimensions regarding keyless fits for flexible couplings. In general, the information in this standard is a consolidation of the most common practices and standards currently in existence.

This AGMA standard and related publications are based on typical or average data, conditions, or applications.

Work was begun on ANSI/AGMA 9003-A91 in 1985 and was approved by the AGMA membership in February 1991. It was approved as an American National Standard on May 20, 1991.

ANSI/AGMA 9103-B08 split the original standard into inch (ANSI/AGMA 9003-B08) and metric versions, updated Annex B and added an example calculation as Annex D.

The first draft of ANSI/AGMA 9103-B08 was made in October 2004. It was approved by the AGMA membership in October 2007. It was approved as an American National Standard on May 20, 2008.

ANSI/AGMA 9103-C17 provides a revised description of the effective hub to shaft engagement length, and Figure 5c has been deleted as a result.

The first draft of ANSI/AGMA 9103-C17 was made in August 2016. It was approved by the membership in November 2017 and as an American National Standard on December 6, 2017.

Suggestions for improvement of this standard will be welcome. They may be submitted to tech@agma.org.

PERSONNEL of the AGMA Flexible Couplings Committee

Chairman: Todd Schatzka.....Rexnord Industries, LLC

ACTIVE MEMBERS

T. Glasener.....Regal Power Transmission Solutions

B. GreenleesA-C Equipment Services

C. HatserasKTR

D. Konopka.....Ameridrives Couplings

P. Petruska.....Lovejoy

L. RiggsRegal Power Transmission Solutions

J. RubelBaldor Electric

American National Standard –

Flexible Couplings – Keyless Fits (Metric Edition)

1 Scope

This standard presents information on design, dimensions, tolerances, inspection, mounting, removal, and equipment that is in common use with keyless tapered and keyless straight (cylindrical) bore hubs for flexible couplings. Calculated hub stress values and hub to shaft torque capacities are nominal values. This standard does not present a rigorous analysis of the components.

1.1 Applicability

This Standard applies only to hubs and solid shafts made of steel, which generally have material properties of modulus of elasticity equal to 2.07×10^5 MPa, density equal to 7830 kg/m^3 , and thermal expansion coefficient equal to $11.4 \times 10^{-6} \text{ mm/mm/}^\circ\text{C}$.

1.2 Exclusions

This standard does not apply to couplings attached to shafts with keyways, splines, split hubs or polygon bores.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this American National Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this American National Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below.

ANSI/AGMA 9112-A04, *Bores and Keyways for Flexible Couplings (Metric Series)*

ANSI/AGMA 9009-D02, *Flexible Couplings – Nomenclature for Flexible Couplings*

3 Terms and symbols

3.1 Terms

The terms used, wherever applicable, conform to the following Standards:

ANSI Y10.3-1968, *Letter Symbols for Quantities Used in Mechanics of Solids*

ANSI/AGMA 1012-G05, *Gear Nomenclature, Definition of Terms with Symbols*

3.2 Symbols

The symbols used in the formulas are shown in Table 1.

NOTE: The symbols and definitions used in this standard may differ from other AGMA standards. The user should not assume that familiar symbols can be used without a careful study of these definitions.