


AMERICAN NATIONAL STANDARD

***Bores and Keyways for Flexible Couplings
(Metric Series)***

ANSI/AGMA 9112-A04



AGMA STANDARD

American National Standard

Bores and Keyways for Flexible Couplings (Metric Series)

ANSI/AGMA 9112-A04

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus, and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretation of this standard should be addressed to the American Gear Manufacturers Association.

CAUTION NOTICE: AGMA technical publications are subject to constant improvement, revision, or withdrawal as dictated by experience. Any person who refers to any AGMA technical publication should be sure that the publication is the latest available from the Association on the subject matter.

[Tables or other self-supporting sections may be referenced. Citations should read: See ANSI/AGMA 9112-A04, *Bores and Keyways for Flexible Couplings (Metric Series)*, published by the American Gear Manufacturers Association, 500 Montgomery Street, Suite 350, Alexandria, Virginia 22314, <http://www.agma.org>.]

Approved May 5, 2005

ABSTRACT

This standard describes sizes and tolerances for straight and tapered bores and the associated keys and keyways, as furnished in flexible couplings. The data in the standard considers commercially standard coupling bores and keyways, not special coupling bores and keyways that may require special tolerances.

Published by

American Gear Manufacturers Association
500 Montgomery Street, Suite 350, Alexandria, Virginia 22314

Copyright © 2005 by American Gear Manufacturers Association
All rights reserved.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without prior written permission of the publisher.

Printed in the United States of America

ISBN: 1-55589-842-4

Contents

	Page
Foreword	iv
1 Scope	1
2 Normative references	1
3 Symbols and definitions	1
4 Straight (finished) bored hubs	2
5 Tapered bore hubs	5
6 Keys	5
7 Hub keyways	7

Bibliography	33
--------------------	----

Annexes

A Straight bore inspection methods	12
B Tapered bore inspection procedure and plug gauge accuracy requirements	13
C Recommended design practice for conical shafts used with flexible couplings	16
D Keyway measurement	19
E Other bore/shaft tolerance combinations found in industry and the resulting fits	24

Figures

1 Tapered bore requirements	5
2 Tapered bore drawing dimensions	5
3 Types of keys	7
4 Keyway dimensions	7
5 Keyway offset	9
6 Keyway lead	10
7 Keyway parallelism	10
8 Multiple keyway index	11

Tables

1 Symbols	1
2 Recommended bores for metric shafts from ISO/R775:1969	3
3 Key sizes for cylindrical shafts from ISO R773:1969	6
4 Key dimensions from ISO R773:1969	6
5 Recommended hub keyway dimensions	8
6 Hub keyway/key fits	9
7 Maximum keyway lead values	10
8 Multiple keyway index tolerances	10

Foreword

[The foreword, footnotes and annexes, if any, in this document are provided for informational purposes only and are not to be construed as a part of ANSI/AGMA 9112-A04, *Bores and Keyways for Flexible Couplings (Metric Series)*.]

This standard incorporates information from the following International Organization for Standardization (ISO) and American National standards Institute (ANSI) standards:

- ISO 286-1, *ISO System of limits and fits - Bases of tolerances, deviations and fits*
- ISO 286-2, *ISO System of limits and fits - Tables of standard tolerance grades and limit deviations for holes and shafts*
- ISO R773 (withdrawn 1998), *Rectangular or Square Parallel Keys and their Corresponding Keyways*
- ISO R775 (withdrawn 1998), *Cylindrical and 1/10 Conical Shaft Ends*
- ANSI/AGMA 9002-B04, *Bores and Keyways for Flexible Couplings (Inch Series)*

The intent of this document is to offer designers and users of flexible couplings preferred dimensions, tolerances and fits for metric bores and keyways.

This standard incorporates a small portion of the numerous variations of shaft/bore fits. These fits and tolerances have been determined to be the preferred fits and tolerances that most closely relate to the bore and keyway fit classes from ANSI/AGMA 9002-A86. A study of the existing metric standards indicated that the many possible combinations of shaft/bore fits would be impractical to adopt as an all encompassing standard. Therefore, this standard does not intend to replace any existing metric standards, but to define what is preferred.

The first draft of ANSI/AGMA 9112-A04 was made in May, 2001. It was approved by the AGMA membership in October 23, 2004. It was approved as an American National Standard on May 5, 2005.

Suggestions for improvement of this standard will be welcome. They should be sent to the American Gear Manufacturers Association, 500 Montgomery Street, Suite 350, Alexandria, Virginia 22314.

PERSONNEL of the AGMA Flexible Couplings Committee

Chairman: Glenn Pokrandt Falk Corporation
Vice Chairman: Jim Paluh Ameridrives Coupling

ACTIVE MEMBERS

T. Hewitt Lord Corporation
D. Hindman Falk Corporation
D. Lyle Ameridrives Coupling
H.A. Lynn, III Falk Corporation
J.W. Mahan Lovejoy, Inc.
J.R. Mancuso Kop-Flex/Emerson Power Transmission
T. Schatzka Rexnord Industries, Inc.
J. Sherred Ameridrives Coupling
R.G. Thompson System Components, Inc.
R. Whitney Riverhawk Company

ASSOCIATE MEMBERS

L.E. Baer TB Wood's Inc.
T. Cain Riverhawk Company
T.A. Geiger Falk Corporation
K.R. Gray Metal Improvement Company
D. Lindsay EPT Gearing
J. Mayhan Xtek, Inc.
M.A. O'Neil Riverhawk Company
E.I. Rivin Wayne State University

(This page is intentionally blank)

American National Standard – Bores and Keyways for Flexible Couplings (Metric Series)

1 Scope

This standard presents metric dimensions, tolerances, sizes and fits for straight bores, tapered bores, keys and keyways for unmounted industrial flexible couplings. The keys and keyways followed the recommendations of ISO R773:1969 and shaft tolerances followed ISO R775:1969. Shaft keyseat dimensions and tolerances were given in ISO R773:1969. This specification includes index tolerances for multiple keyways.

Inspection methods for straight and tapered bores and keyways are included in the annexes. The annexes also include the recommended design practice for tapered shafts for use with flexible couplings.

1.1 Application area

This standard is applicable to couplings as defined in ANSI/AGMA 9009-D02, *Nomenclature for Flexible Couplings*, with metric bores and keyways.

1.2 Excluded area

This standard does not apply to couplings attached to shafts without keys (see ANSI/AGMA 9003-A91), shafts and bores with tapered keys, inch bores with metric keyways, metric bores with inch keyways, inch bores with inch keyways, or shaft keyseat tolerances. See ANSI/AGMA 9002-B04 for inch bores with inch keyways.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this American National Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on the American National Standard are encouraged to investigate the possibility of applying the most recent editions of the standards listed.

ANSI/AGMA 9009-D02, *Flexible Couplings – Nomenclature for Flexible Couplings*

3 Symbols and definitions

3.1 Symbols

The symbols used in this standard are shown in table 1.

NOTE: The symbols and terms contained in this document may vary from those used in other AGMA standards. Users of this standard should assure themselves that they are using these symbols and terms in the manner indicated herein.

Table 1 – Symbols

Symbol	Description	Units	First used
b	Key width	mm	Table 3
D_b	Large end diameter of hub bore	mm	Figure 1
D_g	Gauge line diameter of hub bore	mm	Figure 2
D_{se}	Small end diameter of hub bore	mm	5.3
d	Cylindrical shaft diameter	mm	Table 3
h	Key height	mm	Table 3
I_{kw}	Multiple keyway index tolerance	mm	7.3.7
L_{kw}	Maximum keyway lead	mm	7.3.5
l	Axial length of the tapered feature	mm	5.3

(continued)