



American
Gear Manufacturers
Association

Technical Resources

ANSI/AGMA 9112-B14
(Revision of ANSI/AGMA 9112-A04)

American National Standard

Bores and Keyways for Flexible Couplings (Metric Series)

**American
National
Standard**

Bores and Keyways for Flexible Couplings (Metric Series)

ANSI/AGMA 9112-B14

[Revision of ANSI/AGMA 9112-A04]

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing or using products, processes or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretation of this standard should be addressed to the American Gear Manufacturers Association.

CAUTION NOTICE: AGMA technical publications are subject to constant improvement, revision or withdrawal as dictated by experience. Any person who refers to any AGMA Technical Publication should be sure that the publication is the latest available from the Association on the subject matter.

[Tables or other self-supporting sections may be referenced. Citations should read: See ANSI/AGMA 9112-B14, *Bores and Keyways for Flexible Couplings (Metric Series)*, published by the American Gear Manufacturers Association, 1001 N. Fairfax Street, Suite 500, Alexandria, Virginia 22314, <http://www.agma.org>.]

Approved _____

ABSTRACT

This standard describes sizes and tolerances for straight and tapered bores and the associated keys and keyways, as furnished in flexible couplings. The data in the standard considers commercially standard coupling bores and keyways, not special coupling bores and keyways that may require special tolerances.

Published by

**American Gear Manufacturers Association
1001 N. Fairfax Street, Suite 500, Alexandria, Virginia 22314**

Copyright © 2014 by American Gear Manufacturers Association
All rights reserved.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without prior written permission of the publisher.

Printed in the United States of America

ISBN: 978-1-61481-092-6

Contents

Foreword	v
1 Scope	1
1.1 Application	1
1.2 Exceptions	1
2 Normative references	1
3 Symbols and definitions	1
3.1 Symbols	1
4 Bore measurement and surface finish	2
4.1 Bore measurement	2
4.2 Bore surface finish	2
5 Straight (finished) bored hubs	2
5.1 Standard bores	2
5.1.1 Hub bore to shaft fit	2
5.1.2 Standard hub bore to shaft fits	2
5.1.3 Unspecified hub bore to shaft fits	5
5.2 Non-standard bores	5
5.3 Set screws	5
6 Tapered bore hubs	6
6.1 Typical tapered bores	6
6.2 Keyways	6
6.3 Tapered bore dimensional control requirements	6
6.4 Dimensioning of tapered bores	6
7 Keys	7
7.1 Key sizes	7
8 Hub keyways	8
8.1 Classes of key-to-hub keyway fit	8
8.1.1 Normal JS9 (default)	8
8.1.2 Close P9 (fitted)	8
8.2 Keyway sizes	9
8.3 Keyway dimensions and tolerances	9
8.3.1 Keyway width	9
8.3.2 Nominal keyway depth	11
8.3.3 Dimension from top of keyway to opposite side of bore	11
8.3.4 Maximum keyway offset tolerance, <i>N</i>	11
8.3.5 Maximum keyway lead	11
8.3.6 Keyway parallelism	12
8.3.7 Multiple keyway index tolerance	12
8.4 Methods of measurement	13
8.5 Finish of keyways	13
8.6 Fillet radii in keyways	13
Bibliography	36

Annexes

Annex A Straight bore inspection methods.....	14
Annex B Tapered bore inspection procedure and plug gauge accuracy requirements.....	15
Annex C Recommended design practice for conical shafts used with flexible couplings	18
Annex D Keyway measurement.....	21
Annex E Other bore/shaft tolerance combinations found in industry and the resulting fits	27

Tables

Table 1 - Symbols	2
Table 2. Recommended bores for metric shafts from ISO R775:1969, mm.....	3
Table 3. Key sizes for cylindrical shafts from ISO R773:1969, mm.....	7
Table 4 - Key dimensions from ISO R773:1969, mm	8
Table 5 - Recommended hub keyway dimensions, mm ¹⁾	9
Table 6 - Hub keyway/key fits, mm	10
Table 7 - Maximum keyway lead values	11
Table 8 - Multiple keyway index tolerances	13

Figures

Figure 1. Tapered bore requirements	6
Figure 2. Tapered bore drawing dimensions	6
Figure 3 - Types of keys.....	7
Figure 4 - Keyway dimensions	10
Figure 5 - Keyway offset	11
Figure 6 - Keyway lead	12
Figure 7 - Keyway parallelism	12
Figure 8 - Multiple keyway index.....	12

Foreword

[The foreword, footnotes and annexes, if any, in this document are provided for informational purposes only and are not to be construed as a part of ANSI/AGMA 9112-B14, *Cylindrical Bores and Keyways for Flexible Couplings (Metric Series)*.]

This standard incorporates information from the following International Organization for Standardization (ISO) and American National standards Institute (ANSI) standards:

- ISO 286-1, *ISO System of limits and fits - Bases of tolerances, deviations and fits*;
- ISO 286-2, *ISO System of limits and fits - Tables of standard tolerance grades and limit deviations for holes and shafts*;
- ISO R773 (withdrawn 1998), *Rectangular or Square Parallel Keys and their Corresponding Keyways*;
- ISO R775 (withdrawn 1998), *Cylindrical and 1/10 Conical Shaft Ends*;
- ANSI/AGMA 9002-C14, *Bores and Keyways for Flexible Couplings (Inch Series)*.

The intent of this document is to offer designers and users of flexible couplings preferred dimensions, tolerances and fits for metric bores and keyways. ANSI/AGMA 9112-B14 describes sizes and tolerances for straight and tapered bores and associated keys and keyways, as furnished in metric flexible couplings.

This standard incorporates a small portion of the numerous variations of shaft/bore fits. These fits and tolerances have been determined to be the preferred fits and tolerances that most closely relate to the bore and keyway fit classes from ANSI/AGMA 9002-A86. A study of the existing metric standards indicated that the many possible combinations of shaft/bore fits would be impractical to adopt as an all-encompassing standard. Therefore, this standard does not intend to replace any existing metric standards, but to define what is preferred. Note that this standard is a pure metric standard, and not a metric conversion of ANSI/AGMA 9002-C14 (Inch Series).

In AGMA 9112-B14 the "measurement of bores" section was moved from an annex to clause 4, now becoming a part of the standard. Bores are to be measured prior to cutting the keyway.

The first draft of ANSI/AGMA 9112-B14 was made in April, 2011. It was approved by the AGMA membership in _____. It was approved as an American National Standard on _____.

Suggestions for improvement of this standard will be welcome. They may be submitted to tech@agma.org.

PERSONNEL of the AGMA Flexible Couplings Committee

Chairman: Glenn Pokrandt.....Rexnord Coupling Operations Group (Retired)
Vice Chairman: Todd SchatzkaRexnord Technical Services

ACTIVE MEMBERS

T.C. Glasener.....Emerson Industrial Automation
B.M. GreenleesA-C Equipment Services Corporation
C.M. HatserasKTR Corporation
D.W. Hindman.....Rexnord Coupling Operations Group
D.R. Lyle.....Ameridrives Gear Coupling Operations
S. McChesney.....Reich USA Corporation
M. McGinnityEmerson Industrial Automation
L. RiggsEmerson Industrial Automation
J. Sherred.....Ameridrives Gear Coupling Operations
E. WilsonLovejoy, Inc.

American National Standard -

Bores and Keyways for Flexible Couplings (Metric Series)

1 Scope

This standard presents metric dimensions, tolerances, sizes and fits for straight bores, tapered bores, keys and keyways for unmounted industrial flexible couplings. The keys and keyways followed the recommendations of ISO R773:1969 and shaft tolerances followed ISO R775:1969. Shaft keyseat dimensions and tolerances were given in ISO R773:1969. This specification includes index tolerances for multiple keyways.

Inspection methods for straight and tapered bores and keyways are included in the annexes. The annexes also include the recommended design practice for tapered shafts for use with flexible couplings.

1.1 Application

This standard is applicable to couplings as defined in ANSI/AGMA 9009-D02, *Flexible Couplings - Nomenclature for Flexible Couplings*, with metric bores and keyways.

1.2 Exceptions

This standard does not apply to:

- couplings attached to shafts without keys, see ANSI/AGMA 9103-B08;
- couplings attached to shafts with tapered bushings or keyless shaft locking devices;
- shafts and bores with tapered keys;
- inch bores with metric keyways;
- metric bores with inch keyways;
- metric bores with metric keyways; or
- shaft keyseat tolerances.

See ANSI/AGMA 9002-C14 for inch bores with inch keyways.

2 Normative references

The following standard contains provisions which, through reference in this text, constitute provisions of this American National Standard. At the time of publication, the edition indicated was valid. All standards are subject to revision, and parties to agreements based on this American National Standard are encouraged to investigate the possibility of applying the most recent edition of the standard indicated below.

ANSI/AGMA 9009-D02, *Flexible Couplings - Nomenclature for Flexible Couplings*

3 Symbols and definitions

3.1 Symbols

The symbols used in this standard are shown in Table 1.

NOTE: The symbols and terms contained in this document may vary from those used in other AGMA standards. Users of this standard should assure themselves that they are using these symbols and terms in the manner indicated herein.