



Method for Measuring the Performance of Portable Household Electric Room Air Cleaners Following Accelerated Particulate Loading

AHAM AC-3-2009 (R2016)



Leadership > Knowledge > Innovation

PREFACE

The Association of Home Appliance Manufacturers (AHAM) develops standards in accordance with AHAM's "Policy and Procedures Governing Technical Standards" which states:

"AHAM Standards shall be in the best interest, mutually, of consumers who use appliances, the industries which provide and service appliances, and other interested parties. They shall relate to actual use conditions, and be technically and scientifically sound."

Use or observance of AHAM standards is voluntary.

This standard contains test procedures which may be applied to any brand or model of portable household electric room air cleaners within the stated confines of the standard's limits for measuring performance. Results of tests in accordance with this standard may be publicly stated in accordance with Section 13, Reporting Results.

When using any of the test procedures to determine performance rating status or to compare the performance of appliances, it is recommended that multiple test units (typically at least 3) be run to ensure that the results obtained are statistically valid.

With regard to safety, AHAM recommends that all appliance products - both major and portable appliances - manufactured or marketed in the United States be submitted to a Nationally Recognized Testing Laboratory (NRTL) for inspection and listing in conformance with the safety standards and procedures followed by such laboratories.

The annexes to this standard are included for informational purposes only unless the annexes are noted as normative.

AHAM welcomes comments and suggestions regarding this standard. Any standard may be reviewed and improved as needed. All standards must be updated or reconfirmed at least every five years. Any interested party, at any time, may request a change in an AHAM standard. Such request should be addressed to AHAM's President, and should be accompanied by a statement of reason for the request and a suggested alternate proposal.

This standard may involve hazardous materials, operations, and equipment. This standard does not purport to address all of the safety problems associated with its use. It is the responsibility of whoever uses this standard to consult and establish appropriate safety and health practices and determine the applicability of any regulatory limitations prior to use.

Copyright © 2016 by the Association of Home Appliance Manufacturers (AHAM) All rights reserved.

The hard copy print version of this document shall be for individual use only.

The electronic file version of this document shall be for storage on one computer for purposes of viewing and/or printing one copy for individual use only.

This document shall not be reproduced in whole or in part by any means, and shall not be transmitted electronically or otherwise to a third person without the prior written permission of AHAM.

TABLE OF CONTENTS

1. PURPOSE	1
2. SCOPE	1
3. DEFINITIONS	2
4. SUMMARY OF THE TEST METHOD	2
5. GENERAL CONDITIONS FOR MEASUREMENTS	3
6. TEST SET UP	4
7. TEST PROCEDURE	5
8. DETERMINING THE AMOUNT OF PARTICULATE LOADING MATERIAL	6
9. PARTICULATE LOADING PROCESS	7
10. INCLUDING MAINTENANCE DURING LOADING	7
11. HANDLING THE LOADED AIR CLEANER	9
12. EVALUATING TEST RESULTS	9
13. REPORTING RESULTS – MINIMUM INFORMATION	9
14. SAFETY	10
15. REFERENCES	11
ANNEX A (normative)	12
ANNEX B (normative)	16
ANNEX D (normative)	23
ANNEX E (normative)	24
ANNEX F (informative)	25
ANNEX G (informative)	27
ANNEX H (informative)	28

1. PURPOSE

- 1.1 This test method establishes a uniform, repeatable procedure for measuring a specified product characteristic of portable household electric room air cleaners.
- 1.2 Used in conjunction with ANSI/AHAM AC-1-2015, this test method provides a means to evaluate and compare the performance of portable household electric air cleaners before and after the air cleaners have been subjected to accelerated particulate loading conditions designed to simulate defined periods of use.
- 1.3 This test method is not intended to inhibit improvement and innovation in product testing, design or performance.

2. SCOPE

- 2.1 This test method applies to portable household electric room air cleaners as defined in ANSI/AHAM AC-1-2015.
- 2.2 This test method is applicable to any type or design of portable electric household electric room air cleaner, provided the device can be adequately plenum mounted since a plenum system is needed to load the particulate matter, and provided the device also meets the conditions specified in 2.3 through 2.5 below.
- 2.3 The initial and final measurements of performance, known as Clean Air Delivery Rates (CADR) are determined utilizing ANSI/AHAM AC-1-2015. The limits of measurability and precision stated in ANSI/AHAM AC-1 shall apply.

Therefore, this standard only applies to portable household electric air cleaners that have a

CADR rating that falls within the following ranges (cfm =
cubic feet per minute): Dust CADR = 10 cfm – 400
cfm
Cigarette smoke CADR = 10 cfm – 450 cfm
Pollen CADR = 25 cfm – 450 cfm

NOTE: Units that have a lower or upper limit that is outside the range specified are not within the scope of this test method.

- 2.4 The stated results of this test method include the percentage change in CADR performance after 90 simulated days of filter loading. See Section 13 for more information.
- 2.5 The maximum air cleaner airflow rate for the method is 600 cfm (16.9 m³/min). It is necessary to have an air flow rate no greater than 600 cfm in order to be able to aerodynamically load the air cleaner in a plenum with a sufficient mass of loading material.