

ANSI/AIAA G-095A-2017
(Revision of AIAA G-095-2004)

Guide

American National Standard

Guide to Safety of Hydrogen and Hydrogen Systems

AIAA standards are copyrighted by the American Institute of Aeronautics and Astronautics (AIAA), 12700 Sunrise Valley Drive, Suite 200, Reston, VA 20191-5807 USA. All rights reserved.

AIAA grants you a license as follows: The right to download an electronic file of this AIAA standard for temporary storage on one computer for purposes of viewing, and/or printing one copy of the AIAA standard for individual use. Neither the electronic file nor the hard copy print may be reproduced in any way. In addition, the electronic file may not be distributed elsewhere over computer networks or otherwise. The hard copy print may only be distributed to other employees for their internal use within your organization.



ANSI/AIAA G-095A-2017
(Revision of AIAA G-095-2004)

American National Standard Guide

Guide to Safety of Hydrogen and Hydrogen Systems

Sponsored by

American Institute of Aeronautics and Astronautics

Approved 30 October 2017

American National Standards Institute

Approved 11 December 2017

Abstract

This Guide presents information that designers, builders, and users of hydrogen systems can use to ensure safe hydrogen systems or resolve hydrogen hazards. Guidance is provided on general safety systems and controls, usage, personnel training, hazard management, design, facilities, detection, storage, transportation, and emergency procedures. Pertinent research is summarized, and supporting data are presented relative to the topic. Additional information regarding codes, standards, and regulations, as well as a sample safety data sheet, extensive bibliography, and other useful material can be found in the annexes.

American National Standard

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus, and other criteria have been met by the standards developer.

Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretations should be addressed to the secretariat or sponsor whose name appears on the title page of this standard.

CAUTION NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken to affirm, revise, or withdraw this standard no later than five years from the date of approval. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute.

Published by
American Institute of Aeronautics and Astronautics
12700 Sunrise Vally Drive, Reston, VA 20191

Copyright © 2017 American Institute of Aeronautics and
Astronautics
All rights reserved

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without prior written permission of the publisher.

Printed in the United States of America

ISBN 978-1-62410-519-7

Contents

Foreword	x
Introduction	xii
Trademarks	xiii
1 Scope.....	1
1.1 Purpose.....	1
1.2 Applicability	1
1.3 Application	1
1.4 Responsibility.....	1
1.5 Exclusions.....	2
1.6 Guidance on Administration.....	2
2 Applicable Documents	2
2.1 Applicable Codes and Standards	3
2.2 Additional Documents.....	6
3 Vocabulary	6
3.1 Acronyms and Abbreviated Terms	6
3.2 Terms and Definitions.....	9
4 Basic Hydrogen Safety Guidelines	15
4.1 General	15
4.2 Hydrogen Usage	15
4.3 Personnel Training.....	15
4.4 Inherent Safety Features	17
4.5 Controls.....	17
4.6 Fail-Safe Design	17
4.7 Safety Assessment and Mishap Reporting.....	18
5 Properties and Hazards of Hydrogen	18
5.1 Hydrogen Properties and Usage Hazards.....	18
5.2 Atomic and Molecular Properties.....	20
5.3 Thermophysical Properties	22
5.4 Characteristic Behaviors of Hydrogen	23
5.5 Combustion-Related Properties	27
5.6 Hydrogen Hazards.....	51
6 Materials for Hydrogen Service	67

6.1	Considerations for Materials Selection	67
6.2	Hydrogen Embrittlement.....	72
6.3	Thermal Considerations in Material Selection.....	77
7	Hydrogen Facilities	78
7.1	Safety Policy	78
7.2	Safety Reviews	79
7.3	General Facility Guidelines.....	81
7.4	Buildings and Test Chambers.....	85
7.5	Control Rooms.....	87
7.6	Location and QD Guidelines.....	88
7.7	Exclusion Areas	92
7.8	Protection of Hydrogen Systems and Surroundings	93
7.9	Fire Protection	95
7.10	Documentation, Tagging, and Labeling of Storage Vessels, Piping, and Components.....	97
7.11	Instrumentation and Monitoring	98
7.12	Examination, Inspection, and Recertification.....	99
8	Hydrogen Storage Vessels, Piping, and Components	101
8.1	General Requirements.....	101
8.2	Storage Vessels.....	102
8.3	Piping Systems	106
8.4	Components	109
8.5	Overpressure Protection of Storage Vessels and Piping Systems	116
8.6	Hydrogen Vent and Flare Systems.....	118
8.7	Contamination.....	123
8.8	Vacuum System.....	124
8.9	Liquid Hydrogen Pumping	126
9	Hydrogen and Hydrogen Fire Detection	126
9.1	Hydrogen Detection	126
9.2	Hydrogen Fire Detection Systems	131
10	Operating Procedures.....	134
10.1	General Policy	134
10.2	Storage and Transfer Procedures	138
11	Transportation.....	143

ANSI/AIAA G-095A-2017

11.1	General	143
11.2	Transport on Public Thoroughfares	144
11.3	Transport on Privately Controlled Thoroughfare	145
11.4	Transportation Emergencies.....	146
12	Emergency Procedures	147
12.1	General	147
12.2	Types of Emergencies	148
12.3	Assistance in Emergencies.....	151
12.4	Fire Suppression.....	152
12.5	First Aid for Cryogenic-Induced Injuries	153
12.6	Safeguards for Entering Permit-Required Confined Spaces.....	154
Annex A	Bibliography (Informative).....	155
Annex B	Codes, Standards and Regulations (Informative)	166
B.1	General.....	166
B.2	Pressure Vessel Codes and Standards	166
B.3	Codes and Standards for Pressure Piping.....	168
B.3.2	ASME B31.12, Hydrogen Piping and Pipelines	169
B.3.3	ASME B31.3, Process Piping (formerly, Chemical Plant and Petroleum Refinery Piping).....	169
B.3.4	CGA G5.4, Standard for Hydrogen Piping Systems at Consumer Locations	170
B.4	Standards and Regulations for the Commercial, Industrial, and Non-Propellant Use of Hydrogen.....	170
B.4.1	NFPA 2, NFPA 55, and NFPA 50A and NFPA 50B.....	170
B.4.1.1	General	170
B.4.1.2	NFPA 50A, Gaseous Hydrogen Systems at Consumer Sites.....	171
B.4.1.3	NFPA 50B, Liquefied Hydrogen Systems at Consumer Sites	172
B.4.2	Code of Federal Regulations	172
B.4.2.1	Title 29 — Labor	172
B.4.2.2	29 CFR 1910.103, Hydrogen	173
B.5	Standard for the Propellant Use of Liquefied Hydrogen	174
B.5.1	General.....	174
B.5.2	Hazards Addressed	174
B.5.3	Protection for Personnel and Property	175
B.5.4	Construction Criteria.....	176
B.5.5	QD and Siting	176

B.5.5.1 General	176
B.5.5.2 QD Requirements for Energetic Liquids	177
Annex C Figures and Tables (Informative).....	186
C.1 Hydrogen Physical Data	186
C.2 Metals Data	216
C.3 Hydrogen Gaseous and Liquid Non-Propellant QD Information	221
Annex D Training Guidance	225
Annex E Safety Data Sheet (SDS) (Informative)	229
E.1 Gaseous Hydrogen.....	229
E.2 Liquid Hydrogen—Cryogenic Liquid	239
Annex F Hazard Assessment Examples (Informative)	252
F.1 Example 1: Calculation of the Pressure Rise With Temperature for Both LH ₂ and SLH ₂	252
F.2 Example 2: Analysis of Heat Leak on LH ₂ and Ortho-to-Para Conversion and Resulting Effects on SLH ₂ Systems	254
F.3 Example 3: Detonation of GH ₂ With Air/Oxygen	257
F.4 Example 4: Deflagration of Hydrogen With Air/Oxygen	257
F.5 Example 5: Dispersion of Hydrogen Release.....	258
F.6 Example 6: Amount of Solid Insulation (not Vacuum) Required for a Specified Test Line	261
F.7 Example 7: Calculation for Siting an LH ₂ Storage Dewar	265
F.8 Example 8: Analysis of a Pressure Relief Valve for a Cryogenic Storage Vessel	267
0.00024in2lbmH2O*771.1gal H2O*1ft37.48 gal*62.2lbmft3 = 1.54in2	270
F.9 Example 9: Analysis of a Hydrogen Vent/Flare System.....	271
F.10 Example 10: Purging a Hydrogen System	272
F.11 Example 11: Analysis of the Heat Leak Into a LH ₂ or SLH ₂ Transfer Line and Analysis of the Quantity of LH ₂ Consumed to Cool the Transfer Line	274
Annex G Scaling Laws, Explosions, Blast Effects, and Fragmentation (Informative)	277
G.1 Scaling Laws.....	277
G.2 Types of Explosions.....	278
G.2.1 Explosions in Buildings	278
G.2.2 Tank Ruptures.....	278
G.2.3 Vapor Cloud Explosions.....	279
G.2.4 Ground-Handling System Explosions	280
G.3 Characteristics of Fragments	280
G.4 Effects of Barricades on Blast Waves.....	281

G.5	Estimates of Explosive Yields from Compressed Gas Bursts	281
G.5.1	Compressed Gas Bursts	281
G.6	Degrees of Hazard	283
G.7	Additional Guidelines	284
Annex H	Relief Devices (Informative).....	285
H.1	General.....	285
H.2	Rupture Disks	286
H.3	Capacity Rating of Relief Devices.....	286
H.4	Recommended Principles	289

List of Tables

Table 1	— Temperature and pressure resulting from combustion of a given amount of hydrogen and oxidizer in a specific volume.....	28
Table 2	— Flammability limits of hydrogen	33
Table 3	— Flammability limits ^a	34
Table 4	— Hydrogen–air flammability ^a	35
Table 5	— Hydrogen–oxygen flammability ^a	35
Table 6	— Effects of diluents ^a on flammable range for hydrogen in air ^b	37
Table 7	— Inhibitor for extinction of hydrogen diffusion flames ^a	39
Table 8	— Minimum ignition energy	40
Table 9	— Detonation overpressures	49
Table 10	— Comparison of relative maximum overpressure by combustion mechanism (assuming near stoichiometric mixtures at initial conditions of 298 K, 1 atm).....	49
Table 11	— Potential ignition sources	52
Table 12	— Critical radiant flux levels ^a	54
Table 13	— Effect of oxygen deficient atmosphere depletion	58
Table 14	— Effects of thermal radiation exposure.....	59
Table 15	— Health effects due to exposure to overpressure	61
Table 16	— Hydrogen accidents—industrial ^a	62
Table 17	— Hydrogen accidents—ammonia plants ^a	63
Table 18	— Hydrogen accidents—aerospace ^a	63
Table 19	— Summary of material compatibility for hydrogen service.....	68
Table 20	— A selection of recommended materials for typical applications	69
Table 21	— Typical characteristics of hydrogen embrittlement types ^a	74
Table 22	— Order of preference for location of GH ₂ storage systems ^{a, b}	89
Table 23	— Order of preference for location of LH ₂ storage systems ^{a, b, c}	90
Table 24	— Sensitivity limits of hydrogen detectors ^a	128
Table 25	— Typical hydrogen gas detectors	128
Table 26	— Typical hydrogen fire detectors ^a	132
Table 27	— Summary of liquefied hydrogen spill data	150

List of Figures

Figure 1	— Equilibrium percentage of parahydrogen vs. temperature (McCarty et al., 1981).	21
----------	--	----

Figure 2 - Hydrogen spectra showing relative emission strength as a function of wavelength in nanometers (Woods, 2013).....	29
Figure 3 - Intensity calibrated irradiance from hydrogen flames for UV/visible/near-IR emissions (Arens, et al., 2014).....	30
Figure 4 — Irradiance of common sources (Rosen, Dayan, and Proffitt, 1970).....	31
Figure 5 — Atmospheric IR transmission and hydrogen-air-flame emission (Rosen, Dayan, and Proffitt 1970).	31
Figure 6 — Ignition energy and flammability limits.	33
Figure 7 — Flammability limits at a pressure of 101.3 kPa (14.7 psia) and a temperature of 298 K (77 °F) (Coward and Jones, 1952; Payman and Titman, 1936).....	37
Figure 8 — Effects of N ₂ , He, and CO ₂ diluents at 298 K (77 °F), and H ₂ O diluent at 422 K (300 °F) on flammability limits of hydrogen in air at 101.3 kPa (14.7 psia) (Coley and Field, 1973; Coward and Jones, 1952; Jones and Perrott, 1927).	38
Figure 9 — Effects of halocarbon inhibitors on flammability limits of hydrogen-oxygen mixtures at a pressure of 101.3 kPa (14.7 psia) and a temperature of 298 K (77 °F) (McHale, Geary, von Elbe, and Huggett, 1971).....	38
Figure 10 — The effect of hydrogen concentration on burning velocity for hydrogen–air mixtures at 298 K (77 F) and 101.3 kPa (14.7 psia) (Lewis and von Elbe, 1961; Liu and MacFarlane, 1983).....	42
Figure 11 — Minimum dimensions of GH ₂ -air mixtures for detonation at 101.3 kPa (14.7 psia) and 298 K (77 °F) (Lee, Kynstantus, Guirao, Benedick, and Shepherd, 1982).....	45
Figure 12 — Smoked foil record of cell structure (diamond patterns etched in soot as detonation progresses from left to right).	46
Figure 13 — Detonation cell widths for hydrogen–air mixtures at 101.3 kPa (14.7 psia) (Lee, Kynstantus, Guirao, Benedick, and Shepherd, 1982).....	47
Figure 14 — Minimum initiation energy for direct detonation of hydrogen–air mixtures (Lee, Kynstantus, Guirao, Benedick, and Shepherd, 1982).....	47
Figure 15 — Variation in distance from a hydrogen fire for a thermal radiation exposure of 2 cal/cm ² deposited over a duration of 10 seconds (Zabetakis and Burgess 1961).	60
Figure 16 — Distance for fireball radiation flux induced third-degree burns per amount of hydrogen fuel burned at a thermal radiation intensity of 134 kJ/m ² (11.8 But/ft ²) (Siegel and Howell, 1971).....	60
Figure 17 — Radiation intensity as a function of exposure time or escape time (Kent 1964).....	61
Figure 18 — General mishap causes (Ordin 1974).....	64
Figure 19 — Detailed mishap causes (Ordin 1974).....	64
Figure 20 — Elements of hydrogen control.	66
Figure 21 — Classification of hydrogen environment embrittlement (HEE), internal hydrogen embrittlement (IHE), and hydrogen reaction embrittlement (HRE).	73
Figure 22 — Double-block-and-bleed arrangement.	109
Figure 23 — Flame dip as a function of stack diameter and hydrogen flow (Grumer, Strasser, Singer, Gussey, and Rowe, 1970).....	120

Figure 24 — Blowout and stable flame region (Grumer, Strasser, Singer, Gussey, and Rowe, 1970)....	121
Figure 25 — Flame shape in crosswinds (Brzustowski, Gollahalli, and Sullivan 1975; Ordin and Carter, 1980).	122
Figure 26 — Flame components.....	133
Figure 27 — Minimum flow rate for nonstratified, two-phase hydrogen and nitrogen flow for pipeline fluid qualities below 95% and 98%.	141
Figure 28 — Liquid hydrogen flow rate limits to avoid excessive cooldown stresses in thick-wall piping sections such as flanges for 304 SS and 6061 Al.....	142
Figure 29 — Liquid nitrogen flow rate limits to avoid excessive cooldown stresses in thick-wall piping sections such as flanges for 304 SS and 6061 Al.....	142
F.6 Example 6: Amount of Solid Insulation (not Vacuum) Required for a Specified Test Line	261

Foreword

Hydrogen is a lightweight, easily ignitable element that is extremely useful in a wide range of applications. In aerospace applications, which are the focus of this guide, it is used as a propulsion fuel and as a reactant in fuel cells to provide electrical power. As with any fuel, there are hazards inherent with hydrogen's use. The users and designers of hydrogen systems must be aware of these hazards and safeguard against them. One of the goals of this technical guide is to document these hazards and the safety considerations involved in addressing them.

Although a substantial amount of information has been compiled in this guide, the user is cautioned that there are many sources of information regarding the safe use of hydrogen. New research is conducted and new applications are being developed regularly. This technical guide is released with the currently compiled information and will be periodically updated as new data are obtained. Users are encouraged to assess their individual programs and develop additional requirements as needed.

The original version of this AIAA Guide replaced the "Safety Standard for Hydrogen and Hydrogen Systems," NASA Safety Standard (NSS) 1740.16, which established a uniform NASA process for hydrogen system design, materials selection, operation, storage, and transportation. This revision of the Guide provides updated information in the field including the following:

- Reorganized information to reflect the actual process
- Placed relevant figures and tables within the document for ease of reference
- Updated information regarding safety, detectors, leaks, and accidents.

In addition, information on embrittlement has been published as a separate document (NASA TM-2016-218602) and has informed key sections of this Guide.

In formulating, revising, and approving standards publications, the Hydrogen CoS will not consider patents that may apply to the subject matter. Prospective users of the publications are responsible for protecting themselves against liability for infringement of patents, or copyrights, or both.

The current members of the Hydrogen CoS acknowledge the valuable input from several original members, especially Howard Julien, William St. Cyr, and David Coote, and are grateful for the contributions of past committee members and reviewers in their efforts to improve this Guide.

At the time of approval, the members of the AIAA Hydrogen Committee on Standards (CoS) were:

Stephen Woods (Chair)	Jacobs Technology, Inc., White Sands Test Facility
Stephen McDougale (Secretary)	Jacobs Technology, Inc., White Sands Test Facility
Joseph Breit	Boeing
Michael Caddy	U.S. Navy
David Coote	NASA Stennis Space Center
Josephine Covino	Department of Defense, Explosives Safety Board
Laurence de Quay	NASA Stennis Space Center
Eric Dirschka	NASA Kennedy Space Center
Randy Fowler	University of Central Florida
Robert Johnson	NASA Kennedy Space Center
John Jurns	European Spallation Source

ANSI/AIAA G-095A-2017

Jonathan Lee	NASA Marshall Space Flight Center
Miguel Maes	NASA Johnson Space Center, White Sands Test Facility
Mohamad Naraghi	Manhattan College
Timothee Pourpoint	Purdue University
Ali T-Raissi	Florida Solar Energy Center
Carl Rivkin	National Renewable Energy Laboratory
Scott Schneider	Hamilton Sundstrand United Technologies
Andy Slifka	National Institute of Standards and Technology
Steve Summer	Federal Aviation Administration
Peter Sunderland	University of Maryland
Yvonne Tran	Federal Aviation Administration
Joseph Zoeckler	NASA Glenn Research Center

The above consensus body approved this document in October 2017.

The AIAA Standards Executive Council (VP-Standards, Mr. Allen Arrington, Chairman) accepted the document for publication in October 2017.

The AIAA Standards Procedures dictates that all approved standards, recommended practices, and guides are advisory only. Their use by anyone engaged in industry or trade is entirely voluntary. There is no agreement to adhere to any AIAA standards publication and no commitment to conform to or be guided by standards reports. In formulating, revising, and approving standards publications, the committees on standards will not consider patents that may apply to the subject matter. Prospective users of the publications are responsible for protecting themselves against liability for infringement of patents or copyright, or both.

Introduction

This Guide contains guidelines for safely storing, handling, and using hydrogen in gaseous (GH_2), liquefied (LH_2), slush (SLH_2), or solid (SH_2) forms, whether used as a propellant or nonpropellant. Topics covered include sections on hydrogen properties and hazards, materials compatibility, facility design, design of components, detection, and transportation. It also covers various operational issues and emergency procedures. The material in these sections is supplemented by details and information in the following informative annexes in this guide:

- Annex A is the bibliography.
- Annex B gives information related to applicable codes, standards, and regulations.
- Annex C provides selected (primarily safety related) chemical, physical, and combustion properties of hydrogen, and information regarding storage siting, venting and flow, materials, hydrogen and hydrogen fire detection, and accidents involving hydrogen.
- Annex D provides guidance on training information recommended for operators.
- Annex E is the sample Safety Data Sheet (SDS).
- Annex F gives assessment examples to illustrate the use of selected requirements.
- Annex G describes scaling laws, explosions, blast effects, and fragmentation.
- Annex H provides information regarding pressure relief devices (PRDs) and requirements.

The information is arranged in an easy-to-use format. The reader will find the following useful to note:

- A numbered outline format is used so information can be readily found and easily cited.
- Acronyms are defined when introduced, and a tabulation of acronyms used in the document is provided in Section 3.1, Acronyms and Abbreviated Terms.
- Definitions of many of the terms used in this guide are given in Section 3.2, Terms and Definitions.
- All sources are referenced so the user can verify original sources as deemed necessary. References cited in the main body of the text can be found in the bibliography in Annex A. The latest revisions of codes, standards, and mandatory regulations should be used when those referenced are superseded.
- The International System of Units (SI) is used for primary units, and U.S. Customary units are given in parentheses following the SI units. Some of the tables and figures contain only one set of units.

Trademarks

The following commercial products that require designation are mentioned in this document. This information is given for the convenience of the users of this guide and does not constitute an endorsement. Equivalent products may be used if they can be shown to lead to the same result.

Braycote™	Bray Oil Company	Los Angeles, CA
Dacron™	E. I. du Pont de Nemours and Company	Wilmington, DE
E-Con™	Reflange, Inc.	Houston, TX
Fluorogold™	Seismic Energy Products	Athens, TX
Fluorogreen™	ATG Group	Houston, TX
Grayloc™	Gray Tool Company	Houston, TX
Hastelloy™	Haynes International, Inc.	Kokomo, IN
Heliarc™	ESAB Welding & Cutting Products	Florence, SC
Inconel™	Inco Alloys International, Inc.	Huntington, WV
Invar™	Carpenter Technology	Reading, PA
Krytox™	E. I. du Pont de Nemours and Company	Wilmington, DE
Monel™	Inco Alloys International, Inc.	Huntington, WV
Mylar™	E. I. du Pont de Nemours and Company	Wilmington, DE
Nomex™	E. I. du Pont de Nemours and Company	Wilmington, DE
R-Con™	Reflange, Inc.	Houston, TX
Teflon™	E. I. du Pont de Nemours & Company	Wilmington, DE
Tygon™	Saint-Gobain Corporation	Malvern, PA
Versilube™	General Electric Company	Schenectady, NY
Viton™	E. I. du Pont de Nemours and Company	Wilmington, DE

This is a preview of "ANSI/AIAA G-095A-201...". [Click here to purchase the full version from the ANSI store.](#)

1 Scope

This Guide presents information that designers, builders, and users of hydrogen systems can use to manage and ensure safe hydrogen systems or resolve hazards related to the material behavior, facility storage, detection, and transportation of hydrogen as well as a review of emergency procedures. Pertinent research is summarized and supporting data are presented relative to the topic. Additional information regarding codes, standards, and regulations, as well as a sample safety data sheet, training examples, and other useful material are referenced and can be found in the annexes.

The intent of this Guide is to provide enough information that it can be used alone; at the same time, data sources that can provide much more detail, if required, are referenced and listed in Annex A (Bibliography).

1.1 Purpose

This Guide provides a minimum set of practical guidelines for safe hydrogen use. Users are encouraged to assess their individual programs and develop additional requirements as needed. The information presented here should be used as a reference to hydrogen design and practice and not as an authorizing document.

1.2 Applicability

The focus of this Guide is on molecular hydrogen formed from protium, as opposed to isotopes of hydrogen deuterium and tritium. This Guide shall apply to the design, installation, storage, use, and handling of hydrogen, in GH₂, LH₂, SLH₂, and SH₂ forms, and for all occupancies. The words "shall" and "must" are used in this Guide to indicate a mandatory requirement, and the authority for the requirement is given. The words "should" and "will" are used to indicate a recommendation or that which is advised but not mandatory.

In this Guide the use of hydrogen is separated into two categories—propellant and nonpropellant as described below.

- 1) The propellant category is distinguished by hydrogen usage wherein system failure could induce mixing of significant amounts of hydrogen and oxidizer, or high-pressure release, or large quantities to catastrophic effect, such as may be anticipated for failures in missile and rocket propulsion applications. The propellant category commonly involves facilities such as launch pads, static test stands, and associated propellant storage tanks at risk to physical damage by the intended operations.
- 2) The nonpropellant category covers the use of hydrogen in any of a multitude of laboratory, commercial, industrial, and consumer applications. The distinguishing features of these applications are that an unintended release of hydrogen can only involve air, and that hazards are minimized, either through use of small quantities or through well characterized operations whose hazards are known and mitigated.

1.3 Application

The practice and requirements of this Guide shall apply to designers, users, operators, maintainers, quality assurance personnel, and designated project managers who are responsible for incorporating the appropriate requirements of this Guide into their projects or facilities.

1.4 Responsibility

The use of this Guide does not relieve the designer, user, operator, maintainer, quality assurance person, or designated managers of professional responsibility or allow them to preclude the exercise of sound engineering judgment.