

# ANSI B11.19-2019

## *Performance Requirements for Risk Reduction Measures: Safeguarding and other Means of Reducing Risk*

ANSI-Accredited Standards Developer and Secretariat:



B11 Standards, Inc.  
POB 690905  
Houston, TX 77269, USA

**APPROVED: 11 OCTOBER 2019**

by the American National Standards Institute  
Board of Standards Review



**COPYRIGHT PROTECTED DOCUMENT**

Copyright © 2019 by B11 Standards, Inc.

All rights reserved. Printed in the United States of America

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of B11 Standards, Inc.

## **AMERICAN NATIONAL STANDARDS**

By approving this American National Standard, the ANSI Board of Standards Review confirms that the requirements for due process, consensus, balance, and openness have been met by B11 Standards, Inc., (the ANSI-accredited standards developing organization). American National Standards are developed through a consensus process. Consensus is established when substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward resolution. This process brings together volunteers and/or seeks out the views of persons who have an interest in the topic covered by this publication. While B11 Standards, Inc., administers the process and establishes procedures to promote fairness in the development of consensus, it does not write the document and it does not independently test, evaluate or verify the accuracy or completeness of any information or the soundness of any judgments contained in its standards or guidelines.

American National Standards are promulgated through ANSI for voluntary use; their existence does not in any respect preclude anyone, whether they have approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards. However, users, distributors, regulatory bodies, certification agencies and others concerned may apply American National Standards as mandatory requirements in commerce and industry.

**Neither B11 Standards, Inc. nor any of the organizations or individuals that assisted in authoring, developing, editing or distributing this standard (B11 Standards, Inc. and such organizations and individuals collectively referred to as the "Contributing Parties") makes any warranty, either expressed or implied, as to the fitness of merchantability or accuracy of the information contained within this standard. The Contributing Parties disclaim and make no warranty that the information in this document will fulfill any of your particular purposes or needs. The Contributing Parties disclaim liability for any personal injury, property or other damages of any nature whatsoever, whether special, indirect, consequential or compensatory, directly or indirectly resulting from the publication, use of, application or reliance on this document. The Contributing Parties do not undertake to guarantee the performance of any individual manufacturer or seller's products or services by virtue of this standard or guide, nor does it take any position with respect to the validity of any patent rights asserted in connection with the items which are mentioned in or are the subject of this document. The Contributing Parties disclaim liability for the infringement of any patent resulting from the use of or reliance on this document. Users of this document are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.**

**In publishing or making this document available, the Contributing Parties are not undertaking to render professional or other services for or on behalf of any person or entity, nor are the Contributing Parties undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment, or as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances. In addition to conforming to the requirements of this standard, the responsible personnel must also make an independent determination as to whether a machine, activity or condition complies with the applicable legal requirements in the relevant jurisdiction(s).**

B11 Standards, Inc., has no power, nor does it undertake to police or enforce conformance to the requirements of this document. B11 Standards, Inc., does not certify, test or inspect products, designs, or installations for safety or health purposes. Any certification or other statement of conformance to any health or safety-related information in this document shall not be attributable to B11 Standards, Inc., and is solely the responsibility of the certifier or maker of the statement. The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of an American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretations should be addressed to the Secretariat (B11 Standards, Inc.).

**NOTICE:** This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this standard. You may contact the Secretariat for current status information on this, or other B11 standards.

Published by: B11 Standards, Inc.  
POB 690905, Houston, Texas 77269, USA

**Copyright © 2019** by B11 Standards, Inc.

**All rights reserved.** Printed in the United States of America

**No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.**

Table of Contents	Page
<b>Foreword</b> .....	<b>v</b>
<b>Application</b> .....	<b>v</b>
<b>Effective Date</b> .....	<b>v</b>
<b>Harmonization</b> .....	<b>v</b>
<b>History</b> .....	<b>vi</b>
<b>Terminology</b> .....	<b>vii</b>
<b>Context</b> .....	<b>vii</b>
<b>1 Scope</b> .....	<b>12</b>
<b>2 References</b> .....	<b>13</b>
2.1 Normative references .....	13
2.2 Informative References .....	13
<b>3 Definitions</b> .....	<b>15</b>
<b>4 Responsibility</b> .....	<b>27</b>
4.1 Supplier responsibilities .....	27
4.2 User responsibilities .....	27
4.3 Integrator / modifier / rebuilder responsibilities .....	28
4.4 Personnel responsibilities .....	28
<b>5 Risk assessment process</b> .....	<b>29</b>
<b>6 Risk reduction measures</b> .....	<b>30</b>
6.1 General requirements for risk reduction measures .....	30
<b>7 Inherently safe by design</b> .....	<b>32</b>
7.1 General requirements for inherently safe design measures .....	32
7.2 Prevention through design .....	32
7.3 Safe-opening safeguarding method .....	32
7.4 Safe-location safeguarding method .....	33
7.5 Minimum gaps to avoid crushing of parts of the human body .....	34
7.6 Maximum gaps to avoid exposure to hazards .....	36
<b>8 Engineering controls – guards</b> .....	<b>37</b>
8.1 General requirements for guards .....	37
8.1.1 Guard design and construction.....	37
8.1.2 Guard visibility.....	39
8.1.3 Guard Location .....	39
8.1.4 Guard operation and maintenance .....	40
8.2 Fixed guards.....	40
8.3 Movable guards.....	41
8.4 Interlocked Guards.....	41
8.5 Adjustable guards .....	43
8.6 Self-adjusting guards .....	43
8.7 Partial guards .....	44
8.8 Perimeter guards.....	45
8.9 Nip guards .....	46
8.10 Shields.....	47
<b>9 Engineering controls – control functions</b> .....	<b>48</b>
9.1 General requirements for control functions .....	48
9.2 Performance of safety functions.....	48
9.2.1 General requirements for safety functions.....	48
9.2.2 Safety interface (safety relay) modules .....	49
9.2.3 Considerations for safety-related application software (SRASW) .....	50
9.3 Monitoring functions .....	51

9.3.1	General requirements for monitoring functions .....	51
9.3.2	Safe condition (stopping performance) monitoring systems .....	52
9.3.3	Speed monitoring function .....	53
9.4	Stop functions.....	54
9.4.1	Normal stop function .....	55
9.4.2	Emergency stop function .....	55
9.4.3	Protective stop function .....	56
9.5	Safety-related reset.....	59
9.5.1	General requirements for reset.....	59
9.5.2	Automatic reset .....	60
9.5.3	Manual reset .....	60
9.6	Safety distance.....	61
9.7	Suspension of safety functions .....	63
9.7.1	Manual suspension (bypassing) .....	63
9.7.2	Muting .....	64
9.8	Variable sensing functions .....	69
9.8.1	Safety-related sensing field switching .....	69
9.8.2	Safety-related sensing field blanking.....	76
9.9	Presence-Sensing Device Initiation (PSDI) .....	78
9.9.1	General requirements for PSDI .....	78
9.9.2	PSDI control logic .....	80
9.9.3	PSDI operation.....	82
9.9.4	User responsibilities for PSDI .....	82
9.10	Perimeter risk reduction measures .....	83
9.11	Whole body access .....	83
9.11.1	General requirements for whole body access .....	83
9.11.2	Control of hazardous energy .....	85
9.11.3	Prevent undetected presence of individuals within the safeguarded space.....	86
9.11.4	Manual reset .....	87
9.11.5	Location of safety-related manual control devices .....	88
9.11.6	Inhibit function.....	88
9.11.7	Interlock devices capable of internal opening.....	89
9.11.8	Initiation warning system .....	90
9.12	Span of control .....	95
9.12.1	Layout analysis .....	95
9.12.2	Level of safety performance .....	96
9.12.3	Identification.....	96
<b>10</b>	<b>Engineering controls – devices.....</b>	<b>97</b>
10.1	General requirements for devices .....	97
10.2	Interlock devices .....	97
10.3	Trapped (captive) key systems .....	103
10.3.1	General requirements for trapped key systems.....	103
10.3.2	Trapped key system design.....	104
10.3.3	Trapped key system installation .....	105
10.3.4	Trapped key system operation .....	105
10.4	Interlock blocking devices .....	106
10.5	Movable barrier devices .....	107
10.5.1	General requirements for movable barrier devices .....	107
10.5.2	Type A movable barrier devices .....	108
10.5.3	Type B movable barrier device .....	108
10.6	Pull back (pull out) and hold out (restraint) devices .....	108
10.6.1	General requirements for pull back and hold out (restraint) devices.....	108
10.6.2	Pull back and hold out (restraint) device operation .....	109
10.7	Presence-sensing devices .....	110
10.7.1	General requirements for presence-sensing devices.....	110
10.7.2	Light curtains and single/multiple beam devices .....	112

10.7.3	Area scanning devices.....	114
10.7.4	Close proximity point of operation AOPDs .....	117
10.7.5	Vision-based protective devices .....	117
10.7.6	Safety mat devices .....	118
10.7.7	Safety edge / bumper devices .....	119
10.7.8	Probe detection devices .....	121
10.7.9	Radio frequency devices .....	121
10.8	Two-hand actuating controls .....	123
10.8.1	General requirements for two-hand actuating controls .....	123
10.8.2	Two-hand control devices .....	125
10.8.3	Two-hand trip devices.....	126
10.8.4	Two-hand operating levers .....	126
10.9	Single actuating controls .....	126
10.9.1	General requirements for single actuating controls .....	126
10.9.2	Single control devices .....	128
10.9.3	Single trip devices.....	128
10.10	Hold-to-run control devices .....	129
10.11	Enabling devices .....	130
10.12	Emergency stop (E-stop) devices .....	131
10.12.1	General requirements for E-stop devices .....	131
10.12.2	Pushbutton-type E-stop devices .....	133
10.12.3	Rope or cable pull-type E-stop devices .....	134
10.12.4	Foot-operated E-stop devices.....	135
10.12.5	Rod-operated E-stop devices .....	135
10.12.6	Push-bar-operated E-stop devices .....	135
10.13	Slide locks .....	136
<b>11</b>	<b>Administrative controls.....</b>	<b>137</b>
11.1	General requirements for administrative controls .....	137
11.2	Awareness means.....	137
11.2.1	General requirements for awareness means .....	137
11.2.2	Awareness barriers .....	138
11.2.3	Awareness signals.....	138
11.2.4	Awareness (safety) signs.....	140
11.2.5	Awareness (safety) markings .....	140
11.3	Information for use (human and organizational) .....	140
11.3.1	Instruction manual (handbook) .....	140
11.3.2	Safe work procedures .....	141
11.3.3	Training .....	142
11.3.4	Inspection and maintenance.....	143
11.4	Administrative safeguarding methods .....	144
11.4.1	Safe-distance safeguarding method.....	144
11.4.2	Safe-holding safeguarding method.....	145
11.4.3	Other safeguarding methods .....	145
11.5	Supervision.....	145
11.5.1	Supervision of the workplace.....	146
11.5.2	Avoidance of unauthorized changes .....	146
11.5.3	Management of change .....	149
11.6	Control of hazardous energy.....	149
11.6.1	Lockout / tagout .....	149
11.6.2	Alternative methods .....	150
11.6.3	Restraint mechanisms .....	150
11.7	Tools.....	152
11.7.1	Workholding equipment .....	152
11.7.2	Hand tools.....	152
11.8	Personal Protective Equipment (PPE) .....	153

**LIST of ANNEXES (all Informative)**

Annex A – Guidance to Understand the ANSI B11 Series of Standards & Technical Reports ..... 154  
 Annex B –Hazard List for Risk Reduction Measures ..... 155  
 Annex C – Performance of the Safety Function(s) ..... 156  
 Annex D – Comparison of Physical Barriers ..... 159  
 Annex E – Reaching Distance Considerations for Protective Structures ..... 160  
 Annex F – Nip Guards..... 171  
 Annex G – Considerations for Transparent Guards ..... 176  
 Annex H – Safety Distance Calculations for Engineering Controls – Devices ..... 182  
 Annex I – Reaching Distance Considerations for Engineering Controls – Devices..... 188  
 Annex J – Measurement & calculation of system performance to achieve a safe condition ..... 211  
 Annex K – Achieving a Safe Condition ..... 214  
 Annex L – Safety Functions for Power Drive Systems ..... 215  
 Annex M – Supplier Information for Time and Distance to Achieve a Safe Condition..... 225  
 Annex N – Awareness Means..... 226  
 Annex O – Risk Reduction Measures in Use..... 230  
 Annex P – Cross-Reference Mapping of ANSI B11.19: 2010 vs. 2019..... 238  
 Bibliography of Informatively Referenced International Documents ..... 251

**LIST of FIGURES**

Figure 1 — Organization of the B11 Series of Documents ..... x  
 Figure 2 — Example of sensing field switching ..... 75  
 Figure 3 — Example of sensing field switching of a light curtain to allow passage of material ..... 75  
 Figure 4 — Example of sensing field switching of an area scanner to allow passage of material..... 76  
 Figure 5 — Determining effective detection capability of a light curtain ..... 77  
 Figure 6 — Example of Whole body Access ..... 84  
 Figure 7 — Example of pre-start warning system used for momentary jog control ..... 94  
 Figure 8 — Example of a mechanical interlock ..... 98  
 Figure 9 — Examples of interlock devices that control energy ..... 98  
 Figure 10 — Example of trapped key transfer system ..... 105  
 Figure 11 — Examples of two-hand actuating device design ..... 124  
 Figure A.1 – Typical clause layout of ANSI B11 ‘base’ standards showing the various responsibilities .. 154  
 Figure E.1 – Reaching over a protective structure ..... 162  
 Figure E.2a – Protective structure location versus opening size for slotted openings ..... 165  
 Figure E.2b – Protective structure location versus opening size for square openings ..... 165  
 Figure E.2c – Protective structure location versus opening size for round openings ..... 165  
 Figure E.3 – Reaching through a protective structure with openings of irregular shape ..... 167  
 Figure E.4 – Prevention of whole body access through a protective structure ..... 167  
 Figure E.5 – Reaching through a protective structure indirectly ..... 168  
 Figure E.6 – Reaching under a protective structure ..... 169  
 Figure E.7 – Consideration of all reaching factors for protective structures ..... 170  
 Figure F.1 – Examples of in-running nip hazards ..... 171  
 Figure F.2 – Examples of nip guards ..... 171  
 Figure F.3 – Examples of protecting nip points from side entry..... 172  
 Figure F.4 – Locating hazard points of in-running nips..... 173  
 Figure F.5 – Minimum cylinder-to-guard angle (<sup>a</sup> preferred, <sup>b</sup> acceptable) ..... 173  
 Figure F.6 – Nip guards that create wedge pockets ..... 173  
 Figure F.7 – Nip guards that do not create wedge pockets ..... 174  
 Figure F.8 – Nip guard clearance ..... 174  
 Figure F.9 – Example determining guard distances and openings..... 175  
 Figure G.1 – Aging curve of unprotected polycarbonate (averaged test points) ..... 177  
 Figure H.1 – Reaction time block diagram ..... 184  
 Figure I.1 – Vertical application of a presence-sensing device ..... 191  
 Figure I.2 – Horizontal application of a presence-sensing device ..... 191  
 Figure I.3 – Reaching over a vertical presence-sensing device ..... 192



Figure I.4 – Reaching over a vertical presence-sensing device with an additional protective structure .. 194  
 Figure I.5 – Reaching through a vertical sensing field with  $d_e \leq 64$  mm (2.52") ..... 195  
 Figure I.6 – Reaching distance when reaching through a vertical sensing field for PSDs ..... 196  
 Figure I.7 – Reaching through a vertical sensing field with  $64$  mm  $< d_e \leq 600$  mm  $d_{dt} = 850$  mm ..... 196  
 Figure I.8 – Reaching under a vertical presence-sensing device ..... 197  
 Figure I.9 – Reaching under a vertical presence-sensing device with an additional protective structure 198  
 Figure I.10 – Consideration of all reaching factors for a vertical sensing field ..... 199  
 Figure I.11 – Reaching over a horizontal presence-sensing device ..... 200  
 Figure I.12 – Height of a horizontal sensing field ..... 201  
 Figure I.13 – Allowable height of a horizontal sensing field,  $H_s$  ..... 201  
 Figure I.14 – Minimum Depth of Sensing Field ..... 202  
 Figure I.15 – Distance from end of horizontal sensing field to nearest obstruction ..... 203  
 Figure I.16 – Safety distance for single beam devices  $d_{ds} = 1200$  mm (47.74") ..... 203  
 Figure I.17 - Safety distance for two-hand actuating controls (no shroud)  $d_{ds} = 550$  mm (21.65") ..... 204  
 Figure I.18 - Safety distance for hand-operated single actuating controls  $d_{ds} = 2200$  mm (86.61") ..... 204  
 Figure I.19 - Safety distance for foot-operated single actuating controls  $d_{ds} = 2500$  mm (98.43") ..... 205  
 Figure I.20 – Safety distance for radio frequency devices ..... 205  
 Figure I.21 – Example of interlocked linear movable guard ..... 206  
 Figure I.22 – Example of interlocked angular movable guard ..... 207  
 Figure I.23 – Variables for determining opening (e) for a movable guard with a hinge switch ..... 207  
 Figure I.24 – Diagram of force-travel relationship ..... 210  
 Figure L.1 – Safe Torque Off (STO) ..... 216  
 Figure L.2 – Safe Stop 1 Deceleration Controlled (SS1-d) ..... 216  
 Figure L.3 – Safe Stop 1 Ramp Monitored (SS1-r) ..... 217  
 Figure L.4 – Safe Stop 2 Deceleration Controlled (SS2-d) ..... 217  
 Figure L.5 – Safe Stop 2 Ramp Monitored (SS2-r) ..... 217  
 Figure L.6 – Safe Operating Stop (SOS) ..... 218  
 Figure L.7 – Safely-Limited Acceleration (SLA) ..... 218  
 Figure L.8 – Safe Acceleration Range (SAR) ..... 220  
 Figure L.9 – Safely-Limited Speed (SLS) ..... 220  
 Figure L.10 – Safely Speed Range (SSR) ..... 220  
 Figure L.11 – Safely-Limited Position (SLP) ..... 221  
 Figure L.12 – Safely-Limited Increment (SLI) ..... 221  
 Figure L.13 – Safe Direction (SDi) ..... 222  
 Figure L.14 – Safe Cam (SCa) ..... 222  
 Figure L.15 – Safe Speed Monitor (SSM) ..... 223  
 Figure L.16 – Safe Maximum Speed (SMS) ..... 223  
 Figure L.17 – Safe Braking and Holding System (SBS) ..... 223  
 Figure L.18 – Safe Door Locking (SDL) ..... 224  
 Figure N.1 — Selection Criteria for Signal Word ..... 227

**LIST of TABLES**

Table 1 — Values for Minimum Gaps to Avoid Crushing of Parts of the Human Body ..... 35  
 Table 2 — Comparison of stop, emergency stop, and protective stops ..... 58  
 Table 3 — Comparison of initiation warning systems defined in 9.11.8 ..... 94  
 Table 4 — Types of Actuation of Interlock Devices (Informative) ..... 100  
 Table 5 — Examples of changes which could increase risk ..... 147  
 Table 6 — Examples means to prevent unauthorized changes ..... 148  
 Table E.1 – Variable key for reaching factors associated with protective structures ..... 161  
 Table E.2 – Horizontal reaching distance when accessing over a protective structure ..... 163  
 Table E.3 – Reaching through regular openings in a protective structure ..... 164  
 Table E.4 – Reaching through (around) a protective structure with limitation of movement ..... 166  
 Table E.5 – Horizontal reaching distance when accessing under a protective structure ..... 170  
 Table H.1 – Safety distance equation for engineering controls – devices ..... 182  
 Table H.2 – Variable key for determining safety distance for engineering controls – devices ..... 183

Table I.1 – Variable key for reaching factors associated with engineering controls – devices .....	190
Table I.2 – Classification of optical presence-sensing devices used in vertical orientation .....	192
Table I.3 – Horizontal reaching distance when accessing over a sensing field .....	193
Table I.4 – Horizontal reaching distance when accessing under a vertical sensing field .....	198
Table I.5 – Sample calculation of $b$ for typical hinge switch actuating angles ( $\alpha$ ) .....	208
Table J.1 – Measured stopping times .....	212
Table J.2 – Comparison of stopping time values .....	213
Table N.1 – Selection Guidance for Awareness (Safety) Signs .....	226
Table N.2 – Preferred Colors for Indicator Lights and Icons .....	228
Table N.3 – Alternate Colors for Indicator Lights and Icons .....	228
Table N.4 – Example Selection Guidance for Awareness (Safety) Markings .....	229
Table O.1 – List of Risk Reduction Measure Reference Standards .....	230



## Foreword

**(This Foreword is not part of the requirements of American National Standard B11.19-2019)**

### General

The primary objective of this standard is to establish the requirements for the design, construction, installation, operation and maintenance of the risk reduction measures used to eliminate or control hazards to individuals associated with machines. This standard relies on other standards to determine which risk reduction measure(s) is required or allowed to control identified hazards / hazardous situations and is intended to be used in conjunction with the ANSI B11.0 standard on general safety requirements and risk assessments of machines, and any relevant ANSI B11 "base" standard for a given machine. To accomplish this objective, this standard has established responsibilities for the supplier (e.g., manufacturer, rebuilder, installer, integrator, and modifier), the user, and individuals in the working environment. The overall goal is to achieve acceptable risk in the work practices and work environment.

### Application

Other industry sectors may benefit from applying this standard. Where a machine-specific "base" (type-C) safety standard exists, ANSI B11.19 may be constructively used to supplement that standard.

The words "safe" and "safety" are not absolutes. Safety begins with good design. While the goal of this standard is to eliminate injuries, this standard recognizes that risk factors cannot practically be reduced to zero in any human activity. This standard is not intended to replace good judgment and personal responsibility. Operator skill, attitude, training, job monotony, fatigue, and experience are factors that affect safety and that must be considered by the user.

Throughout its history, ANSI B11.19 has not provided the requirements for the selection of the risk reduction measures, but only the implementation of the risk reduction measure once chosen. No hierarchical order, no level of risk reduction, or any relationship between risk reduction measure options are implied within this standard.

### Effective Date

The following information on effective dates is informative guidance only, and not a normative part of this standard. This Subcommittee recognizes that some period of time after the approval date on the title page of this document is necessary for suppliers and users to develop new designs or modify existing designs or manufacturing processes in order to incorporate the new or revised requirements of this standard into their product development or production system.

This Subcommittee recommends that suppliers complete and implement design changes for new machines and machinery systems within 30 months of the approval date of this standard.

The Subcommittee recommends that users evaluating whether existing machinery and machinery systems implement this edition within 30 months of the approval date of this standard using generally recognized risk assessment methods. If the risk assessment shows that modification(s) is necessary, refer to the requirements of this standard or the machine-specific "base" safety standard to implement risk reduction measures (protective measures) for appropriate risk reduction.

### Harmonization

The requirements of this standard have been harmonized with similar requirements in several international (ISO and IEC) and European (EN) standards. Harmonization means that the requirements have been aligned in essence to achieve a similar level of risk reduction. Harmonization does not mean duplication of exact requirements.

ANSI B11.19 implements a standardization philosophy that differs significantly from that often found in some ISO, IEC, and EN standards. ISO, IEC, and EN standards tend towards individual documents for each type of risk reduction measure (e.g., light curtains, emergency stop controls, prevention of unexpected start-up, etc.). ANSI B11.19 has historically combined the various requirements into this single standard, thereby allowing readers to understand and compare the requirements for different approaches to reducing risk.