## ANSI/ASA S12.11-2013/Part 2 / ISO 10302-2:2011

AMERICAN	NATIONAL	STANDARD
AMENICAN	INATIONAL	JIANDAND

Acoustics – Measurement of airborne noise emitted and structure-borne vibration induced by small air-moving devices – Part 2: Structure-borne vibration measurements (a nationally adopted international standard)

ANSI/ASA S12.11-2013/Part 2 / ISO 10302-2 :2011

Accredited Standards Committee S12, Noise

Standards Secretariat Acoustical Society of America 35 Pinelawn Road, Suite 114 E Melville, NY 11747-3177 This is a preview of "ANSI/ASA S12.11-2013...". Click here to purchase the full version from the ANSI store.

The American National Standards Institute, Inc. (ANSI) is the national coordinator of voluntary standards development and the clearinghouse in the U.S.A. for information on national and international standards.

The Acoustical Society of America (ASA) is an organization of scientists and engineers formed in 1929 to increase and diffuse the knowledge of acoustics and to promote its practical applications.



ANSI/ASA S12.11-2013/Part 2/ ISO 10302-2:2011 (Revision of ANSI/ASA S12.11-2003/Part 2 (R 2008))

## AMERICAN NATIONAL STANDARD

# Acoustics – Measurement of airborne noise emitted and structure-borne vibration induced by small airmoving devices – Part 2: Structure-borne vibration measurements (a nationally adopted international standard)

Secretariat:

**Acoustical Society of America** 

Approved on December 4, 2013 by:

American National Standards Institute, Inc.

### **Abstract**

ANSI/ASA S12.11-2013/Part 2 / ISO 10302-2:2011 covers vibration levels from small air-moving devices (AMDs) with mounting footprints of less than  $0.48~\text{m}\times0.90~\text{m}$  for the full-size test plenum defined in ANSI/ASA S12.11/Part 1 / ISO 10302-1 and less than  $0.18~\text{m}\times0.3~\text{m}$  for the half-size plenum.

It covers all types of AMDs which can be mounted on, and are self-supported at, the discharge or inlet plane of a test plenum box as specified in ANSI/ASA S12.11-2013/Part 1 / ISO 10302-1:2011.

The procedures defined in this part of this American National Standard specify methods for determining the vibration levels that a small AMD would induce in an average structure used in information technology and telecommunications equipment. The methods specified in this part of this American National Standard allow the determination of induced vibration levels for the individual AMD that is tested. These data can be used to determine the statistical values of vibration levels for a production series if levels are measured for several units of that series.

### AMERICAN NATIONAL STANDARDS ON ACOUSTICS

The Acoustical Society of America (ASA) provides the Secretariat for Accredited Standards Committees S1 on Acoustics, S2 on Mechanical Vibration and Shock, S3 on Bioacoustics, S3/SC 1 on Animal Bioacoustics, and S12 on Noise. These committees have wide representation from the technical community (manufacturers, consumers, trade associations, organizations with a general interest, and government representatives). The standards are published by the Acoustical Society of America as American National Standards after approval by their respective Standards Committees and the American National Standards Institute (ANSI).

These standards are developed and published as a public service to provide standards useful to the public, industry, and consumers, and to Federal, State, and local governments.

Each of the Accredited Standards Committees (operating in accordance with procedures approved by ANSI) is responsible for developing, voting upon, and maintaining or revising its own Standards. The ASA Standards Secretariat administers Committee organization and activity and provides liaison between the Accredited Standards Committees and ANSI. After the Standards have been produced and adopted by the Accredited Standards Committees, and approved as American National Standards by ANSI, the ASA Standards Secretariat arranges for their publication and distribution.

An American National Standard implies a consensus of those substantially concerned with its scope and provisions. Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered and that a concerted effort be made towards their resolution.

The use of an American National Standard is completely voluntary. Their existence does not in any respect preclude anyone, whether he or she has approved the Standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the Standards.

NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this Standard.



Acoustical Society of America Standards Secretariat 35 Pinelawn Road, Suite 114E Melville, New York 11747-3177 Telephone: 1 (631) 390-0215

Fax: 1 (631) 390-0217 E-mail: asastds@aip.org

© 2013 by Acoustical Society of America. This standard may not be reproduced in whole or in part in any form for sale, promotion, or any commercial purpose, or any purpose not falling within the provisions of the U.S. Copyright Act of 1976, without prior written permission of the publisher. For permission, address a request to the Standards Secretariat of the Acoustical Society of America.

These materials are subject to copyright claims of ISO, ANSI, and ASA. No part of this publication may be reproduced in any form, including an electronic retrieval system, without the prior written permission of the Acoustical Society of America (ASA). All requests pertaining to this standard should be submitted to the ASA at the address above.

# **Contents**

1	Sco	pe	1
2	•	mative references	
3	Ter	ms and definitions	2
4	Des	criptors	2
_			
5	Mea	asurement uncertainty	3
6		ign and performance requirements for test fixture	
	6.1	Basic design	
	6.2	Damped panel	
	6.3	Mounting area	4
7	Inst	allation	
	7.1	Orientation of the AMD	5
	7.2	Mounting of the AMD	
	7.3	Damped panel opening	5
8	Орє	eration of AMDs	
	8.1	Input power	5
	8.2	Points of operation	6
9	Inst	rumentation	6
	9.1	Plenum pressure measurements	6
	9.2	Accelerometer and accelerometer system	6
	9.3	Signal conditioners	7
	9.4	Analyzer	7
	9.5	Basic calibration	7
1(	) N	leasurement procedure	7
	10.1	Preparation	7
	10.2	Operational test for AMD	7
	10.3	Operational calibration	
	10.4	Measurement	
	10.5	Corrections for background acceleration levels	
	10.6	Accelerometer mounting	
	10.7	Accelerometer cable	
	10.8	Accelerometer locations	
	10.9	Data acquisition time	11
11	1 T	est report	12
	11.1	Information to be recorded	
	11.2	Information to be reported	13
Aı	nnex A	(informative) Suggested data format for presentation	14
Aı	nnex B	(informative) Recommended voltages for testing AMDs that operate with variable speeds	19
	B.1	Background of measurement	
	B.2	Recommended procedure	

i

Annex (	(informative) Sample specification of AMD structure-borne vibratory acceleration levels	20
C.1	Recommended specification format	20
C.2	Optional specification format	20
C.3	Determination of specification values	20
Annex I	O Guidance on the development of information on measurement uncertainty	
D.1	General	21
D.2	GeneralModel function	21
D.3	Input quantities and their contributions to measurement uncertainty	
D.4	Uncertainty budget	24
D.5	Combined standard uncertainty and expanded uncertainty	
Table	s	
	— Estimated values of the standard deviation of reproducibility of vibratory acceleration le-moving devices determined in accordance with this part of this American National Standard	
Table D	Example of an uncertainty budget for determination of vibratory acceleration levels	24

### **Foreword**

[This Foreword is for information only, and is not a part of the American National Standard **ANSI/ASA S12.11-2013/Part 2 / ISO 10302-2:2011** American National Standard Acoustics – Measurement of airborne noise emitted and structure-borne vibration induced by small air-moving devices – Part 2: Structure-borne vibration measurements.]

This standard comprises a part of a group of definitions, standards, and specifications for use in noise. It was developed and approved by Accredited Standards Committee S12 Noise, under its approved operating procedures. Those procedures have been accredited by the American National Standards Institute (ANSI). The Scope of Accredited Standards Committee S12 is as follows:

Standards, specifications, and terminology in the field of acoustical noise pertaining to methods of measurement, evaluation, and control, including biological safety, tolerance, and comfort, and physical acoustics as related to environmental and occupational noise.

This standard is an identical national adoption of ISO 10302-2:2011. It revises and replaces ANSI/ASA S12.11–2003/Part 2 (R 2008) American National Standard Acoustics – Measurement of Noise and Vibration of Small Air-Moving Devices – Part 2: Structure-Borne Vibration. ISO 10302-2:2011 was prepared by Technical Committee ISO/TC 43 Subcommittee SC 1, Noise.

In conformance with ANSI and ISO rules, the words "this part of this American National Standard" replace the words "this part of ISO 10302" where they appear in the ISO document, decimal points were substituted in place of the decimal commas used in ISO documents, and American English spelling is used in place of British English spelling.

The ANSI/ASA equivalent for one of the ISO standards referenced in this standard is:

 ANSI/ASA S12.11-2013 Part 1 / ISO 10302-1:2011 is the identical national adoption of ISO 10302-1:2011

At the time this Standard was submitted to Accredited Standards Committee S12, Noise for approval, the membership was as follows:

W.J. Murphy, *Chair* S.J. Lind, *Vice-Chair* 

S.B. Blaeser, Secretary

3M Occupational Health & Environmental Safety Division	E.H. Berger
Acoustical Society of America	R.D. Hellweg D. Lubman (Alt.)
Air-Conditioning, Heating and Refrigeration Institute	S.J. Lind D. Abbate (Alt.)
Air Movement & Control Association, Inc.	J.A. Brooks M. Stevens (Alt.)
American Academy of Audiology	D. Ostergren S. Gordon-Salant (Alt.)

American Academy of Otolaryngology - Head and Neck Surgery	
American Industrial Hygiene Association	
American Speech-Language-Hearing Association	
Caterpillar, Inc.	K.G. Meitl
Compressed Air and Gas Institute	
Council for Accreditation in Occupational Hearing Conservation	
Emerson Electric - Copeland Corporation	
ETS - Lindgren Acoustic Systems	
ExxonMobil	B. Moulton
G.R.A.S. Sound & Vibration	,
GE Aviation	
General Motors	D.B. Moore
InfoComm International	
Information Technology Industry Council	
Institute of Noise Control Engineering	
International Safety Equipment Association	
John Deere	
National Council of Acoustical Consultants	,
National Hearing Conservation Association	P.A. Brogan

National Institute for Occupational Safety and Health	
National Institute of Standards and Technology - National Voluntary Laboratory Accreditation Program	B.A. Sandoval
National Park Service	
Noise Control Engineering, Inc	
Noise Pollution Clearinghouse	L. Blomberg
PCB Group	
Power Tool Institute, Inc.	_
Schomer and Associates, Inc.	P.D. Schomer
Sperian Hearing Protection, LLC	
U.S. Air Force	
U.S. Army Aeromedical Research Lab	W.A. Ahroon
U.S. Army Construction Engineering Research Laboratory	
U.S. Army Public Health Command	
U.S. Army Research Laboratory, Human Research and Engineering Direc	
U.S. Department of Transportation	K. Grasty
U.S. Naval Surface Warfare Center - Carderock	M. Craun
Université du Québec ETS	

Individual Experts of Accredited Standards Committee S12, Noise, were:

P.K. Baade	W.W. Lang	R.J. Peppin
E.H. Berger	D. Lubman	J. Schmitt
B.M. Brooks	D. Michaud	P.D. Schomer
A.J. Campanella	N.P. Miller	L.C. Sutherland
L.S. Finegold	W.J. Murphy	W.R. Thornton
R.D. Godfrey	M.A. Nobile	L.A. Wilber
R.D. Hellweg		G.E. Winzer

Working Group S12/WG 3, Measurement of Noise from Information Technology and Telecommunications Equipment, which assisted Accredited Standards Committee S12, Noise, in the development of this standard, had the following membership.

### S. Bard, Chair

D. Ali	R.D. Hellweg	C. Saunder
B.A. Bard	K.X.C. Man	J. Schmitt
E. Baugh	A. Nava	R. Underwood
W.M. Beltman	M.A. Nobile	L. Wittig
J. DeMoss	V. Ojeda	J. Wong
E. Dunens	R.J. Peppin	Y. Xu
	D. Quinlan	

Suggestions for improvements of this standard will be welcomed. They should be sent to Accredited Standards Committee S12, Noise, in care of the Standards Secretariat of the Acoustical Society of America, 35 Pinelawn Road, Suite 114E, Melville, New York 11747-3177. Telephone: 631-390-0215; Fax: 631-390-0217; E-mail: asastds@aip.org.

### **American National Standard**

# Acoustics – Measurement of airborne noise emitted and structure-borne vibration induced by small airmoving devices – Part 2: Structure-borne vibration measurements (a nationally adopted international standard)

# 1 Scope

This part of this American National Standard covers vibration levels from small air-moving devices (AMDs) with mounting footprints of less than  $0.48 \text{ m} \times 0.90 \text{ m}$  for the full-size test plenum defined in ISO 10302-1 and less than  $0.18 \text{ m} \times 0.3 \text{ m}$  for the half-size plenum.

It covers all types of AMDs which can be mounted on, and are self-supported at, the discharge or inlet plane of a test plenum box as specified in ISO 10302-1.

The procedures defined in this part of this American National Standard specify methods for determining the vibration levels that a small AMD would induce in an average structure used in information technology and telecommunications equipment. The methods specified in this part of this American National Standard allow the determination of induced vibration levels for the individual AMD that is tested. These data can be used to determine the statistical values of vibration levels for a production series if levels are measured for several units of that series.

### 2 Normative references

The following referenced documents are indispensable for the application of this standard. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 266, Acoustics — Preferred frequencies

ISO 5348, Mechanical vibration and shock — Mechanical mounting of accelerometers

ISO 10302-1:2011, Acoustics — Measurement of airborne noise emitted and structure-borne vibration induced by small air-moving devices — Part 1: Airborne noise measurement

ISO 16063-11, Methods for the calibration of vibration and shock transducers — Part 11: Primary vibration calibration by laser interferometry

ISO 16063-21, Methods for the calibration of vibration and shock transducers — Part 21: Vibration calibration by comparison to a reference transducer

IEC 61260, Electroacoustics — Octave-band and fractional-octave-band filters

ISO/IEC Guide 98-3, Uncertainty in measurement — Part 3: Guide to the expression of uncertainty in measurement (GUM:1995)