ANSI/ASA S12.44-1997 (Formerly ANSI S12.44-1997)

Reaffirmed by ANSI June 19, 2020

Reaffirmed by ANSI July 17, 2002

Reaffirmed by ANSI September 12, 2007

Reaffirmed by ANSI September 5, 2012

Reaffirmed by ANSI September 29, 2017

AMERICAN NATIONAL STANDARD

Methods for Calculation of Sound Emitted by Machinery and Equipment at Workstations and Other Specified Positions from Sound Power Level

ANSI/ASA S12.44-1997 (Formerly ANSI S12.44-1997)

Accredited Standards Committee S12, Noise

Standards Secretariat Acoustical Society of America 35 Pinelawn Road, Suite 114 E Melville, NY 11747-3177 This is a preview of "ANSI/ASA S12.44-1997...". Click here to purchase the full version from the ANSI store.

The American National Standards Institute, Inc. (ANSI) is the national coordinator of voluntary standards development and the clearinghouse in the U.S.A. for information on national and international standards.

The Acoustical Society of America (ASA) is an organization of scientists and engineers formed in 1929 to increase and diffuse the knowledge of acoustics and to promote its practical applications.



ANSI/ASA S12.44-1997 (Formerly ANSI S12.44-1997)

AMERICAN NATIONAL STANDARD

Methods for Calculation of Sound Emitted by Machinery and Equipment at Workstations and Other Specified Positions from Sound Power Level

Secretariat

Acoustical Society of America

Approved 27 January 1997

American National Standards Institute, Inc.

Abstract

This Standard provides a method for determining emission sound pressure levels from the sound power level produced by all types of machinery and equipment at workstations and other specified locations. These sound pressure levels are, in general, less than those that would be measured when the machinery or equipment is operating in its normal surroundings where the environment may influence the measurement of an emission sound pressure level.

AMERICAN NATIONAL STANDARDS ON ACOUSTICS

The Acoustical Society of America (ASA) provides the Secretariat for Accredited Standards Committees S1 on Acoustics, S2 on Mechanical Vibration and Shock, S3 on Bioacoustics, and S12 on Noise. These committees have wide representation from the technical community (manufacturers, consumers, and general-interest representatives). The standards are published by the Acoustical Society of America through the American Institute of Physics as American National Standards after approval by their respective standards committees and the American National Standards Institute.

These standards are developed and published as a public service to provide standards useful to the public, industry, and consumers, and to Federal, State, and local governments.

Each of the Accredited Standards Committees [operating in accordance with procedures approved by American National Standards Institute (ANSI)] is responsible for developing, voting upon, and maintaining or revising its own standards. The ASA Standards Secretariat administers committee organization and activity and provides liaison between the Accredited Standards Committees and ANSI. After the standards have been produced and adopted by the Accredited Standards Committees, and approved as American National Standards by ANSI, the ASA Standards Secretariat arranges for their publication and distribution.

An American National Standard implies a consensus of those substantially concerned with its scope and provisions. Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered and that a concerted effort be made towards their resolution.

The use of an American National Standard is completely voluntary. Their existence does not in any respect preclude anyone, whether he or she has approved the Standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this standard.



Standards Secretariat
Acoustical Society of America
120 Wall Street, 32nd Floor
New York, New York 10005-3993

Telephone: +1 212 248 0373 Telefax: +1 212 248 0146

© 1997 by Acoustical Society of America. This standard may not be reproduced in whole or in part in any form for sale, promotion, or any commercial purpose, or any purpose not falling within the provisions of the Copyright Act of 1976, without prior written permission of the publisher. For permission, address a request to the Standards Secretariat of the Acoustical Society of America.

Contents

Forewordii 1 2 3 4 5 6 Calculation methods 4 7 8 Information to be reported 5 Annex A Guidelines for selecting a measurement method 6 **Table** Overview of methods for determination of emission sound pressure levels at a work station **Figures** A.1 Flow chart guiding the choice of appropriate method for determining emission sound pressure levels at locations A.2 Scope of Methods A, B, and C, depending on the background noise correction ΔL_A , the environmental indicator K_{2A} ,

Foreword

[This foreword is for information only and is not an integral part of American National Standard Methods for Calculation of Sound Emitted by Machinery and Equipment at Workstations and Other Specified Positions From Sound Power Level \$12.44-1997.]

This American National Standard was developed as a national counterpart to International Standard ISO 11203:1995 Acoustics—Noise Emitted by Machinery and Equipment—Determination of Emission Sound Pressure Levels at a Workstation and at Other Specified Positions.

This Standard was developed under the jurisdiction of Accredited Standards Committee S12, Noise, which has the following scope:

Standards, specifications, and terminology in the field of acoustical noise pertaining to methods of measurement, evaluation, and control, including biological safety, tolerance, and comfort, and physical acoustics as related to environmental and occupational noise.

At the time this standard was submitted to Accredited Standards Committee S12, Noise, for final approval, the membership was as follows:

D. L. Johnson, *Chair* P. D. Schomer, *Vice Chair*

A. Brenig, Secretary

Acoustical Society of America	
	W. J. Galloway (Alt.)
Acoustical Systems, Inc	
	R. Seitz (Alt.)
Air-Conditioning and Refrigeration Institute	
	G. Acton (Alt.)
Aluminum Company of America (ALCOA)	S. I. Roth
American Academy of Otolaryngology,	
Head and Neck Surgery, Inc	G. A. Gates
	L. A. Michael (Alt.)
American College of Occupational Medicine	P. J. Brownson
	J. Sataloff (Alt.)
American Industrial Hygiene Association	L. H. Royster
. •	J. F. Meagher (Alt.)
American Otological Society	R. F. Naunton
American Society of Heating, Refrigerating, and	
Air-Conditioning Engineers (ASHRAE)	H. S. Pei
	J. L. Heldenbrand (Alt.)
American Speech-Hearing-Language Association (ASHA) .	R. F. Burkard
Audio Engineering Society, Inc.	
Bruel and Kjaer Instruments	E. Schonthal
Compressed Air and Gas Institute (CAGI)	J. D. Addington
Council for Accreditation in Occupational	-
Hearing Conservation (CAOHC)	W. Monk
	D. Driscoll (Alt.)
Industrial Safety Equipment Association	J. Birkner
	W. J. Erny (Alt.)
Information Technology Industry Council	R. Lotz
•	W. F. Hanrahan (Alt.)
Larson-Davis Instrumentation Systems	R. J. Peppin
·	B. Chanaud (Alt.)

J. Erdreich R. L. Richards (Alt.) National Electrical Manufacturers Association (NEMA) . . D. Rawlings National Hearing Conservation Association (NHCA) J. Franks E. H. Berger (Alt.) National Surface Warfare Center D. J. Vendittis J. Niemiec (Alt.) R. Callahan D. H. Montague (A/t.) U.S. Army Aeromedical Research Laboratory B. Mozo U.S. Army Construction Engineering P. D. Schomer Research Laboratories (USA-CERL) M. White (Alt.) U.S. Army Human Engineering Laboratory G. R. Price J. Kalb (Alt.) R. L. McKinley U.S. Department of the Air Force U.S. Department of the Army, Walter Reed Medical Center, Army Audiology and Speech Center R. W. Danielson U.S. Department of the Navy, Navy Environmental Health Center J. Page L. Marshall (Alt.) U.S. Department of Transportation A. Konheim

Individual experts of Accredited Standards Committee S12, Noise, were:

P. K. Baade	R. M. Guernsey	P. D. Schomer
R. G. Bartheld	R. K. Hillquist	W. R. Thornton
R. W. Benson	D. L. Johnson	H. E. von Gierke
L. L. Beranek	W. W. Lang	L. A. Wilber
E. H. Berger	L. F. Luttrell	G. E. Winzer
S. H. P. Bly	G. C. Maling, Jr.	G. S. K. Wong
K. M. Eldred	A. H. Marsh	R. W. Young
R. S. Gales	J. Pope	
W. J. Galloway	L. H. Royster	

This Standard is closely related to ANSI S12.43-1997 American National Standard Methods for Measurement of Sound Emitted by Machinery and Equipment at Workstations and Other Specified Positions.

The ad hoc Working Group which assisted Accredited Standards Committee S12, Noise, in the preparation of this standard, had the following membership:

W. J. Galloway, Chairman

B. M. Brooks	R. J. Peppin	R. W. Young
Δ H Marsh	P D Schomer	

Suggestions for improvement will be welcomed. They should be made in writing to Accredited Standards Committee S12, Noise, in care of the Standards Secretariat, Acoustical Society of America, 120 Wall Street, 32nd floor, New York, New York, 10005-3993.

Telephone: +1 212 248 0373 FAX: +1 212 248 0146

ANSI S12.44-1997

American National Standard

Methods for Calculation of Sound Emitted by Machinery and Equipment at Workstations and Other Specified Positions from Sound Power Level

1 Scope

1.1 General

This Standard specifies two methods for determining the emission sound pressure levels of machinery and equipment, at workstations and at other specified positions nearby, by calculation from the sound power level. The principal purpose of this determination is to permit comparison of the performance of different units of a given family of machinery or equipment, under defined environmental conditions and standardized mounting and operating conditions.

Emission sound pressure levels are determined with the same frequency weighting and time weighting, or in the same frequency bands, as those for which the corresponding sound power levels were determined.

NOTES

- 1 This Standard is closely related to the measurement of emission sound pressure levels of machinery and equipment at workstations and other specified positions as specified in ANSI S12.43-1997. Guidance on the selection of a measurement method from ANSI S12.43-1997 or a method of calculating emissions sound pressure levels from sound power levels as specified in this Standard is provided in annex A of S12.43-1997. That annex, including its table and figures, is also included in this Standard as annex A.
- 2 At any given position in relation to a particular machine, and for given mounting and operating conditions, the emission sound pressure levels

determined by the methods of this Standard will in general be less than the directly measured sound pressure levels for the same machine in the typical workroom where it is used. This is because of reverberation and the contributions of other machines. Commonly observed differences are 1 dB to 5 dB. In extreme cases, the difference may be greater.

1.2 Types of noise and noise sources

This Standard is, in principle, applicable to moving or stationary machines, for indoor or outdoor use, particularly those machines which are mass produced. The methods of this Standard are not applicable to highly directional sound sources used outdoors.

This Standard is particularly applicable to machines for which the largest dimension is less than or equal to 1 m. It is also applicable to larger machines in certain cases (see 6.2.3).

This Standard is applicable to all types of sounds for which methods for determining the sound power level are available.

1.3 Test environment

The test environment to be used is that which is specified for the determination of the sound power level in accordance with the Standards of the ANSI S12.30 series.

1.4 Specified positions

This Standard is applicable to workstation positions and other specified positions in the vicinity of the source under test where emission sound pressure levels are to be determined. It is not applicable to workstations and other defined positions which are situated inside a cab or a cabin, or behind an acoustical screen.

A workstation position can be a single point, corresponding to the specified position of a standing or seated operator. It can also be a specified path.

NOTE – More detailed specifications regarding seated, standing, stationary, or moving operators, as well as information concerning bystanders, are provided in ANSI S12.43-1997.