

ANSI/ASA S12.55-2012 / ISO 3745:2012
(a revision of ANSI S12.55-2006 / ISO 3745:2003)

AMERICAN NATIONAL STANDARD

Acoustics – Determination of sound power levels and sound energy levels of noise sources using sound pressure – Precision methods for anechoic rooms and hemi-anechoic rooms

(a Nationally Adopted International Standard)

ANSI/ASA S12.55-2012 / ISO 3745:2012

Accredited Standards Committee S12, Noise

Standards Secretariat
Acoustical Society of America
35 Pinelawn Road, Suite 114 E
Melville, NY 11747-3177

The American National Standards Institute, Inc. (ANSI) is the national coordinator of voluntary standards development and the clearinghouse in the U.S.A. for information on national and international standards.

The Acoustical Society of America (ASA) is an organization of scientists and engineers formed in 1929 to increase and diffuse the knowledge of acoustics and to promote its practical applications.



ANSI/ASA S12.55-2012 / ISO 3745:2012
(Revision of ANSI S12.55-2006 / ISO 3745:2003)

AMERICAN NATIONAL STANDARD

**Acoustics – Determination of sound power levels and
sound energy levels of noise sources using sound
pressure – Precision methods for anechoic rooms and
hemi-anechoic rooms**

(a nationally adopted international standard)

Secretariat:

Acoustical Society of America

Approved on August 23, 2012 by:

American National Standards Institute, Inc.

Abstract

This American National Standard specifies methods for measuring the sound pressure levels on a measurement surface enveloping a noise source (machinery or equipment) in an anechoic room or a hemi-anechoic room. The sound power level (or, in the case of impulsive or transient noise emission, the sound energy level) produced by the noise source, in frequency bands of width one-third octave or with frequency weighting A applied, is calculated using those measurements, including corrections to allow for any differences between the meteorological conditions at the time and place of the test and those corresponding to a reference characteristic acoustic impedance.

AMERICAN NATIONAL STANDARDS ON ACOUSTICS

The Acoustical Society of America (ASA) provides the Secretariat for Accredited Standards Committees S1 on Acoustics, S2 on Mechanical Vibration and Shock, S3 on Bioacoustics, S3/SC 1 on Animal Bioacoustics, and S12 on Noise. These committees have wide representation from the technical community (manufacturers, consumers, trade associations, organizations with a general interest, and government representatives). The standards are published by the Acoustical Society of America as American National Standards after approval by their respective Standards Committees and the American National Standards Institute (ANSI).


These standards are developed and published as a public service to provide standards useful to the public, industry, and consumers, and to Federal, State, and local governments.

Each of the Accredited Standards Committees (operating in accordance with procedures approved by ANSI) is responsible for developing, voting upon, and maintaining or revising its own Standards. The ASA Standards Secretariat administers Committee organization and activity and provides liaison between the Accredited Standards Committees and ANSI. After the Standards have been produced and adopted by the Accredited Standards Committees, and approved as American National Standards by ANSI, the ASA Standards Secretariat arranges for their publication and distribution.

An American National Standard implies a consensus of those substantially concerned with its scope and provisions. Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered and that a concerted effort be made towards their resolution.

The use of an American National Standard is completely voluntary. Their existence does not in any respect preclude anyone, whether he or she has approved the Standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the Standards.

NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this Standard.



Acoustical Society of America
ASA Secretariat
35 Pinelawn Road, Suite 114E
Melville, New York 11747-3177
Telephone: 1 (631) 390-0215
Fax: 1 (631) 390-0217
E-mail: asastds@aip.org

© 2012 by Acoustical Society of America. This standard may not be reproduced in whole or in part in any form for sale, promotion, or any commercial purpose, or any purpose not falling within the provisions of the U.S. Copyright Act of 1976, without prior written permission of the publisher. For permission, address a request to the Standards Secretariat of the Acoustical Society of America.

These materials are subject to copyright claims of ISO, IEC, ANSI, and ASA. No part of this publication may be reproduced in any form, including an electronic retrieval system, without the prior written permission of the Acoustical Society of America (ASA). All requests pertaining to this standard should be submitted to the Acoustical Society of America (ASA).

Contents

1	Scope	1
1.1	General	1
1.2	Types of noise and noise sources	1
1.3	Test room.....	1
1.4	Measurement uncertainty	1
2	Normative references.....	1
3	Terms and definitions.....	2
4	Reference meteorological conditions.....	8
5	Test rooms	8
5.1	Acoustic criterion for adequacy of the test room	8
5.2	Criteria for background noise	9
5.3	Criterion for air temperature	10
6	Instrumentation	12
6.1	Instruments for acoustical measurements.....	12
6.2	Instruments for meteorological measurements	12
7	Definition, location, installation and operation of noise source under test.....	13
7.1	General	13
7.2	Auxiliary equipment	13
7.3	Noise source location	13
7.4	Mounting of the noise source	13
7.5	Operation of source during test	14
8	Measurement surface	15
8.1	Spherical measurement surface for use in an anechoic room	15
8.2	Hemispherical measurement surface for use in a hemi-anechoic room	15
9	Determination of sound power levels and sound energy levels	17
9.1	Measurements in the test room	17
9.2	Measurement of meteorological conditions.....	17
9.3	Microphone positions.....	17
9.4	Determination of sound power levels of a noise source which emits steady or non-steady noise.....	19
9.5	Determination of sound energy levels for a noise source which emits impulsive noise.....	23
9.6	Calculation of directivity indices.....	26
9.7	Calculation of surface sound pressure level non-uniformity index	26
9.8	Frequency-weighted sound power level and sound energy level	27
10	Measurement uncertainty.....	27
10.1	Methodology	27
10.2	Determination of σ_{omc}	28
10.3	Determination of σ_{R0}	28
10.4	Typical upper bound values of σ_{R0}	29
10.5	Total standard deviation, σ_{tot} , and expanded measurement uncertainty, U	30
11	Information to be recorded	31
11.1	General	31

11.2	Noise source under test.....	31
11.3	Test room.....	31
11.4	Instrumentation.....	31
11.5	Acoustical data.....	32
12	Test report.....	32
Annex A (normative) General procedures for qualification of anechoic and hemi-anechoic rooms..... 33		
A.1	General.....	33
A.2	Instrumentation and measuring equipment.....	33
A.3	Installation of test sources and microphones.....	36
A.4	Test procedures.....	37
A.5	Qualification procedure.....	39
Annex B (normative) Qualification procedure for spaces within test rooms used in the determination of sound power levels and sound energy levels of specific noise sources..... 41		
B.1	General.....	41
B.2	Properties of reflecting plane.....	41
B.3	Procedure using two measurement spheres or hemispheres with different radii (two-surface method).....	42
Annex C (normative) Calculation of A-weighted sound power levels and A-weighted sound energy levels from one-third-octave band levels..... 43		
C.1	A-weighted sound power levels.....	43
C.2	A-weighted sound energy levels.....	43
C.3	Values of j and C_j for use in calculations.....	43
Annex D (normative) Array of microphone positions on a spherical measurement surface in a free field 45		
Annex E (normative) Arrays of microphone positions on a hemispherical measurement surface in a hemi-free field..... 48		
Annex F (normative) Coaxial circular paths of microphones on a hemispherical measurement surface in a hemi-free field..... 53		
Annex G (normative) Meridional paths of microphones on a hemispherical measurement surface in a hemi-free field..... 54		
Annex H (normative) Spiral paths of microphones on a hemispherical measurement surface in a hemi-free field..... 56		
Annex I (informative) Guidance on the development of information on measurement uncertainty..... 57		
I.1	General.....	57
I.2	Considerations on the total standard deviation, σ_{tot}	57
I.3	Considerations on σ_{omc}	57
I.4	Considerations on σ_{R0}	59
I.5	Combined standard uncertainty.....	66
I.6	Measurement uncertainty based on reproducibility data.....	66
I.7	Example of an uncertainty budget for a reference sound source in a national laboratory.....	67

Figures

Figure 1 — Reference box, center for the measurement surface (when using the geometric center of the source) and characteristic source dimensions for application in an anechoic and a hemi-anechoic room.....	16
Figure A.1 — Microphone positions on the spherical surface for test sound source directivity measurements	35
Figure D.1 — Microphone positions on the spherical measurement surface	47
Figure E.1 — Microphone positions on the hemispherical measurement surface (general case)	51
Figure E.2 — Microphone positions on the hemispherical measurement surface for broadband omnidirectional sources	52
Figure F.1 — Coaxial circular paths for a moving microphone.....	53
Figure G.1 — Meridional paths for a moving microphone	54
Figure G.2 — Example of a mechanical system to realize a meridional path	55
Figure G.3 — Example of an electronic control circuit.....	55
Figure H.1 — Spiral path for a moving microphone.....	56

Tables

Table 1 — Maximum background noise levels in test room for absolute criteria	11
Table 2 — Typical upper bound values of the standard deviation of reproducibility of the method, σ_{RO} , for sound power levels and sound energy levels determined in a hemi-anechoic room in accordance with this American National Standard	30
Table 3 — Typical upper bound values of the standard deviation of reproducibility of the method, σ_{RO} , for the sound power levels and sound energy levels determined in an anechoic room, in accordance with this American National Standard	30
Table A.1 — Allowable deviation in directivity of the test source.....	34
Table A.2 — Maximum allowable deviation of measured sound pressure levels from theoretical levels using the inverse square law	40
Table C.1 — Values of j and C_j for mid-band frequencies of one-third-octave bands.....	44
Table D.1 — Microphone positions.....	46
Table E.1 — Microphone positions (general case).....	49
Table E.2 — Microphone positions for a broadband omnidirectional source	50

Table I.1 — Examples of calculated total standard deviations, σ_{tot} , for three different cases	59
Table I.2 — Example of an uncertainty budget for determinations of σ_{R0} for sound power level and sound energy level, valid for frequencies from 500 Hz to 4 kHz, or for A-weighted measurements of a source with a relatively flat frequency spectrum.....	62

Foreword

[This Foreword is for information only, and is not a part of the American National Standard ANSI/ASA S12.55-2012 / ISO 3745:2012 American National Standard Acoustics — Determination of sound power levels and sound energy levels of noise sources using sound pressure — Precision methods for anechoic rooms and hemi-anechoic rooms.]

This standard comprises a part of a group of definitions, standards, and specifications for use in noise. It was developed and approved by Accredited Standards Committee S12, Noise, under its approved operating procedures. Those procedures have been accredited by the American National Standards Institute (ANSI). The Scope of Accredited Standards Committee S12 is as follows:

Standards, specifications, and terminology in the field of acoustical noise pertaining to methods of measurement, evaluation, and control, including biological safety, tolerance, and comfort, and physical acoustics as related to environmental and occupational noise.

This standard is a revision of ANSI S12.55-2006 / ISO 3745:2003, which has been technically revised.

This Standard is identical to International Standard ISO 3745, Acoustics — Determination of sound power levels and sound energy levels of noise sources using sound pressure — Precision methods for anechoic rooms and hemi-anechoic rooms, which was prepared by Technical Committee ISO/TC 43 Subcommittee SC 1, Noise. However, in conformance with ANSI and ISO rules, the words "American National Standard" replace the words "International Standard" where they appear in the ISO document, decimal points were substituted in place of the decimal commas used in ISO documents, and American English spelling is used in place of British English spelling. In addition, editorial correction was made to the caption of Figure E.2. In ISO 3745:2012 this figure and the previous one were numbered E.1.

The ANSI or ANSI/ASA equivalents for the ISO standards in the ISO 3740 series and other referenced nationally adopted standards are given below:

- ANSI/ASA S12.5 / ISO 6926 is an identical national adoption of ISO 6926;
- ANSI/ASA S12.50/ISO 3740 is an identical national adoption of ISO 3740;
- ANSI/ASA S12.51/ISO 3741 is an identical national adoption of ISO 3741;
- ANSI/ASA S12.53/Part 1/ISO 3743-1 is an identical national adoption of ISO 3743-1;
- ANSI/ASA S12.53/Part 2/ISO 3743-2 is an identical national adoption of ISO 3743-2;
- ANSI/ASA S12.54/ISO 3744 is an identical national adoption of ISO 3744;
- ANSI/ASA S12.55/ISO 3745 is an identical national adoption of ISO 3745;
- ANSI/ASA S12.56/ISO 3746 is an identical national adoption of ISO 3746; and
- ANSI/ASA S12.57/ISO 3747 is an identical national adoption of ISO 3747.

At the time this Standard was submitted to Accredited Standards Committee S12, Noise for approval, the membership was as follows:

W.J. Murphy, *Chair*
S.J. Lind, *Vice-Chair*

S.B. Blaeser, *Secretary*

3M Occupational Health & Environmental Safety Division E.H. Berger

Acoustical Society of America R.D. Hellweg
..... D. Lubman (Alt.)

Air-Conditioning, Heating and Refrigeration Institute	S. Lind
.....	D. Abbate (Alt.)
Air Movement & Control Association, Inc.	J.A. Brooks
.....	M. Stevens (Alt.)
American Academy of Audiology	D. Ostergren
.....	S. Gordon-Salant (Alt.)
American Academy of Otolaryngology - Head and Neck Surgery	R.A. Dobie
.....	L.A. Michael (Alt.)
American Industrial Hygiene Association	D. Driscoll
.....	S.N. Hacker (Alt.)
American Speech-Language-Hearing Association	L.A. Wilber
.....	V. Gladstone (Alt.)
Caterpillar, Inc.	K.G. Meitl
Compressed Air and Gas Institute	R.C. Johnson
.....	D.R. Bookshar (Alt.)
Council for Accreditation in Occupational Hearing Conservation	VACANT
.....	L.D. Hager (Alt.)
Emerson Electric – Copeland Corporation	A.T. Herfat
.....	G. Williamson (Alt.)
ETS – Lindgren Acoustic Systems	D. Winker
.....	M. Black (Alt.)
ExxonMobil	B. Moulton
G.R.A.S. Sound & Vibration	J. Soendergaard
.....	B. Schustrich (Alt.)
GE Aviation	R. Majjigi
.....	R. Babbitt (Alt.)
General Motors	D.B. Moore
Harley-Davidson Motor Company	D. Jaeger
Information Technology Industry Council	W.M. Beltman
.....	J. Rosenberg (Alt.)
Institute of Noise Control Engineering	R.J. Peppin
.....	B. Tinianov (Alt.)
International Safety Equipment Association	J. Birkner
.....	C.Z. Fargo (Alt.)
John Deere	K.B. Washburn
.....	K. Cone (Alt.)
National Council of Acoustical Consultants	J. Erdreich
.....	G.E. Winzer (Alt.)
National Hearing Conservation Association	P.A. Brogan

National Institute for Occupational Safety and Health	W.J. Murphy E. Zechmann (Alt.)
National Institute of Standards and Technology – National Voluntary Laboratory Accreditation Program	B.A. Sandoval
National Park Service	G.R. Stanley K. Fristrup (Alt.)
Noise Control Engineering, Inc.	M.A. Bahtiaran R. Fischer (Alt.)
Noise Pollution Clearinghouse	L. Blomberg
PCB Group	K. Cox L. Harbaugh (Alt.)
Power Tool Institute, Inc.	W.D. Spencer M. Hickok (Alt.)
Schomer and Associates, Inc.	P.D. Schomer
Sperian Hearing Protection, LLC	R. Ghent B. Witt (Alt.)
U.S. Air Force	R.L. McKinley H. Gallagher (Alt.)
U.S. Army Aeromedical Research Lab	W.A. Ahroon
U.S. Army Construction Engineering Research Laboratory	M.J. White M. Swearingen (Alt.)
U.S. Army Public Health Command	C. Stewart M. Grantham (Alt.)
U.S. Army Research Laboratory, Human Research and Engineering Directorate	J. Gaston M.S. Binseel (Alt.)
U.S. Department of Transportation	A. Konheim
U.S. Naval Surface Warfare Center - Carderock	M. Craun
Université du Québec ETS	J. Voix F. Laville (Alt.)

Individual Experts of Accredited Standards Committee S12, Noise, were:

P.K. Baade	W.W. Lang	J. Schmitt
E.H. Berger	D. Lubman	P.D. Schomer
B.M. Brooks	D. Michaud	L.C. Sutherland
A.J. Campanella	N.P. Miller	W.R. Thornton
L.S. Finegold	W.J. Murphy	L.A. Wilber
R.D. Godfrey	M.A. Nobile	G.E. Winzer
R.D. Hellweg	R.J. Peppin	

Working Group S12/WG 23, *Determination of Sound Power*, which assisted Accredited Standards Committee S12, Noise, in the development of this standard, had the following membership:

B.M. Brooks, Co-Chair
J. Schmitt, Co-Chair

M.C. Black
S. Bly
A.J. Campanella
D.A. Collings
K. Cunefare

R.D. Hellweg
A.T. Herfat
S. Keith
G.C. Maling

M.A. Nobile
M. O'Connell
P.D. Schomer
J. Weinstein

Suggestions for improvements of this standard will be welcomed. They should be sent to Accredited Standards Committee S12, Noise, in care of the Standards Secretariat of the Acoustical Society of America, 35 Pinelawn Road, Suite 114E, Melville, New York 11747-3177. Telephone: 631-390-0215; FAX: 631-390-0217; E-mail: asastds@aip.org.

Introduction

This American National Standard is a national adoption of one of the series ISO 3741^[3] to ISO 3747^[8], which specify various methods for determining the sound power levels and sound energy levels of noise sources including machinery, equipment and their sub-assemblies. The selection of one of the methods from the series for use in a particular application depends on the purpose of the test to determine the sound power level or sound energy level and on the facilities available. General guidelines to assist in the selection are provided in ISO 3740^[2]. ISO 3741^[3] to ISO 3747^[8] give only general principles regarding the operating and mounting conditions of the machinery or equipment for the purposes of the test. It is important that test codes be established for individual kinds of noise source, in order to give detailed requirements on mounting, loading and operating conditions under which the sound power levels or sound energy levels are to be obtained and to select the appropriate measurement surface and microphone array from among those specified in this American National Standard.

The methods given in this American National Standard require the source to be mounted in either an anechoic room or a hemi-anechoic room having specified acoustical characteristics. The methods are then based on the premise that the sound power or sound energy of the source is directly proportional to the mean-square sound pressure over a hypothetical measurement surface enclosing the source and otherwise depends on the physical constants of air.

The methods specified in this American National Standard permit the determination of the sound power level and the sound energy level in frequency bands and/or with frequency A-weighting applied.

The methods give a precision grade of accuracy (grade 1) as defined in ISO 12001. The resulting sound power levels and sound energy levels include corrections to allow for any differences that might exist between the meteorological conditions under which the tests are conducted and reference meteorological conditions. For applications where there are large uncertainties due to operating conditions or where reduced accuracy is acceptable, reference can be made to the more practical methods of ISO 3744^[6] or ISO 3746^[7]. Guidance on evaluation of measurement uncertainty is given in Annex I.

This is a preview of "ANSI/ASA S12.55-2012...". [Click here to purchase the full version from the ANSI store.](#)

AMERICAN NATIONAL STANDARD

Acoustics – Determination of sound power levels and sound energy levels of noise sources using sound pressure – Precision methods for anechoic rooms and hemi-anechoic rooms (a nationally adopted international standard)

1 Scope

1.1 General

This American National Standard specifies methods for measuring the sound pressure levels on a measurement surface enveloping a noise source (machinery or equipment) in an anechoic room or a hemi-anechoic room. The sound power level (or, in the case of impulsive or transient noise emission, the sound energy level) produced by the noise source, in frequency bands of width one-third octave or with frequency weighting A applied, is calculated using those measurements, including corrections to allow for any differences between the meteorological conditions at the time and place of the test and those corresponding to a reference characteristic acoustic impedance.

In general, the frequency range of interest includes the one-third-octave bands with mid-band frequencies from 100 Hz to 10,000 Hz. In practice, the range is extended or restricted to frequencies beyond or within these limits, to those between which the test room is qualified for the purposes of the measurements.

1.2 Types of noise and noise sources

The methods specified in this American National Standard are suitable for all types of noise (steady, non-steady, fluctuating, isolated bursts of sound energy, etc.) defined in ISO 12001.

The noise source under test can be a device, machine, component or sub-assembly. The maximum size of the noise source depends on specified requirements regarding the radius of the hypothetical sphere or hemisphere used as the enveloping measurement surface.

1.3 Test room

The test rooms that are applicable for measurements made in accordance with this American National Standard are an anechoic room or hemi-anechoic room, also called, respectively, a free-field test room or hemi-free-field test room.

1.4 Measurement uncertainty

Information is given on the uncertainty of the sound power levels and sound energy levels determined in accordance with this American National Standard, for measurements made in limited bands of frequency and with frequency weighting A applied. The uncertainty conforms to ISO 12001:1996, accuracy grade 1 (precision grade).

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.