

**ANSI/ASA S12.56-2011 / ISO 3746:2010**

(a revision of ANSI S12.56-1999 / ISO 3746:1995)

---

---

---

## AMERICAN NATIONAL STANDARD

### **Acoustics – Determination of sound power levels and sound energy levels of noise sources using sound pressure – Survey method using an enveloping measurement surface over a reflecting plane**

(a Nationally Adopted International Standard)

---

---

---

ANSI/ASA S12.56-2011 / ISO 3746:2010

Accredited Standards Committee S12, Noise

---

Standards Secretariat  
Acoustical Society of America  
35 Pinelawn Road, Suite 114 E  
Melville, NY 11747-3177

The American National Standards Institute, Inc. (ANSI) is the national coordinator of voluntary standards development and the clearinghouse in the U.S.A. for information on national and international standards.

The Acoustical Society of America (ASA) is an organization of scientists and engineers formed in 1929 to increase and diffuse the knowledge of acoustics and to promote its practical applications.



**ANSI/ASA S12.56-2011 / ISO 3746:2010**

**AMERICAN NATIONAL STANDARD**

**Acoustics — Determination of sound power levels and sound energy levels of noise sources using sound pressure — Survey method using an enveloping measurement surface over a reflecting plane**

**(a nationally adopted international standard)**

**Secretariat:**

**Acoustical Society of America**

**Approved on June 28, 2011 by:**

**American National Standards Institute, Inc.**

**Abstract**

This American National Standard specifies methods for determining the sound power level or sound energy level of a noise source from sound pressure levels measured on a surface enveloping a noise source (machinery or equipment) in a test environment for which requirements are given. The sound power level (or, in the case of noise bursts or transient noise emission, the sound energy level) produced by the noise source with frequency A-weighting applied is calculated using those measurements.

## AMERICAN NATIONAL STANDARDS ON ACOUSTICS

The Acoustical Society of America (ASA) provides the Secretariat for Accredited Standards Committees S1 on Acoustics, S2 on Mechanical Vibration and Shock, S3 on Bioacoustics, S3/SC 1 on Animal Bioacoustics, and S12 on Noise. These committees have wide representation from the technical community (manufacturers, consumers, trade associations, organizations with a general interest, and government representatives). The standards are published by the Acoustical Society of America as American National Standards after approval by their respective Standards Committees and the American National Standards Institute (ANSI).


These standards are developed and published as a public service to provide standards useful to the public, industry, and consumers, and to Federal, State, and local governments.

Each of the Accredited Standards Committees (operating in accordance with procedures approved by ANSI) is responsible for developing, voting upon, and maintaining or revising its own Standards. The ASA Standards Secretariat administers Committee organization and activity and provides liaison between the Accredited Standards Committees and ANSI. After the Standards have been produced and adopted by the Accredited Standards Committees, and approved as American National Standards by ANSI, the ASA Standards Secretariat arranges for their publication and distribution.

An American National Standard implies a consensus of those substantially concerned with its scope and provisions. Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered and that a concerted effort be made towards their resolution.

The use of an American National Standard is completely voluntary. Their existence does not in any respect preclude anyone, whether he or she has approved the Standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the Standards.

NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this Standard.



Acoustical Society of America  
ASA Secretariat  
35 Pinelawn Road, Suite 114E  
Melville, New York 11747-3177  
Telephone: 1 (631) 390-0215  
Fax: 1 (631) 390-0217  
E-mail: [asastds@aip.org](mailto:asastds@aip.org)

© 2011 by Acoustical Society of America. This standard may not be reproduced in whole or in part in any form for sale, promotion, or any commercial purpose, or any purpose not falling within the provisions of the U.S. Copyright Act of 1976, without prior written permission of the publisher. For permission, address a request to the Standards Secretariat of the Acoustical Society of America.

## Contents

1	Scope .....	1
1.1	General .....	1
1.2	Types of noise and noise sources .....	1
1.3	Test environment .....	1
1.4	Measurement uncertainty .....	1
2	Normative references .....	2
3	Terms and definitions .....	2
4	Test environment .....	7
4.1	General .....	7
4.2	Criterion for background noise .....	7
4.3	Criterion for acoustic adequacy of test environment .....	7
5	Instrumentation .....	7
5.1	General .....	7
5.2	Calibration .....	8
6	Definition, location, installation and operation of noise source under test .....	8
6.1	General .....	8
6.2	Auxiliary equipment .....	8
6.3	Noise source location .....	9
6.4	Mounting of the noise source .....	9
6.5	Operation of source during test .....	10
7	Reference box and measurement surface .....	10
7.1	Reference box .....	10
7.2	Measurement surface .....	11
8	Determination of sound power levels and sound energy levels .....	14
8.1	Determination of environmental correction .....	14
8.2	Microphone positions on the measurement surface .....	14
8.3	Determination of sound power levels .....	15
8.4	Determination of sound energy levels .....	18
9	Measurement uncertainty .....	20
9.1	Methodology .....	20
9.2	Determination of $\sigma_{omc}$ .....	21
9.3	Determination of $\sigma_{R0}$ .....	21
9.4	Typical upper bound values of $\sigma_{R0}$ .....	23
9.5	Total standard deviation $\sigma_{tot}$ and expanded measurement uncertainty $U$ .....	23
10	Information to be recorded .....	24
10.1	General .....	24
10.2	Noise source under test .....	24
10.3	Test environment .....	24
10.4	Instrumentation .....	24
10.5	Acoustical data .....	25

11	Test report .....	25
<b>Annex A</b>	(normative) Determination of the environmental correction .....	26
<b>Annex B</b>	(normative) Microphone arrays on a hemispherical measurement surface .....	27
B.1	Key microphone positions and additional microphone positions .....	27
B.2	Microphone positions for sources adjacent to two reflecting planes .....	27
B.3	Microphone positions for sources adjacent to three reflecting planes .....	27
<b>Annex C</b>	(normative) Microphone arrays on a parallelepiped measurement surface .....	32
C.1	Microphone positions for sources mounted on one reflecting plane .....	32
C.2	Microphone positions for sources adjacent to two or three reflecting planes .....	32
<b>Annex D</b>	(informative) Guidelines on the development of information on measurement uncertainty .....	40
D.1	General .....	40
D.2	Considerations on the total standard deviation $\sigma_{tot}$ .....	40
D.3	Considerations on $\sigma_{omc}$ .....	40
D.4	Considerations on $\sigma_{R0}$ .....	42
D.5	Combined standard uncertainty .....	48
D.6	Measurement uncertainty based on reproducibility data .....	49

## Tables

Table 1	— Typical upper bound values of the standard deviation of reproducibility of the method, $\sigma_{R0}$ , for A-weighted sound power levels and sound energy levels determined in accordance with this American National Standard .....	23
Table A.1	— Approximate values of the mean sound absorption coefficient, $\alpha$ .....	26
Table B.1	— Microphone positions for a noise source over a reflecting plane (key microphone positions: 4,5,6,10; additional microphone positions: 14,15,16,20; $r$ is the radius of the measurement hemisphere) .....	27
Table B.2	— Microphone positions for a source adjacent to two or three reflecting planes .....	28
Table D.1	— Examples of calculated total standard deviations $\sigma_{tot}$ for three different cases .....	42
Table D.2	— Uncertainty budget for determinations of $\sigma_{R0}$ for sound power level and sound energy level, valid for A-weighted measurements of a source with a relatively flat frequency spectrum .....	44

## Foreword

*[This Foreword is for information only, and is not a part of the American National Standard ANSI/ASA S12.56-2011 / ISO 3746:2010 American National Standard Acoustics — Determination of sound power levels and sound energy levels of noise sources using sound pressure — Survey method using an enveloping measurement surface over a reflecting plane.]*

This standard comprises a part of a group of definitions, standards, and specifications for use in noise. It was developed and approved by Accredited Standards Committee S12, Noise, under its approved operating procedures. Those procedures have been accredited by the American National Standards Institute (ANSI). The Scope of Accredited Standards Committee S12 is as follows:

*Standards, specifications, and terminology in the field of acoustical noise pertaining to methods of measurement, evaluation, and control, including biological safety, tolerance, and comfort, and physical acoustics as related to environmental and occupational noise.*

This standard is a revision of ANSI S12.56-1999 (R 2004) / ISO 3746:1995, which has been technically revised.

This Standard is identical to International Standard ISO 3746, Acoustics — Determination of sound power levels and sound energy levels of noise sources using sound pressure — Survey method using an enveloping measurement surface over a reflecting plane, which was prepared by Technical Committee ISO/TC 43 Subcommittee SC 1, Noise. However, in conformance with ANSI and ISO rules, the words "American National Standard" replace the words "International Standard" where they appear in the ISO document, decimal points were substituted in place of the decimal commas used in ISO documents, and American English spelling is used in place of British English spelling.

The ANSI or ANSI/ASA equivalents for the ISO standards in the ISO 3740 series and other referenced nationally adopted standards are given below:

- ANSI S12.5 / ISO 6926 is an identical national adoption of ISO 6926;
- ANSI/ASA S12.50/ISO 3740 is an identical national adoption of ISO 3740;
- ANSI/ASA S12.51/ISO 3741 is an identical national adoption of ISO 3741;
- ANSI/ASA S12.53/Part 1/ISO 3743-1 is an identical national adoption of ISO 3743-1;
- ANSI/ASA S12.53/Part 2/ISO 3743-2 is an identical national adoption of ISO 3743-2;
- ANSI/ASA S12.54/ISO 3744 is an identical national adoption of ISO 3744;
- ANSI S12.55/ISO 3745 is an identical national adoption of ISO 3745;
- ANSI/ASA S12.56/ISO 3746 is an identical national adoption of ISO 3746; and
- ANSI/ASA S12.57/ISO 3747 is an identical national adoption of ISO 3747.

At the time this Standard was submitted to Accredited Standards Committee S12, Noise for approval, the membership was as follows:

W.J. Murphy, *Chair*  
R.D. Hellweg, *Vice-Chair*

S.B. Blaeser, *Secretary*

**3M Occupational Health & Environmental Safety Division** ..... E.H. Berger

**Acoustical Society of America** ..... R.D. Hellweg  
..... D. Lubman (Alt.)

<b>Air-Conditioning, Heating and Refrigeration Institute</b> .....	S. Lind
.....	D. Abbate (Alt.)
<b>Air Movement &amp; Control Association</b> .....	J.A. Brooks
.....	M. Stevens (Alt.)
<b>Alcoa Inc.</b> .....	W.D. Gallagher
<b>American Academy of Audiology</b> .....	D. Ostergren
.....	S. Gordon-Salant (Alt.)
<b>American Academy of Otolaryngology - Head and Neck Surgery</b> .....	R.A. Dobie
.....	L.A. Michael (Alt.)
<b>American Industrial Hygiene Association</b> .....	D. Driscoll
.....	S.N. Hacker (Alt.)
<b>American Speech-Language-Hearing Association</b> .....	L.A. Wilber
.....	V. Gladstone (Alt.)
<b>Caterpillar, Inc.</b> .....	K.G. Meitl
<b>Compressed Air and Gas Institute</b> .....	R.C. Johnson
.....	D.R. Bookshar (Alt.)
<b>Council for Accreditation in Occupational Hearing Conservation</b> .....	VACANT
.....	L.D. Hager (Alt.)
<b>Emerson Electric – Copeland Corporation</b> .....	A.T. Herfat
.....	G. Williamson (Alt.)
<b>ETS – Lindgren Acoustic Systems</b> .....	D. Winker
.....	M. Black (Alt.)
<b>ExxonMobil</b> .....	B. Moulton
<b>G.R.A.S. Sound &amp; Vibration</b> .....	B. Schustrich
<b>General Motors</b> .....	D.B. Moore
<b>Harley-Davidson Motor Company</b> .....	D. Jaeger
<b>Information Technology Industry Council</b> .....	W.M. Beltman
.....	J. Rosenberg (Alt.)
<b>Institute of Noise Control Engineering</b> .....	B. Tinianov
<b>International Safety Equipment Association</b> .....	J. Birkner
.....	C.Z. Fargo (Alt.)
<b>John Deere</b> .....	K.B. Washburn
.....	K. Cone (Alt.)
<b>National Council of Acoustical Consultants</b> .....	J. Erdreich
.....	G.E. Winzer (Alt.)
<b>National Hearing Conservation Association</b> .....	J. Cissna
<b>National Institute for Occupational Safety and Health</b> .....	W.J. Murphy
.....	E. Zechmann (Alt.)



<b>National Institute of Standards and Technology – National Voluntary Laboratory Accreditation Program</b> .....	B.A. Sandoval
<b>National Park Service</b> .....	G.R. Stanley
.....	K. Frstrup (Alt.)
<b>Noise Control Engineering, Inc.</b> .....	M.A. Bahtiarian
.....	R. Fischer (Alt.)
<b>Noise Pollution Clearinghouse</b> .....	L. Blomberg
<b>North American Insulation Manufacturers Association</b> .....	H. Alter
<b>PCB Group</b> .....	K. Cox
.....	L. Harbaugh (Alt.)
<b>Power Tool Institute, Inc.</b> .....	W.D. Spencer
.....	M. Hickok (Alt.)
<b>Quest Technologies, Inc.</b> .....	M. Wurm
.....	P.J. Battenberg (Alt.)
<b>Schomer and Associates, Inc.</b> .....	P.D. Schomer
<b>Sierra Club – National Parks and Monuments Committee</b> .....	D.J. Hingson
<b>Sperian Hearing Protection, LLC</b> .....	B. Witt
.....	T. Schulz (Alt.)
<b>U.S. Access Board</b> .....	M.K. Mazz
<b>U.S. Air Force</b> .....	R.L. McKinley
.....	H. Gallagher (Alt.)
<b>U.S. Army Aeromedical Research Lab</b> .....	W.A. Ahroon
<b>U.S. Army Construction Engineering Research Laboratory</b> .....	M.J. White
.....	M. Swearington (Alt.)
<b>U.S. Army Public Health Command</b> .....	C. Stewart
.....	M. Grantham (Alt.)
<b>U.S. Army Research Laboratory, Human Research and Engineering Directorate</b> .....	J. Gaston
.....	M.S. Binseel (Alt.)
<b>U.S. Department of Transportation</b> .....	A. Konheim
<b>U.S. Naval Surface Warfare Center - Carderock</b> .....	M. Craun
.....	VACANT (Alt.)
<b>Université du Québec ETS</b> .....	J. Voix
.....	F. Laville (Alt.)

Individual Experts of Accredited Standards Committee S12, Noise, were:

P.K. Baade	R.D. Hellweg	R.J. Peppin
E.H. Berger	W.W. Lang	J. Schmitt
B.M. Brooks	D. Lubman	P.D. Schomer
A.J. Campanella	D. Michaud	L.C. Sutherland
K.M. Eldred	N.P. Miller	W.R. Thornton
L.S. Finegold	W.J. Murphy	L.A. Wilber
R.D. Godfrey	M.A. Nobile	G.E. Winzer

Working Group S12/WG 23, Determination of Sound Power, which assisted Accredited Standards Committee S12, Noise, in the development of this standard, had the following membership.

	B.M. Brooks, Co-Chair	
	J. Schmitt, Co-Chair	
M.C. Black	K. Cunefare	M.A. Nobile
S. Bly	R.D. Hellweg	M. O'Connell
A.J. Campanella	A.T. Herfat	P.D. Schomer
D.A. Collings	S. Keith	J. Weinstein
	G.C. Maling	

Suggestions for improvements of this standard will be welcomed. They should be sent to Accredited Standards Committee S12, Noise, in care of the Standards Secretariat of the Acoustical Society of America, 35 Pinelawn Road, Suite 114E, Melville, New York 11747-3177. Telephone: 631-390-0215; FAX: 631-390-0217; E-mail: [asastds@aip.org](mailto:asastds@aip.org).

## Introduction

This American National Standard is a national adoption of one of the series ISO 3741<sup>[2]</sup> to ISO 3747<sup>[6]</sup>, which specify methods for determining the sound power levels and sound energy levels of noise sources including machinery, equipment and their sub-assemblies. Guidelines to select one of those methods are provided in ISO 3740<sup>[1]</sup>. The selection depends on the environment of the available test facility and on the precision of the sound power level or sound energy level values required. It may be necessary to establish a test code for the individual noise source in order to select the appropriate sound measurement surface and microphone array from among those allowed in each of the ISO 3740<sup>[1]</sup> to ISO 3747<sup>[6]</sup> series, and to give requirements for test unit mounting, loading, and operating conditions under which the sound power levels or sound energy levels are to be obtained. The sound power emitted by a given source into the test environment is calculated from the mean square sound pressure that is measured over a hypothetical measurement surface enclosing the source, and the area of that surface. The sound energy for a single machine event is calculated from this sound power and the time over which it existed.

This American National Standard specifies methods giving results of ISO 12001:1996, accuracy grade 3 (survey grade) when measurements are performed within industrial buildings or outdoors. Ideally, the test source should be mounted on a sound-reflecting plane located in a large open space. For sources normally installed on the floor of machine rooms, corrections are defined to account for undesired reflections from nearby objects, walls, and the ceiling, and for the residual background noises that occur there.

The methods specified in this American National Standard permit the determination of the sound power level and the sound energy level with frequency A-weighting applied.

For applications where greater accuracy is required, reference can be made to ISO 3744, ISO 3745<sup>[5]</sup> or an appropriate part of ISO 9614<sup>[14]-[16]</sup>. If the relevant criteria for the measurement environment specified in this American National Standard are not met, it might be possible to refer to another of the ISO 3741<sup>[2]</sup> to ISO 3747<sup>[6]</sup> series, or to an appropriate part of ISO 9614<sup>[14]-[16]</sup>.

This is a preview of "ANSI/ASA S12.56-2011...". [Click here to purchase the full version from the ANSI store.](#)

# **Acoustics — Determination of sound power levels and sound energy levels of noise sources using sound pressure — Survey method using an enveloping measurement surface over a reflecting plane**

## **1 Scope**

### **1.1 General**

This American National Standard specifies methods for determining the sound power level or sound energy level of a noise source from sound pressure levels measured on a surface enveloping a noise source (machinery or equipment) in a test environment for which requirements are given. The sound power level (or, in the case of noise bursts or transient noise emission, the sound energy level) produced by the noise source with frequency A-weighting applied is calculated using those measurements.

**NOTE** Differently shaped measurement surfaces can yield differing estimates of the sound power level of a given noise source and an appropriately drafted test code (see ISO 12001) gives detailed information on the selection of the surface.

### **1.2 Types of noise and noise sources**

The methods specified in this American National Standard are suitable for all types of noise (steady, non-steady, fluctuating, isolated bursts of sound energy, etc.) defined in ISO 12001.

This American National Standard is applicable to all types and sizes of noise source (e.g. stationary or slowly moving plant, installation, machine, component or sub-assembly), provided the conditions for the measurements can be met.

**NOTE** The conditions for measurements given in this American National Standard can be impracticable for very tall or very long sources such as chimneys, ducts, conveyors, and multi-source industrial plants. A test code for the determination of noise emission of specific sources can provide alternative methods in such cases.

### **1.3 Test environment**

The test environments that are applicable for measurements made in accordance with this American National Standard can be located indoors or outdoors, with one or more sound-reflecting planes present on or near which the noise source under test is mounted.

### **1.4 Measurement uncertainty**

Information is given on the uncertainty of the sound power levels and sound energy levels determined in accordance with this American National Standard, for measurements made with frequency A-weighting applied. The uncertainty conforms with that of ISO 12001:1996, accuracy grade 3 (survey grade).