

ANSI/ASA S2.73-2014 / ISO 10819:2013
(Revision of ANSI S2.73-2002 / ISO 10819:1996)

AMERICAN NATIONAL STANDARD

Mechanical Vibration and Shock – Hand-arm Vibration – Measurement and Evaluation of the Vibration Transmissibility of Gloves at the Palm of the Hand (a nationally adopted international standard)

ANSI/ASA S2.73-2014 /
ISO 10819:2013

Accredited Standards Committee S2, Mechanical Vibration and Shock

Standards Secretariat
Acoustical Society of America
1305 Walt Whitman Road
Melville, NY 11747

The American National Standards Institute, Inc. (ANSI) is the national coordinator of voluntary standards development and the clearinghouse in the U.S.A. for information on national and international standards.

The Acoustical Society of America (ASA) is an organization of scientists and engineers formed in 1929 to increase and diffuse the knowledge of acoustics and to promote its practical applications.



ANSI/ASA S2.73-2014 / ISO 10819:2013
(Revision of ANSI S2.73-2002 / ISO 10819:1996)

AMERICAN NATIONAL STANDARD

Mechanical vibration and shock — Hand-arm vibration — Measurement and evaluation of the vibration transmissibility of gloves at the palm of the hand

(a nationally adopted international standard)

Secretariat:

Acoustical Society of America

Approved on April 16, 2014 by:

American National Standards Institute, Inc.

Abstract

This American National Standard specifies a method for the laboratory measurement, data analysis, and reporting of the vibration transmissibility of a glove with a vibration-reducing material that covers the palm, fingers, and thumb of the hand. ANSI/ASA S2.73-2014 / ISO 10819:2013 specifies vibration transmissibility in terms of vibration transmitted from a handle through a glove to the palm of the hand in one-third-octave frequency bands with center frequencies of 25 Hz to 1,250 Hz.

AMERICAN NATIONAL STANDARDS ON ACOUSTICS

The Acoustical Society of America (ASA) provides the Secretariat for Accredited Standards Committees S1 on Acoustics, S2 on Mechanical Vibration and Shock, S3 on Bioacoustics, S3/SC 1 on Animal Bioacoustics, and S12 on Noise. These committees have wide representation from the technical community (manufacturers, consumers, trade associations, organizations with a general interest, and government representatives). The standards are published by the Acoustical Society of America as American National Standards after approval by their respective Standards Committees and the American National Standards Institute (ANSI).


These standards are developed and published as a public service to provide standards useful to the public, industry, and consumers, and to Federal, State, and local governments.

Each of the Accredited Standards Committees (operating in accordance with procedures approved by ANSI) is responsible for developing, voting upon, and maintaining or revising its own Standards. The ASA Standards Secretariat administers Committee organization and activity and provides liaison between the Accredited Standards Committees and ANSI. After the Standards have been produced and adopted by the Accredited Standards Committees, and approved as American National Standards by ANSI, the ASA Standards Secretariat arranges for their publication and distribution.

An American National Standard implies a consensus of those substantially concerned with its scope and provisions. Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered and that a concerted effort be made towards their resolution.

The use of an American National Standard is completely voluntary. Their existence does not in any respect preclude anyone, whether he or she has approved the Standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the Standards.

NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this Standard.



Acoustical Society of America
ASA Secretariat
1305 Walt Whitman Road, Suite 300
Melville, New York 11747
Telephone: 1 (631) 390-0215
Fax: 1 (631) 923-2875
E-mail: asastds@aip.org

© 2014 by Acoustical Society of America. This standard may not be reproduced in whole or in part in any form for sale, promotion, or any commercial purpose, or any purpose not falling within the provisions of the U.S. Copyright Act of 1976, without prior written permission of the publisher. For permission, address a request to the Standards Secretariat of the Acoustical Society of America.

These materials are subject to copyright claims of ISO, IEC, and ASA. No part of this publication may be reproduced in any form, including an electronic retrieval system, without the prior written permission of the Acoustical Society of America (ASA). All requests pertaining to this standard should be submitted to the ASA.

Contents

1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Symbols and abbreviations	2
5	Measuring principle and equipment.....	3
5.1	General principle and setup	3
5.2	Measuring equipment.....	4
5.3	Vibration excitation system	7
6	Measurement conditions and procedure.....	8
6.1	Measurement conditions.....	8
6.2	Vibration signal	10
6.3	Test procedure.....	12
7	Evaluation of results	14
7.1	Calculation of transmissibility	14
7.2	Bare palm adaptor vibration transmissibility	15
7.3	Uncorrected glove vibration transmissibility	16
7.4	Corrected glove vibration transmissibility	17
8	Calculation of statistical values	18
8.1	General	18
8.2	One-third-octave vibration transmissibility.....	18
8.3	Frequency-weighted vibration transmissibility	19
9	Criteria for designating gloves as antivibration gloves	20
9.1	General	20
9.2	Vibration transmissibility of the gloves.....	20
9.3	Construction of the gloves	20
10	Test report.....	23
	Annex A (informative) Examples of handles with force and acceleration measuring systems	25
	Bibliography	28

Figures

Figure 1	— Schematic diagram for measurement of glove vibration transmissibility	4
Figure 2	— Adaptor for holding the accelerometer in the palm of the hand	5
Figure 3	— Grip force to be measured.....	6
Figure 4	— Posture of the test subject during measurements	7
Figure 5	— Position of hand with handle and adaptor	9
Figure 6	— Palm adaptor alignment on top of handle	10

Figure 7 — Triaxial accelerometer location in palm adaptor	10
Figure 8 — Handle acceleration power spectral density spectrum	11
Figure 9 — One-third-octave band handle acceleration values	11
Figure 10 — Flow diagram for determining the mean corrected transmissibility values, standard deviations and coefficients of variation	14
Figure 11 — Example of a measurement setup for measuring the glove vibration-reducing material thickness.....	21
Figure A.1 — Example 1 of a handle with grip force measuring system.....	26
Figure A.2 — Example 2 of a handle with feed and grip force measuring systems.....	27

Tables

Table 1 — Required handle acceleration values.....	12
Table 2 — Frequency weighting factors W_{hi} for hand-transmitted vibration for conversion of one- third-octave band magnitudes to frequency-weighted magnitudes	15

Foreword

[This Foreword is for information only, and is not a part of the American National Standard ANSI/ASA S2.73-2014 / ISO 10819:2013 American National Standard Acoustics — Mechanical vibration and shock – Hand-arm vibration – Measurement and evaluation of the vibration transmissibility of gloves at the palm of the hand.]

This nationally adopted international standard specifies a method for the laboratory measurement, data analysis, and reporting of the vibration transmissibility of a glove with a vibration-reducing material that covers the palm, fingers, and thumb of the hand. It was approved by Accredited Standards Committee S2 Mechanical Vibration and Shock, under its approved operating procedures. Those procedures have been accredited by the American National Standards Institute (ANSI). The Scope of Accredited Standards Committee S2 is as follows:

Standards, specification, methods of measurement and test, and terminology in the field of mechanical vibration and shock, and condition monitoring and diagnostics of machines, including the effects of exposure to mechanical vibration and shock on humans, including those aspects which pertain to biological safety, tolerance and comfort.

This standard is an identical national adoption of ISO 10819:2013 which was prepared by Technical Committee ISO/TC 108/SC 4, *Human exposure to mechanical vibration and shock*. This standard is a revision of ANSI S2.73-2002 (R 2007) / ISO 10819:1996. This revision incorporates stronger criteria for antivibration gloves and the addition of a method for measuring the material thickness. In conformance with ANSI and ISO rules, the words "American National Standard" replace the words "International Standard" where they appear in the ISO document, decimal points were substituted in place of the decimal commas used in ISO documents, and American English spelling is used in place of British English spelling.

The ANSI/ASA equivalent for ISO 2041 referenced in this standard is:

- ANSI/ASA S2.1-2009 / ISO 2041:2009 American National Standard Mechanical vibration, shock and condition monitoring –Vocabulary.

At the time this American National Standard was submitted to Accredited Standards Committee S2, Mechanical Vibration and Shock for approval, the membership was as follows:

A.T. Herfat, *Chair*
C.F. Gaumont, *Vice-Chair*

S.B. Blaeser, *Secretary*

Acoustical Society of America C.F. Gaumont
..... B.E. Douglas (Alt.)

American Industrial Hygiene Association..... J.J. Earshen
..... D. Driscoll (Alt.)

Ariel Corporation..... T. Stephens
..... C. Lingel (Alt.)

Association of American Railroads..... J. Moller
..... N. Cooperrider (Alt.)

Bose Corporation J. Parison

BP America..... W.C. Foiles
..... J. McCraw (Alt.)

Calnetix	L.A. Hawkins P. McMullen (Alt.)
Caterpillar, Inc.	D.G. Roley
Commercial Vehicle Group	L. Mullinix
Condition Analyzing Corporation	M. Williams J. McNeil (Alt.)
Duke University - Dept. of Biomedical Engineering	C.R. Bass
Eckardt Johanning, MD, PC	E. Johanning
Emerson Electric – Copeland Corporation	A.T. Herfat
Endevco Corp.	B. Yang
FLIR Systems	G.L. Orlove
Florida Atlantic University – Dept. of Ocean Engineering	P.P.J. Beaujean
G.E. Energy	R. Bankert
John Deere	L. DeVries
Marketing Assessment, Inc.	P. Chambers
Mechanical Solutions, Inc.	W.D. Marscher M. Onari (Alt.)
MIMOSA	K. Bever A. Johnston (Alt.)
NASA Ames Research Center	K.F. Goebel
National Institute for Occupational Safety and Health (NIOSH)	R. Dong T.W. McDowell (Alt.)
National Institute of Standards & Technology	D.J. Evans S. Fick (Alt.)
PCB Group	R.D. Sill D. Lally (Alt.)
Power Tool Institute, Inc.	W.D. Spencer M. Hickok (Alt.)
Schenck Trebel Corp.	B. Dittmar
Shock and Vibration Exchange	V.I. Bateman J.E. Howell (Alt.)
Siemens Power Generation, Inc.	M. L'vov L. Zeller (Alt.)
Sinclair PLLC Occupational & Environmental Legal Consulting	D.C. Sinclair
U.S. Air Force	S.D. Smith

U.S. Army Aeromedical Research Laboratory	K. Barazanji
U.S. Army Public Health Command	S. Chervak
.....	J. Clasing (Alt.)
U.S. Department of Transportation – Volpe Center	J.K. Pollard
.....	T. Raslear (Alt.)
U.S. Naval Surface Warfare Center – Carderock	K.A. Michalis
.....	W. Martin (Alt.)
U.S. Naval Surface Warfare Center – Panama City	B.L. Price
UE Systems, Inc.	M. Goodman
University of Washington – Environmental & Occupational Health Sciences	P.W. Johnson
Vibration Institute	R.L. Eshleman
.....	B. Biby (Alt.)
Waukesha Magnetic Bearings	K. Bornstein
.....	R. Shultz (Alt.)

Individual Experts of Accredited Standards Committee S2, Mechanical Vibration and Shock, were:

A.J. Brammer
D.D. Reynolds
D.E. Wasserman

Working Group S2/WG 39, *Human Exposure to Mechanical Vibration and Shock*, which assisted Accredited Standards Committee S2, Mechanical Vibration and Shock, in the development of this standard, had the following membership:

D.D. Reynolds, Chair
R. Dong, Vice-Chair

K. Barazanji	L. DeVries	B.L. Price
C.R. Bass	T. Jetzer	D.G. Roley
M. Callison	E. Johanning	D.C. Sinclair
P. Chambers	L. Mullinix	S.D. Smith
M. Cherniack	J. Parison	W.D. Spencer
S. Chervak	J.E. Phillips	D.E. Wasserman
N. Cooperrider	J.K. Pollard	D. Wilder

Suggestions for improvements of this American National Standard will be welcomed. They should be sent to Accredited Standards Committee S2, Mechanical Vibration and Shock, in care of the Standards Secretariat of the Acoustical Society of America, 1305 Walt Whitman Road, Suite 300, Melville, New York 11747. Telephone: 631-390-0215; FAX: 631 923-2875; E-mail: asastds@aip.org.

Introduction

Because of the growing demand to reduce health risks associated with exposure to hand-transmitted vibration, gloves with vibration-reducing materials are often used to attenuate vibration transmitted to the hands. These gloves normally provide little reduction in hand-transmitted vibration at frequencies below 150 Hz. Some gloves can increase the vibration transmitted to the hands at these low frequencies. Gloves with vibration-reducing materials that meet the requirements of this American National Standard to be classified as an antivibration glove can be expected to reduce hand-transmitted vibration at frequencies above 150 Hz. These gloves can reduce but not eliminate health risks associated with hand-transmitted vibration exposure.

Field observations indicate that gloves with vibration-reducing materials can result in positive and negative health effects. Positive health effects can occur with gloves that reduce finger tingling and numbness and that keep the hands warm and dry. Negative health effects can occur with gloves that increase the vibration transmitted to the hands at low frequencies and that increase hand and arm fatigue because they increase the hand grip effort required to control a vibrating machine.

Gloves tested in accordance with the requirements of this American National Standard are evaluated in a controlled laboratory environment. The actual vibration attenuation of a glove in a work environment can differ from that measured in a controlled laboratory environment.

Vibration transmissibility measurements made in accordance with the requirements of this American National Standard are performed only at the palm of the hand. The transmission of vibration to the fingers is not measured. When evaluating the effectiveness of a glove with a vibration-reducing material used to reduce vibration transmitted to the hand, vibration transmission to the fingers should also be assessed. However, research subsequent to the publication of this American National Standard is needed to develop a measurement procedure that can be used to measure the vibration transmissibility of gloves at the fingers.

The measurement procedure specified in this American National Standard only addresses glove properties that can reduce health risks associated with hand-transmitted vibration in work environments. It does not address glove properties necessary to reduce other hand-related health and safety risks in work environments.

The measurement procedure specified in this American National Standard can also be used to measure the vibration transmissibility of a material that is being evaluated for use to cover a handle of a machine or for potential use in a glove.

AMERICAN NATIONAL STANDARD

Mechanical vibration and shock — Hand-arm vibration — Measurement and evaluation of the vibration transmissibility of gloves at the palm of the hand (a nationally adopted international standard)

WARNING — This American National Standard defines a screening test procedure for measuring the vibration transmission through gloves with an embedded vibration-reducing material. Many factors not addressed in this American National Standard can influence the transmission of vibration through these gloves. Therefore, use the vibration transmissibility values obtained in accordance with this American National Standard with caution in the assessment of the vibration-reducing effects of gloves.

1 Scope

This American National Standard specifies a method for the laboratory measurement, data analysis, and reporting of the vibration transmissibility of a glove with a vibration-reducing material that covers the palm, fingers, and thumb of the hand. This American National Standard specifies vibration transmissibility in terms of vibration transmitted from a handle through a glove to the palm of the hand in one-third-octave frequency bands with center frequencies of 25 Hz to 1,250 Hz.

The measurement procedure specified in this American National Standard can also be used to measure the vibration transmissibility of a material that is being evaluated for use to cover a handle of a machine or for potential use in a glove. However, results from this test cannot be used to certify that a material used to cover a handle meets the requirements of this American National Standard to be classified as an antivibration covering. A material tested in this manner could later be placed in a glove. When this is the case, the glove needs to be tested in accordance with the measurement procedure of this American National Standard and needs to meet the vibration attenuation performance requirements of this American National Standard in order to be classified as an antivibration glove.

NOTE ISO 13753^[1] defines a method for screening materials used for vibration attenuation on the handles of machines and for gloves.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

- a) ISO 2041, *Mechanical vibration, shock and condition monitoring — Vocabulary*
- b) ISO 5349-1, *Mechanical vibration — Measurement and evaluation of human exposure to hand-transmitted vibration — Part 1: General requirements*
- c) ISO 5805, *Mechanical vibration and shock — Human exposure — Vocabulary*