

**ANSI/ASA S3/SC1.100-2014**  
**ANSI/ASA S12.100-2014**  
(a joint project between ASC S3/SC 1 and ASC S12)

---

---

---

## AMERICAN NATIONAL STANDARD

### **Methods to Define and Measure the Residual Sound in Protected Natural and Quiet Residential Areas**

---

---

---

ANSI/ASA S3/SC1.100-2014  
ANSI/ASA S12.100-2014

Accredited Standards Committee S3/SC 1, Animal Bioacoustics AND  
Accredited Standards Committee S12, Noise

---

Standards Secretariat  
Acoustical Society of America  
1305 Walt Whitman Road, Suite 300  
Melville, NY 11747

The American National Standards Institute, Inc. (ANSI) is the national coordinator of voluntary standards development and the clearinghouse in the U.S.A. for information on national and international standards.

The Acoustical Society of America (ASA) is an organization of scientists and engineers formed in 1929 to increase and diffuse the knowledge of acoustics and to promote its practical applications.



**ANSI/ASA S3/SC1.100-2014**  
**ANSI/ASA S12.100-2014**  
(a joint project between ASC S3/SC 1 and ASC S12)

AMERICAN NATIONAL STANDARD

**Methods to Define and Measure the  
Residual Sound in Protected Natural and Quiet  
Residential Areas**

**Secretariat:**

**Acoustical Society of America**

**Approved on December 5, 2014, by:**

**American National Standards Institute, Inc.**

**Abstract**

This standard specifies measurement procedures for characterizing residual sound levels in protected natural areas and quiet residential areas. The standard specifies instrumentation, measurement durations, and statistical procedures for summarizing the data. A filtering procedure is provided that can be applied to A-weighted data to exclude high frequency sound energy where appropriate or warranted. The statistical procedure for calculating exceedance values like  $L_{90}$  is specified.

## AMERICAN NATIONAL STANDARDS ON ACOUSTICS

The Acoustical Society of America (ASA) provides the Secretariat for Accredited Standards Committees S1 on Acoustics, S2 on Mechanical Vibration and Shock, S3 on Bioacoustics, S3/SC 1 on Animal Bioacoustics, and S12 on Noise. These committees have wide representation from the technical community (manufacturers, consumers, trade associations, organizations with a general interest, and government representatives). The standards are published by the Acoustical Society of America as American National Standards after approval by their respective Standards Committees and the American National Standards Institute (ANSI).


These standards are developed and published as a public service to provide standards useful to the public, industry, and consumers, and to Federal, State, and local governments.

Each of the Accredited Standards Committees (operating in accordance with procedures approved by ANSI) is responsible for developing, voting upon, and maintaining or revising its own Standards. The ASA Standards Secretariat administers Committee organization and activity and provides liaison between the Accredited Standards Committees and ANSI. After the Standards have been produced and adopted by the Accredited Standards Committees, and approved as American National Standards by ANSI, the ASA Standards Secretariat arranges for their publication and distribution.

An American National Standard implies a consensus of those substantially concerned with its scope and provisions. Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered and that a concerted effort be made towards their resolution.

The use of an American National Standard is completely voluntary. Their existence does not in any respect preclude anyone, whether he or she has approved the Standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the Standards.

NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this Standard.



Acoustical Society of America  
Standards Secretariat  
1305 Walt Whitman Road, Suite 300  
Melville, New York 11747  
Telephone: 1 (631) 390-0215  
Fax: 1 (631) 923-2875  
E-mail: [asastds@acousticalsociety.org](mailto:asastds@acousticalsociety.org)

© 2014 by Acoustical Society of America. This standard may not be reproduced in whole or in part in any form for sale, promotion, or any commercial purpose, or any purpose not falling within the provisions of the U.S. Copyright Act of 1976, without prior written permission of the publisher. For permission, address a request to the Standards Secretariat of the Acoustical Society of America.

## Contents

1	Scope .....	1
2	Normative references .....	1
3	Terms and definitions .....	2
4	Filter requirements .....	3
5	Residual measurement procedure .....	3
6	Reporting .....	6
Annex A (informative) Average differences between A-weighted and ANS-weighted sound levels and the standard deviation to these differences for several noise sources .....		
	A.1 Various noise sources and general residual noise without significant natural sounds.....	8
	A.2 Several residual noise situations with significant natural sounds .....	8
Annex B (informative) Noise floor of sound level meters when using A-weighting and when using ANS-weighting .....		
	B.1 Introduction .....	10
	B.2 A theoretical analysis of the effect of ANS-weighting on the electrical noise floor of a type 1 sound level meter.....	10
	B.3 Comparison of theory with data .....	10
	B.4 Additional benefits of ANS-weighting.....	13
	B.5 An explanation for the anomalous differences.....	14
	B.6 Conclusions.....	15
Annex C (normative) Minimum requirements for measurements in parks and wilderness areas.....		
	C.1 Introduction .....	16
	C.2 Instruments .....	16
	C.3 System sensitivity checks during measurements .....	17
Bibliography .....		18

## Tables

Table A.1 — Comparison of A-weighted and ANS-weighted sound level differences for various noise sources* .....	8
Table A.2 — Example differences between A-weighted and ANS-weighted sound levels.....	9
Table B.1 — Differences between A-weighted and ANS-weighted levels of leaf-rustle noise .....	14

## Figures

Figure B.1 — Noise floor of the Larson-Davis 831 sound level meter .....	11
Figure B.2 — Histogram of the second-by-second differences between A-weighted and corresponding ANS-weighted levels .....	11

Figure B.3 — A scatter plot of the differences between A-weighted levels and corresponding ANS-weighted levels as a function of the A-weighted level ..... 12

Figure B.4 — A boxplot of the differences between A-weighted levels and corresponding ANS-weighted levels as a function of the wind speed ..... 13

Figure B.5 — A scatter plot of the differences between A-weighted levels and corresponding ANS-weighted levels as a function of the change in the A-weighted level from the preceding second ..... 14

## Foreword

[This Foreword is for information only, and is not a part of the American National Standard ANSI/ASA S3/SC1.100-2014 / ANSI/ASA S12.100-2014 American National Standard Methods to Define and Measure the Residual Sound in Protected Natural and Quiet Residential Areas. As such, this Foreword may contain material that has not been subjected to public review or a consensus process. In addition, it does not contain requirements necessary for conformance to the standard.]

This new standard, for which there is no ISO or EN counterpart, was developed and approved as a joint project between ANSI-Accredited Standards Committee S3/SC 1, Animal Bioacoustics, and ANSI-Accredited Standards Committee S12, Noise. It comprises a part of a group of definitions, standards, and specifications for use in the fields of psychological acoustics, physiological acoustics, and acoustic ecology as it affects both humans and animals. It was developed and approved by both ASC S3/SC 1 and ASC S12 under their approved operating procedures. Those procedures have been accredited by the American National Standards Institute (ANSI).

The Scope of **Accredited Standards Committee S3/SC 1** is as follows:

*Standards, specifications, methods of measurement and test, instrumentation, and terminology in the field of psychological and physiological acoustics, including aspects of general acoustics which pertain to biological safety, tolerance, and comfort of non-human animals, including both risk to individual animals and to the long-term viability of populations. Animals to be covered may potentially include commercially grown food animals; animals harvested for food in the wild; pets; laboratory animals; exotic species in zoos, oceanaria or aquariums; or free-ranging wild animals.*

The Scope of **Accredited Standards Committee S12** is as follows:

*Standards, specifications, and terminology in the field of acoustical noise pertaining to methods of measurement, evaluation, and control, including biological safety, tolerance, and comfort, and physical acoustics as related to environmental and occupational noise.*

At the time this Standard was submitted to Accredited Standards Committee S3/SC 1, Animal Bioacoustics, for approval the membership was as follows:

D.K. Delaney, *Chair*  
M.C. Hastings, *Vice-Chair*

S.B. Blaeser, *Secretary*

**Acoustical Society of America** .....M.C. Hastings  
**American Academy of Otolaryngology, Head and Neck Surgery** .....R.A. Dobie  
**American Speech-Language-Hearing Association (ASHA)** .....B.M. Ryals  
.....V. Gladstone (Alt.)  
**G.R.A.S. Sound & Vibration**..... B. Schustrich  
..... J. Soendergaard (Alt.)  
**International Association of Geophysical Contractors**..... S. Tsouflas

<b>National Park Service</b> .....	K. Fristrup G.R. Stanley (Alt.)
<b>Ocean Conservation Research</b> .....	M. Stocker
<b>SpeakDolphin.com</b> .....	J. Kassewitz S. Kuczaj (Alt.)
<b>U.S. Army Aeromedical Research Laboratory</b> .....	W. Ahroon
<b>U.S. Army CERL</b> .....	D.K. Delaney M.J. White (Alt.)
<b>U.S. Navy Marine Mammal Program</b> .....	J.J. Finneran D.S. Houser (Alt.)
<b>University of Cincinnati Animal Audiology Clinic/Bioacoustics Lab</b> .....	P.M. Scheifele D.K. Brown (Alt.)

At the time this Standard was submitted to Accredited Standards Committee S12, Noise, for approval, the membership was as follows:

W.J. Murphy, *Chair*  
R.D. Hellweg, *Vice-Chair*  
S.B. Blaeser, *Secretary*

<b>3M Occupational Health &amp; Environmental Safety Division</b> .....	E.H. Berger
<b>Acoustical Society of America</b> .....	R.D. Hellweg D. Lubman (Alt.)
<b>Air-Conditioning, Heating and Refrigeration Institute</b> .....	S. Lind D. Abbate (Alt.)
<b>Air Movement &amp; Control Association, Inc.</b> .....	J.A. Brooks M. Stevens (Alt.)
<b>Alcoa Inc.</b> .....	W.D. Gallagher
<b>American Academy of Audiology</b> .....	D. Ostergren S. Gordon-Salant (Alt.)
<b>American Academy of Otolaryngology - Head and Neck Surgery</b> .....	R.A. Dobie L.A. Michael (Alt.)
<b>American Industrial Hygiene Association</b> .....	D. Driscoll S.N. Hacker (Alt.)
<b>American Speech-Language-Hearing Association</b> .....	L.A. Wilber V. Gladstone (Alt.)
<b>Caterpillar, Inc.</b> .....	K.G. Meitl
<b>Compressed Air and Gas Institute</b> .....	R.C. Johnson D.R. Bookshar (Alt.)



<b>Council for Accreditation in Occupational Hearing Conservation</b> .....	VACANT
.....	L.D. Hager (Alt.)
<b>Emerson Electric – Copeland Corporation</b> .....	A.T. Herfat
.....	G. Williamson (Alt.)
<b>ETS – Lindgren Acoustic Systems</b> .....	D. Winker
.....	M. Black (Alt.)
<b>ExxonMobil</b> .....	B. Moulton
<b>G.R.A.S. Sound &amp; Vibration</b> .....	B. Schustrich
.....	J. Soendergaard (Alt.)
<b>GE Aviation</b> .....	R. Majjigi
.....	R. Babbitt (Alt.)
<b>General Motors</b> .....	D.B. Moore
<b>Harley-Davidson Motor Company</b> .....	D. Jaeger
<b>Information Technology Industry Council</b> .....	W.M. Beltman
.....	J. Rosenberg (Alt.)
<b>Institute of Noise Control Engineering</b> .....	R.J. Peppin
.....	B. Tinianov (Alt.)
<b>International Safety Equipment Association</b> .....	J. Birkner
.....	C.Z. Fargo (Alt.)
<b>John Deere</b> .....	K.B. Washburn
.....	K. Cone (Alt.)
<b>National Council of Acoustical Consultants</b> .....	J. Erdreich
.....	G.E. Winzer (Alt.)
<b>National Hearing Conservation Association</b> .....	J. Cissna
<b>National Institute for Occupational Safety and Health</b> .....	W.J. Murphy
.....	E. Zechmann (Alt.)
<b>National Institute of Standards and Technology – National Voluntary Laboratory Accreditation Program</b> .....	B.A. Sandoval
<b>National Park Service</b> .....	G.R. Stanley
.....	K. Frstrup (Alt.)
<b>Noise Control Engineering, Inc.</b> .....	M.A. Bahtiarian
.....	R. Fischer (Alt.)
<b>Noise Pollution Clearinghouse</b> .....	L. Blomberg
<b>PCB Group</b> .....	K. Cox
.....	L. Harbaugh (Alt.)
<b>Power Tool Institute, Inc.</b> .....	W.D. Spencer
.....	M. Hickok (Alt.)
<b>Schomer and Associates, Inc.</b> .....	P.D. Schomer

<b>Sierra Club – National Parks and Monuments Committee</b> .....	D.J. Hingson
<b>Sperian Hearing Protection, LLC</b> .....	R. Ghent B. Witt (Alt.)
<b>U.S. Air Force</b> .....	R.L. McKinley H. Gallagher (Alt.)
<b>U.S. Army Aeromedical Research Laboratory</b> .....	W.A. Ahroon
<b>U.S. Army Construction Engineering Research Laboratory</b> .....	M.J. White M. Swearingen (Alt.)
<b>U.S. Army Public Health Command</b> .....	C. Stewart M. Grantham (Alt.)
<b>U.S. Army Research Laboratory, Human Research and Engineering Directorate</b> .....	J. Gaston M.S. Binseel (Alt.)
<b>U.S. Department of Transportation</b> .....	A. Konheim
<b>U.S. Naval Surface Warfare Center - Carderock</b> .....	M. Craun
<b>Université du Québec ETS</b> .....	J. Voix F. Laville (Alt.)

Individual Experts of Accredited Standards Committee S12, Noise, were:

P.K. Baade	W.W. Lang	R.J. Peppin
E.H. Berger	D. Lubman	J. Schmitt
B.M. Brooks	D. Michaud	P.D. Schomer
A.J. Campanella	N.P. Miller	L.C. Sutherland
L.S. Finegold	W.J. Murphy	W.R. Thornton
R.D. Godfrey	M.A. Nobile	L.A. Wilber
R.D. Hellweg		G.E. Winzer

Working Group S3/SC 1/WG 4, Description and Measurement of the Ambient Sound in Parks, Wilderness Areas, and Other Quiet and/or Pristine Areas, which assisted Accredited Standards Committee S3/SC 1, Animal Bioacoustics, in the development of this standard, had the following membership.

K. Fristrup, Co-Chair  
G.R. Stanley, Co-Chair

M.A. Bahtiarian	D.J. Hingson	A.P. Nash
D.K. Delaney	R.D. Horonjeff	J. Soendergaard
L.S. Finegold	T.R. Letowski	K.G. Standlee
R.D. Hellweg	N.P. Miller	N. Timmerman

Working Group S12/WG15, Measurement and Evaluation of Outdoor Community Noise, which assisted Accredited Standards Committee S12, Noise, in the development of this standard, had the following membership.

P.D. Schomer, Chair

L. Blomberg  
B.M. Brooks  
G.A. Daigle  
S. Fidell  
L.S. Finegold  
L. Goodfriend

R.D. Hellweg  
G. Hessler  
R.D. Horonjeff  
A. Konheim  
S.J. Lind  
G.A. Luz

D. Michaud  
N.P. Miller  
E.T. Nykaza  
L. Pater  
K.S. Pearsons  
E. Ryherd  
J. Zhang

Suggestions for improvements to this standard will be welcomed. They should be sent to Accredited Standards Committees S3/SC 1, Animal Bioacoustics, and/or S12, Noise, in care of the Standards Secretariat of the Acoustical Society of America, 1305 Walt Whitman Road, Suite 300, Melville, New York 11747. Telephone: 631-390-0215; FAX: 631-923-2875; E-mail: [asastds@acousticalsociety.org](mailto:asastds@acousticalsociety.org).

## Introduction

Currently, no standard method exists for describing or measuring residual sound levels in protected natural areas and quiet residential areas. The main purpose of this standard is to develop procedures to estimate the residual sound levels in an area where these levels are used to evaluate the effects of a noise source, with two examples being wind turbine noise in quiet rural areas and transportation noise in U.S. National Parks and wilderness areas. A second purpose is to develop estimates of the ambient sound in the same or similar settings to those above.

It is desirable that residual sound levels be characterized in units that offer opportunities for comparison with a broad range of available information. The most commonly available noise source data are provided as A-weighted sound levels in decibels.

This standard has been written to reflect the most common measurement conventions and instrumentation, which were designed for application to human noise impacts. Other weighting schemes may ultimately be more efficient for characterizing residual sound levels for other species of animals. This standard is not intended to characterize pristine ambient conditions, or to provide sensitive methods for detecting anthropogenic noise.

A common purpose of residual sound level measurement is to evaluate the projection of a noise source into an area. In this case, one question of interest concerns, in a broad sense, the capacity of residual sounds to “mask,” or inhibit perception of, a noise source. High frequency natural sounds (HFNS)—sounds above the 1 kHz octave band that are significantly above the primary frequencies of the noise source—contribute little to masking. The problem is that these high-frequency sounds can make large contributions to A-weighted sound levels that substantially exaggerate the environment’s capacity to mask most anthropogenic noise sources.

The effects of discarding HFNS from measurements of A-weighted sound levels have been investigated in two settings. The Natural Sounds and Night Skies Division of the National Park Service processed hourly ambient data from 62 sites in 10 national parks. More than 20% of the one-hour-average sound levels were decreased by 3 dB or more when HFNS were excluded. Five percent of the measurements of hourly sound levels were decreased by nearly 6 dB. Spring and summer measurements from sites with high percentages of vegetation coverage showed the greatest differences. Schomer, Slauch, and Hessler (2010) evaluated over 115 community noise octave-band spectra and found the exclusion of high-frequency sounds causes A-weighted sound levels to decrease by less than 1 dB, and that the standard deviation was 0.5 dB or less. Excluding HFNS substantially reduces residual levels in national park and quiet residential settings while having a much smaller effect on measurements of urban noise levels. Annex A reproduces the Schomer *et al.* data showing the average differences and the standard deviation to these differences for various noise sources.

Elimination of the high-frequency sound has two potential additional benefits. First, elimination of all data above the 1 kHz octave band (or in the 1.6 kHz one-third octave band and above) may significantly lower the self-generated electrical noise on the order of 10 dB when compared to the self-generated A-weighted electrical noise floor of a typical Type 1 sound level meter. Annex B contains a detailed analysis of this effect for a typical, well-known Type 1 meter. Second, elimination of all data above the 1 kHz octave band significantly lowers the contributions of the wind-induced noise of rustling leaves and noise flow around the microphone windscreen. This effect is illustrated in Figures B.3 and B.4. As an example, leaf-rustle noise analyzed by Schomer and Beck (2010) has an A-weighted one-third octave-band spectrum that peaks in the 2 to 3.15 kHz range. Elimination of all data above the 1 kHz octave band lowers the resulting measured A-weighted leaf-rustle levels by about 3.5 dB when compared to the equivalent A-weighted measurement—a reduction that is quite consistent with Figure B.4.

## American National Standard

# Methods to Define and Measure the Residual Sound in Protected Natural and Quiet Residential Areas

## 1 Scope

This standard provides basic quantities and procedures for the description of residual sound levels in protected natural areas and quiet residential areas. This information supplements the basic information contained in the American National Standards listed as references. This standard specifies a method to measure residual sound in protected natural areas and quiet residential areas. This standard sets minimum requirements for the instruments used and for the sensitivity checks performed in conjunction with measurements in parks, wilderness areas, and quiet residential areas. This standard defines the A-weighted, noise-compensated (ANS-weighted metric), which is the standard A-weighting filtered to exclude sounds above the 1 kHz octave band.

The resulting data can be used to characterize residual sound levels with respect to anthropogenic noise. Data obtained in quiet residential areas can be used to assess the residual sound in relation to manmade noise sources such as wind turbine generators, compressor stations for pipelines, highways, and airports.

## 2 Normative references

The following referenced documents are indispensable for the application of this standard. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ANSI/ASA S1.1 *American National Standard Acoustical Terminology*

ANSI S1.4-1983 (R 2006) *American National Standard Specification for Sound Level Meters*. This Standard includes ANSI S1.4A-1985 (R 2006) Amendment to ANSI S1.4-1983

ANSI/ASA S1.11-2004 (R 2009) *American National Standard Specification for Octave-Band and Fractional-Octave-Band Analog and Digital Filters*

ANSI/ASA S1.13-2005 (R 2010) *American National Standard Measurement of Sound Pressure Levels in Air*

ANSI/ASA S12.9-2013/Part 1 *American National Standard Quantities and Procedures for Description and Measurement of Environmental Sound - Part 1: Basic Quantities and Definitions*

ANSI/ASA S12.9-1992/Part 2 (R 2013) *American National Standard Quantities and Procedures for Description and Measurement of Environmental Sound - Part 2: Measurement of Long-Term, Wide-Area Sound*

ANSI/ASA S12.9-2013/Part 3 *American National Standard Quantities and Procedures for Description and Measurement of Environmental Sound - Part 3: Short-term Measurements with an Observer Present*

ANSI/ASA S12.18-1994 (R 2009) *American National Standard Procedures for Outdoor Measurement of Sound Pressure Level*