

ANSI S3.4-2007
(Revision of ANSI S3.4-2005)

Reaffirmed by ANSI June 15, 2012, July
13, 2017, and June 5, 2020

AMERICAN NATIONAL STANDARD

**Procedure for the Computation of Loudness
of Steady Sounds**

ANSI S3.4-2007

Accredited Standards Committee S3, Bioacoustics

Standards Secretariat
Acoustical Society of America
35 Pinelawn Road, Suite 114E
Melville, NY 11747-3177

The American National Standards Institute, Inc. (ANSI) is the national coordinator of voluntary standards development and the clearinghouse in the U.S.A. for information on national and international standards.

The Acoustical Society of America (ASA) is an organization of scientists and engineers formed in 1929 to increase and diffuse the knowledge of acoustics and to promote its practical applications.



ANSI S3.4-2007
(Revision of ANSI S3.4-2005)

AMERICAN NATIONAL STANDARD

Procedure for the Computation of Loudness of Steady Sounds

Secretariat
Acoustical Society of America

Approved: May 24, 2007
American National Standards Institute, Inc.

Abstract

This standard specifies a procedure for calculating the monaural and binaural loudness of steady sounds as perceived by listeners with normal hearing. The procedure is based on the spectra of the sounds. The possible sounds include simple and complex tones (both harmonic and inharmonic), bands of noise and mixtures of tones and noise. The spectra can be specified exactly, in terms of the frequencies and levels of individual spectral components, or approximately, in terms of the levels in 1/3 octave bands covering center frequencies from 50 to 16,000 Hz. The standard is applicable to sounds presented in free field with a frontal incidence, in a diffuse field, or listening via headphones. The procedure is available as a computer program that provides the loudness level in phons and the corresponding loudness estimate in sones. Examples of the estimates generated by the program for a variety of input spectra are presented in Annex A. The software for calculation of loudness according to ANSI S3.4-2007 is described in Annex B. It accompanies the standard for the convenience of the purchaser. Use of this software is not required for conformance.

AMERICAN NATIONAL STANDARDS ON ACOUSTICS

The Acoustical Society of America (ASA) provides the Secretariat for Accredited Standards Committees S1 on Acoustics, S2 on Mechanical Vibration and Shock, S3 on Bioacoustics, and S12 on Noise. These committees have wide representation from the technical community (manufacturers, consumers, trade associations, organizations with a general interest, and government representatives). The standards are published by the Acoustical Society of America as American National Standards after approval by their respective Standards Committees and the American National Standards Institute.

These standards are developed and published as a public service to provide standards useful to the public, industry, and consumers, and to Federal, State, and local governments.

Each of the accredited Standards Committees [operating in accordance with procedures approved by American National Standards Institute (ANSI)] is responsible for developing, voting upon, and maintaining or revising its own Standards. The ASA Standards Secretariat administers Committee organization and activity and provides liaison between the Accredited Standards Committees and ANSI. After the Standards have been produced and adopted by the Accredited Standards Committees, and approved as American National Standards by ANSI, the ASA Standards Secretariat arranges for their publication and distribution.

An American National Standard implies a consensus of those substantially concerned with its scope and provisions. Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered and that a concerted effort be made towards their resolution.

The use of an American National Standard is completely voluntary. Their existence does not in any respect preclude anyone, whether he or she has approved the Standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the Standards.

NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this Standard.



Acoustical Society of America
ASA Secretariat
35 Pinelawn Road, Suite 114E
Melville, New York 11747-3177
Telephone: 1 (631) 390-0215
Fax: 1 (631) 390-0217
E-mail: asastds@aip.org

© 2007 by Acoustical Society of America. This standard may not be reproduced in whole or in part in any form for sale, promotion, or any commercial purpose, or any purpose not falling within the provisions of the U.S. Copyright Act of 1976, without prior written permission of the publisher. For permission, address a request to the Standards Secretariat of the Acoustical Society of America.

Contents

1	Scope	1
2	Terms and definitions	1
3	Procedure	3
3.1	Introduction.....	3
3.2	Specification of input signal.....	3
3.3	Transfer function to take into account transfer to the eardrum	4
3.4	Transfer function to take into account transmission through the middle ear	5
3.5	Transformation of spectrum to excitation pattern.....	10
3.6	Transformation from excitation to specific loudness	16
3.7	Summation of specific loudness across frequency	24
3.8	Monaural versus binaural loudness (diotic and dichotic stimuli).....	24
3.9	Conversion from phons to sones	24
3.10	Calculation of absolute threshold.....	24
Annex A	(informative) Sample results using ANSI S3.4-2007	27
A.1	Sinusoidal tones.....	27
A.2	Filtered noise.....	28
A.3	Multiple tones	29
A.4	Tones plus noise	30
Annex B	(informative) Software for calculation of loudness according to ANSI S3.4-2007	31

Tables

Table 1	— Free field to eardrum transfer function (frontal incidence). The first column specifies the frequency (Hz) and the second column specifies the level at the eardrum minus the level measured in the free field (in the absence of a listener), in dB.....	6
Table 2	— Diffuse field to eardrum transfer function. The first column specifies the frequency (Hz) and the second column specifies the level at the eardrum minus the level measured in the diffuse field (in the absence of a listener), in dB.....	8
Table 3	— Transfer function of middle ear. The first column specifies the frequency (Hz) and the second column specifies the effective level at the cochlea, relative to the level at the eardrum, in dB. Values in italics are in a range that has not been validated.	12
Table 4	— Internal excitation level at threshold for monaural listening. The first column shows the center frequency (Hz) and the second column shows the excitation level in dB. The value is constant for all frequencies above 500 Hz.	17
Table 5	— Value of the parameter α (alpha) as a function of the parameter G (dB).....	20
Table 6	— Value of the parameter A as a function of the parameter G (dB).....	21
Table 7	— Relationship between loudness level in phons and loudness in sones. Values in italics are given for completeness, but have not been validated.....	25

Figures

- Figure 1 — Free field to eardrum transfer function. The level at the eardrum minus the level measured in the free field (in the absence of a listener) is plotted as a function of frequency in kHz. 7
- Figure 2 — Diffuse field to eardrum transfer function. The level at the eardrum minus the level measured in the diffuse field (in the absence of a listener) is plotted as a function of frequency in kHz. 9
- Figure 3 — Transfer function of middle ear (dB) plotted as a function of frequency in kHz. The dashed line indicates a range that has not been validated. 13
- Figure 4 — The shape of the auditory filter centered at 1 kHz for input levels/ ERB_N from 20 to 100 dB in 10-dB steps. The output level in dB of the filter is plotted as a function of frequency of the input in kHz. 14
- Figure 5 — Excitation patterns for 1-kHz sinewaves with levels ranging from 20 to 100 dB in 10-dB steps. The frequency scale has been transformed to an ERB_N -number scale, as defined by Equation 4. The lower abscissa shows the ERB_N -number. The corresponding frequency in Hz is shown at the top. 15
- Figure 6 — Internal excitation level at threshold for monaural listening in dB, plotted as a function of center frequency in kHz. The value is constant for all frequencies above 0.5 kHz. 17
- Figure 7 — Value of the parameter α (alpha) as a function of the parameter G (dB)..... 20
- Figure 8 — Value of the parameter A as a function of the parameter G (dB)..... 22
- Figure 9 — The transformation from excitation level in dB to specific loudness, with the excitation level at absolute threshold (E_{THRQ} converted to decibels) as parameter. The curve labeled 3.6 applies for all center frequencies above 500 Hz. Other curves are for values of the excitation level at absolute threshold of 6.3, 14.5, 20.2 and 26.2 dB, corresponding to center frequencies of 253, 108, 74 and 52 Hz, respectively. The dashed line indicates a range, above 100 dB, that has not been validated. 23
- Figure 10 — Value of loudness in sones as a function of the loudness level in phons. The dashed line indicates a range, above 100 phons, that has not been validated..... 26

Foreword

[This Foreword is for information only, and is not a part of the American National Standard ANSI S3.4-2007 American National Standard Procedure for the Computation of Loudness of Steady Sounds.]

This standard comprises a part of a group of definitions, standards, and specifications for use in bioacoustics. It was developed and approved by Accredited Standards Committee S3 Bioacoustics, under its approved operating procedures. Those procedures have been accredited by the American National Standards Institute (ANSI). The Scope of Accredited Standards Committee S3 is as follows:

Standards, specifications, methods of measurement and test, and terminology in the fields of psychological and physiological acoustics, including aspects of general acoustics, which pertain to biological safety, tolerance and comfort.

This standard is a revision of ANSI S3.4-2005, which was in turn a revision of ANSI S3.4-1980. Loudness is the perceived intensity of a sound (see below for definition). Loudness depends on both the acoustic properties of the sound that impinges on a listener and on the listener. This standard gives an estimate of the loudness of steady sounds as perceived by normally hearing listeners under specified conditions. The recommended procedure is based on a model of loudness perception (Moore, Glasberg, and Baer, 1997; Glasberg and Moore, 2006) that was developed from a model originally proposed by Zwicker and his co-workers (1958, 1965, 1984, 1999). Zwicker's model is part of ISO 532:1975. These models have their roots in the pioneering work of Fletcher and Munson (1933). The current procedure extends and improves the accuracy of these earlier methods. It replaces the more limited computational procedure used in the old ANSI S3.4-1980 that was based on the method proposed by S.S. Stevens (1957, 1961). Unlike the old ANSI S3.4-1980, the current standard can be applied to sounds with sharp line spectral components, e.g., transformer hum or fan noise, as well as to sounds with broadband spectra. Provided the measurement of sound pressure levels is sufficiently precise, and subject to certain restrictions specified below, the recommended procedure may also be used to estimate loudness, or loudness level, with reasonable accuracy down to near threshold levels. Moreover, it enables the loudness of complex sounds containing spectral energy below 500 Hz to be determined. The equal-loudness contours derived from this standard are in good agreement with ISO 226:2003 (see also Suzuki and Takeshima, 2004). Because loudness is a subjective quantity, the perception of which may vary among people, any calculated loudness value represents only an estimate of the average loudness as perceived by a group of individuals with normal hearing.

The changes made in this revision are: (1) A modification to the method for calculating specific loudness from excitation for center frequencies below 500 Hz to make the standard fully compatible with the provided software and with the model of Moore et al. (1997) and with its amendment by Glasberg and Moore (2006); (2) A modification to the transfer function of the middle ear, as proposed by Glasberg and Moore (2006), which allows more accurate predictions of the absolute thresholds in ISO 389-7:2005 and of the equal-loudness contours in ISO 226:2003.

The software provided with this American National Standard is entirely informative and provided for the convenience of the user. Use of the provided software is not required for conformance with the Standard.

ASA and the owners of the copyright to the software provided with this American National Standard make no other representation or warranty or condition of any kind, whether express or implied (either in fact or by operation of law) with respect to any part of the product, including, without limitation, with respect to the sufficiency, accuracy or utilization of, or any information or opinion contained or reflected in, any of the product. ASA and the owner expressly disclaim all warranties or conditions of merchantability or fitness for a particular purpose. No officer, director, employee, member, agent,

representative or publisher of the copyright holder is authorized to make any modification, extension, or addition to this limited warranty.

At the time this Standard was submitted to Accredited Standards Committee S3, Bioacoustics for approval, the membership was as follows:

C.A. Champlin, *Chair*

R.F. Burkard, *Vice-Chair*

S.B. Blaeser, *Secretary*

Acoustical Society of America	C.A. Champlin
.....	R.F. Burkard (Alt.)
American Academy of Audiology	Y. Szymko-Bennett
.....	D.A. Fabry (Alt.)
American Academy of Otolaryngology, Head and Neck Surgery, Inc.	R.A. Dobie
.....	L.A. Michael (Alt.)
American Industrial Hygiene Association	T.K. Madison
.....	D. Driscoll (Alt.)
American-Speech-Language-Hearing Association (ASHA)	L.A. Wilber
.....	V. Gladstone (Alt.)
Beltone/GN Resound	S. Petrovic
Council for Accreditation in Occupational Hearing Conservation (CAOHC)	E.H. Berger
.....	J.A. Mann (Alt.)
Etymotic Research, Inc.	M.C. Killion
.....	R. Scicluna (Alt.)
Food and Drug Administration	J. Kane
Frye Electronics, Inc.	G.J. Frye
.....	K.E. Frye (Alt.)
Hearing Industries Association	T.A. Victorian
.....	C.M. Rogin (Alt.)
National Hearing Conservation Association	T. Schulz
National Institute for Occupational Safety and Health	M. Stephenson
.....	W.J. Murphy (Alt.)
National Institute of Standards and Technology	V. Nedzelnitsky
.....	R. Wagner (Alt.)
Quest Technologies, Inc.	M. Wurm
.....	P. Battenberg (Alt.)
Starkey Laboratories	D.A. Preves
.....	T. Burns (Alt.)

U.S. Air Force R. McKinley

U.S. Army Aeromedical Research Lab W. Ahroon

U.S. Army Construction Engineering Research Laboratories L. Pater
..... D. Delaney (Alt.)

U.S. Army Human Research & Engineering Directorate T.R. Letowski
..... P. Henry (Alt.)

Individual Experts of the Accredited Standards Committee S3, Bioacoustics, were:

J.R. Bareham	T. Frank	P.D. Schomer
A.J. Brammer	K.D. Kryter	L.A. Wilber
A.J. Campanella	R. McKinley	W.A. Yost

Working Group S3/WG 51, Auditory Magnitudes, which assisted Accredited Standards Committee S3, Bioacoustics, in the development of this standard, had the following membership.

	R.P. Hellman, Chair	
A.J. Campanella	B.R. Glasberg	B. Scharf
P. Davies	T.R. Letowski	R.S. Schlauch
	B.C.J. Moore	

Suggestions for improvements of this standard will be welcomed. They should be sent to Accredited Standards Committee S3, Bioacoustics, in care of the Standards Secretariat of the Acoustical Society of America, 35 Pinelawn Road, Suite 114E, Melville, New York 11747-3177. Telephone: 631-390-0215; FAX: 631-390-0217; E-mail: asastds@aip.org

This is a preview of "ANSI/ASA S3.4-2007 (...". [Click here to purchase the full version from the ANSI store.](#)

American National Standard

Procedure for the Computation of Loudness of Steady Sounds

1 Scope

This standard specifies a procedure for calculating the monaural and binaural loudness experienced by listeners with normal hearing under the following conditions:

1.1. Listening conditions. The standard applies to three listening conditions: free field with a frontal incidence, diffuse field, or listening via headphones. Listening in a free field with a frontal incidence is assumed when the sound source is located at least one meter directly in front of the listener and there are no space boundaries or other surfaces that affect the sound field. The free-field condition can be achieved in an anechoic chamber or in open space. Listening in a diffuse field is assumed when the sound reaches the listener's ears from all directions with essentially the same acoustic power. The sound field in a room with hard reflective walls where the sound is reflected many times before being significantly absorbed approximates a diffuse field. Listening through headphones is assumed when the sound is delivered directly to the listener's ears through circumaural or supra-aural headphones, or insert earphones. For simplicity, the term headphones will be used hereafter to denote both headphones and earphones.

NOTE 1 The equal-loudness contour for narrow-band noise in a free field differs from that in the diffuse field, but the difference measured at 1/3-octave-band center frequencies varies from -2.0 to +4.3 decibels with the mean difference equal to only 0.8 decibels. These differences do not significantly affect calculations for broadband spectra. Nevertheless, since the loudness of a sound depends on the nature of the enclosure in which it is heard, comparative evaluations of different sources should be based on measurements all made in essentially similar enclosures or all made in a free sound field.

NOTE 2 Pressure levels in a diffuse field should be measured by means of an omnidirectional microphone located in the unobstructed sound field at the position corresponding to the center of the listener's head.

1.2 Spectrum. The computational procedure described in the standard applies to a variety of sounds including complex tones, noise bands, and mixtures of the two. The characteristics of the sounds are specified in terms of their spectra. The procedure applies to sounds with a frequency range that extends from 20 Hz to 18,000 Hz. However, the procedure may not give accurate estimates of loudness for sounds with strong components above 12,500 Hz, and perceived loudness for such sounds is likely to vary markedly across individuals.

1.3 Steady state. The procedure described in the standard applies to steady state sounds and should not be used for impulse sounds or intermittent sounds. Application to such sounds may lead to discrepancies between measured and calculated loudness levels. The magnitude of the discrepancy is related to the dynamic characteristics of the device used to determine the sound pressure levels.

2 Terms and definitions

For the purposes of this standard, the terms and definitions given in ANSI S1.1-1994 and ANSI S3.20-1995 and the following apply: