

**ANSI S2.70-2006**  
**(Revision of ANSI S3.34-1986)**

---

---

---

**AMERICAN NATIONAL STANDARD**

**Guide for the Measurement and Evaluation of Human  
Exposure to Vibration Transmitted to the Hand**

---

---

---

**ANSI S2.70-2006**  
**(Revision of ANSI S3.34-1986)**

**Accredited Standards Committee S2, Mechanical Vibration and Shock**

---

Standards Secretariat  
Acoustical Society of America  
35 Pinelawn Road, Suite 114 E  
Melville, NY 11747-3177

The American National Standards Institute, Inc. (ANSI) is the national coordinator of voluntary standards development and the clearinghouse in the U.S.A. for information on national and international standards.

The Acoustical Society of America (ASA) is an organization of scientists and engineers formed in 1929 to increase and diffuse the knowledge of acoustics and to promote its practical applications.



**ANSI S2.70-2006**  
(Revision of ANSI S3.34-1986)

AMERICAN NATIONAL STANDARD

**Guide for the Measurement and Evaluation of  
Human Exposure to Vibration  
Transmitted to the Hand**

**Secretariat**

**Acoustical Society of America**

**Approved 19 May 2006**

**American National Standards Institute, Inc.**

**Abstract**

This standard specifies the recommended method for the measurement, data analysis, vibration and health risk assessments, and reporting of human exposure to hand-transmitted vibration. A standard format is established for measurement, data analysis, vibration and health risk assessments, and reporting of hand-transmitted vibration, periodic or random, in three orthogonal axes, in the frequency range from 5.6 Hz to 1,400 Hz. Three normative annexes provide guidance for vibration and health risk assessments, mitigating health risks, training, and medical surveillance related to hand-transmitted vibration.

## AMERICAN NATIONAL STANDARDS ON ACOUSTICS

The Acoustical Society of America (ASA) provides the Secretariat for Accredited Standards Committees S1 on Acoustics, S2 on Mechanical Vibration and Shock, S3 on Bioacoustics, and S12 on Noise. These committees have wide representation from the technical community (manufacturers, consumers, trade associations, organizations with a general interest, and government representatives). The standards are published by the Acoustical Society of America as American National Standards after approval by their respective Standards Committees and the American National Standards Institute.


These standards are developed and published as a public service to provide standards useful to the public, industry, and consumers, and to Federal, State, and local governments.

Each of the accredited Standards Committees [operating in accordance with procedures approved by American National Standards Institute (ANSI)] is responsible for developing, voting upon, and maintaining or revising its own Standards. The ASA Standards Secretariat administers Committee organization and activity and provides liaison between the Accredited Standards Committees and ANSI. After the Standards have been produced and adopted by the Accredited Standards Committees and approved as American National Standards by ANSI, the ASA Standards Secretariat arranges for their publication and distribution.

An American National Standard implies a consensus of those substantially concerned with its scope and provisions. Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered and that a concerted effort be made towards their resolution.

The use of an American National Standard is completely voluntary. Their existence does not in any respect preclude anyone, whether he or she has approved the Standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the Standards.

NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this Standard.



Acoustical Society of America  
ASA Secretariat  
35 Pinelawn Road, Suite 114E  
Melville, New York 11747-3177  
Telephone: 1 (631) 390-0215  
Fax: 1 (631) 390-0217  
E-mail: [asastds@aip.org](mailto:asastds@aip.org)

© 2006 by Acoustical Society of America. This standard may not be reproduced in whole or in part in any form for sale, promotion, or any commercial purpose, or any purpose not falling within the provisions of the U.S. Copyright Act of 1976, without prior written permission of the publisher. For permission, address a request to the Standards Secretariat of the Acoustical Society of America.

## Contents

1	Scope .....	1
2	Normative references.....	1
3	Terms and definitions.....	2
4	Symbols .....	2
5	General considerations .....	3
6	Characterization of hand-transmitted vibration exposure .....	4
6.1	Magnitude of vibration.....	4
6.2	Frequency spectrum of vibration.....	4
6.3	Direction of vibration .....	7
6.4	Daily vibration exposure.....	7
7	Measurement of hand-arm vibration.....	8
8	Information to be reported.....	8
Annex A	Vibration exposure and health risk assessments .....	11
A.1	Daily exposure action and limit values.....	11
A.2	Vibration exposure assessment.....	12
A.3	Health risk assessment.....	12
Annex B	Mitigating health risks associated with hand-transmitted vibration exposure.....	14
B.1	Guidelines to avoid or reduce potential health risks .....	14
B.2	Low vibration tools and personal protective equipment.....	14
Annex C	Training and medical surveillance .....	15
C.1	Training .....	15
C.2	Health surveillance.....	15

## Tables

Table 1 — ISO frequency-weighting factors,  $W_{hi}$ , for hand-transmitted vibration for conversion of one-third octave band magnitudes to ISO frequency-weighted magnitudes .....5

## Figures

Figure 1 — Coordinate system for the hand. The origin of the system lies in the head of the third metacarpal, and the  $z_{(hand)}$  axis is defined by the longitudinal axis of that bone. The  $x$  axis projects forward from the origin when the hand is in the normal anatomical position (palm facing forward). The  $y$  axis passes through the origin and is perpendicular to the  $x$  axis. When the hand is gripping a cylindrical handle, the coordinate system shall be rotated so that the  $y_h$  axis is parallel to the axis of the handle. (a) "Handgrip" position. In this position, the hand adopts a standardized grip on a cylindrical bar of radius 2 cm. (b) "Flat palm" position. In this position, the hand presses down onto a spherical surface of radius 5 cm. ....6

Figure A.1 — Plots of the  $a_{hv(DEAV)}$  and  $a_{hv(DELV)}$  values for vibration exposure times other than 8 hours12

Figure A.2 — Plot of  $D_y$  as a function of the daily vibration exposure value,  $A(8)$  .....13

## Foreword

[This Foreword is for information only and is not a part of the American National Standard ANSI S2.70-2006 American National Standard Guide for the Measurement and Evaluation of Human Exposure to Vibration Transmitted to the Hand.]

This standard comprises a part of a group of definitions, standards, and specifications for use in mechanical vibration and shock. It was developed and approved by Accredited Standards Committee S2, Mechanical Vibration and Shock, under its approved operating procedures. Those procedures have been accredited by the American National Standards Institute (ANSI). The Scope of Accredited Standards Committee S2 is as follows:

*Standards, specifications, methods of measurement and test, and terminology in the field of mechanical vibration and shock and condition monitoring and diagnostics of machines, including the effects of exposure to mechanical vibration and shock on humans, including those aspects which pertain to biological safety, tolerance, and comfort.*

This standard is a revision of ANSI S3.34-1986 (R 1997), which has been technically revised. The revisions incorporated into this standard make the measurement and data analysis procedures of the standard compatible with the corresponding procedures specified in ISO 5349 – Part 1 and ISO 5349 – Part 2. Vibration and health risks assessment procedures, methods for mitigating the potential for workers developing symptoms related to hand-arm vibration syndrome (HAVS), and training and medical surveillance guidelines have been added to this standard.

This standard is not comparable to any existing ISO Standard.

At the time this Standard was submitted to Accredited Standards Committee S2, Mechanical Vibration and Shock, for approval, the membership was as follows:

R.J. Peppin, *Chair*

D.J. Evans, *Vice-Chair*

S.B. Blaeser, *Secretary*

<b>Acoustical Society of America</b> .....	S.I. Hayek
.....	B.E. Douglas (Alt.)
<b>Acquip, Inc.</b> .....	D. Josefsberg
<b>American Industrial Hygiene Association</b> .....	J.J. Earshen
.....	D. Driscoll (Alt.)
<b>Association of American Railroads</b> .....	J. Moller
.....	N. Cooperrider (Alt.)
<b>BJM Corp.</b> .....	W. Kruger

<b>Bruel &amp; Kjaer Instruments, Inc.</b> .....	M. Alexander J. Chou (Alt.)
<b>Calnetix</b> .....	L. Hawkins P. McMullen (Alt.)
<b>Caterpillar, Inc.</b> .....	D. Roley K.G. Meitl (Alt.)
<b>Emerson Electric – Copeland Corporation</b> .....	A.T. Herfat M. Mezache (Alt.)
<b>Endevco</b> .....	B. Yang
<b>GE Energy</b> .....	R. Bankert
<b>Infrared Training Center</b> .....	G. Orlove R. Madding (Alt.)
<b>International Council for Machinery Lubrication</b> .....	J. Fitch D. Troyer (Alt.)
<b>John Deere</b> .....	L. DeVries
<b>Lord Corporation</b> .....	L. Miller A. Crockett (Alt.)
<b>Mechanical Solutions, Inc.</b> .....	W.D. Marscher M. Gaydon (Alt.)
<b>MIMOSA</b> .....	K. Bever A. Johnston (Alt.)
<b>National Institute for Occupational Safety &amp; Health</b> .....	R.G. Dong N.K. Kittusamy (Alt.)
<b>National Institute of Standards &amp; Technology</b> .....	D.J. Evans S. Fick (Alt.)
<b>PCB Group</b> .....	R.D. Sill D. Lally (Alt.)
<b>Power Tool Institute, Inc.</b> .....	W.D. Spencer M. Hickok (Alt.)
<b>Quest Technologies, Inc.</b> .....	M. Wurm P. Battenberg (Alt.)
<b>Sandia National Laboratory</b> .....	V.I. Bateman T.S. Edwards (Alt.)
<b>Shock and Vibration Information and Analysis Center</b> .....	J. Leifer
<b>Scantek</b> .....	R.J. Peppin M. Buzduga (Alt.)
<b>Schenck Trebel Corp.</b> .....	B. Dittmar
<b>Snell Infrared</b> .....	J. Snell

<b>Society for Machinery Failure Prevention Technology</b> .....	A.J. Hess
.....	H.A. Gaberson (Alt.)
<b>T Solutions</b> .....	H. Penrose
<b>U.S. Air Force</b> .....	S.D. Smith
<b>U.S. Department of Transportation</b> .....	B. Marquis
.....	T. Raslear (Alt.)
<b>U.S. Naval Sea Systems Command</b> .....	R. Taddeo
.....	M.T. McGown (Alt.)
<b>U.S. Naval Surface Warfare Center</b> .....	P. Shang
.....	S. Antonides (Alt.)
<b>UE Systems, Inc.</b> .....	M. Goodman
<b>Vibration Institute</b> .....	R. Eshleman
.....	D.J. Vendittis (Alt.)
<b>Waukesha Magnetic Bearings</b> .....	K. Bornstein
.....	R. Shultz (Alt.)

Individual Experts of Accredited Standards Committee S2, Mechanical Vibration and Shock, were:

L.A. Herstein                      D.F. Muster

Working Group S2/WG 39, Human Exposure to Mechanical Vibration and Shock, which assisted Accredited Standards Committee S2, Mechanical Vibration and Shock, in the development of this standard, had the following membership.

D.D. Reynolds, Chair  
R.G. Dong, Vice Chair

N. Alem	B. Marquis	D.E. Wasserman
M. Cherniack	W. Pielemeier	J. Wasserman
N. Cooperrider	D. Roley	D. Wilder
L. DeVries	S.D. Smith	
T. Jetzer	E.D. Sussman	

Suggestions for improvements of this standard will be welcomed. They should be sent to Accredited Standards Committee S2, Mechanical Vibration and Shock, in care of the Standards Secretariat of the Acoustical Society of America, 35 Pinelawn Road, Suite 114E, Melville, New York 11747-3177. Telephone: 631-390-0215; FAX: 631-390-0217; E-mail: [asastds@aip.org](mailto:asastds@aip.org)

## Introduction

Intense vibration can be transmitted from hand-held percussive or vibrating devices, tools, and work pieces to the hands and arms of the user. Such situations occur when a person uses pneumatically, hydraulically, and electrically powered percussive tools (i.e., chipping hammers, needle scalars, impact wrenches, etc.); pneumatically, hydraulically, and electrically powered grinders and sanders; gasoline powered tools (i.e., chain saws, circular saws, edge trimmers, etc.); and pedestal grinders. These vibrations are usually transmitted through the hand to the arm and shoulder. Depending on individual work practices and work situations, this vibration can be transmitted to one hand only or to both hands simultaneously. Continued habitual use of some types of hand-held vibrating devices, tools, and work pieces has been found under certain circumstances to be associated with patterns of diseases affecting the hand and arm. The patterns of various symptoms observed have been called vibration disease, vibration syndrome, vibration white finger (VWF), or Raynaud's phenomenon of occupational origin. These disorders have been grouped into a single syndrome referred to as the hand-arm vibration syndrome (HAVS). Hand-arm vibration may also cause entrapment syndromes, such as carpal tunnel syndrome, as well as other upper extremity cumulative trauma disorders (CTDs). For the purpose of this standard, hand-transmitted vibration is defined as *the mechanical vibration that, when transmitted to the human hand-arm system, may entail risks to worker health and safety, in particular vascular, bone or joint, neurological, and muscular.*

The International Organization for Standardization (ISO) has developed two international standards: (1) ISO 5349 – Part 1 and (2) ISO 5349 – Part 2. The appendices in ISO 5349 – Part 1 give specific guidance on the health effects related to hand-transmitted vibration, the relationship between vibration exposure and effects on health, factors likely to influence the effects of human exposure to hand-transmitted vibration in working conditions, and preventative measures to be adopted to reduce the potential for developing symptoms related to HAVS. ISO 5349 – Part 2 gives specific guidelines on how to make vibration measurements on hand-held vibrating and percussive tools. The user of this standard is, therefore, directed to these ISO standards for specific guidance in these areas.

The Parliament of the European Union has issued the European Union Human Vibration Directive-2002/44/EC. This directive specifies vibration daily exposure action values (DEAV) of  $2.5 \text{ m/s}^2$  and daily exposure limit values (DELV) of  $5.0 \text{ m/s}^2$  that, when achieved, will reduce the potential for users of hand-held vibrating and percussive devices, tools, and work pieces to develop symptoms related to HAVS. The DEAV and DELV specified in the EU human vibration directive have generally been accepted by medical experts, scientists, and engineers in governmental agencies, research institutions, and industry in the USA and other countries.

The guidance provided in this standard and its annexes are intended to assist in reducing the potential for the occurrences of HAVS and other related hand-arm vibration disorders among persons who work with hand-held vibrating and percussive devices, tools and work pieces. Many factors affect the potential for an individual to develop symptoms related to HAVS. Because the subjective symptoms and objective clinical findings associated with HAVS are similar to the pathology arising from other causes, it is imperative that a proper differential diagnosis be performed on workers who display pathology related to HAVS by a physician with qualifications and experience in differential diagnosis of hand-arm syndromes and diseases.

## American National Standard

# Guide for the Measurement and Evaluation of Human Exposure to Vibration Transmitted to the Hand

## 1 Scope

**1.1** This standard specifies the recommended method for the measurement, data analysis and evaluation, vibration and health risk assessments, and reporting of hand-transmitted vibration exposure. The methods specified in this standard are to be used to characterize and evaluate vibration impinging on the hands of humans and to give guidance on assessing the potential for this vibration to result in pathology related to hand-arm vibration exposure among the users of hand-held percussive or vibrating devices, tools, and work pieces. Factors, such as grip and push forces applied to tool handles, orientation of the hands and tool relative to a specific work piece, and intermittency of vibration exposure that can affect one's exposure to hand-transmitted vibration are not addressed in this standard.

**1.2** Prolonged excessive exposure to hand-transmitted vibration may result in adverse health effect, such as hand-arm vibration syndrome (HAVS) and other conditions of the upper extremities, such as carpal tunnel syndrome. For the purpose of this standard, hand-arm vibration syndrome is defined as *the complex of peripheral vascular, neurological, and musculoskeletal disorders of the hand and arm that are associated with industrial exposure to hand-transmitted vibration.*

**1.3** This standard is intended as a guide for the measurement, data analysis and evaluation, vibration and health risk assessments, and reporting of human exposure to vibration transmitted to the hands, with a view toward reducing the potential for the occurrence of pathology related to hand-arm vibration exposure among the users of hand-held percussive or vibrating devices, tools, and work pieces.

**1.4** The methods of measurement, data analysis, evaluation, assessments, and reporting apply to periodic or random hand-transmitted vibration in three mutually orthogonal axes in the frequency range from 5.6 Hz to 1,400 Hz. The information presented in this standard applies only to vibration exposure from hand-held devices, tools, and work pieces used in industrial work processes that involve the use of hand-held devices, tools, and work pieces.

## 2 Normative references

The following referenced documents are indispensable for the application of this standard. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ANSI S1.11 *American National Standard Octave, Half-Octave, and Third-Octave Band Filter Sets.*

ANSI S2.1/ISO 2041 *American National Standard Vibration and Shock—Vocabulary.*

ISO 5349-1 *Mechanical Vibration – Measurement and Evaluation of Human Exposure to Hand-Transmitted Vibration – Part 1: General Requirements.*