

ASME/CSA Standard

ASME A112.18.6-2009/CSA B125.6-09
Flexible water connectors



®Registered trade-mark of Canadian Standards Association

Contents

ASME Standards Committee on Plumbing Materials and Equipment v

ASME Project Team 18.6 — Flexible Water Connectors vii

CSA Technical Committee on Plumbing Fittings ix

ASME/CSA Joint Harmonization Task Group on Plumbing Fittings xii

Preface xiii

1 Scope 1

2 Reference publications 1

3 Definitions 2

4 General requirements 2

- 4.1 Materials 2
- 4.2 Coatings 3
- 4.3 Connections 3
 - 4.3.1 General 3
 - 4.3.2 Pipe threads 3
 - 4.3.3 Hose end threads 3
 - 4.3.4 Fill valve threads 3
 - 4.3.5 Solder connections 3
 - 4.3.6 Flare connections 3
 - 4.3.7 Compression connections 3
 - 4.3.8 Push-fit fittings 4
 - 4.3.9 Alternate connections 4
- 4.4 Water heater flexible connectors 4
- 4.5 Working pressure 4
- 4.6 Working temperature 4

5 Performance requirements and test methods 4

- 5.1 General 4
- 5.2 Intermittent impulse pressure test 4
 - 5.2.1 Performance 4
 - 5.2.2 Procedure 4
- 5.3 Burst pressure test 5
 - 5.3.1 Performance 5
 - 5.3.2 Procedure 5
- 5.4 Pressure drop test 5
 - 5.4.1 Performance 5
 - 5.4.2 Set-up 5
 - 5.4.3 Procedure 5
- 5.5 Torque test 5

6 Markings 5

Annexes

A (informative) — Exposure to aqueous chloramine 7

B (informative) — Unit conversion criteria 8

Tables

1 — Maximum pressure drop for flexible connectors 6