ASME B18.2.6M-2012

[Revision, redesignation, and consolidation of ASME B18.2.3.7M-1979 (R2006) and ASME B18.2.4.6M-2010]

Metric Fasteners for Use in Structural Applications

AN AMERICAN NATIONAL STANDARD



ASME B18.2.6M-2012

[Revision, redesignation, and consolidation of ASME B18.2.3.7M-1979 (R2006) and ASME B18.2.4.6M-2010]

Metric Fasteners for Use in Structural Applications

AN AMERICAN NATIONAL STANDARD



Date of Issuance: March 23, 2012

This Standard will be revised when the Society approves the issuance of a new edition.

ASME issues written replies to inquiries concerning interpretations of technical aspects of this Standard. Periodically certain actions of the ASME B18 Committee may be published as Cases. Cases and interpretations are published on the ASME Web site under the Committee Pages at http://cstools.asme.org/ as they are issued.

Errata to codes and standards may be posted on the ASME Web site under the Committee Pages to provide corrections to incorrectly published items, or to correct typographical or grammatical errors in codes and standards. Such errata shall be used on the date posted.

The Committee Pages can be found at http://cstools.asme.org/. There is an option available to automatically receive an e-mail notification when errata are posted to a particular code or standard. This option can be found on the appropriate Committee Page after selecting "Errata" in the "Publication Information" section.

ASME is the registered trademark of The American Society of Mechanical Engineers.

This code or standard was developed under procedures accredited as meeting the criteria for American National Standards. The Standards Committee that approved the code or standard was balanced to assure that individuals from competent and concerned interests have had an opportunity to participate. The proposed code or standard was made available for public review and comment that provides an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

ASME does not "approve," "rate," or "endorse" any item, construction, proprietary device, or activity.

ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable letters patent, nor assumes any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representative(s) or person(s) affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

ASME accepts responsibility for only those interpretations of this document issued in accordance with the established ASME procedures and policies, which precludes the issuance of interpretations by individuals.

No part of this document may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

The American Society of Mechanical Engineers Three Park Avenue, New York, NY 10016-5990

Copyright © 2012 by THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS All rights reserved Printed in U.S.A.

CONTENTS

rore	eword	1V
Con	nmittee Roster	V
Cor	respondence With the B18 Committee	vi
1	Introduction	1
2	Metric Heavy Hex Structural Bolts: ASTM A325M and ASTM A490M	2
3	Metric Heavy Hex Nuts: ASTM A563M	5
4	Metric Hardened Steel Washers: ASTM F436M	6
5	Metric Compressible Washer-Type Direct Tension Indicators: ASTM F959M	7
Tabl	les	
1	Dimensions of Metric Heavy Hex Structural Bolts	2
2	Maximum Grip Gaging Lengths and Minimum Body Lengths for Metric Heavy	
	Hex Structural Bolts	4
3	Dimensions of Metric Heavy Hex Nuts for Use With Structural Bolts	6 7
4	Dimensions of Metric Hardened Steel Circular and Circular Clipped Washers	7
5	Dimensions for Metric Compressible Washer-Type Direct Tension Indicators	8