

ASME B31G-2012
(Revision of ASME B31G-2009)

Manual for Determining the Remaining Strength of Corroded Pipelines

**Supplement to ASME B31 Code for
Pressure Piping**

AN AMERICAN NATIONAL STANDARD



**The American Society of
Mechanical Engineers**

ASME B31G-2012
(Revision of ASME B31G-2009)

Manual for Determining the Remaining Strength of Corroded Pipelines

**Supplement to ASME B31 Code for
Pressure Piping**

AN AMERICAN NATIONAL STANDARD



**The American Society of
Mechanical Engineers**

Three Park Avenue • New York, NY • 10016 USA

Date of Issuance: October 24, 2012

The next edition of this Manual is scheduled for publication in 2015.

ASME issues written replies to inquiries concerning interpretations of technical aspects of this Manual. Periodically certain actions of the ASME B31 Committee may be published as Code Cases. Code Cases and interpretations are published on the ASME Web site under the Committee Pages at <http://cstools.asme.org/> as they are issued.

Errata to codes and standards may be posted on the ASME Web site under the Committee Pages to provide corrections to incorrectly published items, or to correct typographical or grammatical errors in codes and standards. Such errata shall be used on the date posted.

The Committee Pages can be found at <http://cstools.asme.org/>. There is an option available to automatically receive an e-mail notification when errata are posted to a particular code or standard. This option can be found on the appropriate Committee Page after selecting "Errata" in the "Publication Information" section.

ASME is the registered trademark of The American Society of Mechanical Engineers.

This Manual was developed under procedures accredited as meeting the criteria for American National Standards. The Standards Committee that approved the Manual was balanced to assure that individuals from competent and concerned interests have had an opportunity to participate. The proposed Manual was made available for public review and comment that provides an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

ASME does not "approve," "rate," or "endorse" any item, construction, proprietary device, or activity.

ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable letters patent, nor assumes any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representative(s) or person(s) affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

ASME accepts responsibility for only those interpretations of this document issued in accordance with the established ASME procedures and policies, which precludes the issuance of interpretations by individuals.

No part of this document may be reproduced in any form,
in an electronic retrieval system or otherwise,
without the prior written permission of the publisher.

The American Society of Mechanical Engineers
Three Park Avenue, New York, NY 10016-5990

Copyright © 2012 by
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS
All rights reserved
Printed in U.S.A.

CONTENTS

Foreword	iv
Committee Roster	v
Correspondence With the B31 Committee	vi
Summary of Changes	vii
1 Introduction	1
2 Evaluation Methods	6
3 Tables of Allowable Length of Corrosion	8
Figures	
1.12-1 Corrosion Pit Interaction Distances	5
1.13-1 Helically Oriented Corrosion Pattern	5
2.1-1 Corrosion Parameters Used in Analysis	7
Tables	
3-1 Values of <i>L</i> for Pipe Sizes \geq NPS 2 and $<$ NPS 6	9
3-1M Values of <i>L</i> for Pipe Sizes \geq 60 mm and $<$ 168 mm O.D.	9
3-2 Values of <i>L</i> for Pipe Sizes \geq NPS 6 and $<$ NPS 10	10
3-2M Values of <i>L</i> for Pipe Sizes \geq 168 mm and $<$ 273 mm O.D.	11
3-3 Values of <i>L</i> for Pipe Sizes \geq NPS 10 and $<$ NPS 16	12
3-3M Values of <i>L</i> for Pipe Sizes \geq 273 mm and $<$ 406 mm O.D.	13
3-4 Values of <i>L</i> for Pipe Sizes \geq NPS 16 and $<$ NPS 20	14
3-4M Values of <i>L</i> for Pipe Sizes \geq 406 mm and $<$ 508 mm O.D.	15
3-5 Values of <i>L</i> for Pipe Sizes \geq NPS 20 and $<$ NPS 24	16
3-5M Values of <i>L</i> for Pipe Sizes \geq 508 mm and $<$ 610 mm O.D.	17
3-6 Values of <i>L</i> for Pipe Sizes \geq NPS 24 and $<$ NPS 30	18
3-6M Values of <i>L</i> for Pipe Sizes \geq 610 mm and $<$ 762 mm O.D.	19
3-7 Values of <i>L</i> for Pipe Sizes \geq NPS 30 and $<$ NPS 36	20
3-7M Values of <i>L</i> for Pipe Sizes \geq 762 mm and $<$ 914 mm O.D.	21
3-8 Values of <i>L</i> for Pipe Sizes \geq NPS 36 and $<$ NPS 42	22
3-8M Values of <i>L</i> for Pipe Sizes \geq 914 mm and $<$ 1 066 mm O.D.	23
3-9 Values of <i>L</i> for Pipe Sizes \geq NPS 42 and $<$ NPS 48	24
3-9M Values of <i>L</i> for Pipe Sizes \geq 1 066 mm and $<$ 1 219 mm O.D.	27
3-10 Values of <i>L</i> for Pipe Sizes \geq NPS 48 and $<$ NPS 52	30
3-10M Values of <i>L</i> for Pipe Sizes \geq 1 219 mm and $<$ 1 320 mm O.D.	33
3-11 Values of <i>L</i> for Pipe Sizes \geq NPS 52 and $<$ NPS 56	36
3-11M Values of <i>L</i> for Pipe Sizes \geq 1 320 mm and $<$ 1 422 mm O.D.	39
3-12 Values of <i>L</i> for Pipe Sizes \geq NPS 56 Through NPS 60	42
3-12M Values of <i>L</i> for Pipe Sizes \geq 1 422 mm Through 1 524 mm O.D.	45