

ASME TR A17.1-8.4-2013
(Technical Report)

Guide for Elevator Seismic Design



**The American Society of
Mechanical Engineers**

ASME TR A17.1-8.4-2013
(Technical Report)

Guide for Elevator Seismic Design



**The American Society of
Mechanical Engineers**

Two Park Avenue • New York, NY • 10016 USA

Date of Issuance: March 31, 2014

This Technical Report will be revised when the Society approves the issuance of a new edition.

ASME is the registered trademark of The American Society of Mechanical Engineers.

ASME does not "approve," "rate," or "endorse" any item, construction, proprietary device, or activity.

ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable letters patent, nor assumes any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representative(s) or person(s) affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

No part of this document may be reproduced in any form,
in an electronic retrieval system or otherwise,
without the prior written permission of the publisher.

The American Society of Mechanical Engineers
Two Park Avenue, New York, NY 10016-5990

Copyright © 2014 by
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS
All rights reserved
Printed in U.S.A.

CONTENTS

| | |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| Foreword | iv |
| Committee Roster | v |
| Part 1 | |
| Modification of ASME A17.1-2010, Section 8.4, Elevator Safety Requirements | |
| for Seismic Risk Zone 2 or Greater | 1 |
| Part 2 | |
| Derivations | 13 |
| Part 3 | |
| Sample Calculations | 23 |
| Figures | |
| 1-2-1 | Seismic Zone Map..... 2 |
| 1-3.1.2-1 | Building Base Designation and Associated Variables..... 4 |
| 2-2-1 | Sample Counterweight Force Diagram |
| 2-4.1-1 | Rail Force Free Body Diagrams for A17.1/B44..... 14 |
| 2-5.1-1 | Rail Force Free Body Diagrams for IBC/NBCC |
| 3-1.5.1-1 | SBC 1994, Fig. 1607.1.5B, Contour Map of Effective Peak Velocity-Related Acceleration Coefficient, A_v |
| 3-3.1.4-1 | A17.1/B44, Fig. 8.4.8.2-4, 22.5 kg/m (15 lb/ft) Guide-Rail Bracket Spacing (Marked for Sample Calculation 3a) |
| 3-3.1.5-1 | A17.1/B44, Fig. 2.23.4.1-1 (Marked for Sample Calculation 3a) |
| 3-3.2.4-1 | A17.1/B44, Fig. 8.4.8.2-4, 22.5 kg/m (15 lb/ft) Guide-Rail Bracket Spacing (Marked for Sample Calculation 3b) |
| 3-6.1.4-1 | A17.1/B44, Fig. 8.4.8.2-4, 22.5 kg/m (15 lb/ft) Guide-Rail Bracket Spacing (Marked for Sample Calculation 3a) |
| 3-6.1.5-1 | A17.1/B44, Fig. 2.23.4.1-1 (Marked for Sample Calculation 3a) |
| Tables | |
| 1-3.1.3-1 | Geographic Impact Comparison: IBC/NBCC Versus A17.1/B44 Seismic Zone 3 (Guide Rail) .. |
| 1-3.1.3-2 | Impact of IBC/NBCC Forces on Elevator Components in U.S. and Canada (Comparison of IBC/NBCC Forces to A17.1/B44 Seismic Zone 3)..... |
| 1-4-1 | IBC/ASCE 7 Seismic Parameters Correlation to A17.1 Zones |
| Mandatory Appendix | |
| I Sample Calculation Figures | 51 |