

ASME Y14.46-2017

Draft Standard for Trial Use

Product Definition for Additive Manufacturing

Engineering Product Definition and Related Documentation Practices

This is a Draft Standard for Trial Use and comment. This Draft Standard is not an approved consensus standard of ASME nor is it an American National Standard. ASME has approved its issuance and publication as a Draft Standard only. Distribution of this Draft Standard for comment shall not continue beyond 1 year from the date of publication. The content of this Draft Standard for Trial Use and comment was not approved through ASME's consensus process. Following the 1-year trial and comment period, this Draft Standard, along with comments received, will be submitted to a Consensus Committee or Project Team. The Consensus Committee or Project Team will review and revise this Draft Standard based, in part, upon experience during the trial term and resulting comments. A public review in accordance with established American National Standards Institute (ANSI) procedures is required at the end of the Trial-Use Period and before a Draft Standard for Trial Use is submitted to ANSI for approval as an American National Standard. Thereafter, it is expected that this Standard (including any revisions thereto) will be submitted to ANSI for approval as an American National Standard. Suggestions for revision should be directed to the Secretary, Y14.46 Subcommittee using the following form: <http://go.asme.org/Y14CommentForm>.



**The American Society of
Mechanical Engineers**

Two Park Avenue • New York, NY • 10016 USA

Date of Issuance: November 15, 2017

This Draft Standard for Trial Use will be revised following the conclusion of the Trial-Use Period. There will be no written interpretations of the requirements of this Draft Standard for Trial Use issued to this edition.

ASME is the registered trademark of The American Society of Mechanical Engineers.

The Standards Committee that approved the Draft Standard was balanced to assure that individuals from competent and concerned interests have had an opportunity to participate.

ASME does not "approve," "rate," or "endorse" any item, construction, proprietary device, or activity.

ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable letters patent, nor assume any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representative(s) or person(s) affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

No part of this document may be reproduced in any form,
in an electronic retrieval system or otherwise,
without the prior written permission of the publisher.

The American Society of Mechanical Engineers
Two Park Avenue, New York, NY 10016-5990

Copyright © 2017 by
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS
All rights reserved
Printed in U.S.A.

CONTENTS

| | |
|---|-----------|
| Foreword | v |
| Committee Roster | vi |
| 1 General | 1 |
| 2 Definitions | 3 |
| 3 Supplemental Geometry | 5 |
| 4 Product and Process Definition Requirements | 8 |
| 5 Product Data Packages (PDP) | 28 |
| Nonmandatory Appendices | |
| A Example AM Notes | 31 |
| B Defining Transition Regions | 32 |
| C Reference Documents to Test for Conformance | 35 |
| Figures | |
| 3-1 Single Coordinate System Related to the Model | 5 |
| 3-2 Multiple Coordinate Systems | 6 |
| 3-3 Unit Vector Indicating Build Direction | 6 |
| 3-4 Unit Vector Indicating Gravity Direction | 7 |
| 3-5 A Surface Representing a Build Surface | 7 |
| 4-1 Example of a Theoretical Supplemental Surface Used on a Rectangular Lattice Cuboid | 8 |
| 4-2 Example of a Theoretical Supplemental Surface Within a Rectangular Lattice Cuboid | 9 |
| 4-3 Example of a Nonplanar Theoretical Supplemental Surface | 9 |
| 4-4 Example of a Tolerance Zone Derived From Figure 4-3 | 10 |
| 4-5 Both Bounded Volume and Surface Regions to Indicate Internal and External Surfaces and Volumes | 10 |
| 4-6 Bounded Volume Region Indicator (VOL1) With a Profile of a Surface Tolerance | 11 |
| 4-7 Multiple Bounded Volume Region Indicators With Profiles of Surface Tolerances | 11 |
| 4-8 Bounded Volume Regions Represented by Several Bounded Volume Region Indicators in a Single Part | 12 |
| 4-9 Bounded Surface Region Indicator Coupled With a Feature Control Frame | 12 |
| 4-10 Examples of Unit Cell Geometries and Lattice Structures | 13 |
| 4-11 Lattice Structure With Multiple Bounded Volume Regions | 14 |
| 4-12 VOL Local Notes That Describe Material Gradient Allocations Shown in Table 4-1 | 15 |
| 4-13 Material Transition Specification Between Bounded Volume Regions With Lattice Fill | 16 |
| 4-14 Complex Geometries Generated From Topology Optimization | 17 |
| 4-15 Wrench Produced as a Single Build With Three Parts | 18 |
| 4-16 Build Direction Indicated Using the Direction Unit Vector | 18 |
| 4-17 Multiple Build Directions | 19 |
| 4-18 Planar Build Surface and a Nonplanar Build Surface | 19 |
| 4-19 Identifying Build Location With Respect to a Specified Build Surface | 20 |

| | | |
|-------------------|--|----|
| 4-20 | Coordinate Systems Are Used to Locate Parts Within a Build Envelope | 20 |
| 4-21 | Four Separate Parts Nested Inside One Another on a Build Surface | 21 |
| 4-22 | Free Zone Description With an Offset Dimension | 21 |
| 4-23 | Free Zone Bounding Box Description | 22 |
| 4-24 | Layer Thickness Specification | 22 |
| 4-25 | Specification of a Track Path With Three Contours | 23 |
| 4-26 | Specification of a Track Path Using a Follow Boundary (FB) Modifier | 23 |
| 4-27 | Specification of Track Paths on Different Layers | 23 |
| 4-28 | Examples of Infill and Unit Cells | 24 |
| 4-29 | Example Where Support Structure Location Is Not Specified | 25 |
| 4-30 | Example Where Bounded Surface Region 1 (SURF1) Is Annotated to Indicate a Structure Exclusion Area (SEA) | 25 |
| 4-31 | Example Where SURF1 Is Annotated to Indicate a Structure Limiting Area (SLA) of 20% | 26 |
| 4-32 | Example Where SURF1 Is Annotated to Indicate a Structure Required Area (SRA) | 26 |
| 4-33 | Indication of Geometry Created Inside the Part to Specify Support Structure | 27 |
| 4-34 | Local Notes Identifying Test Coupons | 27 |
| B-1 | Part With Material Transition Region (Heterogeneous Material Indicator) and Specification of Tolerance | 33 |
| B-2 | Acceptable Void Fractions for MAT1 and MAT2 | 33 |
| B-3 | Allowable Material Fractions for MAT1 and MAT2 | 34 |
| Tables | | |
| 4-1 | Material Gradient Values Used in Figure 4-12 | 15 |
| 5-1 | Required and Optional Data Packages for AM Products | 28 |
| 5-2 | Required and Optional Elements Within the AM Design DP | 28 |
| 5-3 | Required and Optional Elements Within the AM Build DP | 29 |
| 5-4 | Required and Optional Elements Within the AM Processed DP | 29 |
| 5-5 | Required and Optional Elements Within the End Product DP | 29 |
| 5-6 | Examples of AM Use Cases Using the Codes in ASME Y14.41.1 to Show the Level of Content in an AM Data Package (ADP) | 30 |
| 5-7 | Examples of Metadata Requirements for Model-Based Definition (MBD) Data Sets | 30 |
| B-1 | Material Gradient Values (Figure 4-12) | 32 |
| C-1 | Select Reference Documents | 35 |