

ASSE Standard #1047-2009

ASSE Board Approved: July, 2009

ANSI Approved: January, 2010

American Society of Sanitary Engineering

Performance Requirements for

Reduced Pressure Detector Fire Protection Backflow Prevention Assemblies

An American National Standard

This is a preview of "ANSI/ASSE 1047-2009". [Click here to purchase the full version from the ANSI store.](#)

General Information

Neither this standard, nor any portion thereof, may be reproduced without the written consent of the American Society of Sanitary Engineering.

No product may be said to be ASSE approved unless the manufacturer has applied to the ASSE has had his product tested according to the applicable ASSE Standards, and when the product has passed the test, displays the ASSE Seal on the product.

Instructions for receiving the authorization to display the Seal are available from the ASSE International Office. Organizations wishing to adopt or list any ASSE Standard should print the ASSE Standard Number on the cover page first and in equal or larger type to that of the adopting or listing organization.

American Society of Sanitary Engineering
Westlake, Ohio
Copyright © 2009, 2005, 1999, 1993, 1990
All rights reserved.

Foreword

This foreword shall not be considered a part of the standard, however, it is offered to provide background information.

ASSE Standards are developed in the interest of consumer safety.

The recognition of probable sources or causes of contamination of a potable water supply system and the application of essential devices, or means, to prevent the entrance of contaminants to the potable water system causing it to become unfit for human consumption, is vital to the maintenance of its continued potability.

This standard focuses on those devices known as reduced pressure detector fire protection backflow prevention assemblies (RPDF), which will fulfill this protective need. The standard was retitled in the 1999 revision to add "fire protection" to better describe the device's primary use.

Typically installed but not limited to fire protection systems, the devices described are primarily designed for two functions. The protection of the public water supply from contaminants found in fire sprinkler systems is a primary function for a backflow preventer. These assemblies are also designed to detect low rates of flow up to 0.126 L/s (2 GPM) within the sprinkler system caused by leakage or unauthorized use. This standard also allows provisions for alarm signaling devices to be included in the assembly.

Although many of the material specifications are detailed within Section 1.4 of this Standard, it is the responsibility of the manufacturer to comply with the requirements of the Safe Drinking Water Act, United States Public Law 93-523.

The working group which developed this standard revision, was set up within the framework of the Standards Committee of the American Society of Sanitary Engineering.

Recognition is made of the time volunteered by members of this working group and of the support of the manufacturers who also participated in the meetings for this standard.

This standard does not imply ASSE's endorsement of a product which conforms to these requirements.

Compliance with this standard does not imply acceptance by any code body.

It is recommended that these devices be installed consistent with local codes by qualified and trained professionals.

This standard was promulgated in accordance with procedures developed by the American National Standards Institute (ANSI).

This edition of the standard was approved by the ASSE Board of Directors on July 24, 2009, as an ASSE standard.

2008-2009 Product Standards Committee

Edward J. Lyczko

*Product Standards Committee Chairman
Cleveland Clinic
Cleveland, Ohio*

John F. Higdon, P.E.

*Apollo Valves/Conbraco Industries, Inc.
Pageland, South Carolina*

Rand H. Ackroyd

*Rand Technical Consulting, LLC
Newburyport, Massachusetts*

Chuck Lott

*Precision Plumbing Products, Inc.
Portland, Oregon*

William Briggs, Jr.

*MGJ Associates
New York, New York*

Peter Marzec

*United Association of
Plumbers and Pipefitters
Pearl River, New York*

Judson W. Collins

*JULYCO Professionals
Mannford, Oklahoma*

Hamid Naderi

*International Code Council
Austin, Texas*

A. Richard Emmerson

*General Interest
Buffalo Grove, Illinois*

Brad Noll

*Wilkins, A Division of Zurn Industries, Inc.
Paso Robles, California*

Ron George

*Ron George Design & Consulting
Newport, Michigan*

Thomas C. Pitcherello

*State of New Jersey
Bordentown, New Jersey*

Charles Gross

*International Association of Plumbing
and Mechanical Officials
Ontario, California*

Shabbir Rawalpindiwala

*Kohler Company
Kohler, Wisconsin*

Steven Hazzard

*ASSE Staff Engineer/ Standards Coordinator
Westlake, Ohio*

Tsan-Liang Su, Ph.D.

*Center for Environmental Systems
Stevens Institute of Technology
Hoboken, New Jersey*

RP / DC Working Group

Rand H. Ackroyd

*Working Group Chairman
Rand Engineering
Newburyport, Massachusetts*

Paul Bladdick

*LPB Company, Inc., Inc.
White Lake, Michigan*

William Chapin

*Cash Acme/Reliance Worldwide
Cullman, Alabama*

Sean Cleary

*IAPMO
Scranton, Pennsylvania*

Robert Cross

*Houston Area Plumbing JAC
Houston, Texas*

John Higdon, P.E.

*Apollo / Conbraco Industries, Inc
Pageland, South Carolina*

Steven Hazzard

*ASSE Staff Engineer/ Standards Coordinator
Westlake, Ohio*

Brad Noll

*Wilkins, a Division of Zurn Industries
Paso Robles, California*

Robert Purzycki

*BAVCO Mechanical Services
Long Beach, California*

Paul Schwartz

*University of Southern California FCCCHR
Los Angeles, California*

Stanley Ziobro

*Factory Mutual Approvals
Norwood, Massachusetts*

Table of Contents

Section I	1
1.0 General	1
1.1 Application	1
1.2 Scope	1
Table 1	2
1.3 Limitations on Design	2
1.4 Reference Standards	3
Section II	5
2.0 Test Specimens	5
2.1 Samples Submitted for Test	5
2.2 Samples Tested	5
2.3 Drawings	5
2.4 Rejection	5
2.5 Manifold Assembly	5
Section III	6
3.0 Performance Requirements and Compliance Testing	6
3.1 Independence of Components	6
3.2 Hydrostatic Test of Complete Assembly	6
3.3 Seat Leakage Test for Shut-off Valves	6
3.4 Hydrostatic Backpressure Test of Bypass Check (for RPDA-II only)	7
3.5 Hydrostatic Backpressure Test of Checks	7
3.6 Allowable Pressure Loss at Rated Flow	7
Figure 1	8
Figure 1A.....	8
3.7 Bypass Flow Detection	9
3.8 Relief Valve Opening Test	10
3.9 Sensitivity of Differential Pressure Relief Valve Test	10
3.10 Drip Tightness of First Check	10
3.11 Drip Tightness of Second Check.....	11
3.12 Drip Tightness of Bypass Check (for RPDA-II only)	11
3.13 Relief Valve Discharge Test with Atmospheric Supply Pressure	11
3.14 Relief Valve Discharge with Positive Supply Pressure	12
Table 2	12
3.15 Backpressure/Backsiphonage Test	13
3.16 Relief Valve vs. Supply Pressure Fluctuation Test	13
3.17 Air Gap Device Backsiphonage Test	13
3.18 Deterioration at Manufacturer's Extremes of Temperature and Pressure Ranges	14
Table 3	14
3.19 Cycle Test	15
3.20 Body Strength Test	15
3.21 Seat Adhesion Test	16
3.22 High Velocity Test	16
3.23 Field Evaluation Test for RPDA and RPDA-II Devices (Optional) - When Required by the Authority Having Jurisdiction	16

Section IV	18
4.0 Detailed Requirements	18
4.1 Materials	18
4.2 Marking Instructions	19
4.3 Installation and Maintenance Instructions	20
4.4 Maintenance	20
4.5 Field Testing	20
Section V	21
5.0 Definitions	21
Appendix A - Installation Guidelines	22
A1.0 Recommended Installation Guidelines	22
A1.1 General	22
A1.2 Orientation	22
A1.3 Side Clearances	22

Reduced Pressure Detector Fire Protection Backflow Prevention Assemblies

Section I

1.0 General

1.1 Application

The purpose of a Reduced Pressure Detector Fire Protection Backflow Prevention Assembly (herein referred to as the "assembly") is to keep contaminated water from fire protection systems from flowing back into a potable water distribution system when some abnormality in the system causes the pressure to be temporarily higher in the contaminated part of the system than in the potable water supply piping. These assemblies are designed to detect low rates of flow up to 2.0 GPM (7.6 L/m) caused by leakage or unauthorized use.

1.2 Scope

1.2.1 Description

This standard applies to the two types of assemblies identified as:

- (a) Reduced Pressure Detector Assembly (RPDA).
- (b) Reduced Pressure Detector Assembly Type II (RPDA-II).

The RPDA and RPDA-II assemblies consist of two (2) independently-acting check valves, internally force loaded to a normally closed position, and separated by an intermediate chamber (or zone) in which there is a hydraulically operated relief means for venting to atmosphere, internally force loaded to a normally open position. These assemblies are designed to operate under continuous pressure conditions. The assembly shall include two (2) properly located, tightly closing shut-off valves per Section 1.3.2.7 and properly located test cocks per Section 1.3.2.5. The assemblies also include a bypass line which provides a visual or audible indication of system leakage or unauthorized use of water.

This standard also applies to Manifold Reduced Pressure Detector Assemblies consisting of two or more complete RPDA or RPDA-II assemblies in parallel. The assemblies do not need to be of the same pipe size. The manifold size shall be identified by the single inlet and outlet of the manifold RPDA or RPDA-II assembly. Manifold Reduced Pressure Principle Backflow Assemblies shall include line-sized shut-off valves on each inlet and outlet of the assemblies making up the manifold.

1.2.2 Size Range

Connection pipe sizes shall be in accordance with Table 1.