

The Authoritative Resource on Safe Water®

ANSI/AWWA B603-10 (Revision of ANSI/AWWA B603-03)



Permanganates





Effective date: Aug. 1, 2010. First edition approved by AWWA Board of Directors Jan. 28, 1968. This edition approved Jan. 17, 2010. Approved by American National Standards Institute June 14, 2010.

6666 West Quincy Avenue Denver, C0 80235-3098 **T** 800.926.7337 www.awwa.org Advocacy Communications Conferences Education and Training Science and Technology Sections

AWWA Standard

This document is an American Water Works Association (AWWA) standard. It is not a specification. AWWA standards describe minimum requirements and do not contain all of the engineering and administrative information normally contained in specifications. The AWWA standards usually contain options that must be evaluated by the user of the standard. Until each optional feature is specified by the user, the product or service is not fully defined. AWWA publication of a standard does not constitute endorsement of any product or product type, nor does AWWA test, certify, or approve any product. The use of AWWA standards is entirely voluntary. This standard does not supersede or take precedence over or displace any applicable law, regulation, or codes of any governmental authority. AWWA standards are intended to represent a consensus of the water supply industry that the product described will provide satisfactory service. When AWWA revises or withdraws this standard, an official notice of action will be placed on the first page of the classified advertising section of *Journal AWWA*. The action becomes effective on the first day of the month following the month of *Journal AWWA* publication of the official notice.

American National Standard

An American National Standard implies a consensus of those substantially concerned with its scope and provisions. An American National Standard is intended as a guide to aid the manufacturer, the consumer, and the general public. The existence of an American National Standard does not in any respect preclude anyone, whether that person has approved the standard or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standard. American National Standards are subject to periodic review, and users are cautioned to obtain the latest editions. Producers of goods made in conformity with an American National Standard are encouraged to state on their own responsibility in advertising and promotional materials or on tags or labels that the goods are produced in conformity with particular American National Standards.

CAUTION NOTICE: The American National Standards Institute (ANSI) approval date on the front cover of this standard indicates completion of the ANSI approval process. This American National Standard may be revised or withdrawn at any time. ANSI procedures require that action be taken to reaffirm, revise, or withdraw this standard no later than five years from the date of publication. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute, 25 West 43rd Street, Fourth Floor, New York, NY 10036; (212) 642-4900, or e-mailing info@ansi.org.

All rights reserved. No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopy, recording, or any information or retrieval system, except in the form of brief excerpts or quotations for review purposes, without the written permission of the publisher.

Copyright © 2010 by American Water Works Association Printed in USA

Committee Personnel

The AWWA Standards Committee on Taste and Odor Control Chemicals, which reviewed and approved this standard, had the following personnel at the time of approval:

Thomas E.T. Gillogly, Chair

General Interest Members

| C.A. Blanck, Richmond, Ind. | (AWWA) | | | |
|--|--------|--|--|--|
| T.E.T. Gillogly, Carollo Engineers, Las Vegas, Nev. | | | | |
| J.S. Kippin, Town of Ipswich Water Department, Ipswich, Mass. | | | | |
| C.B. Lind, Mauser Corporation, Bridgewater, N.J. | (AWWA) | | | |
| N.E. Otto, Denver, Colo. | (AWWA) | | | |
| S.J. Posavec,* Standards Group Liaison, AWWA, Denver, Colo. | (AWWA) | | | |
| Mohamed Siddiqui, University of Utah, Salt Lake City, Utah | (AWWA) | | | |
| B.H. Wilder, Daytona Beach, Fla. | (AWWA) | | | |
| Producer Members | | | | |
| I.P. Fairchild, Chemical Specialty Group Inc., Cartersville, Ga. | (AWWA) | | | |
| J.E. Boll, Carus Corporation, Peru, Ill. | (AWWA) | | | |
| T.R. Walton, Stuart, Fla. | | | | |
| | | | | |

User Members

| J.T. Harvey, Little Rock, Ark. | (AWWA) |
|---|--------|
| J.J. Parker, City Utilities, Springfield, Mo. | (AWWA) |

^{*} Liaison, nonvoting

This page intentionally blank.

Contents

All AWWA standards follow the general format indicated subsequently. Some variations from this format may be found in a particular standard.

| SEC. | PAGE | SEC. | PAGE |
|----------|--------------------------------------|------|----------------------------|
| Forei | word | 4 | Requirements |
| Ι | Introduction vii | 4.1 | Materials 3 |
| I.A | Background vii | 4.2 | Physical Requirements 3 |
| I.B | History vii | 4.3 | Chemical Requirements 4 |
| I.C | Acceptance viii | 4.4 | Impurities 4 |
| II | Special Issues ix | 5 | Verification |
| II.A | Storage and Handling Precautions ix | 5.1 | Sampling 5 |
| III | Use of This Standard x | 5.2 | Test Procedures 6 |
| III.A | Purchaser Options and Alternatives x | 5.3 | KMnO4 and NaMnO4 Assay |
| III.B | Modification to Standard xi | 5.4 | Particle Size |
| IV | Major Revisions xi | 5.5 | Water Tolerance |
| V | Comments xi | 5.6 | Notice of Nonconformance |
| Standard | | 6 | Delivery |
| 1 | General | 6.1 | Marking |
| 1.1 | Scope 1 | 6.2 | Packaging and Shipping 9 |
| 1.2 | Purpose 1 | 6.3 | Affidavit of Compliance 10 |
| 1.3 | Application 1 | Tahl | les |
| 2 | References | 1 | Potassium Permanganate 7 |
| 3 | Definitions | 2 | Sodium Permanganate 7 |
| | | | |

This page intentionally blank.

Foreword

This foreword is for information only and is not a part of ANSI*/AWWA B603.

I. Introduction.

I.A. *Background.* Potassium and sodium permanganate are strong oxidizing agents. They oxidize organic matter responsible for many types of tastes, odors, and colors. Potassium and sodium permanganate oxidize dissolved iron, manganese, and arsenic to produce oxides, which can then be settled or filtered out. They also oxidize hydrogen sulfide, thereby eliminating the rotten-egg odor. Potassium permanganate is listed by the US Environmental Protection Agency (USEPA) as a substitute preoxidant for chlorine to control total trihalomethanes (TTHMs).

Potassium permanganate (KMnO₄) is a manufactured product. The manufacturer should comply with the regulations stated in parts 210 through 226 of 21 CFR, as applicable, which contain minimum current good manufacturing practices as defined by the Food and Drug Administration (FDA). Potassium permanganate crystals are rhombic or needle-like in shape and are purple or bronze in color. They are manufactured in several different grades, including USP. Any grade of potassium permanganate that meets quality and feed requirements may be used in water treatment. The two most widely used grades are technical grade, designed for solution feed, and free-flowing grade, suitable for either solid or solution feed. The free-flowing grade contains an additive to minimize caking and lumping caused by moisture and compaction. It may be gray because of the additive.

Liquid sodium permanganate (NaMnO₄) solution is an alternative to dry potassium permanganate crystals. This product was developed in response to requests by users for a liquid permanganate solution. Because of the limited solubility of potassium permanganate (6 percent at room temperature) the cation was exchanged to increase the solubility. Sodium permanganate is commercially available in concentrations up to 40 percent by weight and is manufactured according to the same manufacturing practices described above that are used in the manufacture of potassium permanganate.

I.B. *History.* AWWA B603 was initially approved as a standard by the AWWA Board of Directors on Jan. 28, 1968. Revisions were approved on May 8, 1977; June 5, 1983; June 19, 1988; June 6, 1993; June 21, 1998; and June 15, 2003. This edition was approved on Jan. 17, 2010.

^{*} American National Standards Institute, 25 West 43rd Street, Fourth Floor, New York, NY 10036.

I.C. Acceptance. In May 1985, the US Environmental Protection Agency (USEPA) entered into a cooperative agreement with a consortium led by NSF International (NSF^{*}) to develop voluntary third-party consensus standards and a certification program for direct and indirect drinking water additives. Other members of the original consortium included the American Water Works Association Research Foundation (AwwaRF, now Water Research Foundation) and the Conference of State Health and Environmental Managers (COSHEM). The American Water Works Association (AWWA) and the Association of State Drinking Water Administrators (ASDWA) joined later.

In the United States, authority to regulate products for use in, or in contact with, drinking water rests with individual states.[†] Local agencies may choose to impose requirements more stringent than those required by the state. To evaluate the health effects of products and drinking water additives from such products, state and local agencies may use various references, including two standards developed under the direction of NSF, NSF/ANSI 60, Drinking Water Treatment Chemicals—Health Effects, and NSF/ANSI 61, Drinking Water System Components—Health Effects.

Various certification organizations may be involved in certifying products in accordance with NSF/ANSI 60. Individual states or local agencies have authority to accept or accredit certification organizations within their jurisdiction. Accreditation of certification organizations may vary from jurisdiction to jurisdiction.

Annex A, "Toxicology Review and Evaluation Procedures," to NSF/ANSI 60 does not stipulate a maximum allowable level (MAL) of a contaminant for substances not regulated by a USEPA final maximum contaminant level (MCL). The MALs of an unspecified list of "unregulated contaminants" are based on toxicity testing guidelines (noncarcinogens) and risk characterization methodology (carcinogens). Use of Annex A procedures may not always be identical, depending on the certifier.

ANSI/AWWA B603 addresses additives requirements in Sec. 4.4 of the standard. The transfer of contaminants from chemicals to processed water or the residual solids is becoming a problem of great concern. The language in Sec. 4.4.2 is a recommendation only for direct additives used in the treatment of potable water to be certified by an accredited certification organization in accordance with NSF/ANSI 60, Drinking Water Treatment Chemicals—Health Effects. However, users of the standard may opt

^{*} NSF International, 789 N. Dixboro Road, Ann Arbor, MI 48105.

[†] Persons outside the United States should contact the appropriate authority having jurisdiction.

to make this certification a requirement for the product. Users of this standard should also consult the appropriate state or local agency having jurisdiction in order to

1. Determine additives requirements, including applicable standards.

2. Determine the status of certifications by parties offering to certify products for contact with, or treatment of, drinking water.

3. Determine current information on product certification.

II. Special Issues.

II.A. *Storage and Handling Precautions.* Permanganates are strong oxidizing agents and should be treated as such. The products themselves are noncombustible but will accelerate the burning of combustible materials. They react with many materials, and care should be exercised in their handling, storage, and use. Therefore, contact with all combustible materials or chemicals must be avoided. These include but are not limited to wood, cloth, organic materials, and charcoal. Avoid contact with acids, peroxides, sulfites, oxalates, and other oxidizable inorganic chemicals. Permanganates should be segregated from ammonium compounds, metallic powders, phosphorus, hydrogen peroxide, carbon, metal hydrides, hydrazine, hydroxylamines, antifreeze, hydraulic oils, and formaldehyde.

The products should be stored in a cool, dry area in closed containers and should be protected from physical damage. Concrete floors are preferred. Avoid wooden decks. Protect the liquid sodium permanganate solution from freezing.

Spills of dry potassium permanganate should be swept up and transferred to clean metal drums and disposed of according to federal, state or provincial, and local regulations. Spilled dry potassium permanganate should not be returned to the original drums that contain uncontaminated product. After the permanganate has been cleaned up, the residual permanganate on the floor should be flushed with water into a sanitary sewer, complying with federal, state or provincial, and local regulations.

Spills of liquid sodium permanganate solution should be collected and disposed of properly. Contain and dilute spillage to approximately 6 percent with water and reduce the permanganate with sodium thiosulfate, sodium bisulfite, or sodium metabisulfite. Deposit sludge in an approved landfill or, where permitted, flush into a sanitary sewer with large quantities of water.

When handling either potassium or sodium permanganate, good safety procedures must be observed. These include the use of safety goggles, safety glasses with side shields, or face shield; impervious rubber or PVC gloves, and apron. A NIOSH– MSHA-approved respirator meeting general industry standards as described in ANSI Z88.2, Practices for Respiratory Protection, latest revision, is recommended when handling dry potassium permanganate crystals and where significant exposure to the liquid sodium permanganate solution exists.

If clothing becomes spotted when handling the liquid sodium permanganate, wash off immediately with large quantities of water.

Permanganates are corrosive to the eyes and can cause severe burns. If exposed to permanganate, immediately flush the affected eye with water for 15 min while holding the eyelid open. Consult a physician immediately.

For additional safety aspects, refer to material safety data sheets (MSDS) available from the chemical supplier or manufacturer.

III. Use of This Standard. It is the responsibility of the user of an AWWA standard to determine that the products described in that standard are suitable for use in the particular application being considered.

III.A. *Purchaser Options and Alternatives.* The following information should be provided by the purchaser.

1. Standard used—that is, ANSI/AWWA B603, Standard for Permanganates, of latest revision.

2. Whether compliance with NSF/ANSI 60, Drinking Water Treatment Chemicals—Health Effects, is required.

3. Quantity required.

4. Details of other federal, state or provincial, and local requirements (Sec. 4.1).

5. Grade desired—technical, free-flowing, USP, or other dry crystals, or liquid solution. Physical and chemical requirements are provided in the standard for both the dry technical and free-flowing grades (Sec. 4.2.1) and the liquid products (Sec. 4.2.2). Chemical requirements for dry potassium permanganate are provided for technical, free-flowing, and the USP grade (Sec. 4.3). Dry USP-grade physical requirements shall be as specified by the purchaser. If a grade other than technical, free-flowing, USP, or liquid product is desired, the purchaser must specify the requirements of the grade desired.

6. Form of shipment—bulk, container size (weight), and type of package (Sec. 6.2).

7. Affidavit of compliance, if required (Sec. 6.3).

8. Whether the purchaser will reject product from containers or packaging with missing or damaged seals. The purchaser may reject product from bulk containers or packages with missing or damaged seals unless the purchaser's tests of representative samples, conducted in accordance with Sec. 5.3, 5.4, and 5.5, demonstrate that the product meets the standard. Failure to meet the standard or the absence of, or irregularities in, seals may be sufficient cause to reject the shipment.

9. Whether alternative security measures have been adopted to replace or augment the security measures set out in Sec. 6.2.3 and 6.2.4.

III.B. *Modification to Standard*. Any modification to the provisions, definitions, or terminology in this standard must be provided by the purchaser.

IV. Major Revisions. Major revisions made to the standard in this edition include the following:

1. Inclusion of a requirement for compliance with the Safe Drinking Water Act and other federal regulations (Sec. 4.1).

2. Inclusion of a requirement for tamper-evident packaging (Sec. 6.2.3 and 6.2.4).

V. Comments. If you have any comments or questions about this standard, please call the AWWA Volunteer and Technical Support Group at 303.794.7711, FAX at 303.795.7603, write to the group at 6666 West Quincy Avenue, Denver, CO 80235-3098, or e-mail the group at standards@awwa.org.

This page intentionally blank.

ANSI/AWWA B603-10 (Revision of AWWA B603-03)



AWWA Standard

Permanganates

SECTION 1: GENERAL

Sec. 1.1 Scope

This standard describes both dry potassium permanganate (KMnO₄) crystals, CAS* No. 7722-64-7, as well as liquid sodium permanganate (NaMnO₄) solutions, CAS* No. 10101-50-5, for use in the treatment of potable and reuse or reclaimed water and wastewater.

Sec. 1.2 Purpose

The purpose of this standard is to provide the minimum requirements for dry potassium permanganate crystals and liquid sodium permanganate solutions, including physical, chemical, sampling, testing, packaging, and shipping requirements.

Sec. 1.3 Application

This standard can be referenced in documents for purchasing and receiving permanganates and can be used as a guide for testing the physical and chemical properties of permanganate samples. The stipulations of this standard apply when this document has been referenced and then only to permanganates used in potable, wastewater, and reuse or reclaimed water.

^{*} Chemical Abstract Service, P.O. Box 3012, Columbus, Ohio 43210.