This is a preview of "AWWA C800-2012". Click here to purchase the full version from the ANSI store.



The Authoritative Resource on Safe Water®

ANSI/AWWA C800-12 (Revision of ANSI/AWWA C800-05)



Underground Service Line Valves and Fittings



American National Stonge

Effective date: Jan. 1, 2013. First edition approved by AWWA Board of Directors Sept. 1, 1948. This edition approved June 10, 2012. Approved by American National Standards Institute Oct. 30, 2012.

6666 West Quincy Avenue Denver, C0 80235-3098 **T** 800.926.7337 www.awwa.org Advocacy Communications Conferences Education and Training Science and Technology Sections

Copyright © 2013 American Water Works Association. All Rights Reserved.

AWWA Standard

This document is an American Water Works Association (AWWA) standard. It is not a specification. AWWA standards describe minimum requirements and do not contain all of the engineering and administrative information normally contained in specifications. The AWWA standards usually contain options that must be evaluated by the user of the standard. Until each optional feature is specified by the user, the product or service is not fully defined. AWWA publication of a standard does not constitute endorsement of any product or product type, nor does AWWA test, certify, or approve any product. The use of AWWA standards is entirely voluntary. This standard does not supersede or take precedence over or displace any applicable law, regulation, or codes of any governmental authority. AWWA standards are intended to represent a consensus of the water supply industry that the product described will provide satisfactory service. When AWWA revises or withdraws this standard, an official notice of action will be placed on the first page of the Official Notice section of *Journal - American Water Works Association*. The action becomes effective on the first day of the month following the month of *Journal - American Water Works Association* publication of the official notice.

American National Standard

An American National Standard implies a consensus of those substantially concerned with its scope and provisions. An American National Standard is intended as a guide to aid the manufacturer, the consumer, and the general public. The existence of an American National Standard does not in any respect preclude anyone, whether that person has approved the standard or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standard. American National Standards are subject to periodic review, and users are cautioned to obtain the latest editions. Producers of goods made in conformity with an American National Standard are encouraged to state on their own responsibility in advertising and promotional materials or on tags or labels that the goods are produced in conformity with particular American National Standards.

CAUTION NOTICE: The American National Standards Institute (ANSI) approval date on the front cover of this standard indicates completion of the ANSI approval process. This American National Standard may be revised or withdrawn at any time. ANSI procedures require that action be taken to reaffirm, revise, or withdraw this standard no later than five years from the date of ANSI approval. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute, 25 West 43rd Street, Fourth Floor, New York, NY 10036; (212) 642-4900, or emailing info@ansi.org.

ISBN-13, print: 978-1-58321-911-9 ISBN-10, print: 1-58321-911-0 elSBN-13, electronic: 978-1-61300-206-3 elSBN-10, electronic: 1-61300-206-8

All rights reserved. No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopy, recording, or any information or retrieval system, except in the form of brief excerpts or quotations for review purposes, without the written permission of the publisher.

Copyright © 2013 by American Water Works Association Printed in USA

Committee Personnel

The AWWA Standards Committee on Water Service Line Fittings, which reviewed and approved this standard, had the following personnel at the time of approval:

Savas C. Danos, Chair

General Interest Members


T. Arnbrister, Nisqually Tribe, Rainier, Wash.	(AWWA)				
L.E. Beck, Hawaii Department of Water Supply, Hilo, Hawaii	(AWWA)				
L.R. Faulkner, Lakewood, Colo.	(AWWA)				
R.L. Gardner,* Standards Council Liaison, Wannacomet Water Company,					
Nantucket, Mass.	(AWWA)				
J.W. Hellums, Booth Hellums and Associates LLC, Lake Charles, La.	(AWWA)				
K.L. Mercer,* Standards Engineer Liaison, AWWA, Denver, Colo.	(AWWA)				
R.A. Waggenspack, Owen & White Inc., Baton Rouge, La.	(AWWA)				
Producer Members					
M. Anderson, Ford Meter Box Company Inc., Wabash, Ind.	(AWWA)				
J.L. Daghe, A.Y. McDonald Manufacturing Company, Dubuque, Iowa	(AWWA)				
L.W. Fleury, Mueller Group, Smithfield, R.I.	(AWWA)				
D.W. Humes, [†] Mueller Company, Decatur, Ill.	(AWWA)				
T.J. Moulton, Emco Corporation, Mississauga, Ont.	(AWWA)				
C. Shanks, Ford Meter Box Company Inc., Wabash, Ind.	(AWWA)				
S. Tefft, [†] A.Y. McDonald Manufacturing Company, Dubuque, Iowa (A					
User Members					
T.M. Bowen, Manchester Water Works, Manchester, N.H.	(AWWA)				
S.C. Danos, Littleton Water Department, Littleton, Mass.	(AWWA)				
R.J. Dudas, Orange County Utilities, Orlando, Fla.	(AWWA)				
R.J. Krol, South Bend Water Works, South Bend, Ind.	(AWWA)				
R.G. Sykes, East Bay Municipal Utility District, Oakland, Calif.	(AWWA)				
A.S. Tong, East Bay Municipal Utility District, Oakland, Calif. (AWW					

^{*} Liaison, nonvoting

[†]Alternate

This is a preview of "AWWA C800-2012". Click here to purchase the full version from the ANSI store.

This page intentionally blank.



Contents

All AWWA standards follow the general format indicated subsequently. Some variations from this format may be found in a particular standard.

SEC.	PAGE				
Foreword					
Ι	Introduction vii				
I.A	History vii				
I.B	Acceptance viii				
II	Special Issues ix				
II.A	Lead Fittings ix				
III	Use of This Standard ix				
III.A	Products Intended for Waterworks				
Applications ix					
III.B	Purchaser Options and				
	Alternatives ix				
III.C	Modification to Standard x				
IV	Major Revisions x				
V	Comments x				

Standard

1 General

1.1	Scope	1
1.2	Purpose	2
1.3	Application	2
2	References	2
3	Definitions	2
4	Requirements	
4.1	Materials	4
4.2	General Design	4
4.3	Detailed Design	5
4.4	End Connections	8
4.5	Fabrication	15

SEC.	F	PAGE	
4.6	Permeation	15	
5	Verification		
5.1	Inspection	15	
5.2	Testing	16	
5.3	Basis for Rejection		
6	Delivery		
6.1	Marking	16	
6.2	Packing and Shipping	16	
6.3	Affidavit of Compliance	16	
A B C <i>Fig.</i> 1 2 3 4	Collected Standards for Service Line Materials Field Testing Installation Ures Curb Valve Heads Standard AWWA Corporation Stop Inlet Thread Coupling Nut for Use With Flared Copper Service Tube, Types K and L Outlet End of Corporation Stop Showing Increased-size NPT External Threads and Internal Driving Threads Flared Fitting End Showing Threads	23 25 7 10	
	for Use With Flared Copper Service Tube	12	

6	Outlet End of Corporation Stop	7	Standard AWWA Corporation Stop
	Showing Special-Purpose		Inlet Threads and Corresponding
	Coupling Threads and Internal		Internal Threads for Saddles 10
	Driving Threads 12	8	Tapered External Iron Pipe (NPT)
7	Meter Coupling Nut 13		Threads for Outlet End of
8	Meter Flange 15		Corporation Stops 12
	C C	9	Internal Driving Thread for
Ta	ables		Corporation Stops 13
1	Maximum Drill Sizes for Installation	10	Meter Coupling Nut 13
	of Corporation Stops in Service	11	Meter Flanges 14
	Clamps or Saddles With a Drilling Machine5	A.1	Dimensions, Weights, and Tolerances
2	Maximum Overall Body Dimensions for Corporation Stops for Use		in Diameter and Wall Thickness for Nominal or Standard Copper
	With Tapping Machine		Water Tube Sizes 18
3	Curb Valve Head Dimensions	A.2	Dimensions, Weights, and Tolerance for Standard Sizes of Seamless
4	Fitting Thread for Use With Flared		Red Brass Pipe 19
	Copper Service Tube 9	A.3	Standard Weights and Dimensions
5	Coupling Nut for Use With Flared		of Welded and Seamless
	Copper Service Tube		Steel Pipe 20
6	Corporation Stop Outlet Special-		
	Purpose Coupling Threads		

Foreword

This foreword is for information only and is not a part of ANSI*/AWWA C800.

I. Introduction.

I.A. *History.* In 1929, the development of a standard for threads for underground service fittings was undertaken by the American Standards Association (ASA). In 1932, the subcommittee that had been appointed for the task asked to be discharged after it had submitted its proposed standards in the form of two drawings. No action was taken by ASA on these proposed standards.

The American Water Works Association (AWWA) recognized the need for standardization of these threads and appointed a committee in 1940 to prepare a standard. The New England Water Works Association (NEWWA) also appointed a committee to prepare a standard for these threads. The AWWA and NEWWA committees cooperated closely in developing a tentative standard in 1947. This was approved as a standard by AWWA on Sept. 1, 1948, and by NEWWA on Sept. 14, 1948. Revisions to the standard were made effective Jan. 17, 1955. In July 1963, a committee was formed to revise C800-55 regarding the evaluation of types K and L copper tubing for water services. In the revision, published in 1966, threads representing current practice were established for those fittings generally used in the water utility field. Sizes 1/2 in. and 5/8 in. were added for inlet and outlet threads for fittings and couplings for use with flared copper service tubing. The 1966 revision introduced an appendix that was not part of the standard, but which listed standards for water service line materials. The appendix was provided for information only because the materials were covered by other standards. The appendix also contained specifications for copper water tubing, red brass pipe, cast-iron pipe, and steel pipe.

In 1974, a standing committee was formed to revise and update C800-66. The committee recognized the need to expand the scope of this standard beyond being a standard covering only threads for underground service fittings. Previous versions of C800 described only the threads for fittings that were in common use in water distribution systems. Subsequently, the scope of the standard was changed to include performance standards for underground service line fittings as well as for the threads. The 1984 revision to C800 was approved by the AWWA Board of Directors on

^{*} American National Standards Institute, 25 West 43rd Street, Fourth Floor, New York, NY 10036.

Jan. 29, 1984. Subsequent revisions were approved on Jan. 1, 1990; Jan. 21, 2001; and Jan. 16, 2005. This revision was approved on June 10, 2012.

I.B. *Acceptance.* In May 1985, the US Environmental Protection Agency (USEPA) entered into a cooperative agreement with a consortium led by NSF International* (NSF) to develop voluntary third-party consensus standards and a certification program for direct and indirect drinking water additives. Other members of the original consortium included the American Water Works Association Research Foundation (AwwaRF, now Water Research Foundation[†]) and the Conference of State Health and Environmental Managers (COSHEM). The American Water Works Association (AWWA) and the Association of State Drinking Water Administrators (ASDWA) joined later.

In the United States, authority to regulate products for use in, or in contact with, drinking water rests with individual states.[‡] Local agencies may choose to impose requirements more stringent than those required by the state. To evaluate the health effects of products and drinking water additives from such products, state, provincial, and local agencies may use various references, including

1. An advisory program formerly administered by USEPA, Office of Drinking Water, discontinued on Apr. 7, 1990.

2. Specific policies of the state, provincial, or local agency.

3. Two standards developed under the direction of NSF, NSF/ANSI 60, Drinking Water Treatment Chemicals—Health Effects, and NSF/ANSI 61, Drinking Water System Components—Health Effects.

4. Other references, including AWWA standards, *Food Chemicals Codex*, *Water Chemicals Codex*,[§] and other standards considered appropriate by the state, provincial, or local agency. Various certification organizations may be involved in certifying products in accordance with NSF/ANSI 61. Individual states, provinces, or local agencies have authority to accept or accredit certification organizations within their jurisdiction. Accreditation of certification organizations may vary from jurisdiction to jurisdiction.

Annex A, "Toxicology Review and Evaluation Procedures," to NSF/ANSI 61 does not stipulate a maximum allowable level (MAL) of a contaminant for substances not regulated by a USEPA final maximum contaminant level (MCL). The MALs of an

^{*} NSF International, 789 N. Dixboro Rd., Ann Arbor, MI 48105.

[†]Water Research Foundation, 6666 W. Quincy Avenue, Denver, CO 80235.

[‡]Persons outside the United States should contact the appropriate authority having jurisdiction.

South publications available from National Academy of Sciences, 500 Fifth St., N.W., Washington, DC 20001.

unspecified list of "unregulated contaminants" are based on toxicity testing guidelines (noncarcinogens) and risk characterization methodology (carcinogens). Use of Annex A procedures may not always be identical, depending on the certifier.

ANSI/AWWA C800 does not address additives requirements. Users of this standard should consult the appropriate state, provincial, or local agency having jurisdiction in order to

1. Determine additives requirements, including applicable standards.

2. Determine the status of certifications by parties offering to certify products for contact with, or treatment of, drinking water.

3. Determine current information on product certification.

II. Special Issues.

II.A. *Lead Fittings.* References to lead fittings have been removed from ANSI/ AWWA C800 and the attached appendixes. The AWWA Standards Department has available to users of ANSI/AWWA C800 copies of ANSI/AWWA C800-84 information that contains references to lead fittings.

III. Use of This Standard. It is the responsibility of the user of an AWWA standard to determine that the products described in that standard are suitable for use in the particular application being considered.

III.A. *Products Intended for Waterworks Applications.* A variety of valves, fittings, and other water conveyance devices are available on the market for water service. For the user, it is important to distinguish between products designated plumbing style versus waterworks service style and to ensure the proper product is selected for the specific application. Waterworks products are designed and constructed for belowground installation. This helps ensure long-term performance under a variety of installation and service conditions. The specific materials established in AWWA C800 were selected to provide long-term performance and corrosion resistance from both internal and external sources. The user is cautioned that underground service line valves and fittings not compliant with AWWA C800 may result in unsatisfactory performance or failure of the product. When in doubt concerning product suitability, contact a waterworks manufacturer for assistance.

III.B. Purchaser Options and Alternatives.

The following information should be provided by the purchaser:

1. Standard used—that is, ANSI/AWWA C800, Standard for Underground Service Line Valves and Fittings, of latest revision.

2. The purchaser should state whether compliance with NSF/ANSI 61, Drinking Water System Components—Health Effects, is to be required.

3. The size and type of fitting or valve.

4. Quantity required.

5. Details of other federal, state or provincial, and local requirements.

6. Working pressures under which the valve or fitting will be operated after installation—normal or high pressure (Sec. 4.2).

7. Minimum inside diameter of waterway through corporation stops (Sec. 4.3.1.1).

8. If meter setter spacing is other than shown to accommodate meter lengths listed in Table 10 or 11 (Sec. 4.3.14).

9. Type of inlet thread (Sec. 4.4).

10. Size and type of outlet thread (Sec. 4.4).

11. If meter flanges other than oval are required (Sec. 4.4.12).

12. Whether records of factory tests are to be provided (Sec. 5.2.1).

13. Description of special castings or patterns, if required. Special casting mark-

ings, if required, should be stated, including location of these markings (Sec. 6.1).

14. Whether an affidavit of compliance is to be provided (Sec. 6.3).

III.C. *Modification to Standard*. Any modification of the provisions, definitions, or terminology in this standard must be provided by the purchaser.

IV. Major Revisions. Major revisions made to the standard in this edition include the following:

1. Addition of Foreword, Section III.A, Products Intended for Waterworks Applications.

2. Revision of Sec. 5.3, Basis for Rejection.

3. Revision of Sec. 6.3, Affidavit of Compliance.

V. Comments. If you have any comments or questions about this standard, please call AWWA Engineering and Technical Services at 303.794.7711, FAX at 303.795.7603, write to the department at 6666 West Quincy Avenue, Denver, CO 80235-3098, or email at standards@awwa.org.

This is a preview of "AWWA C800-2012". Click here to purchase the full version from the ANSI store.

ANSI/AWWA C800-12 (Revision of ANSI/AWWA C800-05)



The Authoritative Resource on Safe Water®

AWWA Standard

Underground Service Line Valves and Fittings

SECTION 1: GENERAL

Sec. 1.1 Scope

This standard covers valves, fittings, service saddles, and meter setters for use in service line from the main through the meter valve or meter-setting appurtenance. Valves, fittings, and meter setters described in this standard include 1/2 in. (12.5 mm) through 2 in. (50.8 mm). Service saddles described have outlet sizes 1/2 in. (12.5 mm) through 2 in. (50.8 mm) and fit mains of 2 in. (50.8 mm) through 12 in. (304.8 mm). Valves include corporation stops and curb stops. Fittings include various types of couplings and adapters. Service saddles include various types of devices circumferentially attached to the main. Meter setters include various configurations of copper tubing, valves, and fittings for the holding of 5/8-in. (15.875-mm) through 2-in. (50.8-mm) meters.

1.1.1 *Installation.* The performance of products depends on proper installation. The purchaser must follow instructions supplied by or available from the manufacturer. If these instructions are not available, good installation practices shall be followed.