

ANSI/BHMA A156.12 – 2018

Revision of ANSI/BHMA A156.12-2013



INTERCONNECTED LOCKS



SPONSOR

BUILDERS HARDWARE MANUFACTURERS ASSOCIATION, INC.

AMERICAN NATIONAL STANDARDS INSTITUTE

Approved August 10, 2018

AMERICAN NATIONAL STANDARD

An American National Standard implies a consensus of those substantially concerned with its scope and provisions. An American National Standard is intended as a guide to aid the manufacturer, the consumer and the general public. The existence of an American National Standard does not in any respect preclude anyone, whether he has approved the standard or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standard. American National Standards are subject to periodic review and users are cautioned to obtain the latest editions.

CAUTION NOTICE: This American National Standard is permitted to be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken to reaffirm, revise, or withdraw this standard no later than five years from the date of publication. Purchasers of American National Standards receive current information on all standards by calling or writing the American National Standards Institute.

Published by
BUILDERS HARDWARE MANUFACTURERS ASSOCIATION, INC.
355 Lexington Avenue, New York, New York, 10017

Copyright © 2018 by the Builders Hardware Manufacturers
Association, Inc.

Not to be reproduced without
specific authorization from BHMA

Printed in the USA

This Standard was approved by ANSI under the Canvass Method. BHMA was accredited on 21 March 1983 by ANSI as a sponsor using the Canvass Method.

FOREWORD (This Foreword is not a part of ANSI/BHMA A156.12)

The general classification of builders hardware includes a wide variety of items which are divided into several categories. To recognize this diversity, a sectional classification system has been established. Interconnected Locks is one such section and this Standard is a result of the collective efforts of members of the Builders Hardware Manufacturers Association, Inc. who manufacture this product. The total Product Standards effort is, therefore, a collection of sections, each covering a specific category of items.

Performance tests and, where necessary, material and dimensional requirements have been established to insure safety and stability to which the public is entitled. There are no restrictions on design except for those dimensional requirements imposed for reasons given above.

This Standard is not intended to obstruct but rather to encourage the development of improved products, methods and materials. The BHMA recognizes that errors will be found, items will become obsolete, and new products, methods and materials will be developed. With this in mind, the Association plans to update, correct and revise these Standards on a regular basis.

In most cases, products have been described in grade levels related to performance. Choice of grade and specific product are to be made on the basis of utility, aesthetics, security objectives and end use desired.

The BHMA numbers which indicate functions of interconnected locks do not identify grade, finish, or design and are not intended to be used without necessary supplementary information. Individual manufacturer's catalogs are consulted.

Users of this Standard consult applicable local building codes as to requirements affecting the functions of locks used on fire doors and doors within a mean of egress. Some communities require use of exterior door locks having a dead bolt with a 1 in. (25.4 mm) projection for the purpose of providing greater security. Only functions compatible with the requirements of the applicable building codes are used.

TABLE OF CONTENTS

1. SCOPE	5
2. DEFINITIONS	5
3. GENERAL	8
4. DIMENSIONAL CHARACTERISTICS	8
5. DESCRIPTION AND FUNCTION NUMBERS OF SERIES 5000 INTERCONNECTED LOCKS	9
6. GENERAL TEST PARAMETERS	11
7 TEST EQUIPMENT AND FIXTURES	12
8 OPERATIONAL TESTS	20
9. CYCLE TESTS	23
10. STRENGTH TESTS	26
11. MATERIAL EVALUATION TESTS	29
12. SECURITY TESTS	30
13 FINISH TESTS	34
APPENDIX A USERS GUIDE (NOT A PART OF ANSI/BHMA A156.12)	35

1. SCOPE

1.1 This Standard establishes performance requirements for Interconnected Locks and includes operational, cycle, strength, material evaluation, security, and finish tests.

1.2 Tests described in this Standard are performed under laboratory conditions. In actual usage, results vary because of installation, door and frame construction, maintenance and environmental conditions.

1.3 **Grade Qualifications** (Also See Appendix A.) Manufacturers shall indicate the Grade level of their locks. Locks shall meet all tests for their grade listing. A Grade 1 lock shall meet all Grade 1 criteria, a Grade 2 lock shall meet all Grade 2 criteria, and a Grade 3 lock shall meet all Grade 3 criteria.

2. DEFINITIONS

2.1 **Armored Strike** A strike reinforced in such a way as to strengthen the frame to which it is applied.

2.2 **Auxiliary Lock** A lock having a latch bolt or dead bolt operated by a key, paddle and/or turn, and usually used in addition to a primary lock or latching device.

2.3 **Backset** The distance from the edge of the door measured at the centerline of the door thickness to the centerline of the function holes or cross bore.

2.4 **Bitting** 1. the number(s) which represent(s) the dimensions of the key, 2. the actual cut(s) or combination of a key

2.5 **Biometric Readers** Optical, Capacitive, Sound Energy, And Heat Sensitive Readers for decoding unique biometric features, including fingerprints, eye, facial, or speech recognition.

2.6 Bolts

2.6.1 **Auxiliary Dead Latch** A plunger which, when actuated, automatically locks a projected latch bolt against return by end pressure.

2.6.2 **Dead Bolt** A lock component having an end, which protrudes from, or is withdrawn into, the lock front by action of the lock mechanism. When the door is closed and the dead bolt thrown, it extends into a hole provided in the strike, locks the door, and does not retract with end pressure.

2.6.3 **Latch Bolt** A lock component having a beveled end which projects from the lock front in an extended position, but is forced back into the lock case by end pressure or drawn back by action of the lock mechanism. When the door is closed, the latch bolt projects into a hole provided in the strike, and holds the door in a closed position.

2.6.4 **Deadlocking Latch Bolt** A spring actuated latch bolt with a beveled end and incorporating a plunger which, when depressed, automatically locks the projected latch bolt against return by end pressure. Also called dead latch.

2.6.5 **Expanding or Interlocking Type Dead Bolt** A bolt which interlocks with its strike when fully engaged.

2.6.6 **Deadlocking Latch Bolt Plunger** A component of the latch bolt which, when actuated, automatically locks a projected latch bolt against return by end pressure.

2.7 **Bored Lock Series 4000** A lock installed in a round bored opening in the edge and face of a door.

2.8 **Cam** 1. a lock or cylinder component which transfers the rotational motion of a key or cylinder plug to the bolt works of a lock, 2. the bolt of a cam lock.