

ANSI/BHMA A156.2-2017

Revision of ANSI/BHMA A156.2-2011



BORED AND PREASSEMBLED LOCKS AND LATCHES



SPONSOR

BUILDERS HARDWARE MANUFACTURERS ASSOCIATION, INC.

AMERICAN NATIONAL INSTITUTE

Approved March 20, 2017

AMERICAN NATIONAL STANDARD

An American National Standard implies a consensus of those substantially concerned with its scope and provisions. An American National Standard is intended as a guide to aid the manufacturer, the consumer and the general public. The existence of an American National Standard does not in any respect preclude anyone, whether he has approved the Standard or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the Standard. American National Standards are subject to periodic review and users are cautioned to obtain the latest editions.

CAUTION NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken to reaffirm, revise, or withdraw this Standard no later than five years from the date of publication. Purchasers of American National Standards may receive current information on all Standards by calling or writing The American National Standards Institute.

Published by
BUILDERS HARDWARE MANUFACTURERS ASSOCIATION, INC.
355 Lexington Avenue New York, New York 10017
www.buildershardware.com

Copyright © 2017 by the Builders Hardware Manufacturers
Association, Inc.

Not to be reproduced without
specific authorization from BHMA

Printed in the USA

This Standard was first published July 1970 by the Builders Hardware Manufacturers Association, Inc. It was entitled "Standard 601 BHMA Product Standards Section F, Locks and Lock Trim." This Standard was approved by ANSI under the canvass method. BHMA was accredited on 21 March 1983 as a sponsor using the Canvass Method.

FOREWORD (This Foreword is not a part of ANSI/BHMA A156.2)

The general classification of builders hardware includes a wide variety of items which are divided into several categories. To recognize this diversity, a sectional classification system has been established. Locks and Lock Trim is one such section and this Standard is the result of the collective efforts of members of the Builders Hardware Manufacturers Association, Inc. who manufacture these products. The total Product Standards effort is therefore a collection of sections, each covering a specific category of items.

Performance tests and, where it has been necessary, dimensional requirements have been established to insure safety, security and stability to which the public is entitled. Performance criteria for resistance to surreptitious and forceful attack are not fully covered. There are no restrictions on design except for those dimensional requirements imposed for the reasons given above. It is also required that locks fit certain cut-out dimensions.

This Standard is not intended to obstruct but rather to encourage the development of improved products, methods and materials. The BHMA recognizes that errors will be found, items will become obsolete, and new products and methods will be developed. With this in mind, the Association will update, correct and revise these Standards on a regular basis. It shall also be the responsibility of manufacturers to request such appropriate revisions.

Bored locks have been described in three grade levels related to performance and security. Choice of grade and specific products are made on the basis of utility, aesthetics, security objectives and end use required.

The BHMA numbers which indicate functions of locks and latches do not identify grade, finish or design and are not intended to be used without necessary supplementary information. Individual manufacturer's catalogs are to be consulted.

Users of this Standard consult applicable local building codes as to requirements affecting the functions of locks used on fire doors and doors within a means of egress. Only functions compatible with the requirements of the applicable building codes are used.

TABLE OF CONTENTS

1. SCOPE.....	5
2. DEFINITIONS.....	5
3. GENERAL.....	6
5. DESCRIPTION AND FUNCTION NUMBERS OF SERIES 2000 PRE-ASSEMBLED LOCKS.....	8
6. DESCRIPTION AND FUNCTION NUMBERS OF SERIES 4000 BORED LOCKS AND LATCHES.....	10
7. GENERAL TEST PARAMETERS.....	14
SAMPLE TEST LOCKS.....	14
8 TEST EQUIPMENT AND FIXTURES	15
9. OPERATIONAL TESTS.....	17
10 STRENGTH TESTS.....	20
11. CYCLE TEST	23
12. SECURITY TESTS.....	25
13. MATERIAL EVALUATION TESTS.....	28
14 FINISH TESTS.....	30
APPENDIX A USERS GUIDE (NOT A PART OF ANSI/BHMA A156.2)	32

1. SCOPE

1.1 This Standard establishes performance requirements for bored and preassembled locks and latches, and includes dimensional criteria, operational tests, strength tests, cycle tests, security tests, material evaluation tests, and finish tests.

1.2 Tests described in this Standard are performed under laboratory conditions. In actual usage, results vary because of installation, door and frame construction, maintenance and environmental conditions.

1.3 **Grade Qualifications** Manufacturers shall indicate the Grade level of their locks. Locks shall meet all tests for their grade listing. A Grade 1 lock shall meet all Grade 1 criteria, a Grade 2 lock shall meet all Grade 2 criteria, and a Grade 3 lock shall meet all Grade 3 criteria.

2. DEFINITIONS

2.1 **Backset** The distance from the edge of the door measured at the centerline of the door thickness to the centerline of the cylinder or spindle.

2.2 Bolts

2.2.1 **Auxiliary Dead Latch** A plunger which, when actuated, automatically locks a projected latch bolt against return by end pressure.

2.2.2 **Latch Bolt** A lock component having a beveled end which projects from the lock front in its extended position, but is forced back into the lock case by end pressure or drawn back by action of the lock mechanism. When the door is closed, the latch bolt projects into a hole provided in the strike, holding the door in a closed position.

2.2.3 **Dead Locking Latch Bolt** A type latch bolt incorporating a plunger which, when depressed, automatically locks the projected latch bolt against return by end pressure. Also called dead latch.

2.3 Cylinders

2.3.1 **Cylinder** The subassembly of a lock containing a plug with a keyway and cylinder body with tumbler mechanism.

2.3.2 **Cylinder Body** The portion of a cylinder that surrounds the plug and contains the tumbler mechanism.

2.3.3 **Cylinder Plug** A component of the cylinder within the body which is actuated when the correct key is inserted.

2.3.4 **Interchangeable Core Cylinder** A cylinder that is removable from the lock with a designated key without disassembly of the lock.

2.4 **Lever Catch** Also called knob catch. The spring activated retainer which engages the lever in order to maintain its attachment to the lever spindle.

2.5 **Lock Front** A plate fastened to the edge of a door through which the bolt(s) pass.

2.6 Lock Series

2.6.1 **Preassembled Lock Series 2000** A lock fitting into a notched cutout in a door.

2.6.2 **Bored Lock Series 4000** A lock installed in a round bored opening in the edge and face of a door.

2.7 **Operating Trim** Lock components including levers, knobs, paddles, or handlesets and equivalent components.

2.8 Push Button and Related Terms

2.8.1 **Push Button Code Mechanism** A mechanism used in place of, or in conjunction with a key and cylinder.

2.8.2 **Push Button** A single inside locking device that when depressed, locks the outside operating trim.

2.8.3 **Turn Button** A single inside locking device that when rotated, locks the outside operating trim.

2.8.4 **Combination Push Button/Turn Button** A single inside locking device that when depressed, locks the outside operating trim, or when depressed and rotated maintains the locked state.