

BHMA A156.23 - 2004
Revision of:
ANSI/BHMA A156.23 - 1999



AMERICAN NATIONAL STANDARD
FOR
ELECTROMAGNETIC LOCKS



SPONSOR
BUILDERS HARDWARE MANUFACTURERS ASSOCIATION, INC.
ANSI APPROVED 5/26/2004

AMERICAN NATIONAL STANDARDS INSTITUTE, INC.

AMERICAN NATIONAL STANDARD

An American National Standard implies a consensus of those substantially concerned with its scope and provisions. An American National Standard is intended as a guide to aid the manufacturer, the consumer and the general public. The existence of an American National Standard does not in any respect preclude anyone, whether he has approved the Standard or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the Standard. American National Standards are subject to periodic review and users are cautioned to obtain the latest editions.

CAUTION NOTICE: This American National Standard is permitted to be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken to reaffirm, revise, or withdraw this standard no later than five years from the date of publication. Purchasers of American National Standards receive current information on all standards by calling or writing The American National Standards Institute.

Published by
BUILDERS HARDWARE MANUFACTURERS ASSOCIATION, INC.
355 Lexington Avenue, New York, New York, 10017

Copyright © 2004 by the Builders Hardware Manufacturers
Association, Inc.

Not to be reproduced without
specific authorization from BHMA

Printed in the USA

This Standard was developed by the Builders Hardware Manufacturers Association, Inc. It was approved by ANSI under the canvass method. BHMA was accredited on 21 March 1983 as a sponsor using the Canvass Method.

FOREWORD (This Foreword is not a part of ANSI/BHMA A156.23)

The general classification of builders hardware includes a wide variety of items which are divided into several categories. To recognize this diversity, a sectional classification system has been established. Electromagnetic locks is one such section and this Standard is the result of the collective efforts of members of the Builders Hardware Manufacturers Association, Inc. who manufacture these products. The total product standards effort is therefore, a collection of sections, each covering a specific category of items.

Strength, cycle, operational tests and where it has been necessary, material and dimensional requirements have been established to insure safety and stability to which the public is entitled. There are no restrictions on design except for those dimensional requirements imposed for the reasons given above.

This Standard is not intended to obstruct but rather to encourage the development of improved products, methods and materials. The BHMA recognizes that errors will be found, items will become obsolete, and new products and methods will be developed. With this in mind the Association plans to update, correct and revise these Standards on a regular basis. It shall also be the responsibility of manufacturers to request such appropriate revisions.

The BHMA numbers which indicate functions of electromagnetic locks do not identify size or design and are not intended to be used without necessary supplementary information. Individual manufacturer's catalogs should be consulted.

TABLE OF CONTENTS

Section	Page
1. SCOPE.....	5
2. DEFINITIONS.....	5
3. GENERAL.....	6
4. TEST METHODS.....	6
5. STRENGTH TESTS.....	7
6. ELECTRICAL TESTS.....	8
7. CYCLE TEST.....	9
8. FINISH TESTS.....	10
9. EXPLANATION OF IDENTIFYING NUMBERS.....	11
10. TYPICAL ILLUSTRATIONS, AND TYPE NUMBER DESCRIPTIONS.....	12
APPENDIX A (NOT A PART OF ANSI/BHMA A156.23).....	15

1. SCOPE

1.1 This Standard establishes requirements for electromagnetic locks and includes cyclical, dynamic, operational, strength and finish tests. This product is used for access control.

1.2 Tests described in this Standard are performed under laboratory conditions. In actual usage, results vary because of installation, maintenance, and environmental conditions.

2. DEFINITIONS

2.1 **Electromagnetic Lock.** An electrically powered lock. It locks or unlocks a door by the activation or deactivation of an electromagnet coupled to an armature.

2.1.1 **Direct Pull** The mounting arrangement of an electromagnetic door lock whereby an opening force applied to the face of the door is directly opposed by the attraction of the magnet and armature along an axis perpendicular to the face of the door, which is obtained when the contact plane between magnet and armature is parallel to the door face.

2.1.2 **Shear Lock** The mounting arrangement of an electromagnetic door lock whereby the attraction between electromagnet and armature moves one or the other (usually the smaller armature) not only into contact with each other but also into a position of mechanical restraint by a third member which prevents sliding separation (shear) of the magnet and armature along their contact plane. To unlock, the moving member is then retracted into its original resting position by mechanical, magnetic, gravitational, or other force.

2.2 **Armature** A plate attracted by the energized electromagnet component of the lock and when in contact with the magnet, resistant to being separated from the magnet. Also called a strike.

2.3 **Indoor-Only** Electromagnetic locks which are not suitable for continuous exposure to an outdoor environment.