

ANSI/BHMA A156.24-2012

Revision of BHMA A156.24 - 2003



STANDARD

FOR

DELAYED EGRESS LOCKING SYSTEMS



SPONSOR

BUILDERS HARDWARE MANUFACTURERS ASSOCIATION, INC.

AMERICAN NATIONAL STANDARDS INSTITUTE

Approved December 12, 2012

AMERICAN NATIONAL STANDARD

An American National Standard implies a consensus of those substantially concerned with its scope and provisions. An American National Standard is intended as a guide to aid the manufacturer, the consumer and the general public. The existence of an American National Standard does not in any respect preclude anyone, whether they have approved the Standard or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the Standard. American National Standards are subject to periodic review and users are cautioned to obtain the latest editions.

CAUTION NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken to reaffirm, revise, or withdraw this standard no later than five years from the date of publication. Purchasers of American National Standards may receive current information on all standards by calling or writing The American National Standards Institute.

Published by
BUILDERS HARDWARE MANUFACTURERS ASSOCIATION, INC.
355 Lexington Avenue, New York, New York, 10017

Copyright 2012 by the Builders Hardware Manufacturers
Association, Inc.

Not to be reproduced without
specific authorization from BHMA

Printed in the USA

This Standard was developed by the Builders Hardware Manufacturers Association, Inc. It was approved by ANSI under the canvass method. BHMA was accredited on 21 March 1983 as a sponsor using the Canvass Method.

FOREWORD (This Foreword is not a part of ANSI/BHMA A156.24)

The general classification of builders hardware includes a wide variety of items which are divided into several categories. To recognize this diversity, a sectional classification system has been established. This Standard is the result of the collective efforts of members of the Builders Hardware Manufacturers Association, Inc. (BHMA) who manufacture these products. The total Product Standards effort is therefore, a collection of sections, each covering a specific category of items.

Strength, cycle, and operational tests have been established to insure safety and stability to which the public is entitled. There are no restrictions on design.

This Standard is not intended to obstruct but rather to encourage the development of improved products, methods and materials. BHMA recognizes that errors will be found, items will become obsolete, and new products and methods will be developed. With this in mind the Association plans to update, correct and revise these Standards on a regular basis. It shall also be the responsibility of manufacturers to request such appropriate revisions.

The BHMA numbers that indicate functions of delayed egress locking systems do not identify size of design and are not intended to be used without necessary supplementary information. Individual manufacturer's catalogs should be consulted.

TABLE OF CONTENTS

1. SCOPE	5
2. DEFINITIONS	5
3. GENERAL	6
4. TEST METHODS.....	7
5. TESTS	7
APPENDIX (NOT A PART OF ANSI/BHMA A156.24).....	9

1. SCOPE

1.1 This standard covers products used in connection with conventional exit devices or locks causing the doors to remain locked after releasing actuation for a predetermined length of time. Performance criteria are included for functional, cycle, operational, fail-safe and overload requirements.

1.2 Tests described in this Standard are performed under laboratory conditions. In actual usage, results vary because of installation, maintenance, and environmental conditions.

2. DEFINITIONS

2.1 Delayed Egress Locking Systems A delayed egress locking system consists of a device or combination of devices arranged to be locked in the direction of egress for a predetermined time after the normal releasing process has been initiated. After the predetermined time, the door allows egress.

2.2 Loss of Power Electrical power failure or voltage drop in the building or at the delayed egress locking system to the extent that the lock will release.

2.3 Nuisance Delay It is the period of time before the delayed egress cycle begins. It deters initiating the irreversible process of delayed egress in the event of accidental bumping of the door or actuating device.

2.4 Rated Line Voltage. The operating voltage specified by the manufacturer of a delayed egress locking system for that lock.