

This is a preview of "BS 6349-8:2007". [Click here to purchase the full version from the ANSI store.](#)

**BRITISH STANDARD**

# **Maritime structures –**

## **Part 8: Code of practice for the design of Ro-Ro ramps, linkspans and walkways**

ICS 47.020.99; 93.140

**BSi**  
British Standards

This is a preview of "BS 6349-8:2007". [Click here to purchase the full version from the ANSI store.](#)

The BSI copyright notice displayed in this document indicates when the document was last issued.

© BSI 2007

ISBN 978 0 580 50203 3

The following BSI references relate to the work on this standard:

Committee reference B/525/11

Draft for comment 06/30124387 DC

### **Publication history**

First published April 2007

### **Amendments issued since publication**

<b>Amd. no.</b>	<b>Date</b>	<b>Text affected</b>
-----------------	-------------	----------------------

---

This is a preview of "BS 6349-8:2007". [Click here to purchase the full version from the ANSI store.](#)

Foreword *iii*

<b>0</b>	Introduction	1
<b>1</b>	Scope	3
<b>2</b>	Normative references	4
<b>3</b>	Terms, definitions and symbols	5
<b>4</b>	General recommendations	10
<b>5</b>	Types of structure	16
<b>6</b>	Geometry	24
<b>7</b>	Loads, movements and factors	38
<b>8</b>	Structural analysis and design	57
<b>9</b>	Furniture, finishes and corrosion protection	62

### Annexes

Annex A (informative) Load combinations and partial safety factors 66

Annex B (informative) Vehicle loadings 70

Bibliography 71

### List of figures

Figure 1	– Linkspan types	18
Figure 2	– Passenger walkways – Type A – Motorized carriage at ship entry, swivel at building	21
Figure 3	– Passenger walkways – Type B – Motorized carriage at ship entry plus slave carriage and pod	22
Figure 4	– Passenger walkways – Type C – Traversing drawbridge on boarding pod	23
Figure 5	– Passenger walkways – Type D – Single tunnel supported on rail mounted gantry	23
Figure 6	– Roadway width and recommended edge clearance at raised kerbs	25
Figure 7	– Plan geometry of linkspans	26
Figure 8	– Interface diagrams	28
Figure 9	– Plan clearances for design	30
Figure 10	– Vertical geometry guidelines for normal circumstances	34
Figure 11	– Preferred transition geometry	37
Figure 12	– Extreme transition changes	37
Figure 13	– Axle weight spacings	50
Figure 14	– Loading influence line	51
Figure 15	– Definition of primary support path for suspension system	61

### List of tables

Table 1	– Minimum roadway widths	24
Table 2	– Suggested motions of moored Ro-Ro vessels in harbour	32
Table 3	– Maximum operational longitudinal gradients for articulated elements (not including local slopes at ship ramp interface ends)	36
Table 4	– Vertical clearances	38
Table 5	– Values of factor $\gamma_{FL}$ for superimposed dead loads	39
Table 6	– Values of factor $\gamma_{FL}$ for dead loads from ship ramps and finger flaps	40
Table 7	– Wind on enclosed walkways	42
Table 8	– Values of factor $\gamma_{FL}$ for snow loads	43
Table 9	– Values of factor $\gamma_{FL}$ for water current loading	44