

This is a preview of "BS EN 60296:2012". [Click here to purchase the full version from the ANSI store.](#)

BS EN 60296:2012



BSI Standards Publication

Fluids for electrotechnical applications — Unused mineral insulating oils for transformers and switchgear

NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW

raising standards worldwide™



This is a preview of "BS EN 60296:2012". [Click here to purchase the full version from the ANSI store.](#)

This British Standard is the UK implementation of EN 60296:2012. It is identical to IEC 60296:2012. It supersedes BS EN 60296:2004 which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee GEL/10, Fluids for electrotechnical applications.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2012

Published by BSI Standards Limited 2012

ISBN 978 0 580 69883 5

ICS 29.040

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 May 2012.

Amendments issued since publication

Amd. No.	Date	Text affected
-----------------	-------------	----------------------

This is a preview of "BS EN 60296:2012". [Click here to purchase the full version from the ANSI store.](#)

NORME EUROPÉENNE
EUROPÄISCHE NORM

April 2012

ICS 29.040

Supersedes EN 60296:2004 + corr. Sep.2004

English version

**Fluids for electrotechnical applications -
Unused mineral insulating oils for transformers and switchgear
(IEC 60296:2012)**

Fluides pour applications
électrotechniques -
Huiles minérales isolantes neuves pour
transformateurs et appareillages de
connexion
(CEI 60296:2012)

Flüssigkeiten für elektrotechnische
Anwendungen -
Neue Isolieröle auf Mineralölbasis für
Transformatoren und Schaltgeräte
(IEC 60296:2012)

This European Standard was approved by CENELEC on 2012-03-26. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Management Centre: Avenue Marnix 17, B - 1000 Brussels

This is a preview of "BS EN 60296:2012". [Click here to purchase the full version from the ANSI store.](#)

Foreword

The text of document 10/878/FDIS, future edition 4 of IEC 60296, prepared by IEC/TC 10 "Fluids for electrotechnical applications" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 60296:2012.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2012-12-26
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2015-03-26

This document supersedes EN 60296:2004 + corrigendum September 2004.

EN 60296:2012 includes the following significant technical changes with respect to EN 60296:2004:

- specifications for corrosive sulphur compounds that can lead to copper sulphide deposition in transformers (in non-passivated and passivated oils);
- definitions of additives in oil; and
- re-insertion of a missing note on oxidation.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

Endorsement notice

The text of the International Standard IEC 60296:2012 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following note has to be added for the standard indicated:

IEC 60867 NOTE Harmonized as EN 60867.

This is a preview of "BS EN 60296:2012". [Click here to purchase the full version from the ANSI store.](#)

ANNEX ZA
(normative)

**Normative references to international publications
with their corresponding European publications**

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
-	-	Surface active agents - Determination of interfacial tension of solutions of surface active agents by the stirrup or ring method	EN 14210	-
IEC 60076-2	-	Power transformers - Part 2: Temperature rise for liquid-immersed transformers	EN 60076-2	-
IEC 60156	-	Insulating liquids - Determination of the breakdown voltage at power frequency - Test method	EN 60156	-
IEC 60247	-	Insulating liquids - Measurement of relative permittivity, dielectric dissipation factor (tan δ) and d.c. resistivity	EN 60247	-
IEC 60422	-	Mineral insulating oils in electrical equipment - Supervision and maintenance guidance	EN 60422	-
IEC 60475	-	Method of sampling insulating liquids	EN 60475	-
IEC 60628	1985	Gassing of insulating liquids under electrical stress and ionization	HD 488 S1	1987
IEC 60666	-	Detection and determination of specified additives in mineral insulating oils	EN 60666	-
IEC 60814	-	Insulating liquids - Oil-impregnated paper and pressboard - Determination of water by automatic coulometric Karl Fischer titration	EN 60814	-
IEC 60970	-	Insulating liquids - Methods for counting and sizing particles	EN 60970	-
IEC 61125 + corr. September + A1	1992 1992 2004	Unused hydrocarbon-based insulating liquids - Test methods for evaluating the oxidation stability	EN 61125 + A1	1993 2004
IEC 61198	-	Mineral insulating oils - Methods for the determination of 2-furfural and related compounds	EN 61198	-
IEC 61619	-	Insulating liquids - Contamination by polychlorinated biphenyls (PCBs) - Method of determination by capillary column gas chromatography	EN 61619	-
IEC 61620	-	Insulating liquids - Determination of the dielectric dissipation factor by measurement of the conductance and capacitance - Test method	EN 61620	-
IEC 61868	-	Mineral insulating oils - Determination of kinematic viscosity at very low temperatures	EN 61868	-

This is a preview of "BS EN 60296:2012". [Click here to purchase the full version from the ANSI store.](#)

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/IEC</u>	<u>Year</u>
IEC 62021-1	-	Insulating liquids - Determination of acidity - Part 1: Automatic potentiometric titration	EN 62021-1	-
IEC 62021-2	-	Insulating liquids - Determination of acidity - Part 2: Colourimetric titration	EN 62021-2	-
IEC 62535	2008	Insulating liquids - Test method for detection of potentially corrosive sulphur in used and unused insulating oil	EN 62535	2009
ISO 2719	-	Determination of flash point - Pensky-Martens closed cup method	EN ISO 2719	-
ISO 3016	-	Petroleum products - Determination of pour point	-	-
ISO 3104	-	Petroleum products - Transparent and opaque liquids - Determination of kinematic viscosity and calculation of dynamic viscosity	EN ISO 3104	-
ISO 3675	-	Crude petroleum and liquid petroleum products - Laboratory determination of density - Hydrometer method	EN ISO 3675	-
ISO 12185	-	Crude petroleum and petroleum products - Determination of density - Oscillating U-tube method	EN ISO 12185	-
ISO 14596	-	Petroleum products - Determination of sulfur content - Wavelength-dispersive X-ray fluorescence spectrometry	EN ISO 14596	-
ASTM D971	-	Standard test method for interfacial tension of oil against water by the ring method	-	-
ASTM D7150	-	Standard test method for the determination of gassing characteristics of insulating liquids under thermal stress at low temperature	-	-
DIN 51353	-	Testing of insulating oils; detection of corrosive sulfur; silver strip test	-	-
IP 346	-	Determination of polycyclic aromatics in lubricant base oils and asphaltene free petroleum fractions - Dimethylsulfoxide refractive method	-	-
IP 373	-	Determination of the sulphur content of light and middle distillates - Oxidative microcoulometry	-	-

This is a preview of "BS EN 60296:2012". [Click here to purchase the full version from the ANSI store.](#)

ANNEX ZD
(normative)

Special national conditions

Special national condition: National characteristic or practice that cannot be changed even over a long period, e.g. climatic conditions, electrical earthing conditions.

NOTE If it affects harmonization, it forms part of the European Standard / Harmonization Document.

For the countries in which the relevant special national conditions apply these provisions are normative, for other countries they are informative.

<u>Clause</u>	<u>Special national condition</u>
---------------	-----------------------------------

7.1	Austria
------------	----------------

The restricted limits of Chapter 7.1 "Higher oxidation stability and low sulphur content" are to be followed as general specification for oxidation stability (See Table 2).

Because of exposed geographical location and cold weather conditions (snow) transformers are not always accessible for service, which sometimes leads to unforeseen longer service intervals and therefore higher oxidation stability of transformer oil is required.

For the same reason and to have an additional criterion for evaluation of oil quality, Interfacial Tension (IFT) is to be used as a general requirement (Table 2, Footnote f)"

This is a preview of "BS EN 60296:2012". [Click here to purchase the full version from the ANSI store.](#)

CONTENTS

INTRODUCTION.....	6
1 Scope.....	7
2 Normative references	7
3 Terms and definitions	9
4 Properties of oil	10
4.1 Functional properties.....	10
4.2 Refining and stability	10
4.3 Performance.....	10
4.4 Health, safety and environment (HSE) properties	10
5 Classification, identification, general delivery requirements and sampling.....	11
5.1 Classification.....	11
5.1.1 Classes	11
5.1.2 Antioxidant additive (inhibitor) content.....	11
5.1.3 Lowest cold start energizing temperature (LCSET)	11
5.2 Requirements	11
5.3 Miscibility	11
5.4 Identification and general delivery requirements.....	11
5.5 Sampling	12
6 Properties, their significance and test methods.....	12
6.1 Viscosity.....	12
6.2 Pour point	12
6.3 Water content.....	12
6.4 Breakdown voltage.....	13
6.5 Dielectric dissipation factor (DDF)	13
6.6 Appearance	13
6.7 Acidity.....	13
6.8 Interfacial tension (IFT)	13
6.9 Sulphur content	13
6.10 Corrosive and potentially corrosive sulphur	13
6.11 Additives (see 3.4)	14
6.11.1 General	14
6.11.2 Antioxidant additives (see 3.5).....	14
6.11.3 Metal passivators	14
6.11.4 Pour point depressants.....	15
6.12 Oxidation stability.....	15
6.13 Gassing tendency.....	15
6.14 Electrostatic charging tendency (ECT).....	15
6.15 Flash point	15
6.16 Density.....	15
6.17 Polycyclic aromatic content (PCAs)	16
6.18 Polychlorinated biphenyl content (PCBs).....	16
6.19 2-Furfural (2-FAL) and related compounds content.....	16
6.20 Particle content	16