

This is a preview of "BS ISO 4548-7:2012". Click [here](#) to purchase the full version from the ANSI store.

BS ISO 4548-7:2012



BSI Standards Publication

Methods of test for full-flow lubricating oil filters for internal combustion engines

Part 7: Vibration fatigue test

NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW

raising standards worldwide™



This is a preview of "BS ISO 4548-7:2012". [Click here to purchase the full version from the ANSI store.](#)

This British Standard is the UK implementation of ISO 4548-7:2012. It supersedes BS 7403-7:1991 which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee MCE/21/5, Filters for lubricating oil.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2012. Published by BSI Standards Limited 2012

ISBN 978 0 580 71007 0

ICS 27.020

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 30 November 2012.

Amendments issued since publication

Date	Text affected
------	---------------

This is a preview of "BS ISO 4548-7:2012". [Click here to purchase the full version from the ANSI store.](#)

Second edition
2012-10-15

Methods of test for full-flow lubricating oil filters for internal combustion engines —

Part 7: Vibration fatigue test

*Méthodes d'essai des filtres à huile de lubrification à passage intégral
pour moteurs à combustion interne —*

Partie 7: Essai de fatigue aux vibrations



Reference number
ISO 4548-7:2012(E)

© ISO 2012

This is a preview of "BS ISO 4548-7:2012". Click here to purchase the full version from the ANSI store.



COPYRIGHT PROTECTED DOCUMENT

© ISO 2012

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

This is a preview of "BS ISO 4548-7:2012". [Click here to purchase the full version from the ANSI store.](#)

Contents

Page

Foreword	iv
1 Scope	1
2 Normative reference	1
3 Terms, definitions and graphical symbols	1
3.1 Definitions.....	1
3.2 Graphical symbols.....	1
4 Principle	1
5 Test rig	1
6 Test liquid	2
7 Vibration fatigue test	2
8 Test report	4
Bibliography	6

This is a preview of "BS ISO 4548-7:2012". [Click here to purchase the full version from the ANSI store.](#)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 4548-7 was prepared by Technical Committee ISO/TC 70, *Internal combustion engines*, Subcommittee SC 7, *Tests for lubricating oil filters*.

This second edition cancels and replaces the first edition (ISO 4548-7:1990), which has been technically revised.

ISO 4548 consists of the following parts, under the general title *Methods of test for full-flow lubricating oil filters for internal combustion engines*:

- *Part 1: Differential pressure/flow characteristics*
- *Part 2: Element by-pass valve characteristics*
- *Part 3: Resistance to high differential pressure and to elevated temperature*
- *Part 4: Initial particle retention efficiency, life and cumulative efficiency (gravimetric method)*
- *Part 5: Method of test for cold start simulation and hydraulic pulse durability*
- *Part 6: Static burst pressure test*
- *Part 7: Vibration fatigue test*
- *Part 9: Inlet and outlet anti-drain valve tests*
- *Part 11: Self-cleaning filters*
- *Part 12: Filtration efficiency using particle counting, and contaminant retention capacity*
- *Part 13: Static burst pressure test for composite pressure vessel materials*
- *Part 15: Vibration fatigue test with composite materials*

This is a preview of "BS ISO 4548-7:2012". [Click here to purchase the full version from the ANSI store.](#)

Methods of test for full-flow lubricating oil filters for internal combustion engines —

Part 7: Vibration fatigue test

1 Scope

This part of ISO 4548 specifies a method of testing the constructional integrity of full-flow lubricating oil filters to withstand engine vibrations. This test is intended for application to spin-on type filters and detachable filters with disposable elements with a maximum flow rate of 100 l/min.

This test method is intended for test parts made from materials that do not experience mechanical property changes within the temperature range experienced in service. The test may be applied to other filters if thought applicable by agreement between the filter manufacturer and the purchaser.

2 Normative reference

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 4548-1, *Methods of test for full-flow lubricating oil filters for internal combustion engines — Part 1: Differential pressure/flow characteristics*

3 Terms, definitions and graphical symbols

3.1 Definitions

For the purposes of this document, the terms and definitions given in ISO 4548-1 apply.

3.2 Graphical symbols

The graphical symbols used in this part of ISO 4548 are in accordance with ISO 1219 [1].

4 Principle

Integrally mounted oil filter assemblies, including filter heads, adaptors, mounting brackets, etc., are subjected to forcing frequencies due to engine or installation vibrations. The test method specified in this part of ISO 4548 verifies the ability of the filter assembly to withstand these vibrations for a predetermined number of cycles, while under pressure.

5 Test rig

The test rig shall comprise the following components, together with the necessary tubing, connectors and supports (see Figure 1):

- a) electro-mechanical vibrator, together with the necessary hardware and electronics to control and monitor displacement, velocity and acceleration;