

This is a preview of "BS EN 50050-2:2013". [Click here to purchase the full version from the ANSI store.](#)

BS EN 50050-2:2013



BSI Standards Publication

Electrostatic hand-held spraying equipment — Safety requirements -

Part 2: Hand-held spraying equipment for
ignitable coating powder

bsi.

...making excellence a habit.™

This is a preview of "BS EN 50050-2:2013". [Click here to purchase the full version from the ANSI store.](#)

This British Standard is the UK implementation of EN 50050-2:2013. Together with BS EN 50050-1:2013 and BS EN 50050-3:2013 it supersedes BS EN 50050:2006 which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee EXL/31/-/1, Electrostatic spray guns.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2014.
Published by BSI Standards Limited 2014

ISBN 978 0 580 75856 0
ICS 29.260.20; 87.100

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 March 2014.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

This is a preview of "BS EN 50050-2:2013". [Click here to purchase the full version from the ANSI store.](#)

EUROPÄISCHE NORM

November 2013

ICS 87.100

Supersedes EN 50050:2006 (partially)

English version

Electrostatic hand-held spraying equipment - Safety requirements - Part 2: Hand-held spraying equipment for ignitable coating powder

Équipement manuel de projection
électrostatique -
Exigences de sécurité -
Partie 2: Équipement manuel de
projection de poudre de revêtement
inflammable

Elektrostatische Handsprüheinrichtungen -
Sicherheitsanforderungen -
Teil 2: Handsprüheinrichtungen für
entzündbares Beschichtungspulver

This European Standard was approved by CENELEC on 2013-10-14. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B - 1000 Brussels

Contents

Page

Foreword	3
0 Introduction	4
0.1 Process	4
0.2 Explosion hazards	4
0.3 Electric hazards	4
1 Scope	6
2 Normative references	7
3 Terms and definitions	8
4 Requirements for hand-held spraying equipment for ignitable coating powders	11
4.1 General requirements	11
4.2 Special requirements for hand-held spraying equipment with corona charging	11
4.3 Requirements for the accessories	12
5 Tests	12
5.1 General	12
5.2 General tests	12
5.3 Conditioning test	13
5.4 Tests for electrical safety (not applicable to triboelectrical applicators)	13
5.5 Ignition test	14
5.6 Tests of the accessories	14
6 Information for use	15
6.1 General	15
6.2 Instruction manual	15
6.3 Marking of electrostatic hand-held spraying equipment and associated control devices	17
Annex A (normative) Test for ignition protection using a shunt and an oscilloscope	20
Annex B (normative) Ignition test within the gas mixture	21
B.1 General	21
B.2 Preparations	21
B.3 Preliminary test	21
B.4 Test	22
B.5 Result	22
Annex C (informative) Quality assurance systems for electrostatic spraying equipment	23
C.1 General	23
C.2 Electrical assembly	23
C.3 Mechanical assembly	24
C.4 Tests	24
Annex D (normative) Requirements for explosion protection and prevention for ionisators	25
Annex ZY (informative) Significant changes between this European Standard and EN 50050:2006	26
Annex ZZ (informative) Coverage of Essential Requirements of EU Directives	28
Bibliography	29
Tables	
Table 1 — Test intervals	17
Table D.1 — Requirements for ionisators	25

This is a preview of "BS EN 50050-2:2013". [Click here to purchase the full version from the ANSI store.](#)

This document (EN 50050-2:2013) has been prepared by SC 31-8, "Electrostatic painting and finishing equipment", of CLC/TC 31, "Electrical apparatus for potentially explosive atmospheres".

The following dates are fixed:

- latest date by which this document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2014-10-14
- latest date by which the national standards conflicting with this document have to be withdrawn (dow) 2016-10-14

In combination with EN 50050-1:2013 and EN 50050-3:2013, this document supersedes EN 50050:2006.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a mandate given to CENELEC by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive(s).

For the relationship with EU Directive(s) see informative Annex ZZ, which is an integral part of this document.

0.1 Process

During the electrostatic coating process the coating powder is transported in an air stream, or by air, from a powder hopper or other container, up to an applicator. As the powder particles are passing the applicator they are electrostatically charged by means of a high voltage in the range of some tens of kilovolts or triboelectrically and ejected in the form of a cloud which is directed towards the workpiece. The charged powder particles of the cloud are attracted by and applied to the earthed workpiece.

Powder, that is not applied to the workpiece (overspray) is removed by a exhaust ventilation system or other means and transported into the powder recovery unit.

After the coating process the workpieces are introduced into an oven where the powder is melted and cured into a coherent coating.

0.2 Explosion hazards

0.2.1 An explosion can occur, if

- the concentration of coating powder in air is above the lower explosion limit,
- an ignition source of appropriate energy for this coating powder cloud is present.

Ignition sources could be, for instance, a hot surface, a naked flame, an electric arc or a spark.

An explosion could be prevented, if at least one condition is avoided. Because it is very difficult to exclude the possibility of ignitable discharges completely, the main focus should be the prevention of ignitable concentrations of coating powder in air.

0.2.2 Deflagration of explosive atmospheres is only possible within a given range of concentration above the lower explosion limit.

NOTE 1 If an explosive cloud of coating powder and air is trapped into a closed room, an explosion can lead to a fatal increase of pressure.

NOTE 2 The particle size distribution of coating powder is usually in the range of 5 μm to 120 μm .

NOTE 3 Coating powder in air is not evenly distributed inside a given volume, therefore it is possible that a part of the mixture is within the ignitable concentration range. An upper limit is safety-related not applicable.

0.2.3 It is important that deposits of powder are not allowed to accumulate within the spraying areas for they may be whirled up and give rise to an explosive atmosphere. This does not apply to deposits on filter devices and accumulations of coating powder in hoppers where filters and hoppers are integrated in the spraying area and are designed to collect the coating powder. See 4.6 of EN 12981:2005.

0.2.4 Particular attention should be paid to the prevention of electrostatic charges on different surfaces located in the vicinity of the powder cloud. This could apply to e.g. workpieces during the coating process. Grounding is very critical to the prevention of electrostatic charge to any conductive objects in the spray area.

0.3 Electric hazards

0.3.1 Electric shock (by direct or indirect contact) can be generated, for instance, by contact with

- live parts, which are not insulated for operational reasons,
- conductive parts, which are not connected to dangerous voltage during normal operation, but only in case of failure,
- insulated live parts with insufficient or damaged insulation due to external impact.

0.3.2 Inadequate earthing may occur, for instance, due to

- faulty connections to the protective earthing system,
- a too high resistance to earth (e. g. contamination by coating powder).

This is a preview of "BS EN 50050-2:2013". [Click here to purchase the full version from the ANSI store.](#)

0.3.4 ~~Control and safety systems.~~

0.3.4 Hazardous electrostatic discharges could be generated, for instance, by non-earthed conductive components or by large insulating surfaces, especially if they are backed with conductive material.

This is a preview of "BS EN 50050-2:2013". [Click here to purchase the full version from the ANSI store.](#)

1.1 This European Standard specifies the requirements for hand-held or hand-operated electrostatic spraying equipment for ignitable coating powders within a temperature range from 5 °C to 40 °C to be used in explosive atmospheres generated by their own spray cloud.

This European Standard deals with all electrical hazards significant for the electrostatic spraying of coating powders, which could also contain small quantities of added metal particles, if the work is carried out under conditions recommended by the manufacturer. In particular, this includes ignition hazards resulting from the generated explosive atmosphere. This European Standard specifies the design-related and test requirements for electrostatic spraying equipment of type A-P according to Table 1 of EN 50177:2009.

1.2 With regard to explosion protection and prevention measures, this standard also applies to ionisators with corona charging. Ionisators used together with or under similar conditions as electrostatic spraying equipment for ignitable coating powders are considered to be equipment of group II, category 2D for use in potentially explosive areas of zone 21 or 22. All other parts of ionisators are considered to be equipment of category 3D if they are installed or used in potentially explosive areas of zone 22, see Annex D.

1.3 Electrostatic applicators are considered to be equipment of group II, category 2D for use in potentially explosive areas of zone 21 or 22, which have been generated by the equipment itself. All other parts of hand-held electrostatic spraying equipment are considered to be equipment of category 3D if they are installed or used in potentially explosive areas of zone 22.

1.4 All other significant hazards relevant for applicators (e.g. ejection of powder, mechanical strength, electrical hazards (apart from the electrostatic hazards)), noise, explosion, contact with or inhalation of dangerous substances, ergonomics) are covered by EN 1953.

1.5 This European Standard also gives details regarding quality assurance systems for electrostatic spraying equipment, see Annex C.

1.6 Additional requirements may be applicable to equipment designed for use in food and pharmaceutical industry.

1.7 This European Standard does not apply to

- zone classification of the areas in and around spray booths [see EN 12981],
- zone classification of other areas with potentially explosive atmosphere [see EN 60079-10-2],
- selection, erection and application of other electrical and non-electrical equipment in areas with explosion hazard [see EN 60079-14 and EN 12981],
- cleaning of spraying areas, see instruction manual of the spray booth,
- fire prevention and protection, for instance fire hazards due to other sources [see EN 12981],
- dust hazards [see EN 12981].