

This is a preview of "BS ISO 5285:2012". [Click here to purchase the full version from the ANSI store.](#)

BS ISO 5285:2012



BSI Standards Publication

Conveyor belts — Guidelines for storage and handling

NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW

raising standards worldwide™



This is a preview of "BS ISO 5285:2012". [Click here to purchase the full version from the ANSI store.](#)

This British Standard is the UK implementation of ISO 5285:2012. It supersedes BS ISO 5285:2004 which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee PRI/67, Conveyor belts.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2012

Published by BSI Standards Limited 2012

ISBN 978 0 580 77352 5

ICS 53.040.20

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 October 2012.

Amendments issued since publication

Amd. No.	Date	Text affected
-----------------	-------------	----------------------

This is a preview of "BS ISO 5285:2012". [Click here to purchase the full version from the ANSI store.](#)

Third edition
2012-10-15

Conveyor belts — Guidelines for storage and handling

Courroies transporteuses — Lignes directrices pour le stockage et la manutention



Reference number
ISO 5285:2012(E)

© ISO 2012

This is a preview of "BS ISO 5285:2012". [Click here to purchase the full version from the ANSI store.](#)



COPYRIGHT PROTECTED DOCUMENT

© ISO 2012

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

This is a preview of "BS ISO 5285:2012". [Click here to purchase the full version from the ANSI store.](#)

Contents

Page

Foreword	iv
1 Scope	1
2 Normative references	1
3 Packing	1
3.1 Coiling	1
3.2 Strapping	1
3.3 Protection	1
3.4 Endless belts	2
4 Storage	2
4.1 Environmental conditions	2
4.2 Form of storage	3
5 Lifting	3
6 Transport over short distance	4
6.1 Forklift trucks	4
6.2 Without mechanical handling facilities	4
7 Running belt onto the structure	4
7.1 Existing structures	4
7.2 New structures	4
Bibliography	8

This is a preview of "BS ISO 5285:2012". [Click here to purchase the full version from the ANSI store.](#)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 5285 was prepared by Technical Committee ISO/TC 41, *Pulleys and belts (including veebelts)*, Subcommittee SC 3, *Conveyor belts*.

This third edition cancels and replaces the second edition (ISO 5285:2004), which has been technically revised.

This is a preview of "BS ISO 5285:2012". [Click here to purchase the full version from the ANSI store.](#)

Conveyor belts — Guidelines for storage and handling

1 Scope

This International Standard gives guidelines for creating the most suitable conditions for the storage and handling of conveyor belts. It is not applicable to light conveyor belts, as described in ISO 21183-1.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2230, *Rubber products — Guidelines for storage*

3 Packing

3.1 Coiling

Belting is generally packed in a coiled form. Core inserts are not always necessary, but for large, heavy belts or where stacking or excessive handling is anticipated (e.g. for overseas delivery), the cores used should be capable of withstanding the loads without damage or collapse. Cores made of wood or steel are recommended, having a square hole in the centre to accept a mounting bar. The diameter of the centre core, and the hole for the bar, depends on the mass, width and physical characteristics of the belting in the roll. Preferred hole sizes accommodate bars 50 mm, 100 mm, 150 mm and 200 mm square. It is important that the coil be wound

- a) tightly enough to prevent telescoping of the layers in subsequent handling and storage, and
- b) "square and true", i.e. the top and bottom of the roll have a flat profile across the width of the belt; the edges of the belt in each layer of the coil should all be in line and at 90° to the outer surface.

3.2 Strapping

3.2.1 Coiled belting should be bound circumferentially by textile, plastic or steel strapping. For double-coiled belts, the configuration should be as shown in Figure 1.

3.2.2 Textile/plastic strapping should not be used for underground belting unless the material is acceptable to the purchaser after suitable risk assessment.

3.2.3 It should be noted that textile or fabric strapping can be subject to stretch or "creep", causing gradual instability of the coil or a tendency to burst open if the coil is dropped. The possibility and consequence of these occurrences should be assessed before selection of the strapping type.

3.2.4 Strapping should have a suitable guaranteed minimum breaking load, be resistant to degradation for the storage life/conditions envisaged and be of sufficient width to prevent damage of the belt surface due to cutting.

3.3 Protection

3.3.1 The belting may be protected by paper, hessian, plastic sheeting, rubberized fabric or any other suitable covering material. All combustible protective packaging should be removed from any belt intended for underground use before the belt is taken underground.