This is a preview of "BS 8081:2015". Click here to purchase the full version from the ANSI store.



BSI Standards Publication

Code of practice for grouted anchors



BS 8081:2015 BRITISH STANDARD

This is a preview of "BS 8081:2015". Click here to purchase the full version from the ANSI store.

The BSI copyright notice displayed in this document indicates when the document was last issued.

© The British Standards Institution 2015. Published by BSI Standards Limited 2015

ISBN 978 0 580 86838 2

ICS 91.200, 93.020

The following BSI references relate to the work on this standard: Committee reference B/526 Draft for comment 15/30302283 DC

Publication history

First published 1989 Second (present) edition, August 2015

Amendments issued since publication

Date Text affected

BRITISH STANDARD BS 8081:2015

This is a preview of "BS 8081:2015". Click here to purchase the full version from the ANSI store.

```
Foreword iv
     Scope 1
1
     Normative references 1
2
3
     Terms, definitions, symbols and abbreviations 3
3.1
     Terms and definitions 3
3.2
     Symbols 9
3.3
     Abbreviations 12
     General rules 12
4
4.1
     General 12
     Responsibilities 12
4.2
     Basis of geotechnical design 13
4.3
     Assessment of the ground into which the anchor is to be fixed 14
4.4
4.5
     Materials to be used in anchor construction 16
4.6
     Effect of water on durability 16
4.7
     Geotechnical analysis 16
4.8
     Structural design 17
4.9
     Execution 17
5
     Limit states 19
6
     Design situations 19
7
     Design considerations 19
7.1
     General 19
7.2
     Design of supported structure 19
     Grouted anchor design
7.3
     Initial determination of anchor dimensions 20
7.4
7.5
     Final design 20
7.6
     Ongoing maintenance and monitoring 20
     Sustainability 20
7.7
8
     Ultimate limit state design 23
8.1
     Tendon 23
     Anchor head 23
8.2
8.3
     Fixed anchor length 23
8.4
     Free anchor length 23
     Serviceability limit state design 23
9
10
     Structural design 24
10.1 Tendon 24
10.2 Anchor head 24
10.3 Grout 24
     Anchor design 24
11
11.1 General 24
11.2 Minimum free anchor length design 24
11.3 Fixed anchor length design 25
11.4 Anchor head design 28
11.5 Fixed anchor interaction 29
12
     Materials 29
12.1 Cement grouts 29
12.2 Resin grouts 30
12.3 Tendon 31
12.4 Anchor head 34
13
     Durability 35
13.1 Corrosion 35
13.2 Corrosion protection 35
14
     Execution 47
14.1 General 47
14.2 Drilling 48
```

14.3 Tendons *49*

BS 8081:2015 BRITISH STANDARD

This is a preview of "BS 8081:2015". Click here to purchase the full version from the ANSI store.

- 14.5 Anchor nead 54
- **14.6** Stressing *55*
- **14.7** Stressing equipment *57*
- 15 Considerations related to testing 58
- 16 Maintenance 58
- **16.1** Precautionary measures 58
- **16.2** Remedial measures 59
- **16.3** Replacement criteria during service *59*
- **16.4** Dismantling after service 59
- **17** Reporting *59*
- 17.1 General 59
- 17.2 Geotechnical feedback report 60

Annexes

Annex A (informative) Indicative record sheets 62

Annex B (informative) Determination of the size of grouted anchors 68

Annex C (informative) Pre-grouting and post-grouting 95

Annex D (informative) Tendon Young's Modulus values 97

Annex E (informative) Corrosion 98

Annex F (informative) Corrosion protection 102

Annex G (normative) Testing 105

Annex H (informative) General considerations on monitoring and testing 127

Annex I (informative) Health and safety 131

Bibliography 132

List of figures

Figure 1 – Grouted anchors 8

Figure 2 – Grouted anchors 21

Figure 3 – Flow chart for the development of strategy for the monitoring and maintenance of grouted anchors 23

Figure 4 – Typical encapsulation centralizers 32

Figure 5 – Typical bar centralizer 33

Figure 6 – Typical cross-section of centralizer/spacer unit for multi-strand tendon in temporary unprotected systems 34

Figure 7 – Typical coupler details in tendon free length of bar tendon 39

Figure 8 – Typical double corrosion protection of tendon bond length of strand tendon using a single corrugated sheath and polyester resin 41

Figure 9 – Typical double corrosion protection of tendon bond length of strand tendon using a double corrugated sheath and cement grout 42

Figure 10 – Tendon bond length protection for a ribbed bar tendon 43

Figure 11 – Typical double corrosion protection of tendon bond length of smooth or ribbed bar tendon using a double corrugated duct 44

Figure 12 – Typical double corrosion protection of restressable anchor head incorporating a strand tendon 46

Figure B.1 – Main types of cement injection grouted anchors 69

Figure B.2 – Detail of tube à manchette for pressure grouting control 70

Figure B.3 – Relationship between resistance efficiency factor and fixed anchor length 78

Figure B.4 – Relationship between bearing capacity factor N_q and angle of shearing resistance in terms of effective stress 79

Figure B.5 – Ultimate load-holding capacity of anchors in sandy gravels and gravelly sands, showing influence of soil type, density and fixed anchor length for Type C anchors 81

Figure B.6 – Relationship between ultimate load-holding capacity, fixed anchor length and dynamic penetration for two types of coarse soil 83

Figure B.7 – Skin friction in fine soils for various fixed anchor lengths, with and without post-grouting 85

BRITISH STANDARD BS 8081:2015

This is a preview of "BS 8081:2015". Click here to purchase the full version from the ANSI store.

Figure B.9 – Load transfer mechanisms for typical encapsulation systems 93

Figure G.1 – Recommended load increments and minimum periods of observation for investigation tests on anchors where the ground conditions are not known, or prior experience of anchoring does not exist 110

Figure G.2 – Recommended load increments and minimum period of observation for investigation tests on anchors where previous anchoring knowledge is available 111

Figure G.3 – Schematic showing typical method of measuring tendon displacement using a dial gauge 113

Figure G.4 – Schematic showing typical method of measuring tendon load loss using a pressure gauge 114

Figure G.5 – Acceptance criteria for tendon displacement at anchor head 116

Figure G.6 – Recommended load increments and minimum periods of observation for suitability tests 118

Figure G.7 – Recommended load increments and minimum periods of observation for acceptance tests 122

Figure G.8 – Typical monitored anchor head for strand tendon 124

Figure G.9 – Typical monitored anchor head for bar tendon 125

List of tables

Table 1 – Recommended design and construction duties 13

Table 2 – Minimum resistance factors recommended for the calculation of the size of individual fixed anchor lengths prior to testing 26

Table A.1 – Typical drilling, grouting and tendon installation record sheet 62

Table A.2 – Typical stressing record sheet 64

Table A.3 – Typical stressing results and analysis record sheet 67

Table B.1 – Rock/grout bond values that have been employed in practice 72

Table B.2 – Rock/grout bond values that have been recommended for design 75

Table B.3 – Rock/grout bond values from rock anchor tests 77

Table B.4 – Approximate relationship between bearing capacity factor N_q and slenderness ratio 79

Table B.5 – Fixed anchor lengths for cement-grouted rock anchors that have been employed or recommended in practice 91

Table E.1 – Soil corrosiveness related to values of soil resistivity and redox potential 101

Table F.1 – Proposed classes of protection for ground anchors 103

Table G.1 – Recommended load increments and minimum periods of observation for investigation tests on anchors where the ground conditions are not known, or prior experience of anchoring does not exist 110

Table G.2 – Recommended load increments and minimum periods of observation for investigation tests on anchors where previous anchoring knowledge is available 111

Table G.3 – Recommended load increments and minimum periods of observation for suitability tests 112

Table G.4 – Acceptance criteria for displacement-time behaviour at $F_{Serv:k}$ 113

Table G.5 – Acceptance criteria for load loss at $F_{Serv;k}$ 115

Table G.6 – Recommended load increments and minimum periods of observation for acceptance tests 121

Table H.1 – Relationship between the acceptance criteria for load-time and displacement-time behaviour 130

Summary of pages

This document comprises a front cover, an inside front cover, pages i to iv, pages 1 to 138, an inside back cover and a back cover.

BS 8081:2015 BRITISH STANDARD

This is a preview of "BS 8081:2015". Click here to purchase the full version from the ANSI store.

Publishing information

This British Standard is published by BSI Standards Limited, under licence from The British Standards Institution, and came into effect on 31 August 2015. It was prepared under the authority of Technical Committee B/526, *Geotechnics*. A list of organizations represented on this committee can be obtained on request to its secretary.

Supersession

Together with BS EN 1997-1:2004+A1:2013, this British Standard supersedes BS 8081:1989, which is withdrawn.

Relationship with other publications

BS 8081 gives non-contradictory, complementary information for use with BS EN 1997-1:2004+A1:2013 and its UK National Annexes, BS EN 1537:2013 and BS EN ISO 22477-5. At the time of publication, BS EN ISO 22477-5 is not published and until such time as it is published, the recommendations for the testing of grouted anchors given in BS 8081:2015 Annex G apply.¹⁾

Use of this document

As a code of practice, this British Standard takes the form of guidance and recommendations. It should not be quoted as if it were a specification and particular care should be taken to ensure that claims of compliance are not misleading.

Any user claiming compliance with this British Standard is expected to be able to justify any course of action that deviates from its recommendations.

Presentational conventions

The provisions of this standard are presented in roman (i.e. upright) type. Its recommendations are expressed in sentences in which the principal auxiliary verb is "should".

Commentary, explanation and general informative material is presented in smaller italic type, and does not constitute a normative element.

Where words have alternative spellings, the preferred spelling of the Shorter Oxford English Dictionary is used (e.g. "organization" rather than "organisation").

The auxiliary verb "may" is used in the text to express permissibility, e.g. as an alternative to the primary recommendation of the Clause. The auxiliary verb "can" is used to express possibility, e.g. a consequence of an action or an event.

Notes and commentaries are provided throughout the text of this standard. Notes give references and additional information that are important but do not form part of the recommendations. Commentaries give background information.

Contractual and legal considerations

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard cannot confer immunity from legal obligations.

¹⁾ BS EN ISO 22477-5 is expected to publish in July 2017 (although this date is subject to change). Please check the BSI Shop website at http://shop.bsigroup.com/ for further information.

BRITISH STANDARD BS 8081:2015

This is a preview of "BS 8081:2015". Click here to purchase the full version from the ANSI store.

- **1.1** This British Standard, as a code of practice, gives recommendations for the design, construction, stressing, testing, monitoring and maintenance of grouted anchors as defined in BS EN 1997-1:2004+A1:2013, BS EN 1537:2013 and BS EN ISO 22477-5.
- 1.2 Further general recommendations for corrosion hazards and protective measures, construction techniques and quality controls, stressing procedures, and the testing of grouted anchor components and complete installations are provided. Information supporting the practical implementation of these recommendations are provided in annexes to this code of practice.
- 1.3 Annex A provides examples of records that are developed during the execution and testing of grouted anchors.
- 1.4 Annex B provides information on the design of a fixed anchor length with respect to the bond or shear resistance at:
- the ground/grout interface;
- the grout/encapsulation interface;
- the grout/tendon interface.
- 1.5 Annex C provides information on the pre-grouting and post-grouting of ground where necessary.
- 1.6 Annex D provides information on the use of appropriate Young's modulus for the steel used in the design of the anchor tendon.
- 1.7 Annex E provides information on the types of corrosion that affect the steel elements of an anchor and the influence on the corrosion of the tendon of the ground and groundwater in which the anchor is installed.
- 1.8 Annex F provides information on the types of corrosion protection available for use in the fabrication and installation of the anchor.
- 1.9 Annex G provides recommendations on the testing of anchors at all stages of construction.
- 1.10 Annex H provides information on monitoring anchors in the long term, including appropriate acceptance criteria and remedial measures that can be applied in the event of non-compliance with the acceptance criteria.
- 1.11 Annex I draws attention to the statutory regulations affecting the safety, welfare and health of persons in the execution of anchor construction.
- 1.12 This code of practice is for the use of clients who commission the use of grouted anchors, ground engineering contractors, and geotechnical and structural designers.

NOTE BS EN ISO 22477-5 is expected to publish in July 2017 (although this date is subject to change). Please check the BSI Shop website at http://shop.bsigroup.com/ for further information.

Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

Standards publications

BS 3148:1980, Methods of test for water for making concrete (including notes on the suitability of the water)