BS ISO 12647-7:2016



#### **BSI Standards Publication**

# Graphic technology — Process control for the production of halftone colour separations, proof and production prints

Part 7: Proofing processes working directly from digital data



This British Standard is the UK implementation of ISO 12647-7:2016. It supersedes BS ISO 12647-7:2013 which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee PAI/43, Graphic technology.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2016. Published by BSI Standards Limited 2016

ISBN 978 0 580 87416 1

ICS 37.100.01

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 30 November 2016.

Amendments/corrigenda issued since publication

Date Text affected

ISO

This is a preview of "BS ISO 12647-7:2016". Click here to purchase the full version from the ANSI store.

Third edition 2016-11-15

## Graphic technology — Process control for the production of halftone colour separations, proof and production prints —

#### Part 7:

### Proofing processes working directly from digital data

Technologie graphique — Contrôle des processus de confection de sélections couleurs tramées, d'épreuves et de tirages —

Partie 7: Processus d'épreuve travaillant directement à partir de données numériques



BS ISO 12647-7:2016 ISO 12647-7:2016(E)

This is a preview of "BS ISO 12647-7:2016". Click here to purchase the full version from the ANSI store.



#### COPYRIGHT PROTECTED DOCUMENT

© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Ch. de Blandonnet 8 • CP 401 CH-1214 Vernier, Geneva, Switzerland Tel. +41 22 749 01 11 Fax +41 22 749 09 47 copyright@iso.org www.iso.org

| Foreword   | Contents |  |  |    |  |
|--|----------|--|--|----|--|
| Scope       1         2       Normative references       1         3       Terms and definitions       1         4       Requirements       3         4       Note in fire rence measurements       3         4       1       Data fielies, simulation of screens       3         4       4.2       Data delivery       3         4.2.1       Data delivery       3         4.2.2       Screen frequency       3         4.2.3       Dots price requency       3         4.2.4       Dot shape       3         4.3.1       General       3         4.3.1       General       3         4.3.2       Porofing substrate colour and gloss       4       4       4.3.4       General       3         4.3.5       Permanence of proofing substrate and printed parts       5         4.3.6       Repeatability of proof printing       6       6 <th>Fore</th> <th>word</th> <th></th> <th>iv</th>  | Fore     | word   |  | iv |  |
| Terms and definitions   1  | Intro    | ductio   | n  | v  |  |
| Terms and definitions   1  | 1        | Scop   | e  | 1  |  |
| Terms and definitions       1         4       Requirements       3         4.1       Colour difference measurements       3         4.2       Data files, simulation of screens       3         4.2.1       Data delivery       3         4.2.2       Screen frequency       3         4.2.3       Screen angle       3         4.2.4       Dot shape       3         4.2.5       Halftone proofs screening       3         4.3       Proof print       3         4.3.1       General       3         4.3.2       Proofing substrate colour and gloss       4         4.3.4       Gamut       5         4.3.5       Permanence of proofing substrate and printed parts       5         4.3.6       Reperatability of proof printing       6         4.3.7       Colourant rub resistance       6         4.3.8       Ink set gloss       7         4.3.10       Reproduction of vignettes       7         4.3.11       Image register and resolving power       7         4.3.12       Margin information       7         5.3       Post information       7         5.3       Post informative       9  | 2        | -  |  |    |  |
| Requirements       3         4.1       Colour difference measurements       3         4.2       Data files, simulation of screens       3         4.2.1       Data delivery       3         4.2.2       Screen frequency       3         4.2.3       Screen angle       3         4.2.4       Dot shape       3         4.2.5       Halftone proofs screening       3         4.3       Proof print       3         4.3.1       General       3         4.3.2       Proofing substrate colour and gloss       4         4.3.2       Proofing substrate parts       4         4.3.4       Gamut       5         4.3.5       Permanence of proofing substrate and printed parts       5         4.3.6       Repeatability of proof printing       6         4.3.7       Colourant rub resistance       6         4.3.8       Ink set gloss       7         4.3.9       Tone value reproduction limits       7         4.3.10       Reproduction of vignettes       7         4.3.11       Image register and resolving power       7         4.3.12       Margin information       7         5.1       Viewing conditions  |          |  |  |    |  |
| 4.1       Colour difference measurements       3         4.2       Data files, simulation of screens       3         4.2.1       Data delivery       3         4.2.2       Screen frequency       3         4.2.3       Screen angle       3         4.2.5       Halftone proofs screening       3         4.3       Proof print       3         4.3.1       General       3         4.3.2       Proofing substrate colour and gloss       4         4.3.3       Colouration of printed parts       4         4.3.4       Gamut       5         4.3.5       Permanence of proofing substrate and printed parts       5         4.3.6       Repeatability of proof printing       6         4.3.7       Colourant rub resistance       6         4.3.8       Ink set gloss       7         4.3.9       Tone value reproduction limits       7         4.3.11       Image register and resolving power       7         4.3.12       Margin information       7         5.1       Viewing conditions       8         5.2       Control strip       8         5.3       Additional test objects       9         5.3.1       Re   | 3        |  |  |    |  |
| 4.2   Data files, simulation of screens   3   4.2.1   Data delivery   3   4.2.2   Screen frequency   3   4.2.3   Screen angle   3   4.2.4   Dot shape   3   4.2.5   Halftone proofs screening   3   4.2.5   Halftone proofs screening   3   4.3.1   General   3   4.3.1   General   3   4.3.2   Proofing substrate colour and gloss   4   4.3.4   Gamut   5   4.3.5   Permanence of proofing substrate and printed parts   4   4.3.4   Gamut   5   5   Permanence of proofing substrate and printed parts   5   4.3.6   Repeatability of proof printing   6   4.3.7   Colourant rub resistance   6   4.3.8   Ink set gloss   7   4.3.10   Reproduction limits   7   4.3.10   Reproduction of vignettes   7   4.3.11   Image register and resolving power   7   4.3.12   Margin information   7   7   7   7   7   7   7   7   7   | 4        |  |  |    |  |
| 4.2.1   Data delivery  |          |  |  |    |  |
| 4.2.2   Screen frequency   3   4.2.3   Screen angle   3   4.2.4   Dot shape   3   4.2.5   Halftone proofs screening   3   3   4.2.5   Halftone proofs screening   3   3   4.3.1   General   3   4.3.1   General   3   4.3.2   Proofing substrate colour and gloss   4   4.3.4   Gamut   5   4.3.5   Permanence of proofing substrate and printed parts   5   4.3.6   Repeatability of proof printing   6   4.3.7   Colourant rub resistance   6   4.3.8   Ink set gloss   7   4.3.9   Tone value reproduction limits   7   4.3.10   Reproduction of vignettes   7   4.3.11   Image register and resolving power   7   4.3.12   Margin information   7   7   7   7   7   7   7   7   7  |          | 4.2  |  |    |  |
| 4.2.4   Dot shape  |          |  |  |    |  |
| 4.2.4   Dot shape   33   4.2.5   Halftone proofs screening   33   4.2.5   Halftone proofs screening   33   4.3.1   General   33   4.3.1   General   34.3.2   Proofing substrate colour and gloss   44   4.3.4   Gamut   55   4.3.5   Permanence of proofing substrate and printed parts   55   4.3.6   Repeatability of proof printing   66   4.3.7   Colourant rub resistance   66   4.3.8   Ink set gloss   77   4.3.9   Tone value reproduction limits   77   4.3.10   Reproduction of vignettes   77   4.3.11   Image register and resolving power   77   4.3.12   Margin information   77   75   Test methods   85.1   Viewing conditions   85.2   Control strip   85.3   Additional test objects   99   5.3.1   Resolution   99   5.3.2   Primary and secondary process colours   99   5.3.4   Uniformity   99   5.4   Colour measurement   99   5.5   Measurement of gloss   10   5.6   Visual appraisal of proof-press-print matches   18   Annex C (normative) Outer gamut patches   18   Annex D (informative) Outer gamut patches   21   21   21   21   21   21   21   2  |          |  |  |    |  |
| 4.2.5   Halftone proofs screening  |          |  |  |    |  |
| 4.3  |          |  |  |    |  |
| 4.3.1   General   3   4.3.2   Proofing substrate colour and gloss   4   4.3.3   Colouration of printed parts   5   4.3.5   Permanence of proofing substrate and printed parts   5   4.3.5   Permanence of proofing substrate and printed parts   5   4.3.6   Repeatability of proof printing   6   4.3.7   Colourant rub resistance   6   4.3.8   Ink set gloss   7   4.3.9   Tone value reproduction limits   7   4.3.11   Image register and resolving power   7   4.3.12   Margin information   7   7   4.3.12   Margin information   7   7   7   7   7   7   7   7   7   |          | 4.0  |  |    |  |
| 4.3.2   Proofing substrate colour and gloss  |          | 4.3  |  |    |  |
| 4.3.3   Colouration of printed parts   4   4.3.4   Gamut   5   |          |  |  |    |  |
| 4.3.4   Gamut  |          |  |  |    |  |
| 4.3.5       Permanence of proofing substrate and printed parts       5         4.3.6       Repeatability of proof printing       6         4.3.7       Colourant rub resistance       6         4.3.8       Ink set gloss       7         4.3.9       Tone value reproduction limits       7         4.3.10       Reproduction of vignettes       7         4.3.11       Image register and resolving power       7         4.3.12       Margin information       7         5       Test methods       8         5.1       Viewing conditions       8         5.2       Control strip       8         5.3       Additional test objects       9         5.3.1       Resolution       9         5.3.2       Primary and secondary process colours       9         5.3.2       Primary and secondary process colours       9         5.3.3       Resolving power       9         5.3.4       Uniformity       9         5.5       Measurement of gloss       10         5.6       Visual appraisal of proof-press-print matches       10         Annex A (normative) Technical requirements for proofing conformity       11         Annex D (informative) Outer gamut patches |          |  |  |    |  |
| 4.3.6 Repeatability of proof printing 4.3.7 Colourant rub resistance 6.4.3.8 Ink set gloss. 7.4.3.9 Tone value reproduction limits 7.4.3.10 Reproduction of vignettes 7.4.3.11 Image register and resolving power 7.4.3.12 Margin information 7.5 Test methods 5.1 Viewing conditions 5.2 Control strip 8.5.3 Additional test objects 9.5.3.1 Resolution 9.5.3.2 Primary and secondary process colours 9.5.3.3 Resolving power 9.5.3.4 Uniformity 9.5.4 Colour measurement 9.5.5 Measurement of gloss 5.6 Visual appraisal of proof-press-print matches 10  Annex A (normative) Technical requirements for proofing conformity 11  Annex B (normative) Quter gamut patches 18  Annex D (informative) Organizational certification routines for visual appraisal of proof-print press-print matches 21  |          |  |  |    |  |
| 4.3.7 Colourant rub resistance 6 4.3.8 Ink set gloss 7 4.3.9 Tone value reproduction limits 7 4.3.10 Reproduction of vignettes 7 4.3.11 Image register and resolving power 7 4.3.12 Margin information 7  Test methods 8 5.1 Viewing conditions 8 5.2 Control strip 8 5.3 Additional test objects 9 5.3.1 Resolution 9 5.3.2 Primary and secondary process colours 9 5.3.3 Resolving power 9 5.3.3 Resolving power 9 5.3.4 Uniformity 9 5.4 Colour measurement 9 5.5 Measurement of gloss 10 5.6 Visual appraisal of proof-press-print matches 10  Annex A (normative) Technical requirements for proofing conformity 11  Annex B (normative) Rub resistance of the proof colourant 15  Annex C (normative) Outer gamut patches 18  Annex D (informative) Organizational certification routines for visual appraisal of proof-print press-print matches 21   |          |  |  |    |  |
| 4.3.8 Ink set gloss  |          |  |  |    |  |
| 4.3.9 Tone value reproduction limits   |          |  |  |    |  |
| 4.3.10 Reproduction of vignettes 7 4.3.11 Image register and resolving power 7 4.3.12 Margin information 7  7 Test methods 8 5.1 Viewing conditions 8 5.2 Control strip 8 5.3 Additional test objects 9 5.3.1 Resolution 9 5.3.2 Primary and secondary process colours 9 5.3.3 Resolving power 9 5.3.4 Uniformity 9 5.4 Colour measurement 9 5.5 Measurement of gloss 10 5.6 Visual appraisal of proof-press-print matches 10  Annex A (normative) Technical requirements for proofing conformity 11  Annex B (normative) Rub resistance of the proof colourant 15  Annex D (informative) Organizational certification routines for visual appraisal of proof-print press-print matches 21   |          |  | O .  |    |  |
| 4.3.11 Image register and resolving power  |          |  | 1  |    |  |
| 4.3.12 Margin information  |          |  | 1 0  |    |  |
| 5Test methods85.1Viewing conditions85.2Control strip85.3Additional test objects95.3.1Resolution95.3.2Primary and secondary process colours95.3.3Resolving power95.3.4Uniformity95.5Measurement of gloss105.6Visual appraisal of proof-press-print matches10Annex A (normative) Technical requirements for proofing conformity11Annex B (normative) Rub resistance of the proof colourant15Annex C (normative) Outer gamut patches18Annex D (informative) Organizational certification routines for visual appraisal of proof-print press-print matches21   |          |  |  |    |  |
| 5.1Viewing conditions85.2Control strip85.3Additional test objects95.3.1Resolution95.3.2Primary and secondary process colours95.3.3Resolving power95.3.4Uniformity95.4Colour measurement95.5Measurement of gloss105.6Visual appraisal of proof-press-print matches10Annex A (normative) Technical requirements for proofing conformity11Annex B (normative) Rub resistance of the proof colourant15Annex C (normative) Outer gamut patches18Annex D (informative) Organizational certification routines for visual appraisal of proof-print press-print matches21   |          |  | 4.3.12 Margin information                      | 7  |  |
| 5.2 Control strip 8 5.3 Additional test objects 9 5.3.1 Resolution 9 5.3.2 Primary and secondary process colours 9 5.3.3 Resolving power 9 5.3.4 Uniformity 9 5.4 Colour measurement 9 5.5 Measurement of gloss 10 5.6 Visual appraisal of proof-press-print matches 10  Annex A (normative) Technical requirements for proofing conformity 11  Annex B (normative) Rub resistance of the proof colourant 15  Annex C (normative) Outer gamut patches 18  Annex D (informative) Organizational certification routines for visual appraisal of proof-print press-print matches 21   | 5        | Test methods   |  |    |  |
| 5.3 Additional test objects 9 5.3.1 Resolution 9 5.3.2 Primary and secondary process colours 9 5.3.3 Resolving power 9 5.3.4 Uniformity 9 5.4 Colour measurement 9 5.5 Measurement of gloss 10 5.6 Visual appraisal of proof-press-print matches 10  Annex A (normative) Technical requirements for proofing conformity 11  Annex B (normative) Rub resistance of the proof colourant 15  Annex C (normative) Outer gamut patches 18  Annex D (informative) Organizational certification routines for visual appraisal of proof-print press-print matches 21   |          | 5.1  | Viewing conditions                             | 8  |  |
| 5.3.1 Resolution 9 5.3.2 Primary and secondary process colours 9 5.3.3 Resolving power 9 5.3.4 Uniformity 9 5.4 Colour measurement 9 5.5 Measurement of gloss 10 5.6 Visual appraisal of proof-press-print matches 10  Annex A (normative) Technical requirements for proofing conformity 11  Annex B (normative) Rub resistance of the proof colourant 15  Annex C (normative) Outer gamut patches 18  Annex D (informative) Organizational certification routines for visual appraisal of proof-print press-print matches 21   |          | 5.2  | Control strip                                  | 8  |  |
| 5.3.2 Primary and secondary process colours  |          | 5.3  | Additional test objects                        | 9  |  |
| 5.3.3 Resolving power 9 5.3.4 Uniformity 9 5.4 Colour measurement 9 5.5 Measurement of gloss 10 5.6 Visual appraisal of proof-press-print matches 10  Annex A (normative) Technical requirements for proofing conformity 11  Annex B (normative) Rub resistance of the proof colourant 15  Annex C (normative) Outer gamut patches 18  Annex D (informative) Organizational certification routines for visual appraisal of proof-print press-print matches 21  |          |  |  |    |  |
| 5.3.4 Uniformity 9 5.4 Colour measurement 9 5.5 Measurement of gloss 10 5.6 Visual appraisal of proof-press-print matches 10  Annex A (normative) Technical requirements for proofing conformity 11  Annex B (normative) Rub resistance of the proof colourant 15  Annex C (normative) Outer gamut patches 18  Annex D (informative) Organizational certification routines for visual appraisal of proof-print press-print matches 21  |          |  | 5.3.2 Primary and secondary process colours    | 9  |  |
| 5.4 Colour measurement 9 5.5 Measurement of gloss 10 5.6 Visual appraisal of proof-press-print matches 10  Annex A (normative) Technical requirements for proofing conformity 11  Annex B (normative) Rub resistance of the proof colourant 15  Annex C (normative) Outer gamut patches 18  Annex D (informative) Organizational certification routines for visual appraisal of proof-print press-print matches 21   |          |  | 5.3.3 Resolving power                          | 9  |  |
| 5.5 Measurement of gloss   |          |  | 5.3.4 Uniformity                               | 9  |  |
| 5.6 Visual appraisal of proof-press-print matches 10  Annex A (normative) Technical requirements for proofing conformity 11  Annex B (normative) Rub resistance of the proof colourant 15  Annex C (normative) Outer gamut patches 18  Annex D (informative) Organizational certification routines for visual appraisal of proof-print press-print matches 21  |          | 5.4  | Colour measurement                             | 9  |  |
| Annex A (normative) Technical requirements for proofing conformity   |          | 5.5  | Measurement of gloss                           | 10 |  |
| Annex B (normative) Rub resistance of the proof colourant  |          | 5.6  | Visual appraisal of proof-press-print matches  | 10 |  |
| Annex C (normative) Outer gamut patches  | Anne     | Annex A (normative) Technical requirements for proofing conformity |  |    |  |
| Annex D (informative) Organizational certification routines for visual appraisal of proofprint press-print matches 21  | Anne     | ex B (no   | rmative) Rub resistance of the proof colourant | 15 |  |
| print press-print matches 21   | Anne     | ex C (no   | rmative) Outer gamut patches                   | 18 |  |
| • •  | Anne     |  |  | 21 |  |
|  | Bihli    | •  |  |    |  |

#### Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see <a href="www.iso.org/directives">www.iso.org/directives</a>).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see <a href="https://www.iso.org/patents">www.iso.org/patents</a>).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: <a href="www.iso.org/iso/foreword.html">www.iso.org/iso/foreword.html</a>.

The committee responsible for this document is ISO/TC 130, *Graphic technology*.

This third edition cancels and replaces the second edition (ISO 12647-7:2013), which has been technically revised with the following changes:

- a number of anomalies identified by industry experts have been addressed;
- substrate selection and measurement specification has been modified to reflect industry practice;
- approximately equivalent CIEDE2000 colour difference values have been added;
- basic support for spot inks has been added;
- wording has been updated to reflect current terminology and industry thinking.

A list of all parts in the ISO 12647 series can be found on the ISO website.

#### Introduction

ISO 12647-1 serves to provide definitions, the general principles, the general order, the material to be covered in ISO 12647-2 to ISO 12647-8, the definition of the data, the measurement conditions, and the reporting style.

This document relates to the subject of digital proofing and establishes proofing requirements for the most demanding part of the printing and publishing market.

This document specifies aim values (or sets of aim values) and tolerances for the primary parameters specified in ISO 12647-1 for digital proof printing. Primary parameters that define a printing condition include screening parameters (where applicable), the colours of the solids, the colour of the print substrate, colours of intermediate tint values and the tone curve. This document also specifies test methods for those properties of digital proof prints and their substrates that are considered relevant for stable and reliable proofing conditions, and thus for a certification procedure.

The graphic technology industry makes extensive use of proofing to predict the rendering of digital data files by a wide variety of high-definition, high-quality off-press printing processes and applications. Each prediction is based on a characterization data set that defines a particular printing condition.

Typically, the specified printing condition is defined through an International Color Consortium (ICC) profile or the associated characterization data set, both of which relate source data and colorimetric values of the printed colour. Such data may be derived from printing conditions conforming to the pertinent process standard of the ISO 12647 series by industry trade groups or individuals.

The purpose of a proof print is to simulate the visual characteristics of the finished production print product as closely as possible. In order to visually match a particular printing condition, proofing processes require a set of parameters to be specified that are not necessarily identical to those put forward in ISO 12647-1 or another part of ISO 12647. This is caused by differences in colourant spectra or phenomena such as gloss, light scatter (within the print substrate or the colourant), and transparency. In such cases, it is also found that spectrocolorimetry takes precedence over densitometry.

Another problem area is the matching of a double-sided production print on a lightweight printing substrate, such as often used in heat-set web and publication gravure printing, to a digital proof on a nearly opaque substrate. If the proof was produced using a colour management profile based on measurements with white backing, there will be an unavoidable visual and measurable difference between the proof on the one hand and the production print placed on black on the other hand. A black backing is required for double-sided production printing on non-opaque prints, as specified in the pertinent parts of ISO 12647. The possible occurrence of such differences needs to be well communicated, in advance, to all parties concerned.

Historically, there has been no consistency in the way that either the characterization data or the criteria and limits for a satisfactory match have been provided. This has led to significant redundancy and inconsistencies in the evaluation of proofing systems for different, but similar, applications, and a cost and time burden on the industry. This document therefore attempts to provide guidance in this area by providing specifications and associated testing procedures.

<u>Annex A</u> summarizes the requirements for the digital proof prints listed in the main body of this document; these are weighted with respect to their relevance in three typical situations:

- requirements with which a proof print, made for a particular printing condition, must comply if it
  is to be referenced in a contract between the printer and the provider of the digital data (Certified
  Proof Creation);
- requirements with which a vendor's proofing system, comprising hardware and software, must comply if it is to be considered capable of reliably producing digital contract proofs for a particular printing condition (Certified Proofing System);
- requirements with which a proof print made for a particular printing condition must comply when tested in the field using only a control wedge (Certified Field Proof).

ISO 12647-8 defines requirements for validation prints. Because data are exchanged electronically and visualizations of those data are produced at multiple sites, there is a market need for defined requirements for validation prints to promote a degree of consistency throughout the workflow. Validation prints are intended to be used at early stages of the print production workflow, particularly at the document design stage and have less stringent requirements, particularly on colour fidelity, to allow their production on less elaborate and less costly devices than are required for contract proofs.

Validation prints are not intended to replace "contract proofs" as specified in this document for predicting colour on production printing devices. It is expected that the modifications of the requirements for both contract proofs and validation prints, along with the requirements for contract proofs, will continue in the future as industry requirements and imaging technologies develop.

### Graphic technology — Process control for the production of halftone colour separations, proof and production prints —

#### Part 7:

#### Proofing processes working directly from digital data

#### 1 Scope

This document specifies requirements for systems that are used to produce hard-copy digital proof prints intended to simulate a printing condition defined by a set of characterization data. Recommendations are provided with regard to appropriate test methods associated with these requirements.

#### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 187, Paper, board and pulps — Standard atmosphere for conditioning and testing and procedure for monitoring the atmosphere and conditioning of samples

ISO 2813, Paints and varnishes — Determination of gloss value at 20°, 60° and 85°

ISO 3664, Graphic technology and photography — Viewing conditions

ISO 8254-1, Paper and board — Measurement of specular gloss — Part 1: 75° gloss with a converging beam, TAPPI method

ISO 12040, Graphic technology — Prints and printing inks — Assessment of light fastness using filtered xenon arc light

ISO 12639, Graphic technology — Prepress digital data exchange — Tag image file format for image technology (TIFF/IT)

ISO 12640-1, Graphic technology — Prepress digital data exchange — Part 1: CMYK standard colour image data (CMYK/SCID)

ISO 12642-2, Graphic technology — Input data for characterization of 4-colour process printing — Part 2: Expanded data set

ISO 13655, Graphic technology — Spectral measurement and colorimetric computation for graphic arts images

ISO 15397:2014, Graphic technology — Communication of graphic paper properties

#### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 12647-1 and the following apply.