

This is a preview of "BS 9295:2020". [Click here to purchase the full version from the ANSI store.](#)

**BS 9295:2020**



**BSI Standards Publication**

## **Guide to the structural design of buried pipes**

**bsi.**

This is a preview of "BS 9295:2020". [Click here to purchase the full version from the ANSI store.](#)

**Publishing and copyright information**

The BSI copyright notice displayed in this document indicates when the document was last issued.

© The British Standards Institution 2020

Published by BSI Standards Limited 2020

ISBN 978 0 580 98319 1

ICS 23.040.01; 93.030

The following BSI references relate to the work on this document:

Committee reference B/505

Draft for comment 19/30359667 DC

**Amendments/corrigenda issued since publication**

Date	Text affected
------	---------------

---

This is a preview of "BS 9295:2020". [Click here to purchase the full version from the ANSI store.](#)

## CONTENTS

	Page
<b>Foreword</b>	<b>iv</b>
0 Introduction	1
1 Scope	1
2 Normative references	1
3 Terms, definitions and symbols	2
4 Concepts used in the structural design of buried pipes	6
4.1 The buried pipe system	6
4.2 Longitudinal and sectional behaviour	6
4.3 Classification of buried pipes	6
<i>Figure 1 — Design criteria for pipes laid in open trench</i>	7
<i>Table 1 — Pipe classification</i>	7
<i>Figure 2 — Rigid and flexible pipe behaviour</i>	8
4.4 Design models	8
<i>Figure 3 — Soil pressure changes immediately after pipe burial</i>	9
4.5 Short-term and long-term stiffness characteristics of polymeric pipe materials	11
4.6 Classification of native/embedment soils and trench width	13
<i>Figure 4 — Effective trench width, <math>B_d</math></i>	13
4.7 Key parameters to be specified by the designer	13
4.8 Pipe and design method selection	14
<i>Figure 5 — Clauses applicable to the selection and design of pipe</i>	14
5 Classification and calculation of loads	14
5.1 Introduction	14
5.2 Vehicle surcharge loads	15
<i>Figure 6 — Illustration of eccentric surcharge load on pipe</i>	15
5.3 Road and field surcharge loads	15
<i>Figure 7 — Loading configurations</i>	16
<i>Figure 8 — Example of calculated backfill, road traffic surcharge and combined loadings expressed as a line load on a rigid DN 300 pipe</i>	17
<i>Table 2 — Surcharge pressures (<math>kN/m^2</math>), <math>P_s</math>, as function of depth of cover to crown, <math>H</math></i>	17
<i>Figure 9 — Surcharge pressure (<math>kN/m^2</math>), <math>P_s</math>, due to vehicle wheels</i>	18
5.4 Surcharge pressure due to construction vehicles	18
<i>Figure 10 — Surcharge pressure, <math>P_s</math>, due to construction vehicles</i>	19
5.5 Railway loadings	19
<i>Figure 11 — Loading configurations for LM 71 and RL railway loading models</i>	20
<i>Figure 12 — BS EN 1991-2:2003, load model 71 (<math>\alpha = 1.0</math>) (RU to BS 5400-2<sup>1)</sup> surcharge pressure at depth</i>	21
<i>Figure 13 — Rail London (RL to BS 5400-2) surcharge pressures at depth</i>	22
<i>Figure 14 — Factor for calculating multi-track railway loadings</i>	23
6 Rigid pipe design	23
<i>Figure 15 — Flowchart for pipe design with rigid pipes</i>	24
6.1 General	24
6.2 Wide and narrow trenches	24
<i>Figure 16 — Effect of trench width, <math>B_d</math>, on calculated vertical backfill load on pipe</i>	25
<i>Figure 17 — The silo effect</i>	26
6.3 Complete and incomplete projection	26
<i>Figure 18 — Complete projection</i>	27
<i>Figure 19 — Incomplete projection</i>	27

<sup>1)</sup> Withdrawn.

This is a preview of "BS 9295:2020". [Click here to purchase the full version from the ANSI store.](#)

	<i>Figure 20 — Settlement deflection ratio</i>	28
	<i>Table 3 — Guide values of Spangler modulus for native soils, <math>E'_3</math></i>	29
6.5	Projection ratio, $\rho$	29
6.6	Soil properties	29
	<i>Table 4 — Values of <math>K\mu</math> and <math>K\mu'</math> for specific soil types</i>	29
6.7	Bedding factors	29
6.8	Crushing strength adjustments for pressure pipes	30
6.9	Minimum bedding factor and factor of safety	30
	<i>Table 5 — Rigid pipe embedment</i>	31
6.10	Design loads for rigid pipes	32
	<i>Table 6 — Design bedding factors for pipes laid in wide trench and embankment conditions with bedding classes B and S and outside diameter greater than or equal to 900 mm<sup>A)</sup></i>	32
	<i>Table 7 — Load coefficients for incomplete projection condition</i>	33
6.11	Supporting strength of rigid pipes	34
6.12	Factors of safety	35
	<i>Table 8 — Minimum values of <math>F_{se}</math> and <math>F_{si}</math></i>	35
6.13	Limit state design	35
	<i>Table 9 — Design factors of actions</i>	36
6.14	Design of egg-shaped pipes	36
	<i>Figure 21 — Dimensions and bedding distribution cases for egg-shaped pipes</i>	37
	<i>Table 10 — Bending moment coefficients for egg-shaped pipes</i>	38
6.15	Simplified bedding table for vitrified clay pipes	38
	<i>Table 11 — Simplified table for the embedment of vitrified clay pipes in wide trench conditions</i>	39
6.16	Simplified bedding table for concrete pipes	42
	<i>Table 12 — Simplified bedding table for concrete pipes – Strength class 120</i>	42
7	Flexible pipe design	44
7.1	General	44
7.2	Marston-Spangler method	44
	<i>Figure 22A — Flowchart for pipe design: GRP pipes</i>	45
	<i>Figure 23B — Flowchart for pipe design: Steel pipes</i>	46
	<i>Figure 23C — Flowchart for pipe design: Thermoplastics pipes</i>	47
	<i>Table 13 — Guide values of Spangler modulus for native soils, <math>E'_3</math></i>	48
	<i>Table 14 — Semi-rigid and flexible pipe embedment properties</i>	49
	<i>Table 15 — Flexible pipe embedments</i>	50
	<i>Figure 23 — Deflection lag factor</i>	51
	<i>Table 16 — Design values of initial deflection, <math>\Delta_v/D</math></i>	53
7.3	Gumbel method	55
	<i>Figure 24 — Principal deformation modes of the buried pipe ring</i>	56
	<i>Figure 25 — External loads on the pipe-soil system</i>	57
	<i>Figure 26 — Components of load on the pipe-soil system</i>	57
	<i>Table 17 — <math>M_{sb}</math> values<sup>A)</sup></i>	59
	<i>Table 18 — <math>M_{sn}</math> values</i>	60
	<i>Table 19 — Values of soil support combination factor, <math>S_c</math></i>	60
	<i>Table 20 — <math>K</math> values for design</i>	62
	<i>Table 21 — Design values of initial deflection, <math>\delta_{y0}</math></i>	65
	<i>Table 22 — Values of <math>\delta_{y2}</math> for design</i>	66
	<i>Figure 27 — Linear buckling modes</i>	66
	<i>Table 23 — Values of <math>k_{sc}</math> for design</i>	67
8	Semi-rigid pipe design	69

This is a preview of "BS 9295:2020". [Click here to purchase the full version from the ANSI store.](#)

	<i>Figure 28 — Flowchart for design of semi-rigid pipes of ductile iron</i>	70
8.2	Installation conditions	70
	<i>Table 24 — Semi-rigid pipe embedments</i>	71
	<i>Table 25 — Semi-rigid and flexible pipe embedment properties</i>	72
8.3	Design pressures for semi-rigid pipes	72
	<i>Table 26 — Load coefficients for incomplete projection condition</i>	73
	<i>Figure 29 — Deflection lag factor</i>	74
	<i>Table 27 — Guide values of Spangler modulus for native soils, <math>E'_3</math></i>	75
8.4	Semi-rigid pipe embedment properties	75
8.5	Design data for semi-rigid pipes	76
8.6	Bedding for ductile iron pipes	76
	<i>Table 28 — Embedment classes</i>	77
8.7	Simplified bedding table for ductile iron pipes	77
	<i>Table 29 — Safe depths of cover (m) for ductile iron water pipe with field surcharge</i>	79
	<i>Table 30 — Safe depths of cover (m) for ductile iron water pipe with main road surcharge</i>	81
	<i>Table 31 — Safe depths of cover (m) for ductile iron sewer pipe with field surcharge</i>	83
	<i>Table 32 — Safe depths of cover (m) for ductile iron sewer pipe with main road surcharge</i>	85
<b>Annex A</b>	<b>(informative) Other design considerations</b>	<b>87</b>
	<i>Figure A.1 — Soil loads and stresses produced by surface loads (after Fadum [13])</i>	88
	<i>Figure A.2 — Uniform surcharge <math>U_s</math> /unit area of limited extent in fixed position</i>	89
	<i>Figure A.3 — Pipe in tunnel, heading or jacked into place</i>	90
	<i>Figure A.4 — Multiple pipe trenches</i>	92
	<i>Figure A.5 — Uneven loading of multiple pipes laid in parallel</i>	93
	<i>Figure A.6 — Circumstances which can result in large lateral loads: Embankment</i>	94
	<i>Figure A.7 — Schematic of groundwater flotation forces</i>	96
	<i>Figure A.8 — Pipelines in poor ground</i>	98
	<i>Figure A.9 — Use of geotextile around pipe embedment</i>	99
	<i>Figure A.10 — Pipeline on piles</i>	100
	<i>Table A.1 — Recommended maximum length of rocker pipes</i>	101
	<i>Figure A.11 — Protection of a shallow pipeline using concrete surround</i>	104
	<i>Figure A.12 — Protection of shallow pipeline with a slab</i>	105
	<i>Figure A.13 — Plain and reinforced beddings and surrounds</i>	107
	<i>Figure A.14 — Pipework under a floor slab</i>	108
	<i>Figure A.15 — Pipework built in to the wall</i>	109
	<i>Figure A.16 — Pipework passing through the wall</i>	109
	<i>Table A.2 — Overview of limit state conditions to be checked for longitudinal effects</i>	111
	<i>Table A.3 — Compaction fractions for bedding materials</i>	115
	<i>Table A.4 — Gradings</i>	116
	<i>Table A.5 — Maximum recommended level of impurity (by mass)</i>	116
	<i>Table A.6 — Equation errors (percent)</i>	118
	<b>Bibliography</b>	<b>135</b>

### Summary of pages

This document comprises a front cover, and inside front cover, pages i to vi, pages 1 to 137, an inside back cover and a back cover.

This is a preview of "BS 9295:2020". [Click here to purchase the full version from the ANSI store.](#)

## Foreword

### Publishing information

This British Standard is published by BSI Standards Limited, under licence from The British Standards Institution, and came into effect on 29 February 2020. It was prepared by Technical Committee B/505, *Wastewater engineering*. A list of organizations represented on this committee can be obtained on request to its secretary.

### Supersession

This British Standard supersedes BS 9295:2010, which is withdrawn.

### Relationship with other publications

This British Standard is complementary to BS EN 1295-1:2019 and PD CEN/TR 1295-2:2005.

BS EN 1295-1:2019 specifies general requirements for the structural design of buried pipes under various conditions of loading. Guidance is also given on the application of the nationally established methods of design declared by, and used in, CEN member countries at the time it was prepared. The established United Kingdom method is described as BS 9295.

PD CEN/TR 1295-2:2005 summarizes the nationally established methods of design made available to CEN. The United Kingdom method is described in [A.9](#), which is consistent with BS EN 1295-1:1997.

This British Standard gives further information to facilitate in full the structural design of buried pipes under various conditions of loading using the established United Kingdom method; it does not alter any of the provisions of BS EN 1295-1:2019.

### Information about this document

This is a full revision of the standard, and introduces the following principal changes:

- incorporation of the content of National Annex A to BS EN 1295:1997; and
- inclusion of the Gumbel method for the design of buried pipes.

This publication can be withdrawn, revised, partially superseded or superseded. Information regarding the status of this publication can be found in the Standards Catalogue on the BSI website at [bsigroup.com/standards](https://bsigroup.com/standards), or by contacting the Customer Services team.

Where websites and webpages have been cited, they are provided for ease of reference and are correct at the time of publication. The location of a webpage or website, or its contents, cannot be guaranteed.

### Use of this document

As a guide, this British Standard takes the form of guidance and recommendations. It should not be quoted as if it were a specification or a code of practice.

### Presentational conventions

The guidance in this standard is presented in roman (i.e. upright) type. Any recommendations are expressed in sentences in which the principal auxiliary verb is "should".

*Commentary, explanation and general informative material is presented in smaller italic type, and does not constitute a normative element.*

This is a preview of "BS 9295:2020". [Click here to purchase the full version from the ANSI store.](#)

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

**Compliance with a British Standard cannot confer immunity from legal obligations.**

This is a preview of "BS 9295:2020". [Click here to purchase the full version from the ANSI store.](#)



This is a preview of "BS 9295:2020". [Click here to purchase the full version from the ANSI store.](#)

## 0 Introduction

This revision of BS 9295 has been prepared to maintain alignment with BS EN 1295-1:2019, which now cites BS 9295 as the primary source of the methods accepted for the structural design of buried pipes in the UK. The opportunity has been taken to review various shortcomings in the earlier UK design methods, many of which have arisen due to changes in the nature of pipes over the period since those methods were originally published.

Changes from the methods previously published as BS EN 1295-1 and BS 9295 include the introduction of a new conceptual model for the design of buried flexible pipes focused on large-diameter structured-wall thermoplastics pipes, explicit consideration of the quality of workmanship envisaged during installation, non-circular shaped concrete pipes, and a wider range of bedding materials. Non-circular shaped pipes in materials other than concrete are not in common use in the UK so their design is not covered by this edition.

## 1 Scope

This British Standard gives the UK established method for the structural design of buried pipes under various conditions of loading. The procedures are explained, with tables listing the recommended design values for the appropriate variables in the design formulae, figures providing graphical information on vehicle surcharge loadings, and tables of rigid pipe bedding factors.

*NOTE* The scope of BS EN 1295-1:2019 is restricted to the structural design of water supply pipelines, drains and sewers, and other water industry pipelines, whether operating at atmospheric, greater or lesser pressure.

Some aspects of longitudinal effects are discussed (see [Annex A](#)), but this topic is not fully covered.

The initial selection of options for the pipe material involves consideration of matters beyond structural design and is outside the scope of this standard.

## 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application<sup>1)</sup>. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

### Standards publications

BS EN 545, *Ductile iron pipes, fittings, accessories and their joints for water pipelines – Requirements and test methods*

BS EN 598, *Ductile iron pipes, fittings, accessories and their joints for sewerage applications – Requirements and test methods*

BS EN 622-4, *Fibreboards – Specifications – Part 4: Requirements for softboards*

BS EN 1295-1:2019, *Structural design of buried pipelines under various conditions of loading – Part 1: General requirements*

BS EN 1610:2015, *Construction and testing of drains and sewers*

BS EN 1992-1-1:2004+A1:2014, *Eurocode 2: Design of concrete structures – Part 1-1: General rules and rules for buildings*

BS EN 13242:2002+A1:2007, *Aggregates for unbound and hydraulically bound materials for use in civil engineering work and road construction*

<sup>1)</sup> Documents that are referred to in an informative manner are listed in the Bibliography.