

This is a preview of "BS 8418:2015+A1:2017". [Click here to purchase the full version from the ANSI store.](#)

BS 8418:2015+A1:2017



BSI Standards Publication

**Installation and remote monitoring
of detector-activated CCTV systems –
Code of practice**

bsi.

This is a preview of "BS 8418:2015+A1:2017". [Click here to purchase the full version from the ANSI store.](#)

Publishing and copyright information

The BSI copyright notice displayed in this document indicates when the document was last issued.

© The British Standards Institution 2017

Published by BSI Standards Limited 2017

ISBN 978 0 580 98849 3

ICS 13.310 | 33.160.40

The following BSI references relate to the work on this document:

Committee reference GW/1/10

Drafts for comment 14/30293253 DC; 17/30361938 DC

Amendments/corrigenda issued since publication

Date	Text affected
October 2017	A1: see foreword

This is a preview of "BS 8418:2015+A1:2017". Click here to purchase the full version from the ANSI store.

CONTENTS		Page
	Foreword	ii
	Introduction	1
1	Scope	1
2	Normative references	1
3	Terms, definitions and abbreviations	2
4	CCTV system planning and design	5
	<i>Table 1 — Tamper detection and indication</i>	11
	<i>Table 2 — Fault recognition and indication</i>	11
5	Installation	15
6	Commissioning	16
7	Setting/unsetting procedures of the remotely monitored CCTV system	18
8	Responsibilities and considerations	21
9	RVRC operator procedures	22
10	Management and operation of the RVRC	23
11	RVRC procedures and documentation	24
12	Activation management	26
13	Service levels	26
14	General maintenance and personnel screening	26
Annex A	(informative) Diagrams for positioning detectors	28
	<i>Figure A.1 — Alignment of long range and wide angle detectors</i>	28
	<i>Figure A.2 — Correctly positioned detectors near a supervised premises boundary</i>	29
	<i>Figure A.3 — An incorrectly adjusted detector facing an entrance gate, where the detection exceeds the secure area</i>	30
	<i>Figure A.4 — An incorrectly positioned detector providing a detection area outside the field of view of the camera</i>	31
	<i>Figure A.5 — Example of multiple cameras positioned to view the total detection area</i>	31
Annex B	(informative) Factors affecting the design requirements for a detector-activated CCTV system	31
Annex C	(informative) Types of technology used in detection equipment	33
Annex D	(informative) Illumination of the field of view of the camera	35
	<i>Figure D.1 — Correct artificial illumination of the field of view of a camera</i>	35
Annex E	(normative) Checklist criteria for the commissioning of a detector-activated CCTV system	35
	<i>Table E.1 — Template for the commissioning of a CCTV system</i>	35
Annex F	(informative) Setting procedure with a detector in the active state	37
	Bibliography	38

Summary of pages

This document comprises a front cover, and inside front cover, pages i to iv, pages 1 to 38, an inside back cover and a back cover.

This is a preview of "BS 8418:2015+A1:2017". [Click here to purchase the full version from the ANSI store.](#)

Foreword

Publishing information

This British Standard is published by BSI Standards Limited, under licence from The British Standards Institution, and came into effect on 31 January 2015. It was prepared by Subcommittee GW/1/10, *Closed circuit television (CCTV)*, under the authority of Technical Committee GW/1, *Electronic security systems*. A list of organizations represented on these committees can be obtained on request to their secretary.

Supersession

This British Standard superseded BS 8418:2010, which was withdrawn on 31 July 2015.

BS 8418:2015+A1:2017 supersedes BS 8418:2015, which is withdrawn.

Information about this document

Text introduced or altered by Amendment No. 1 is indicated in the text by tags A1 A1. Minor editorial changes are not tagged.

BS 8418:2015 was a full revision of the standard, and introduced the following principal changes:

- The need to carry out a threat assessment and risk analysis and produce an Operational Requirement document to reflect the requirements of BS IEC 62676-4 has been included.
- Clarified the use of portable/mobile systems within the standard.
- Relaxed some of the tamper recommendations and provided a tamper protection/indication table to add clarity to the requirements.
- Included a fault recognition/indication table to provide clarity to the recommendations.
- Decreased the number of event memory recommendations.
- The need for an Uninterruptable Power Supply (UPS) is now determined by threat analysis and risk assessment.
- Signalled the need for a minimum of one data transmission path. Further paths determined by threat analysis and risk assessment.

Use of this document

As a code of practice, this British Standard takes the form of guidance and recommendations. It should not be quoted as if it were a specification and particular care should be taken to ensure that claims of compliance are not misleading.

Any user claiming compliance with this British Standard is expected to be able to justify any course of action that deviates from its recommendations.

Presentational conventions

The provisions of this standard are presented in roman (i.e. upright) type. Its recommendations are expressed in sentences in which the principal auxiliary verb is "should".

Commentary, explanation and general informative material is presented in smaller italic type, and does not constitute a normative element.

The word "should" is used to express recommendations of this standard. The word "may" is used in the text to express permissibility, e.g. as an alternative to the primary recommendation of the clause. The word "can" is used to express possibility, e.g. a consequence of an action or an event.

This is a preview of "BS 8418:2015+A1:2017". [Click here to purchase the full version from the ANSI store.](#)

and additional information that are important but do not form part of the recommendations. Commentaries give background information.

Contractual and legal considerations

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard cannot confer immunity from legal obligations.

This is a preview of "BS 8418:2015+A1:2017". [Click here to purchase the full version from the ANSI store.](#)

This is a preview of "BS 8418:2015+A1:2017". [Click here to purchase the full version from the ANSI store.](#)

Introduction

Closed circuit television (CCTV) systems, also known as video surveillance systems (VSS), installed and monitored in accordance with this standard are capable of obtaining a response to a confirmed incident from the police (or other responding authority).

The key principles of this standard are to assist in ensuring that the integrity and effectiveness of an installed CCTV system are not compromised. The resilience and quality of the CCTV system need to be maintained at all times and in all environments in which the system is required to work.

When a detector senses an event, images are transmitted to, and displayed at, an RVRC and this is regarded as an activation. Prior to taking action, RVRC operators view these images for a period of time. Under normal circumstances an emergency response is only requested by the RVRC if there is positive evidence in these images of unauthorized access to the secure area and of actual criminal or other untoward activity, i.e. an incident.

1 Scope

This British Standard gives recommendations for the design, installation, commissioning, maintenance, operation and remote monitoring of detector-activated CCTV systems, whether "permanent" or temporary/portable.

This standard applies irrespective of the length of time the CCTV systems are installed and/or whether the equipment can be re-used on another site.

This standard is intended to provide recommendations to the following parties:

- a) CCTV companies, on best practice for the design, installation, commissioning, maintenance and operation of detector-activated CCTV systems;
NOTE This includes the installation and maintenance engineers working for the CCTV company.
- b) Remote video response centres (RVRCs) monitoring CCTV systems; and
- c) customers regarding the management of CCTV systems.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

BS 5979:2007, *Remote centres receiving signals from fire and security systems — Code of practice*

BS 7671, *Requirements for electrical installations — IET wiring regulations — Seventeenth edition*

BS 7858, *Security screening of individuals employed in a security environment — Code of practice*

BS 7958:2009, *Closed-circuit television (CCTV) — Management and operation — Code of practice*¹

BS 8243:2010+A1:2014, *Installation and configuration of intruder and hold-up alarm systems designed to generate confirmed alarm conditions — Code of practice*

BS 8591:2014, *Remote centres receiving signals from alarm systems — Code of practice*

BS EN 62676-1-1, *Video surveillance systems for use in security applications — System requirement — Part 1-1: General*

¹ At the time of the publication of BS 8418:2015, BS 7958:2009 was under review.