

This is a preview of "BS 8081:2015+A1:2017". [Click here to purchase the full version from the ANSI store.](#)

**BS 8081:2015+A1:2017**



**BSI Standards Publication**

## **Code of practice for grouted anchors**

This is a preview of "BS 8081:2015+A1:2017". [Click here to purchase the full version from the ANSI store.](#)

### **Publishing and copyright information**

The BSI copyright notice displayed in this document indicates when the document was last issued.

© The British Standards Institution 2017

Published by BSI Standards Limited 2017

ISBN 978 0 580 51926 0

ICS 91.200, 93.020

The following BSI references relate to the work on this document:

Committee reference B/526

Drafts for comment 15/30302283 DC; 17/30359711 DC

### **Amendments/corrigenda issued since publication**

Date	Text affected
30 September 2017	A1: see Foreword
30 November 2017	C1: 11.3 subclause heading corrected

This is a preview of "BS 8081:2015+A1:2017". Click here to purchase the full version from the ANSI store.

## CONTENTS

	Page
<b>Foreword</b>	<b>iv</b>
1 Scope	1
2 Normative references	2
3 Terms, definitions, symbols and abbreviations	3
<i>Figure 1 — Grouted anchors</i>	9
4 General rules	13
<i>Table 1 — Recommended design and construction duties</i>	14
5 Limit states	19
6 Design situations	20
7 Design considerations	20
<i>Figure 2 — Grouted anchors</i>	22
<i>Figure 3 — Flow chart for the development of strategy for the monitoring and maintenance of grouted anchors</i>	24
8 Ultimate limit state design	24
9 Serviceability limit state design	24
10 Structural design	24
11 Anchor design	25
<i>Table 2 — Minimum resistance factors recommended for the calculation of the size of individual fixed anchor lengths prior to testing</i>	27
12 Materials	30
<i>Figure 4 — Typical encapsulation centralizers</i>	33
<i>Figure 5 — Typical bar centralizer</i>	34
<i>Figure 6 — Typical cross-section of centralizer/spacer unit for multi-strand tendon in temporary unprotected systems</i>	35
13 Durability	36
<i>Figure 7 — Typical coupler details in tendon free length of bar tendon</i>	40
<i>Figure 8 — Typical double corrosion protection of tendon bond length of strand tendon using a single corrugated sheath and polyester resin</i>	42
<i>Figure 9 — Typical double corrosion protection of tendon bond length of strand tendon using a double corrugated sheath and cement grout</i>	43
<i>Figure 10 — Tendon bond length protection for a ribbed bar tendon</i>	44
<i>Figure 11 — Typical double corrosion protection of tendon bond length of smooth or ribbed bar tendon using a double corrugated duct</i>	45
<i>Figure 12 — Typical double corrosion protection of restressable anchor head incorporating a strand tendon</i>	46
14 Execution	48
15 Considerations related to testing	58
16 Maintenance	59
17 Reporting	60
<b>Annex A</b> (informative) <b>Indicative record sheets</b>	<b>62</b>
<i>Table A.1 — Typical drilling, grouting and tendon installation record sheet</i>	63
<i>Table A.2 — Typical stressing record sheet</i>	64
<i>Table A.2 (continued) — Typical stressing record sheet</i>	65
<i>Table A.3 — Typical stressing results and analysis record sheet</i>	67
<b>Annex B</b> (informative) <b>Determination of the size of grouted anchors</b>	<b>67</b>
<i>Figure B.1 — Main types of cement injection grouted anchors</i>	69
<i>Figure B.2 — Detail of tube à manchette for pressure grouting control</i>	70

This is a preview of "BS 8081:2015+A1:2017". [Click here to purchase the full version from the ANSI store.](#)

	<i>Table B.2 — Rock/grout bond values that have been recommended for design</i>	75
	<i>Table B.3 — Rock/grout bond values from rock anchor tests</i>	77
	<i>Figure B.3 — Relationship between resistance efficiency factor and fixed anchor length</i>	78
	<i>Table B.4 — Approximate relationship between bearing capacity factor <math>N_q</math> and slenderness ratio</i>	79
	<i>Figure B.4 — Relationship between bearing capacity factor <math>N_q</math> and angle of shearing resistance in terms of effective stress</i>	80
	<i>Figure B.5 — Ultimate load-holding capacity of anchors in sandy gravels and gravelly sands, showing influence of soil type, density and fixed anchor length for Type C anchors</i>	82
	<i>Figure B.6 — Relationship between ultimate load-holding capacity, fixed anchor length and dynamic penetration for two types of coarse soil</i>	84
	<i>Figure B.7 — Skin friction in fine soils for various fixed anchor lengths, with and without post-grouting</i>	86
	<i>Figure B.8 — Influence of post-grouting pressure on skin friction in a fine soil</i>	87
	<i>Table B.5 — Fixed anchor lengths for cement-grouted rock anchors that have been employed or recommended in practice</i>	91
	<i>Figure B.9 — Load transfer mechanisms for typical encapsulation systems</i>	93
<b>Annex C</b>	<b>(informative) Pre-grouting and post-grouting</b>	<b>96</b>
<b>Annex D</b>	<b>(informative) Tendon Young's Modulus values</b>	<b>97</b>
<b>Annex E</b>	<b>(informative) Corrosion</b>	<b>98</b>
	<i>Table E.1 — Soil corrosiveness related to values of soil resistivity and redox potential</i>	102
<b>Annex F</b>	<b>(informative) Corrosion protection</b>	<b>103</b>
	<i>Table F.1 — Proposed classes of protection for ground anchors</i>	103
<b>Annex G</b>	<b>(normative) Testing</b>	<b>105</b>
	<i>Table G.1 — Recommended load increments and minimum periods of observation for investigation tests on anchors where the ground conditions are not known, or prior experience of anchoring does not exist</i>	111
	<i>Figure G.1 — Recommended load increments and minimum periods of observation for investigation tests on anchors where the ground conditions are not known, or prior experience of anchoring does not exist</i>	111
	<i>Table G.2 — Recommended load increments and minimum periods of observation for investigation tests on anchors where previous anchoring knowledge is available</i>	112
	<i>Figure G.2 — Recommended load increments and minimum period of observation for investigation tests on anchors where previous anchoring knowledge is available</i>	112
	<i>Table G.3 — Recommended load increments and minimum periods of observation for suitability tests</i>	113
	<i>Table G.4 — Acceptance criteria for displacement-time behaviour at <math>F_{\text{Serv};k}</math></i>	113
	<i>Figure G.3 — Schematic showing typical method of measuring tendon displacement using a dial gauge</i>	114
	<i>Figure G.4 — Schematic showing typical method of measuring tendon load loss using a pressure gauge</i>	115
	<i>Table G.5 — Acceptance criteria for load loss at <math>F_{\text{Serv};k}</math></i>	115
	<i>Figure G.5 — Acceptance criteria for tendon displacement at anchor head</i>	116
	<i>Figure G.6 — Recommended load increments and minimum periods of observation for suitability tests</i>	119
	<i>Table G.6 — Recommended load increments and minimum periods of observation for acceptance tests</i>	121

This is a preview of "BS 8081:2015+A1:2017". [Click here to purchase the full version from the ANSI store.](#)

	<i>acceptance tests</i>	122
	<i>Figure G.8 — Typical monitored anchor head for strand tendon</i>	124
	<i>Figure G.9 — Typical monitored anchor head for bar tendon</i>	125
<b>Annex H</b>	<b>(informative) General considerations on monitoring and testing</b>	<b>127</b>
	<i>Table H.1 — Relationship between the acceptance criteria for load-time and displacement-time behaviour</i>	130
<b>Annex I</b>	<b>(informative) Health and safety</b>	<b>131</b>
	<b>Bibliography</b>	<b>132</b>

### Summary of pages

This document comprises a front cover, and inside front cover, pages i to vi, pages 1 to 137, an inside back cover and a back cover.

This is a preview of "BS 8081:2015+A1:2017". Click here to purchase the full version from the ANSI store.

# Foreword

## Publishing information

This British Standard is published by BSI Standards Limited, under licence from The British Standards Institution, and came into effect on 31 August 2015. It was prepared under the authority of Technical Committee B/526, *Geotechnics*. A list of organizations represented on this committee can be obtained on request to its secretary.

## Supersession

BS 8081:2015+A1:2017 supersedes BS 8081:2015, which is withdrawn.

## Information about this document

Text introduced or altered by Amendment No. 1 is indicated in the text by the tags  $\boxed{A_1}$   $\langle A_1 \rangle$ . Minor editorial changes are not tagged. Amendment No. 1 introduces the following changes:

- Table 2 has been updated;
- a new Clause 11.3 has been inserted and the following subclauses renumbered; and
- Clause 11.3.5 has been deleted.

Corrigendum No. 1 is indicated in the text by the tags  $\boxed{C_1}$   $\langle C_1 \rangle$ .

## Relationship with other publications

BS 8081 gives non-contradictory, complementary information for use with BS EN 1997-1:2004+A1:2013 and its UK National Annexes, BS EN 1537:2013 and BS EN ISO 22477-5. At the time of publication, BS EN ISO 22477-5 is not published and until such time as it is published, the recommendations for the testing of grouted anchors given in BS 8081:2015 Annex G apply.<sup>1</sup>

## Use of this document

As a code of practice, this British Standard takes the form of guidance and recommendations. It should not be quoted as if it were a specification and particular care should be taken to ensure that claims of compliance are not misleading.

Any user claiming compliance with this British Standard is expected to be able to justify any course of action that deviates from its recommendations.

## Presentational conventions

The provisions of this standard are presented in roman (i.e. upright) type. Its recommendations are expressed in sentences in which the principal auxiliary verb is "should".

*Commentary, explanation and general informative material is presented in smaller italic type, and does not constitute a normative element.*

Where words have alternative spellings, the preferred spelling of the Shorter Oxford English Dictionary is used (e.g. "organization" rather than "organisation").

The auxiliary verb "may" is used in the text to express permissibility, e.g. as an alternative to the primary recommendation of the Clause. The auxiliary verb "can" is used to express possibility, e.g. a consequence of an action or an event.

<sup>1</sup> BS EN ISO 22477-5 is expected to publish in June 2018 (although this date is subject to change). Please check the BSI Shop website at <http://shop.bsigroup.com/> for further information.

This is a preview of "BS 8081:2015+A1:2017". [Click here to purchase the full version from the ANSI store.](#)

and additional information that are important but do not form part of the recommendations. Commentaries give background information.

### **Contractual and legal considerations**

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

**Compliance with a British Standard cannot confer immunity from legal obligations.**

This is a preview of "BS 8081:2015+A1:2017". [Click here to purchase the full version from the ANSI store.](#)



This is a preview of "BS 8081:2015+A1:2017". Click here to purchase the full version from the ANSI store.

## 1 Scope

- 1.1** This British Standard, as a code of practice, gives recommendations for the design, construction, stressing, testing, monitoring and maintenance of grouted anchors as defined in BS EN 1997-1:2004+A1:2013, BS EN 1537:2013 and BS EN ISO 22477-5.
- 1.2** Further general recommendations for corrosion hazards and protective measures, construction techniques and quality controls, stressing procedures, and the testing of grouted anchor components and complete installations are provided. Information supporting the practical implementation of these recommendations are provided in annexes to this code of practice.
- 1.3** Annex A provides examples of records that are developed during the execution and testing of grouted anchors.
- 1.4** Annex B provides information on the design of a fixed anchor length with respect to the bond or shear resistance at:
- a) the ground/grout interface;
  - b) the grout/encapsulation interface;
  - c) the grout/tendon interface.
- 1.5** Annex C provides information on the pre-grouting and post-grouting of ground, where necessary.
- 1.6** Annex D provides information on the use of appropriate Young's modulus for the steel used in the design of the anchor tendon.
- 1.7** Annex E provides information on the types of corrosion that affect the steel elements of an anchor and the influence on the corrosion of the tendon of the ground and groundwater in which the anchor is installed.
- 1.8** Annex F provides information on the types of corrosion protection available for use in the fabrication and installation of the anchor.
- 1.9** Annex G provides recommendations on the testing of anchors at all stages of construction.
- 1.10** Annex H provides information on monitoring anchors in the long term, including appropriate acceptance criteria and remedial measures that can be applied in the event of non-compliance with the acceptance criteria.
- 1.11** Annex I draws attention to the statutory regulations affecting the safety, welfare and health of persons in the execution of anchor construction.
- 1.12** This code of practice is for the use of clients who commission the use of grouted anchors, ground engineering contractors, and geotechnical and structural designers.

*NOTE* BS EN ISO 22477-5 is expected to publish in June 2018 (although this date is subject to change). Please check the BSI Shop website at <http://shop.bsigroup.com/> for further information.