

### **BSI Standards Publication**

# Nanotechnologies — Characterization of individualized cellulose nanofibril samples



#### **National foreword**

This Published Document is the UK implementation of ISO/TS 21346:2021.

The UK participation in its preparation was entrusted to Technical Committee NTI/1, Nanotechnologies.

A list of organizations represented on this committee can be obtained on request to its committee manager.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2021 Published by BSI Standards Limited 2021

ISBN 978 0 580 51955 0

ICS 07.120

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 31 March 2021.

Amendments/corrigenda issued since publication

Date Text affected

#### TECHNICAL

ISU/LS

This is a preview of "PD ISO/TS 21346:2021". Click here to purchase the full version from the ANSI store.

First edition 2021-03-15

# Nanotechnologies — Characterization of individualized cellulose nanofibril samples

Nanotechnologies — Caractérisation d'échantillons de nanofibrilles individualisées de cellulose



## PD ISO/TS 21346:2021 **ISO/TS 21346:2021(E)**

This is a preview of "PD ISO/TS 21346:2021". Click here to purchase the full version from the ANSI store.



#### **COPYRIGHT PROTECTED DOCUMENT**

© ISO 2021, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Ch. de Blandonnet 8 • CP 401 CH-1214 Vernier, Geneva, Switzerland Tel. +41 22 749 01 11 Fax +41 22 749 09 47 copyright@iso.org www.iso.org

<b>Contents</b> Pa				
Fore	word			iv
Intro	oductio	n		<b>v</b>
1	Scop	e		1
2	Norr	Normative references		
3	Terms and definitions			
4	Abbreviated terms			
5	Characteristics to be measured of iCNF samples and their measurement methods			
	5.1 General			
	5.2		teristics required to be measured or identified	
		5.2.1	Morphology and size	
		5.2.2	Total dry matter content	
		5.2.3	Crystal structure	4
		5.2.4	Optical transmittance	
		5.2.5	Surface functional groups: Types	
		5.2.6	Surface functional groups: Content	
		5.2.7	Viscosity	5
	5.3		Characteristics recommended to be measured or identified	
		5.3.1	Width and height	
		5.3.2	Length	
		5.3.3	Molecular weight distribution	
		5.3.4	Supernatant dry matter ratio	
		5.3.5 5.3.6	CrystallinityThermal stability	
		5.3.7	Ash content	
		5.3.8	Acid-soluble metal content	
		5.3.9	Organic contaminant content	
		5.3.10	Acetone-soluble matter content	8
		5.3.11	Constituent sugar content	
6	Repo	orting		9
Anno	ex <b>A</b> (in	formative	e) Protocols for sample preparation, measurement and data analysis	11
	-		e) Description of individualized cellulose nanofibril (iCNF)	
	_			

#### Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see <a href="www.iso.org/directives">www.iso.org/directives</a>).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see <a href="https://www.iso.org/patents">www.iso.org/patents</a>).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see <a href="https://www.iso.org/iso/foreword.html">www.iso.org/iso/foreword.html</a>.

This document was prepared by Technical Committee ISO/TC 229, Nanotechnologies.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <a href="https://www.iso.org/members.html">www.iso.org/members.html</a>.

#### Introduction

Cellulose nanomaterials derived from naturally occurring cellulosic fibres are renewable advanced materials with unprecedented properties. They are of wide variety in morphology, e.g. different shapes, branching and networking. Basic research related to cellulosic nanomaterials has been increasingly conducted worldwide. At the same time, manufacturing industries have already started to deliver cellulose nanomaterials to the market. Application industries are also becoming more and more interested in these new materials.

All native cellulosic fibres are composed of bundles in which the smallest fibril unit is an elementary fibril originating from a cellulose terminal enzyme complex. An elementary fibril is made of a certain number of cellulose molecules and contains crystalline regions predominantly. The size of an elementary fibril is specific to the native cellulose source. In wood pulp, the cross-sectional dimension of an elementary fibril is about 3 nm and its aspect ratio can reach more than 200. In native cellulose fibres, elementary fibrils do not exist as single fibrils but adhere to each other through hydrogen bonding and are densely packed to form a bundle of fibrils. Very recently, however, some novel methods to extract and separate these elementary fibrils, through chemical modification of the outer surface of the fibrils followed by mechanical treatment, were developed. The chemical modification methods include TEMPO-mediated oxidation and phosphorylation. Using the above treatments, each native elementary fibril can be converted to an individualized cellulose nanofibril (iCNF) with charges at its surface. An iCNF has the functional groups on the outer surface of the fibril, and iCNFs can be separated from each other, one by one, by the static repulsion due to the electrostatic charge of newly introduced functional groups. Refer to Annex B for more explanations on iCNFs.

Several manufacturing companies have already begun producing iCNFs. iCNFs are now delivered increasingly to the worldwide market for applications in the industrial fields of polymer composites, adhesives, additives, gels, etc. Some examples of iCNF-containing commercial products are diapers with deodorant performance and gel ink for ballpoint pens. In all applications, appropriate characterization of the iCNF samples is necessary so that desired products can be manufactured.

This document provides a sound basis for the commercialization as well as the research and development of iCNF materials.



## Nanotechnologies — Characterization of individualized cellulose nanofibril samples

#### 1 Scope

This document specifies characteristics to be measured of individualized cellulose nanofibril (iCNF) samples in suspension and powder forms and their measurement methods. In addition, it provides sample preparation, measurement and data analysis procedures.

This document does not apply to the characterization of iCNFs that have been modified after they are manufactured.

#### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/TS 80004-2, Nanotechnologies — Vocabulary — Part 2: Nano-objects

#### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/TS 80004-2 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <a href="https://www.iso.org/obp">https://www.iso.org/obp</a>
- IEC Electropedia: available at <a href="http://www.electropedia.org/">http://www.electropedia.org/</a>

#### 3.1

#### elementary fibril

structure, originating from a single terminal enzyme complex, having a configuration of cellulose chains specific to each cellulose-producing plant, animal, algal and bacteria species

[SOURCE: ISO/TS 20477:2017, 3.2.5]

#### 3.2

#### cellulose nanofibril

#### CNF

cellulose nanofibre composed of at least one *elementary fibril* (3.1), containing crystalline, paracrystalline and amorphous regions, with aspect ratio usually greater than 10, which may contain longitudinal splits, entanglement between particles, or network-like structures

[SOURCE: ISO/TS 20477:2017, 3.3.6, modified — The notes to entry have been deleted.]

#### 3.3

#### individualized cellulose nanofibril

#### **CNF**

discrete *cellulose nanofibril* (3.2) composed of one *elementary fibril* (3.1) with ionic functional groups on its surface